

KASK

**SAFETY
COLLECTION**

KASK

PERFORMANCE IS
A BEAUTIFUL THING.





I N D E X

OUR MISSION OUR PASSION	6
20 YEARS TO A GLOBAL NETWORK	8
KASK TIMELINE	10
THE KASK DIFFERENCE	14
KASK ROTATIONAL IMPACT WG11 TEST	22
LOWERING CARBON FOOTPRINT WHILE MAINTAINING KASK SAFETY STANDARDS	24
HEAD PROTECTION	26
STANDARDS	28
ZENITH X	30
ZENITH X	34
ZENITH X HI VIZ	36
ZENITH X AIR	38
ZENITH X AIR HI VIZ	40
ZENITH X PL	42
ZENITH X PL HI VIZ	44
ZENITH X MAX	46
ZENITH X MAX HI VIZ	48
ZENITH X MAX AIR	50
ZENITH X MAX AIR HI VIZ	52
ZENITH X COMBO	54
ZENITH X AIR COMBO	56
ZENITH X PL COMBO	58
PRIMERO	60
PRIMERO	64
PRIMERO HI VIZ	66
PRIMERO AIR	68
PRIMERO AIR HI VIZ	70
PRIMERO PL	72
PRIMERO PL HI VIZ	74
SUPERPLASMA	76
SUPERPLASMA AQ	80
SUPERPLASMA AQ HI VIZ	82
SUPERPLASMA HP	84
SUPERPLASMA HP VISOR	86
SUPERPLASMA PL	88
SUPERPLASMA PL HI VIZ	90
EYE & FACE PROTECTION	92
STANDARDS	94
PROTECTION FROM ELECTRIC ARC	108
HEARING PROTECTION	112
WEATHER PROTECTION	116
HEADLAMPS	124
OTHER ACCESSORIES	130
CUSTOM PRINTING: AS EASY AS 1, 2, 3	132
SPARE PARTS	134
SALES SUPPORT	136
ZENITH X FULL RANGE	140
PRIMERO FULL RANGE	142
SUPERPLASMA FULL RANGE	144



OUR MISSION.

Develop helmets that exceed the strictest global safety protection standards.

— 6

OUR PASSION.

Designing helmets for all-day comfort and optimal worker performance.





"Every great adventure starts in your head. We take care of it. We create and develop advanced helmets that combine comfort, safety, and design to look just as great as they perform."

KASK CEO Angelo Gotti

KASK IN THE WORLD

MORE THAN 20 YEARS TO A GLOBAL NETWORK.



KASK AMERICA
Est. 2010

8



3

GLOBAL OFFICES


Started in 2004, KASK has built an industry-leading global team of engineers, product specialists, and premier partners.

**KASK ITALIA**

Headquarters Est. 2004

**KASK AUSTRALIA**

Est. 2014



2004

R&D

KASK is founded to develop advanced helmet safety improvements for OEM customers.

2009

SNOW

KASK performance benefits are extended to meet the challenging applications of winter sport enthusiasts.

2006

CYCLING

KASK brings safety, comfort, and design helmet philosophies to demanding cycling market.

2008

SAFETY

KASK shifts from OEM supplier to manufacturer to accelerate innovations in industrial helmets.

2011

URBAN

KASK comfort and design competencies are extended into the immersing consumer markets.

2021 2024

VOGEL F.LLI FABBRI

KASK acquires Vogel, an American bespoke equestrian footwear brand, sharing the same values of luxury, service, and quality with a dedication to craftsmanship.

Since 1924, Fratelli Fabbri boots have been handcrafted. The exclusivity of Fabbri's products comes from the excellence of the materials and the possibility of making unique customizations that KASK stands for.

2015 2016

EQUESTRIAN KOO EYEWEAR

KASK recognizes a gap in protection and performance in equestrian helmets, and delivers advanced design and innovative features.

KASK launches new performance eyewear brand to deliver integrated head and eye protection solutions.

KASK

— 12






THE KASK DIFFERENCE.

Delivering performance helmets
requires:

- a dedication to SAFETY
- a commitment to COMFORT
- a passion for DESIGN





KASK



SAFETY.

Engineered to exceed the strictest global safety protection standards.



The first to introduce high-density polystyrene interior for a complete whole head protection.



Offices in Europe, Australia, and North America ensure KASK helmets exceed global safety standards.



The first to standardize chinstrap systems to ensure consistently secure head protection.

COMFORT.

New technologies that increase worker confidence for all-day performance.

18




Ratchet fit systems enable comfort as the wearer's head moves ensuring firm helmet stability.



Integrated ventilation systems that channel airflow through the helmet for all-day comfort.



Advanced materials and fabrics wick away moisture to keep workers cool and dry.





KASK



DESIGN.

Uncompromising attention to details that produces helmets workers want to wear.



Designed with easily replaceable components to ensure helmets are a long-lasting investment.



A suite of advanced, fully integrated accessories that allow all helmets to be customized for your needs.



Recognized by the global design community for exceptional attention to form and function.



KASK ROTATIONAL IMPACT WG11 TEST.

Every KASK helmet is tested for rotational impact performance.



— 22

KASK has always been committed to creating products that provide both excellent safety and comfort, exceeding requirements set by international standards and norms.

KASK WG11 test is an internal protocol adopted by KASK to identify an objective method, based on scientific sources, for measuring the performance of its helmets against rotational impacts.

Most helmets tests use rotational impact prevention technologies with headforms that have a higher coefficient of friction than those of the human skull and therefore may not reflect what occurs in some accidents.

The “pass-fail” criterion is based on the BrIC value, an algorithm that defines the level of brain injury. This value must be lower than 0,68.

The final test protocol is:

OBLIQUE IMPACT TESTs:

oblique tests @ 45°, impact speed 4,5 m/s, BrIC < 0,68

- grade 80 closed-coat aluminum oxide abrasive paper
- headform nominal coefficient of friction 0,3
- wireless system: triaxial accelerometer + n. 3 ARS

Headform: EN 960 series

Measurements: Peak of rotational acceleration, Peak of linear acceleration, HIC, BRIC (< 0,68)



All KASK helmets successfully pass this test with values that are substantially less than 0,68: BrIC 0,39.

HIGHER RISK OF BRAIN INJURY: >0.68

KASK PROTECTION: <0.39

ROTATIONAL IMPACT WG11 TEST PASSED is a KASK registered trademark. The ROTATIONAL IMPACT TEST PASSED is a KASK internal oblique impact test that measures the performance of its helmets against rotational impacts. This Test has not been adopted by CEN or its Working Group CEN TC158/Working Group 11.

LOWERING CARBON FOOTPRINT WHILE MAINTAINING KASK SAFETY STANDARDS.

SUPERPLASMA, PRIMERO AND ZENITH X SERIES HAVE THE INTERNAL SHELL MADE OF



**Neopor®
Cycled®**

by BASF

— 24

NEOPOR® CCYCLED® EPS IS OBTAINED FROM CHEMICAL RECYCLING OF PLASTIC WASTE AND HAS A REDUCED CARBON FOOTPRINT, ENSURING THE SAME HIGH QUALITY, PERFORMANCE AND SAFETY AS EPS MADE FROM FOSSIL RAW MATERIAL.



SUPERPLASMA



PRIMERO




ZENITH X

BENEFITS OF USING NEOPOR® CCYCLED® EPS


- Ensures the same mechanical characteristics as conventional Neopor®, such as all-around high impact energy absorption
- Saves fossil resources and reduces CO₂ emissions compared to conventional EPS
- Contributes to a circular economy by turning plastic waste into feedstock for the chemical industry, when no other recycling processes are applicable

REDUCED PRODUCT CARBON FOOTPRINT




Neopor® Cycled® has a product carbon footprint reduced by about 90% compared to conventional Neopor® produced on the basis of fossil feedstock. CO₂ emissions are saved when manufacturing EPS using pyrolysis oil under a mass balance approach*. The lower emissions result from chemically recycling the mixed plastic waste instead of incinerating it.

THE PRODUCTION PROCESS



CONSERVING RESOURCES



- 01 Consumers dispose plastic products
- 02 Plastic waste is sorted and delivered to BASF technology partners
- 03 Plastic waste is chemically recycled and converted into pyrolysis oil
- 04 The pyrolysis oil obtained is used as feedstock at the very beginning of the BASF value chain
- 05 The pyrolysis oil is attributed to Neopor® Cycled® via a certified mass balance approach*
- 06 New products, e.g. internal shell of KASK safety helmet, are manufactured from Neopor® Cycled®

KASK helmets featuring an internal shell made from Neopor® Cycled® EPS include the entire Primero and Zenith X series, as well as the AQ, AQ HI VIZ, PL, and PL HI VIZ models within the Superplasma series.

* Conventional fossil raw materials required to manufacture BASF products are replaced with recycled feedstock from the chemical recycling of plastic waste or end of life tires along BASF's integrated production chain. The corresponding share of recycled feedstock, e.g. pyrolysis oil, is attributed to the specific Cycled® product via a certified mass balance approach. BASF sites and Cycled® products are third party certified according to internationally recognized certification schemes like REDcert2 and ISCC PLUS and meet the definitions by ISO 22095:2020. The recycled feedstock is not measurable in the BASF mass balance product. The cradle to gate PCF is calculated according to TFS Methodology using an Upstream System Expansion (USE) approach. USE accounts for a credit for the displaced waste treatment from the first life cycle (e.g. incineration), thereby reducing the product carbon footprint compared to the equivalent conventional fossil product. PCF data is subject to periodical reviews.



KASK

HEAD PROTECTION

— 26

GLOBAL ICONS

KASK safety helmets have become recognized around the world for their exceptional safety, attention to design details, and worker comfort.

OVERVIEW OF SELECT STANDARDS FOR KASK HELMETS

EUROPEAN STANDARDS

EN 397

The European safety standard for industrial helmets covering top impact absorption, penetration resistance, flame resistance, and chinstrap requirements with additional optional testing.

IMPACT & PENETRATION

- Meets top of head protection requirements

CHINSTRAP STRENGTH

- Withstands >15 kg to reduce risk of coming off in a fall
- Not exceed < 25 kg to reduce risk of strangulation if snagged

OPTIONAL TESTING

- Electrical Insulation (440 Volts)
- Extreme Temperature Resistance
- Molten Metal Splash Protection
- Lateral Deformation

EN 14052

The European High Performance industrial standard for high risk environments covering top and lateral impact absorption, penetration resistance, and chinstrap requirements with additional optional testing.

IMPACT & PENETRATION

- Meets high level top of head & lateral protection requirements

CHINSTRAP STRENGTH

- Withstands >15 kg to reduce risk of coming off in a fall
- Not exceed < 25 kg to reduce risk of strangulation if snagged

OPTIONAL TESTING

- Molten Metal Splash Protection
- Performance at higher and lower temperatures
- Resistance to radiant heat
- Electrical properties

EN 12492

The European safety standard for climbing and mountaineering helmets covering top and lateral impact absorption, penetration resistance, and chinstrap requirements.

IMPACT & PENETRATION

- Meets top of head and lateral protection requirements

CHINSTRAP STRENGTH

- Withstands > 50 kg to reduce risk of coming off in a fall
- Chinstrap is only able to stretch up to 25 mm max
- Helmet must not be able to slide from head

EN 50365

Supplemental to EN 397. The European testing method for electrical insulation helmets in low voltage environments.

REQUIREMENTS

- Helmet must meet requirements in accordance with EN397
- Helmet must not contain any conductive parts
- Air vents (if applicable) must not allow contact with live parts

ELECTRICAL INSULATION FOR A CLASS 0 MUST MEET EITHER/OR

- Protection against alternating voltage up to 1,000 Volts AC
- Protection against direct voltage up to 1,500 Volts DC



AMERICAN STANDARDS

ANSI Z89.1

The U.S. safety standard for industrial helmets covering impact absorption, penetration resistance, flame resistance, and electrical insulation ratings.

HELMET TYPE

- TYPE I – Meets top of head protection requirements
- TYPE II – Meets top and lateral protection requirements

ELECTRICAL INSULATION

- CLASS C – Conductive - No electrical protection
- CLASS G – General - withstands 2,200 Volts
- CLASS E – Electrical - withstands 20,000 Volts

OPTIONAL TESTING

- Meets low or high temperature operating ranges

CANADIAN STANDARDS

CSA Z94.1

The Canadian safety standard for industrial helmets covering impact absorption, penetration resistance, flame resistance, and electrical insulation ratings.

HELMET TYPE

- TYPE I – Meets top of head protection requirements
- TYPE II – Meets top and lateral protection requirements

ELECTRICAL INSULATION

- CLASS C – Conductive - No electrical protection
- CLASS G – General - withstands 2,200 Volts
- CLASS E – Electrical - withstands 20,000 Volts

OPTIONAL TESTING

- Helmet can be worn backwards and meet standards

AUSTRALIAN & NEW ZEALAND STANDARDS

AS/NZS 1801

The Australian safety standard for industrial helmets covering impact absorption, penetration resistance, flame resistance, and electrical insulation ratings.

HELMET TYPE

- TYPE 1 – Meets top and lateral protection requirements
- TYPE 2 – Meets high temperature workplace requirements
- TYPE 3 – Meets bushfire fighting requirements

ELECTRICAL INSULATION

- Operation up to 650 Volts

OPTIONAL TESTING

- Meets low or high temperature operating ranges
- Flame Resistance

KASK HELMETS

EXCEEDING SAFETY STANDARDS

		TOP IMPACTS		PENETRATION OF OBJECTS	SIDE, FRONT AND REAR IMPACTS	CHINSTAP RELEASE
	ZENITH X MAX ZENITH X HI VIZ MAX EN 397 - EN 50365	● 5 kg from 1 m 100 J		● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	● > 15 kg < 25 kg
	ZENITH X AIR ZENITH X AIR HI VIZ EN 397 - EN 50365	● 5 kg from 1 m 50 J		● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	● > 15 kg < 25 kg
	ZENITH X MAX AIR ZENITH X MAX AIR HI VIZ EN 397	● 5 kg from 1 m 100 J		● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	● > 15 kg < 25 kg
	ZENITH X PL ZENITH X PL HI VIZ EN 12492	● 5 kg from 2 m 100 J		● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	
	PRIMERO PRIMERO HI VIZ EN 397 - EN 50365	● 5 kg from 1 m 50 J	● 5 kg from 2 m 100 J	● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	● > 15 kg < 25 kg
	PRIMERO AIR PRIMERO AIR HI VIZ EN 397 - EN 50365	● 5 kg from 1 m 50 J	● 5 kg from 2 m 100 J	● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	● > 15 kg < 25 kg
	PRIMERO PL PRIMERO PL HI VIZ EN 12492	● 5 kg from 2 m 100 J		● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	
	SUPERPLASMA AQ SUPERPLASMA AQ HI VIZ EN 397	● 5 kg from 1 m 50 J		● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	● > 15 kg < 25 kg
	SUPERPLASMA PL SUPERPLASMA PL HI VIZ EN 12492	● 5 kg from 2 m 100 J		● 3 kg from 1 m 30 J	● 5 kg from 0,5 m 25 J	
	SUPERPLASMA HP SUPERPLASMA HP VISOR EN 14052	● 5 kg from 2 m 100 J		● 1 kg from 2,5 m 25 J Off-Crown: 1 kg from 2 m 20 J	● 5 kg from 1 m 50 J	● > 15 kg < 25 kg

- Required performance tests for certification
- Ⓚ EN 397 optional requirements
- Ⓚ EN 12492 added performance tests

CHINSTAP RESISTANCE	RETENTION SYSTEM EFFECTIVENESS	ELECTRIC INSULATION	ELECTRIC SHOCK PROTECTION	LOWER TEMPERATURE RESISTANCE	LATERAL DEFORMATION	MOLTEN METAL SPLASH
		Ⓚ 440V	● EN 50365 (Class 0)	Ⓚ T= -30°C	Ⓚ LD	Ⓚ MM
			● EN 50365 (Class 0)	Ⓚ T= -30°C	Ⓚ LD	Ⓚ MM
				Ⓚ T= -30°C	Ⓚ LD	Ⓚ MM
● > 50 kg	●					
		Ⓚ 440V	● EN 50365 (Class 0)	Ⓚ T= -30°C	Ⓚ LD	Ⓚ MM
			● EN 50365 (Class 0)	Ⓚ T= -30°C	Ⓚ LD	Ⓚ MM
● > 50 kg	●			Ⓚ T= -30°C	Ⓚ LD	Ⓚ MM
				Ⓚ T= -30°C	Ⓚ LD	Ⓚ MM
● > 50 kg	●					
	●				Ⓚ LD	



ZENITH X

— 30

Our passion for worker comfort and performance fueled the inspiration to design a helmet without compromise – one that is exponentially better.



FEATURES.



FRONT ATTACHMENT POINT
Holds accessories such as badges and headlamps.



EARMUFF ATTACHMENT SLOTS
Designed with integrated slots for attaching earmuffs.



HI-VIZ NAMEPLATE
Designed with rear high visibility nameplate for easy identification.

32



RING TO HOOK
Enables secure attachment of helmet to harness or other items.



EASY CLICK SYSTEM
Integrated slots that enable seamless accessory attachment. Applies to KASK eye, face, and hearing protection.



ADVANCED CHINSTRAP
Eco-leather chinstrap designed with new, rear adjustment points for a more personalized fit. Accommodates wider sizes and adapts to earmuff use. Color-coded fasteners indicate which EN standard the chinstrap meets.

**DRY+ LINER**

Advanced composite fabric integrated with Hydrocool® moisture-wicking technology and exceptionally soft textiles for enhanced user comfort.

**POLYPROPYLENE HD EXTERNAL SHELL**

Offers exponentially better impact protection especially at lower temperatures.

**ELECTRIC SHOCK PROTECTION**

Protection against electric hazards.

**ADAPTIVE FIT SYSTEM**

A size adjustment system which integrates three components for all-day comfort. A new, double diameter dial allows for easier size adjustments. Ergonomic side wings ensure a fast and secure fit against the back of the head. The patented Self Adaptive Live Hinge is the latest, self-adjusting fit technology that moves as the wearer moves.

**LATERAL ADJUSTMENT DIVIDER**

Side adjustment points on chinstrap for secure fit.

**REPLACEABLE LAMP CLIPS**

Four lamp attachment points designed to be removable.



ZENITH X

Exceptional safety and comfort designed with multiple accessory options for enhanced protection in high voltage environments.

WHE00073
EN 397 - EN 50365



WHE00073-201
WHITE



WHE00073-202
YELLOW



WHE00073-203
ORANGE



WHE00073-204
RED



WHE00073-205
GREEN



WHE00073-206
BRITISH GREEN



WHE00073-208
BLUE



WHE00073-209
ANTHRACITE



WHE00073-210
BLACK



WHE00073-214
PINK



WHE00073-215
LIGHT GREY



INCLUDES

WAC00026
DRAWSTRING
HELMET BAG

All colors are available as made-to-order with Longer Chinstrap (↔ +10 cm)
Part number WHE00125 - Zenith X LC

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)

CE 2008 UK 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: Neopor® Cycloled® by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 52 to 63 cm



WEIGHT
490 g



CATEGORY
III

ORDER LOGISTICS

MASTERBOX
pieces 18

DIMENSIONS
cm 82 x 47 x 56

WEIGHT
kg 16

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X HI VIZ

Exceptional safety and comfort designed with multiple accessory options for enhanced protection in high voltage environments. Available in high-visibility color options.

WHE00074

EN 397 - EN 50365



WHE00074-201
WHITE



WHE00074-221
YELLOW FLUO



WHE00074-222
ORANGE FLUO

INCLUDES



WAC00026
DRAWSTRING
HELMET BAG

All colors are available as made-to-order with Longer Chinstrap (↔ +10 cm)
Part number WHE00126 - Zenith X LC HI VIZ

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)

CE 2008 UK 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycloled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 52 to 63 cm



WEIGHT
490 g



CATEGORY
III

ORDER LOGISTICS

MASTERBOX
pieces 18

DIMENSIONS
cm 82 x 47 x 56

WEIGHT
kg 16

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X AIR

Exceptional safety and comfort designed with ventilation channels and multiple accessory options for enhanced protection.

WHE00075
EN 397 - EN 50365



38



WHE00075-201
WHITE



WHE00075-202
YELLOW



WHE00075-203
ORANGE



WHE00075-204
RED



WHE00075-205
GREEN



WHE00075-206
BRITISH GREEN



WHE00075-208
BLUE



WHE00075-209
ANTHRACITE



WHE00075-210
BLACK



WHE00075-214
PINK



WHE00075-215
LIGHT GREY



WAC00026
DRAWSTRING
HELMET BAG

All colors are available as made-to-order with Longer Chinstrap (↔ +10 cm)
Part number WHE00127 - Zenith X AIR LC

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM
EN 50365 (Class 0)
CE 2008 **UK** 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycloled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 52 to 63 cm



WEIGHT
490 g



CATEGORY
III

ORDER LOGISTICS

MASTERBOX
pieces 18

DIMENSIONS
cm 82 x 47 x 56

WEIGHT
kg 16

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X AIR HI VIZ

Exceptional safety and comfort designed with ventilation channels and multiple accessory options for enhanced protection. Available in high-visibility color options.

WHE00076

EN 397 - EN 50365



WHE00076-201
WHITE



WHE00076-221
YELLOW FLUO



WHE00076-222
ORANGE FLUO

INCLUDES



WAC00026
DRAWSTRING
HELMET BAG

All colors are available as made-to-order with Longer Chinstrap (↔ +10 cm)

Part number WHE00128 - Zenith X AIR LC HI VIZ

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM
EN 50365 (Class 0)
CE 2008 **UK** 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



CATEGORY
III



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 52 to 63 cm



WEIGHT
490 g

ORDER LOGISTICS

MASTERBOX
pieces 18

DIMENSIONS
cm 82 x 47 x 56

WEIGHT
kg 16

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X PL

Exceptional safety and comfort designed with ventilation channels and multiple accessory options for enhanced protection. Exceeds EN Mountaineering standards.

WHE00079

EN 12492



42



WHE00079-201
WHITE



WHE00079-202
YELLOW



WHE00079-203
ORANGE



WHE00079-204
RED



WHE00079-210
BLACK




WHE00079-214
PINK

INCLUDES



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS

**MATERIAL**

EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon

**TEMPERATURE OF USE**

-20°C / +35°C

**SIZE**

Adjustable from 52 to 63 cm

**WEIGHT**

480 g

**CATEGORY**

II

ORDER LOGISTICS

MASTERBOX
pieces 18

DIMENSIONS
cm 82 x 47 x 56

WEIGHT
kg 15,5

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X PL HI VIZ

Exceptional safety and comfort designed with ventilation channels and multiple accessory options for enhanced protection. Exceeds EN Mountaineering standards. Available in high-visibility color options.

WHE00080

EN 12492



WHE00080-201
WHITE



WHE00080-221
YELLOW FLUO

INCLUDES



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



MATERIAL

EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE

-20°C / +35°C



SIZE

Adjustable from 52 to 63 cm



CATEGORY

II



WEIGHT

480 g

ORDER LOGISTICS

MASTERBOX
pieces 18

DIMENSIONS
cm 82 x 47 x 56

WEIGHT
kg 15,5

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X MAX

Maximizing the potential of the exponential upgrade.

WHE00130
EN 397 - EN 50365



46



WHE00130-201
WHITE



WHE00130-202
YELLOW



WHE00130-203
ORANGE



WHE00130-204
RED



WHE00130-205
GREEN
(made-to-order)



WHE00130-206
BRITISH GREEN
(made-to-order)



WHE00130-208
BLUE



WHE00130-209
ANTHRACITE
(made-to-order)



WHE00130-210
BLACK



WHE00130-214
PINK
(made-to-order)



WHE00130-215
LIGHT GREY
(made-to-order)



INCLUDES



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)

CE 2008

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration



CATEGORY
III



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 60 to 66 cm



WEIGHT
570 g

ORDER LOGISTICS

MASTERBOX
pieces 16

DIMENSIONS
cm 51 x 60 x 74

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

KASK

ZENITH X MAX HI VIZ

Maximizing the potential of the exponential upgrade. Available in high-visibility color options.

WHE00131
EN 397 - EN 50365



WHE00131-201
WHITE



WHE00131-221
YELLOW

INCLUDES



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)

CE 2008

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 60 to 66 cm



WEIGHT
570 g



CATEGORY
III

ORDER LOGISTICS

MASTERBOX
pieces 16

DIMENSIONS
cm 51 x 60 x 74

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X MAX AIR

Maximizing the potential of the exponential upgrade with ventilation channels. Available in high-visibility color options.

WHE00132
EN 397



WHE00132-201
WHITE



WHE00132-202
YELLOW



WHE00132-203
ORANGE



WHE00132-204
RED



WHE00132-205
GREEN
(made-to-order)



WHE00132-206
BRITISH GREEN
(made-to-order)



WHE00132-208
BLUE



WHE00132-209
ANTHRACITE
(made-to-order)



WHE00132-210
BLACK



WHE00132-214
PINK
(made-to-order)



WHE00132-215
LIGHT GREY
(made-to-order)



INCLUDES

WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM



EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 60 to 66 cm



WEIGHT
570 g



CATEGORY
II

ORDER LOGISTICS

MASTERBOX
pieces 16

DIMENSIONS
cm 51 x 60 x 74

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X MAX AIR HI VIZ

Maximizing the potential of the exponential upgrade with ventilation channels. Available in high-visibility color options.

WHE00133
EN 397



WHE00133-201
WHITE



WHE00133-221
YELLOW

INCLUDES



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM



EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



CATEGORY
II



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 60 to 66 cm



WEIGHT
570 g

ORDER LOGISTICS

MASTERBOX
pieces 16

DIMENSIONS
cm 51 x 60 x 74

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X COMBO

Exceptional safety and comfort designed with preinstalled mesh face shield and earmuffs for enhanced protection in high-voltage environments.

WHE00077

EN 397 - EN 50365



54



WHE00077-203
ORANGE



WHE00077-221
YELLOW FLUO



WHE00077-210
BLACK

INCLUDES



WHP00005
EARMUFFS SC2



VV100009
ZEN MM VISOR



WAC00009
EASY CLICK
ADAPTERS



WAC00010
VISOR CARRIER



VV100011
BRIM



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)

CE 2008 UK CA 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact,
4.2.1.4 rear impact
4.2.2 | Penetration



CATEGORY
III

VISOR
STANDARD
EN 1731
ANSI Z87.1

CATEGORY: II

CE UK CA

EARMUFFS
STANDARD
EN 352-3
ANSI S3.19

CATEGORY: III

CE UK CA 1974



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 52 to 63 cm



WEIGHT
490 g (helmet)

ORDER LOGISTICS

MASTERBOX
pieces 8

DIMENSIONS
cm 82 x 54 x 47

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X AIR COMBO

Exceptional safety and comfort designed with ventilation channels, preinstalled mesh face shield and earmuffs for enhanced protection.

WHE00078

EN 397 - EN 50365



56



WHE00078-203
ORANGE



WHE00078-221
YELLOW FLUO



WHE00078-210
BLACK

INCLUDES



WHP00005
EARMUFFS SC2



WVI00009
ZEN MM VISOR



WAC00009
EASY CLICK
ADAPTERS



WAC00010
VISOR CARRIER



WVI00011
BRIM



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM
EN 50365 (Class 0)

CE 2008 UK CA 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact,
4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



CATEGORY
III

VISOR
STANDARD
EN 1731
ANSI Z87.1

CATEGORY: II

CE UK CA

EARMUFFS
STANDARD
EN 352-3
ANSI S3.19

CATEGORY: III

CE UK CA 1974



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Adjustable from 52 to 63 cm



WEIGHT
490 g

ORDER LOGISTICS

MASTERBOX
pieces 8

DIMENSIONS
cm 82 x 54 x 47

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

ZENITH X PL COMBO

Exceptional safety and comfort designed with ventilation channels, preinstalled mesh face shield and earmuffs for enhanced protection. Exceeds EN Mountaineering standards.

WHE00081

EN 12492



WHE00081-203
ORANGE



WHE00081-221
YELLOW FLUO



WHE00081-210
BLACK

INCLUDES



WHP00005
EARMUFFS SC2



WV100009
ZEN MM VISOR



WAC00009
EASY CLICK
ADAPTERS



WAC00010
VISOR CARRIER



WV100011
BRIM



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS

 HELMET STANDARD EN 12492  	VISOR STANDARD EN 1731 ANSI Z87.1	 MATERIAL EXTERNAL SHELL: HD Polypropylene INTERNAL SHELL: Neopor® Cycled® by BASF HEADBAND: Soft PA Nylon
 CATEGORY II	CATEGORY: II   EARMUFFS STANDARD EN 352-3 ANSI S3.19	 TEMPERATURE OF USE -20°C / +35°C  SIZE Adjustable from 52 to 63 cm
	CATEGORY: III   1974	 WEIGHT 480 g (helmet)

ORDER LOGISTICS

MASTERBOX
pieces 8

DIMENSIONS
cm 82 x 54 x 47

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

PRIMERO

— 60

Our commitment to safety, comfort, and design enabled the development of a helmet that makes it easy for anyone to experience advanced head protection.





FEATURES.



FRONT ATTACHMENT POINT
Holds accessories such as badges and headlamps.



POLYPROPYLENE HD EXTERNAL SHELL
Lightweight external shell with exponential better performance. Excels in impact absorption, especially at lower temperatures (-30°C). Resists yellowing and degradation.



EARMUFF ATTACHMENT SLOTS
Designed with integrated slots for attaching earmuffs.



RING TO HOOK
Enables secure attachment of helmet to harness or other items.



EASY CLICK SYSTEM
Integrated slots that enable seamless accessory attachment. Applies to KASK eye, face, and hearing protection.



ADVANCED LITE CHINSTRAP
Chinstrap with 5 adjustment points for a personalized fit. Accommodates wider head sizes and adapts to earmuff use. Color-coded fasteners indicate EN standard compliance rating.

**CLICK-IN SYSTEM**

Attachment system that lets padding easily snap in and out.

**NEOPOR® CCYCLED® INTERNAL SHELL**

Inner shell composed of high-density Neopor® Cycled® foam for all-around impact energy absorption and improved comfort.

**VENTILATION CHANNELS**

14 air intakes shaped for preventing debris entry.

**ERGO FIT SYSTEM**

Helmet size adjusting system that allows for an easy and secure fit by turning the large diameter dial. The system moves up and down to adapt to a range of head shapes. The ergonomically shaped wings cradle the back of the neck for added comfort.

**2DRY LINER**

Moisture-wicking fabric technology for all-day comfort.

**LATERAL ADJUSTMENT DIVIDER**

Side adjustment points on chin-strap for secure fit.



PRIMERO

Advanced head protection made easy.

WHE00111
EN 397 - EN 50365



64



WHE00111-201
WHITE



WHE00111-202
YELLOW



WHE00111-203
ORANGE



WHE00111-204
RED



WHE00111-205
GREEN



WHE00111-206
BRITISH GREEN
(made-to-order)



WHE00111-207
ROYAL
(made-to-order)



WHE00111-208
BLUE



WHE00111-210
BLACK




WHE00111-209
ANTHRACITE
(made-to-order)



WHE00111-215
LIGHT GREY
(made-to-order)

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)

CE 2008 UK 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.1 top impact, 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: Neopor® Cycled® by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Universal-adjustable from 52 to 63 cm



WEIGHT
460 g



CATEGORY
III

ORDER LOGISTICS

MASTERBOX
pieces 24

DIMENSIONS
cm 79,5 x 58 x 47

WEIGHT
kg 17

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

PRIMERO HI VIZ

Advanced head protection made easy. Available in high-visibility color options.

WHE00112
EN 397 - EN 50365



WHE00112-201
WHITE



WHE00112-221
YELLOW FLUO



WHE00112-222
ORANGE FLUO
(made-to-order)

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)

CE 2008 UK 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.1 top impact, 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Universal-adjustable from 52 to 63 cm



WEIGHT
460 g



CATEGORY
III

ORDER LOGISTICS

MASTERBOX
pieces 24

DIMENSIONS
cm 79,5 x 58 x 47

WEIGHT
kg 17

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

PRIMERO AIR

Advanced vented head protection made easy.

WHE00113
EN 397 - EN 50365



WHE00113-201
WHITE



WHE00113-202
YELLOW



WHE00113-203
ORANGE



WHE00113-204
RED



WHE00113-205
GREEN



WHE00113-206
BRITISH GREEN
(made-to-order)



WHE00113-207
ROYAL
(made-to-order)



WHE00113-208
BLUE



WHE00113-210
BLACK




WHE00113-209
ANTHRACITE
(made-to-order)



WHE00113-215
LIGHT GREY
(made-to-order)

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM
EN 50365 (Class 0)
CE 2008 **UK** 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.1 top impact, 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Universal-adjustable from 52 to 63 cm



WEIGHT
460 g



CATEGORY
III

ORDER LOGISTICS

MASTERBOX
pieces 24

DIMENSIONS
cm 79,5 x 58 x 47

WEIGHT
kg 17

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

PRIMERO AIR HI VIZ

Advanced vented head protection made easy. Available in high-visibility color options.

WHE00114
EN 397 - EN 50365



WHE00114-201
WHITE



WHE00114-221
YELLOW FLUO



WHE00114-222
ORANGE FLUO
(made-to-order)

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM
EN 50365 (Class 0)
CE 2008 **UK** 8503

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.1 top impact, 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Universal-adjustable from 52 to 63 cm



WEIGHT
460 g



CATEGORY
III

ORDER LOGISTICS

MASTERBOX
pieces 24

DIMENSIONS
cm 79,5 x 58 x 47

WEIGHT
kg 17

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

PRIMERO PL

Advanced head protection made easy meets the EN mountaineering standard.

WHE00115
EN 12492



WHE00115-201
WHITE



WHE00115-202
YELLOW



WHE00115-203
ORANGE



WHE00115-204
RED



WHE00115-206
BRITISH GREEN
(made-to-order)



WHE00115-210
BLACK



WHE00115-209
ANTHRACITE
(made-to-order)



WHE00115-215
LIGHT GREY
(made-to-order)

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 12492



EN 397 | -30°C / LD / MM
for the following clauses only:
5.1.1 | Top impacts
5.1.2 | Penetration
5.1.3 | Flame resistance



CATEGORY
II

**MATERIAL**

EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® CCycled®** by BASF
HEADBAND: Soft PA Nylon

**TEMPERATURE OF USE**

-30°C / +50°C

**SIZE**

Universal-adjustable from 52 to 63 cm

**WEIGHT**

460 g

ORDER LOGISTICS

MASTERBOX
pieces 24

DIMENSIONS
cm 79,5 x 58 x 47

WEIGHT
kg 17

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

PRIMERO PL HI VIZ

Advanced head protection made easy meets the EN mountaineering standard. Available in high-visibility color options.

WHE00116

EN 12492



WHE00116-201
WHITE



WHE00116-221
YELLOW FLUO



WHE00116-222
ORANGE FLUO
(made-to-order)

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 12492



EN 397 | -30°C / LD / MM
for the following clauses only:
5.1.1 | Top impacts
5.1.2 | Penetration
5.1.3 | Flame resistance

**MATERIAL**

EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon

**TEMPERATURE OF USE**

-30°C / +50°C

**SIZE**

Universal-adjustable from 52 to 63 cm

**WEIGHT**

460 g

**CATEGORY**

II

ORDER LOGISTICS

MASTERBOX
pieces 24

DIMENSIONS
cm 79,5 x 58 x 47

WEIGHT
kg 17

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

SUPERPLASMA

— 76

With a globally recognized design that signals KASK, these helmets enable workers to perform with confidence in a variety of demanding applications.

R130



FEATURES.



VENTILATION CHANNELS

Helmet designed with 10 air intakes that maximize internal airflow through outflow channels providing exceptional helmet breathability.



ANTI-INTRUSION MESH

Metal mesh vent covers that prevent debris from entering the ventilation channels while maintaining breathability.



HD POLYPROPYLENE EXTERNAL SHELL

Offers high impact resistance and lighter weight.



INTEGRATED LAMP CLIPS

Designed with 4 built-in, nylon lamp attachment points. Compatible with KASK headlamps and other headlamps with elastic bands.



LATERAL ADJUSTMENT DIVIDER

Side adjustment points on chinstrap for secure fit.

**2DRY LINER**

A quick-drying technical fabric that accelerates the dispersion of sweat and moisture to the surface of the helmet padding for a dryer, more comfortable wear.

**VISOR ATTACHMENT POINTS**

Helmet designed with attachment points for securing KASK eye protection accessories.

**QUICK FIT SYSTEM**

Size adjustment system for maximum stability, easy to use thanks to a large diameter wheel.

**DETACHABLE INNER PADDING**

Hook-and-loop-enabled for easy removal, replacement, and washing.

**EARMUFF ADAPTER ATTACHMENT POINTS**

Helmet designed with attachment points for earmuff adapters.



SUPERPLASMA AQ

The global benchmark for quality, safety, and design.

WHE00104
EN 397



WHE00104-201
WHITE



WHE00104-202
YELLOW



WHE00104-203
ORANGE



WHE00104-204
RED



WHE00104-205
GREEN



WHE00104-206
BRITISH GREEN



WHE00104-207
ROYAL



WHE00104-208
BLUE




WHE00104-210
BLACK



WHE00104-214
PINK

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM



EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



CATEGORY
II



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Universal-adjustable from 51 to 63 cm



WEIGHT
390 g

ORDER LOGISTICS

MASTERBOX
pieces 24

DIMENSIONS
cm 82 x 54 x 47

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

SUPERPLASMA AQ HI VIZ

The global benchmark for quality, safety, and design. Available in high-visibility color options.

WHE00105
EN 397



82



WHE00105-201
WHITE



WHE00105-208
BLUE



WHE00105-210
BLACK



WHE00105-221
YELLOW FLUO



WHE00105-222
ORANGE FLUO



WHE00105-223
RED FLUO



WHE00105-224
LIME FLUO



WHE00105-241
WHITE/RED




WHE00105-251
BLUE/YELLOW



WHE00105-253
WHITE/GREEN

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 397 | -30°C / LD / MM



EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
4.2.2 | Penetration
4.1.4 | Ventilation



CATEGORY
II



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-30°C / +50°C



SIZE
Universal-adjustable from 51 to 63 cm



WEIGHT
390 g

ORDER LOGISTICS

MASTERBOX
pieces 24

DIMENSIONS
cm 82 x 54 x 47

WEIGHT
kg 14

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

SUPERPLASMA HP

Designed for demanding environments that require High Performance standards.

WHE00106
EN 14052



WHE00106-201
WHITE



WHE00106-202
YELLOW



WHE00106-204
RED

FEATURED TECHNOLOGIES



ABS EXTERNAL SHELL



HD EPS INTERNAL SHELL



2DRY LINER



QUICK FIT SYSTEM



RING TO HOOK



EARMUFF ATTACHMENT SLOTS



VENTILATION CHANNELS



VISOR ATTACHMENT POINTS



INTEGRATED LAMP CLIPS



TECHNICAL DETAILS

**STANDARD**
EN 14052

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
EN 397 | LD
for the following clauses only:
5.1.1 | Shock absorption
5.1.2 | Penetration resistance

**CATEGORY**
II**MATERIAL**

EXTERNAL SHELL: ABS
INTERNAL SHELL: HD Expanded Polystyrene
HEADBAND: Soft PA Nylon

**TEMPERATURE OF USE**

-10°C / +50°C

**SIZE**

Universal-adjustable from 51 to 63 cm

**WEIGHT**

450 g

ORDER LOGISTICS

MASTERBOX
pieces 24**DIMENSIONS**
cm 82 x 54 x 47**WEIGHT**
kg 16

KASK DURABILITY

3 YEARS
GUARANTEE**10** YEARS
LIFE SPAN

SUPERPLASMA HP VISOR

Designed for demanding environments that require High Performance standards. Available in high-visibility color options with preinstalled visor.

WHE00107

EN 14052



86



WHE00107-201
WHITE



WHE00107-202
YELLOW



WHE00107-204
RED

INCLUDES



VV100036-500
V2 PLUS CLEAR



WAC00026
DRAWSTRING
HELMET BAG

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



STANDARD
EN 14052



EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact
EN 397 | LD
for the following clauses only:
5.1.1 | Shock absorption
5.1.2 | Penetration resistance



CATEGORY
II

**VISOR
STANDARD**
EN ISO 16321 | EN 14458
ANSI Z87.1

CATEGORY: II



MATERIAL
EXTERNAL SHELL: ABS
INTERNAL SHELL: HD Expanded Polystyrene
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-10°C / +50°C



SIZE
Universal-adjustable from 51 to 63 cm



WEIGHT
450 g (helmet)

ORDER LOGISTICS

MASTERBOX
pieces 12

DIMENSIONS
cm 61 x 47 x 69

WEIGHT
kg 12

KASK DURABILITY

**3 YEARS
GUARANTEE**

**10 YEARS
LIFE SPAN**

SUPERPLASMA PL

The preferred choice for active and above-ground applications.

WHE00108
EN 12492



WHE00108-201
WHITE



WHE00108-202
YELLOW



WHE00108-203
ORANGE



WHE00108-204
RED



WHE00108-208
BLUE



WHE00108-209
ANTHRACITE




WHE00108-210
BLACK



WHE00108-214
PINK

FEATURED TECHNOLOGIES



TECHNICAL DETAILS



MATERIAL
EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon



TEMPERATURE OF USE
-20°C / +35°C



SIZE
Universal-adjustable from 51 to 62 cm



CATEGORY
II



WEIGHT
420 g

ORDER LOGISTICS

MASTERBOX
pieces 28

DIMENSIONS
cm 82 x 54 x 47

WEIGHT
kg 17

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

SUPERPLASMA PL HI VIZ

The preferred choice for active and above-ground applications. Available in high-visibility color options.

WHE00109

EN 12492



WHE00109-201
WHITE



WHE00109-210
BLACK



WHE00109-221
YELLOW FLUO




WHE00109-223
RED FLUO



WHE00109-224
LIME FLUO

FEATURED TECHNOLOGIES



TECHNICAL DETAILS

**MATERIAL**

EXTERNAL SHELL: HD Polypropylene
INTERNAL SHELL: **Neopor® Cycled®** by BASF
HEADBAND: Soft PA Nylon

**TEMPERATURE OF USE**

-20°C / +35°C

**SIZE**

Universal-adjustable from 51 to 62 cm

**CATEGORY**

II

**WEIGHT**

420 g

ORDER LOGISTICS

MASTERBOX
pieces 28

DIMENSIONS
cm 82 x 54 x 47

WEIGHT
kg 17

KASK DURABILITY

3 YEARS
GUARANTEE

10 YEARS
LIFE SPAN

EYE & FACE PROTECTION

— 92

SEE EASY

An advanced range of eye and face protection solutions designed to meet workers' needs for an expanding variety of dynamic hazardous environments.



OVERVIEW OF SELECT STANDARDS FOR KASK EYE & FACE PROTECTION

EUROPEAN STANDARDS

EN ISO 16321

The new European safety standard required for eye and face protection for industrial use.

EN ISO 16321-1:2020 (Part 1) – General requirements
EN ISO 16321-2:2020 (Part 2) – Welding requirements
EN ISO 16321-3:2020 (Part 3) – Mesh visor requirements

MARKINGS:

OPTICAL CLASS

1 – Enhanced optical performance (optional)

LIGHT PROTECTION CODE

W – Welding filter (scale of 1.2 to 10)
U – Ultraviolet filter (scale of 1.2 to 5)
R – Infrared filter (scale of 1.2 to 10)
G – Sun glare filter (scale of 0 to 4)
L – Lens does not affect color or light

HEADFORMS

1-S - European headform Small
1-M - European headform Medium
1-L - European headform Large
2-S – Asian headform Small
2-M - Asian headform Medium
2-L - Asian headform Large
M – Medium size only

MECHANICAL PROTECTION

C – Low Impact Resistance (45m/s) + OPZ*
D – Medium Impact Resistance (80m/s) + EOZ*
E – High Impact Resistance (120m/s) + FPZ*
CT – Low Impact at Extreme Temp (45m/s)
DT – Medium Impact at Extreme Temp (80m/s)
ET – High Impact at Extreme Temp (120m/s)
HM – High Mass (500g) Impact Resistance

* Note: Impact protection levels are now accompanied by a *protection zone* code — the higher the impact level, the larger the required protection zone.

OPZ: Orbital Protection Zone
EOZ: Extended Orbital Protection Zone
FPZ: Face Protection Zone

FIELD OF USE

3 – Protection against liquid droplets
4 – Protection against large dust particles
5 – Protection against gas and fine dust particles
6 – Protection against streams of liquid
7 – Protection against radiant heat
9 – Protection against molten metal and hot solids

OPTIONAL REQUIREMENTS

K – Protection against fine dust particles
N – Resistance to lens fogging
CH – Chemical resistance

EN 166

The core European safety standard required for eye and face protection. Includes a number of sub-categories.

SUPPLEMENTAL STANDARDS

EN 167 – Optical test methods
EN 168 – Non-optical test methods
EN 169 – Welding filters and related techniques
EN 170 – Ultraviolet (UV) filters
EN 171 – Infrared filters
EN 172 – Solar filters for industrial use
EN 1731 – Mesh face protection
EN 379 – Automatic welding filters
DGUV GS ET29 / ET30 – Arc flash protection

MARKINGS:

There are a number of standards and markings for eye and face protection. Selected ones are described here. Contact a KASK representative for additional information.

OPTICAL CLASS

1 – Best optical quality, for regular use
2 – Lesser optical quality, for occasional use
3 – Lowest optical quality, for exceptional use

LIGHT PROTECTION CODE

NONE – Welding filter
2 – Ultraviolet filter
2C – Ultraviolet filter with good color recognition
4 – Infrared filter
5 – Solar filter
6 – Solar filter with infrared protection

LIGHT PROTECTION GRADUATION

1.2 – Clear
1.7 – Yellow, clear with mirror finishing, UVR
2.5 – Brown, smoke
3.1 – Green, smoke with mirror finishing
3,2,5,...11 – Welding

MECHANICAL PROTECTION

A (T) – Resistance to high speed/high energy impact
B (T) – Resistance to high speed/medium energy impact
F (T) – Resistance to high speed/low energy impact
S – Increased robustness
A, B, or F, followed by T, indicates extreme temperature impact protection (-5° C / +55° C)

FIELD OF USE

3 – Protection against liquid droplets, splashes
4 – Protection against large dust particles
5 – Protection against fine dust particles
8 – Protection against short circuit electric arcs
9 – Protection against molten metal and hot solids

OPTIONAL REQUIREMENTS

K – Protection against fine dust particles
N – Resistance to lens fogging
H – Products designed for small heads
R – Enhanced infrared reflectance

EN 14458

The European standard for high performance visors used with protective helmets for firefighting, ambulance and emergency services.

MARKINGS:**CLASSIFICATION**

= – General use
+ – Firefighter use
NONE – Net visors

PROTECTED AREA

☺ – Face protection
● – Eye protection

MECHANICAL & LIGHT PROTECTION

(same as EN ISO 16321 & EN 166)

**AMERICAN STANDARDS****ANSI Z87.1**

The U.S. safety standard for testing, marking, and maintaining eye and face protection – includes sub-categories.

SUPPLEMENTAL STANDARDS*

ASTM F2178 – Arc flash protection

MARKINGS:

There are a number of standards and markings for eye and face protection. Selected ones are described here. Contact a KASK representative for additional information.

MECHANICAL PROTECTION

Z87 – General lens and frame impact resistance
Z87+ – Impact mark

FILTER PERFORMANCE

NONE – Clear lens
U – Ultraviolet filter
V – Variable tint filter
W – Welding filter
L – Visible light filter
R – Infrared filter
X – Anti-fog filter
S – Special purpose lenses

Symbols are followed by a number, indicating filter performance level

FIELD OF USE

D3 – Protection against droplets, splashes
D4 – Protection against dust
D5 – Protection against fine dust



MARKINGS OVERVIEW.

EN ISO 16321

		STANDARDS	VLT	COMPATIBLE HELMETS
V2 PLUS VISOR	CLEAR	EN ISO 16321 - EN 14458 - ANSI Z87.1	85%	SUPERPLASMA AQ HP PL
	SMOKE	EN ISO 16321 - EN 14458 - ANSI Z87.1	62.5%	SUPERPLASMA AQ HP PL
	SILVER MIRROR	EN ISO 16321 - EN 14458 - ANSI Z87.1	26.5%	SUPERPLASMA AQ HP PL
V2 FULL FACE VISOR	CLEAR	EN ISO 16321 - ANSI Z87.1	88%	SUPERPLASMA AQ HP PL
	SMOKE	EN ISO 16321 - ANSI Z87.1	37%	SUPERPLASMA AQ HP PL
	SILVER MIRROR	EN ISO 16321 - ANSI Z87.1	32%	SUPERPLASMA AQ HP PL
ZEN VISOR	CLEAR	EN ISO 16321 - ANSI Z87.1	89%	ZENITH X / PRIMERO
	SMOKE	EN ISO 16321 - ANSI Z87.1	65%	ZENITH X / PRIMERO
	SILVER MIRROR	EN ISO 16321 - ANSI Z87.1	26%	ZENITH X / PRIMERO
ZEN FOAM VISOR	CLEAR	EN ISO 16321 - ANSI Z87.1	89%	ZENITH X / PRIMERO
	SMOKE	EN ISO 16321 - ANSI Z87.1	65%	ZENITH X / PRIMERO
	SILVER MIRROR	EN ISO 16321 - ANSI Z87.1	26%	ZENITH X / PRIMERO
ARC VISOR CLASS 1	CLEAR	EN ISO 16321 - DGUV GS ET29	88%	ZENITH X / PRIMERO
ARC VISOR CLASS 2 ERGO	SMOKE	ISO 16321 - DGUV GS ET29 Additional ANSI test: ASTM F2178: ATPV 12.0 cal/cm² ARC 2	43%	ZENITH X / PRIMERO
ZEN PLUS VISOR	CLEAR	EN ISO 16321 - ANSI Z87.1	89%	ZENITH X / PRIMERO
	SMOKE	EN ISO 16321 - ANSI Z87.1	65%	ZENITH X / PRIMERO
	SILVER MIRROR	EN ISO 16321 - ANSI Z87.1	26%	ZENITH X / PRIMERO
ZEN FF PLUS VISOR	CLEAR	EN ISO 16321 - ANSI Z87.1	65%	ZENITH X / PRIMERO
	SILVER MIRROR	EN ISO 16321 - ANSI Z87.1	26%	ZENITH X / PRIMERO

EN 166

MESH VISOR	STEEL MESH	EN 166 - EN 1731 - ANSI Z87.1	-	SUPERPLASMA AQ HP PL
ZEN FF VISOR	CLEAR	EN 166 - EN 170 - ANSI Z87.1	90%	ZENITH X / PRIMERO
	SMOKE	EN 166 - EN 172 - ANSI Z87.1	22%	ZENITH X / PRIMERO
ZEN VISOR MM	METAL MESH	EN 166 - EN 1731 - ANSI Z87.1	-	ZENITH X / PRIMERO

CATEGORY	LIGHT PROTECTION CODE	ENHANCED OPTICAL PERFORMANCE	MECHANICAL PROTECTION	OPTIONAL REQUIREMENTS	FIELD OF USE	ELECTRIC ARC PROTECTION			CLASSIFICATION	PROTECTED AREA	EXTREME TEMPERATURES	ABRASION RESISTANCE	MOLTEN METAL/SOLID LIQUID	IMPACT RESISTANCE	UV FILTER	VISIBLE LIGHT FILTER	ANTI-FOGGING	SPLASH/DROPLETS PROTECTION
						CLASS	TRANSMISSION CLASS											
EN ISO 16321							DGUV GS-ET-29			EN 14458				ANSI Z87.1				
II	UL1,2	1	DT	KN CH	7	-	-	-	=	-	-30°C / +50°C	√	√	+	U6	-	X	D3
II	GL1	1	DT	KN CH	7	-	-	-	=	-	-30°C / +50°C	√	√	+	U6	L1.5	X	D3
II	G2	1	DT	KN CH	7	-	-	-	=	-	-30°C / +50°C	√	√	+	U6	L2.5	X	D3
II	UL1,2	-	ET	KN CH 9	9	-	-	-	-	-	-	-	-	+	-	-	X	D3
II	GL2	-	ET	KN CH 9	9	-	-	-	-	-	-	-	-	+	U6	L2	X	D3
II	GL1	-	ET	KN CH 9	9	-	-	-	-	-	-	-	-	+	U6	L2	X	D3
II	UL1,2	1	DT	KN CH	-	-	-	-	-	-	-	-	-	+	U6	-	X	D3
II	GL1	1	DT	KN CH	-	-	-	-	-	-	-	-	-	+	U6	L1.5	X	D3
II	GL2	1	DT	KN CH	-	-	-	-	-	-	-	-	-	+	U6	L2.5	X	D3
II	UL1,2	1	DT	KN CH	-	-	-	-	-	-	-	-	-	+	U6	-	X	D3
II	GL1	1	DT	KN CH	-	-	-	-	-	-	-	-	-	+	U6	L1.5	X	D3
II	GL2	1	DT	KN CH	-	-	-	-	-	-	-	-	-	+	U6	L2.5	X	D3
III	UL1,2	-	E	-	6	8	1	0	-	-	-	-	-	-	U6	-	-	-
III	UL2	-	E	-	6-9	8	2	2	-	-	-	-	-	-	U6	-	-	-
III	UL1,2	1	DT	KN CH	-	-	-	-	=	☉	-30°C / +50°C	√	√	+	U6	-	X	D3
III	GL1	1	DT	KN CH	-	-	-	-	=	☉	-30°C / +50°C	√	√	+	U6	L1.5	X	D3
III	GL2	1	DT	KN CH	-	-	-	-	=	☉	-30°C / +50°C	√	√	+	U6	L2.5	X	D3
III	UL1,2	1	ET	KN CH	9	-	-	-	+R1	☹	-30°C / +50°C	√	√	+	U6	-	X	D3
III	GL2	1	ET	KN CH	9	-	-	-	+R1	☹	-30°C / +50°C	√	√	+	U6	-	X	D3
OPTICAL CLASS																		
II	-	-	F	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
II	2C-1.2	1	BT	KN	3-9	-	-	-	-	-	-	-	-	+	U6	-	X	D3
II	5-2.5	1	BT	KN	3-9	-	-	-	-	-	-	-	-	+	U6	L2.5	X	D3
II	-	-	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-



OVERVIEW OF TECHNOLOGIES.



COMPATIBLE WITH GLASSES

Designed for use over corrective glasses.



ANTI-FOG

Equipped with an anti-fog treatment to increase wearer visibility in a variety of conditions.



MICRO VENTILATION

Provides airflow and breathability while resisting debris intrusion.



PANORAMIC LENS

Developed to maximize visibility with minimal viewing distortion.



CUT PROOF EDGE

Eye shield edge detail designed with a cut proof edge for enhanced wearer safety.



DRIP PROOF UPPER CONTOUR

Rubber edge protects eyes from liquid and debris from entering the visor.



DEBRIS PROTECTION

Designed with a reinforced frame for protection against debris.



HEXAGONAL MESH

The hexagonal mesh pattern provides airflow, visibility and durability.



ANTI-INTRUSION GUARDS

Highly comfortable polyurethane foam that protects against dust, liquids and chemical splashes.



STABLE CARRIER

Reinforced face shield carrier for added protection and durability.



SEE-THROUGH CHIN PROTECTION

Equipped with transparent chin protection for enhanced range of visibility.



ABRASION AND SCRATCH RESISTANCE

Lens treatment designed with protection from abrasion and scratches with increased durability and viewing clarity.



EXTREME TEMP IMPACT RESISTANCE

Able to withstand impacts at extreme temperatures for use in a variety of environments.



> CRI 95

Designed with excellent Color Rendering Index (CRI) performance for greater color contrast and visibility.



ZEN VISOR

WVI00038
EN ISO 16321 - ANSI Z87.1



OPTIONS



WVI00038-500
CLEAR



WVI00038-510
SMOKE



WVI00038-520
SILVER MIRROR

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

ALL VISORS NEED ADAPTERS (WAC00009) TO BE MOUNTED ON HELMET.

TECHNICAL DETAILS

MATERIAL Polycarbonate	STANDARD EN ISO 16321 CE
LENGTH 110 mm	ANSI Z87.1
WEIGHT 80 g	CATEGORY II

ENHANCED OPTICAL PERFORMANCE
1

MARKINGS

CLEAR: ZEN | MM/YY | CE | KASK | UL1,2 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH
SMOKE: ZEN | MM/YY | CE | KASK | GL1 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH
SILVER MIRROR: ZEN | MM/YY | CE | KASK | GL2 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH

ORDER LOGISTICS

MASTERBOX	pieces	36
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	10

TECHNOLOGIES



ANTI-FOG



ABRASION
AND
SCRATCH
RESISTANCE



PANORAMIC
LENS



CUT PROOF
EDGE



DRIP PROOF
UPPER CON-
TOUR



COMPATIBLE
WITH
GLASSES



EASY CLICK
ADAPTERS

ZENITH X | PRIMERO KIT

ZEN VISOR KIT

WKI00020
EN ISO 16321 - ANSI Z87.1



OPTIONS



WKI00020-500
KIT ZEN VISOR
CLEAR



WKI00020-510
KIT ZEN VISOR
SMOKE



WKI00020-520
KIT ZEN VISOR
SILVER MIRROR

KIT INCLUDES



=



WVI00038-500 | 510 | 520
VISOR

+



WAC00009
ADAPTERS

TECHNICAL DETAILS

MATERIAL Polycarbonate	STANDARD EN ISO 16321 CE
LENGTH 110 mm	ANSI Z87.1
WEIGHT 80 g	CATEGORY II

ENHANCED OPTICAL PERFORMANCE
1

MARKINGS

CLEAR: ZEN | MM/YY | CE | KASK | UL1,2 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH
SMOKE: ZEN | MM/YY | CE | KASK | GL1 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH
SILVER MIRROR: ZEN | MM/YY | CE | KASK | GL2 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH

ORDER LOGISTICS

MASTERBOX	pieces	36
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	10

TECHNOLOGIES



ANTI-FOG



ABRASION
AND
SCRATCH
RESISTANCE



PANORAMIC
LENS



CUT PROOF
EDGE



DRIP PROOF
UPPER CON-
TOUR



COMPATIBLE
WITH
GLASSES



EASY CLICK
ADAPTERS

ZENITH X | PRIMERO

ZEN FF VISOR

WVI00008
EN 166 - EN 170 (clear) - EN 172 (smoke) - ANSI Z87.1



OPTIONS



WVI00008-500
CLEAR



WVI00008-510
SMOKE

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

ALL VISORS NEED ADAPTERS (WAC00009) AND VISOR CARRIER (WAC00010) TO BE MOUNTED ON HELMET.

TECHNICAL DETAILS

MATERIAL	Polycarbonate	STANDARD	EN 166 EN 170 (clear) EN 172 (smoke)
LENGTH	120 mm		CE UK CA
			ANSI Z87.1
WEIGHT	190 g	CATEGORY	II
OPTICAL CLASS	1	TEMPERATURE OF USE	-5°C / +55°C

MARKINGS

CLEAR:
ZEN FF | MM/YY | CE | UKCA | 2C-1,2 | KASK | 1 | BT | 3 | 9 | KN | EN166

SMOKE:
ZEN FF | MM/YY | CE | UKCA | 5-2,5 | KASK | 1 | BT | 3 | 9 | KN | EN166

TECHNOLOGIES



ANTI-FOG



ABRASION AND SCRATCH RESISTANCE



PANORAMIC LENS



EASY CLICK ADAPTERS



DRIP PROOF UPPER CONTOUR



COMPATIBLE WITH GLASSES

ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	8

ZENITH X | PRIMERO KIT

ZEN FF VISOR KIT

WKI00003
EN 166 - EN 170 (clear) - EN 172 (smoke) - ANSI Z87.1



OPTIONS



WKI00003-500
KIT ZEN VISOR
CLEAR



WKI00003-510
KIT ZEN VISOR
SMOKE

KIT INCLUDES



WVI00008-500 | 510
FF VISOR



WAC00009
ADAPTERS



WAC00010
VISOR CARRIER

TECHNICAL DETAILS

MATERIAL	Polycarbonate	STANDARD	EN 166 EN 170 (clear) EN 172 (smoke)
LENGTH	120 mm		CE UK CA
			ANSI Z87.1
WEIGHT	190 g	CATEGORY	II
OPTICAL CLASS	1	TEMPERATURE OF USE	-5°C / +55°C

MARKINGS

CLEAR:
ZEN FF | MM/YY | CE | UKCA | 2C-1,2 | KASK | 1 | BT | 3 | 9 | KN | EN166

SMOKE:
ZEN FF | MM/YY | CE | UKCA | 5-2,5 | KASK | 1 | BT | 3 | 9 | KN | EN166

TECHNOLOGIES



ANTI-FOG



ABRASION AND SCRATCH RESISTANCE



PANORAMIC LENS



EASY CLICK ADAPTERS



DRIP PROOF UPPER CONTOUR



COMPATIBLE WITH GLASSES

ORDER LOGISTICS

MASTERBOX	pieces	36
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	10



ZENITH X | PRIMERO

ZEN METAL MESH VISOR

WVI00009
EN 1731- ANSI Z87.1



OPTIONS



WVI00009
METAL

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

MESH VISOR NEEDS ADAPTERS (WAC00009) AND VISOR CARRIER (WAC00010) TO BE MOUNTED ON HELMET.

TECHNICAL DETAILS

MATERIAL Metal	STANDARD EN 1731  
LENGTH 190 mm	ANSI Z87.1

WEIGHT 100 g	CATEGORY II
OPTICAL CLASS 1	LIGHT TRANSMISSION 50%

MARKINGS

ZEN MM | MM/YY | KASK | CE | UKCA | EN 1731 | S

ORDER LOGISTICS

MASTERBOX DIMENSIONS	pieces	24
WEIGHT	cm	78 x 48 x 50
	kg	10

TECHNOLOGIES



ZENITH X | PRIMERO KIT

ZEN METAL MESH KIT

WKI00005
EN 1731- ANSI Z87.1



OPTIONS



WKI00005
METAL

KIT INCLUDES



TECHNICAL DETAILS

MATERIAL Metal	STANDARD EN 1731  
LENGTH 190 mm	ANSI Z87.1

WEIGHT 100 g	CATEGORY II
OPTICAL CLASS 1	LIGHT TRANSMISSION 50%

MARKINGS

ZEN MM | MM/YY | KASK | CE | UKCA | EN 1731 | S

ORDER LOGISTICS

MASTERBOX DIMENSIONS	pieces	24
WEIGHT	cm	78 x 48 x 50
	kg	10

TECHNOLOGIES



ZENITH X | PRIMERO

ZEN PLUS VISOR

WVI00039
EN ISO 16321 - EN 14458 - ANSI Z87.1



OPTIONS



WVI00039-500
CLEAR



WVI00039-510
SMOKE



WVI00039-520
SILVER MIRROR

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

ALL VISORS NEED ADAPTERS (WAC00074) TO BE MOUNTED ON HELMET.

TECHNICAL DETAILS

MATERIAL	STANDARD
Polycarbonate	EN ISO 16321 EN 14458
LENGTH	CE 2754
110 mm	ANSI Z87.1
WEIGHT	CATEGORY
80 g	III

ENHANCED OPTICAL PERFORMANCE
1

MARKINGS

CLEAR: CE 2754 | EN14458:2018 | KASK | ZEN PLUS | MM/YY | = | O | BT | E1/E3 | 2C-1,2* | -30°C +50°C | □□ | KASK | UL1,2** | DT | 1 | CH | -5°C +55°C | K | N | CH | 16321 | KASK | DT | 1-M | -5°C +55°C
SMOKE: same as clear except for: *5-1,4 | **GL1
SILVER MIRROR: same as clear except for: *5-2,5 | **GL2

ORDER LOGISTICS

MASTERBOX	pieces	36
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	10

TECHNOLOGIES



ANTI-FOG



ABRASION
AND
SCRATCH
RESISTANCE



PANORAMIC
LENS



CUT PROOF
EDGE



DRIP PROOF
UPPER CON-
TOUR



COMPATIBLE
WITH
GLASSES



EASY CLICK
ADAPTERS

ZENITH X | PRIMERO KIT

ZEN PLUS VISOR KIT

WKI00022
EN ISO 16321 - EN 14458 - ANSI Z87.1



OPTIONS



WKI00022-500
KIT ZEN PLUS VISOR
CLEAR



WKI00022-510
KIT ZEN PLUS VISOR
SMOKE



WKI00022-520
KIT ZEN PLUS VISOR
SILVER MIRROR

COMPATIBLE WITH SERIES



WVI00039-500 | 510 | 520
VISOR

WAC00074
FR ADAPTERS

TECHNICAL DETAILS

MATERIAL	STANDARD
Polycarbonate	EN ISO 16321 EN 14458
LENGTH	CE 2754
110 mm	ANSI Z87.1
WEIGHT	CATEGORY
80 g	III

ENHANCED OPTICAL PERFORMANCE
1

MARKINGS

CLEAR: CE 2754 | EN14458:2018 | KASK | ZEN PLUS | MM/YY | = | O | BT | E1/E3 | 2C-1,2* | -30°C +50°C | □□ | KASK | UL1,2** | DT | 1 | CH | -5°C +55°C | K | N | CH | 16321 | KASK | DT | 1-M | -5°C +55°C
SMOKE: same as clear except for: *5-1,4 | **GL1
SILVER MIRROR: same as clear except for: *5-2,5 | **GL2

ORDER LOGISTICS

MASTERBOX	pieces	36
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	10

TECHNOLOGIES



ANTI-FOG



ABRASION
AND
SCRATCH
RESISTANCE



PANORAMIC
LENS



CUT PROOF
EDGE



DRIP PROOF
UPPER CON-
TOUR



COMPATIBLE
WITH
GLASSES



EASY CLICK
ADAPTERS

ZEN FF PLUS VISOR

WV100040

EN ISO 16321 - EN 14458 - ANSI Z87.1



OPTIONS



WV100040-500
CLEAR



WV100040-510
SMOKE

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

ALL VISORS NEED ADAPTERS (WAC00074) TO BE MOUNTED ON HELMET.

TECHNICAL DETAILS

MATERIAL
Polycarbonate

STANDARD
EN ISO 16321
EN 14458

LENGTH
190 mm

CE 2754

WEIGHT
145 g

CATEGORY
III

ENHANCED OPTICAL PERFORMANCE
1

MARKINGS

CLEAR: CE 2754 | EN14458:2018 | KASK | ZEN FF PLUS | MM/YY | +R1 | ☉ | BT | E1/E3 | 2C-1,2* | -30°C +50°C | ☐ | KASK | UL1,2** | ET | 1 | -5°C +55°C | K | N | CH | 9 | 16321 | KASK | ET | 1-M | -5°C +55°C | 3 | CH | 9

SMOKE: same as clear except for: *5-1,4 | **GL2

ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	52 x 49 x 79
WEIGHT	kg	2,5

TECHNOLOGIES



ANTI-FOG



ABRASION
AND
SCRATCH
RESISTANCE



PANORAMIC
LENS



EASY CLICK
ADAPTERS



DRIP PROOF
UPPER CON-
TOUR



COMPATIBLE
WITH
GLASSES

ZENITH X | PRIMERO KIT

ZEN FF PLUS KIT

WK100023

EN ISO 16321 - EN 14458 - ANSI Z87.1



OPTIONS



WK100023-500
KIT ZEN PLUS VISOR CLEAR



WK100023-510
KIT ZEN PLUS VISOR SMOKE

COMPATIBLE WITH SERIES



WV100040-500 | 510
VISOR



WAC00074
FR ADAPTERS

TECHNICAL DETAILS

MATERIAL
Polycarbonate

STANDARD
EN ISO 16321
EN 14458

LENGTH
190 mm

CE 2754

WEIGHT
145 g

CATEGORY
III

ENHANCED OPTICAL PERFORMANCE
1

MARKINGS

CLEAR: CE 2754 | EN14458:2018 | KASK | ZEN FF PLUS | MM/YY | +R1 | ☉ | BT | E1/E3 | 2C-1,2* | -30°C +50°C | ☐ | KASK | UL1,2** | ET | 1 | -5°C +55°C | K | N | CH | 9 | 16321 | KASK | ET | 1-M | -5°C +55°C | 3 | CH | 9

SMOKE: same as clear except for: *5-1,4 | **GL2

ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	52 x 49 x 79
WEIGHT	kg	2,5

TECHNOLOGIES



ANTI-FOG



ABRASION
AND
SCRATCH
RESISTANCE



PANORAMIC
LENS



EASY CLICK
ADAPTERS



DRIP PROOF
UPPER CON-
TOUR



COMPATIBLE
WITH
GLASSES

ZENITH X | PRIMERO

ZEN FOAM VISOR

WVI00041 | S - WVI00042 | M
EN ISO 16321 - ANSI Z87.1



OPTIONS



WVI00041-500
CLEAR



WVI00041-510
SMOKE



WVI00041-520
SILVER MIRROR



WVI00042-500
CLEAR



WVI00042-510
SMOKE



WVI00042-520
SILVER MIRROR

COMPATIBLE WITH SERIES



ALL VISORS NEED ADAPTERS (WAC00009) TO BE MOUNTED ON HELMET.

TECHNICAL DETAILS

MATERIAL
Polycarbonate

LENGTH
110 mm

WEIGHT
90 g

ENHANCED OPTICAL PERFORMANCE
1

STANDARD
EN ISO 16321

CE

CATEGORY
II

MARKINGS

CLEAR: ZEN | MM/YY | CE | KASK | UL1,2 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH

SMOKE: ZEN | MM/YY | CE | KASK | GL1 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH

SILVER MIRROR: ZEN | MM/YY | CE | KASK | GL2 | DT | 1 | K | N | CH | 16321 | KASK | DT | 1-M | CH

ORDER LOGISTICS

MASTERBOX	pieces	36
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	10

TECHNOLOGIES



ANTI-FOG



ABRASION AND SCRATCH RESISTANCE



PANORAMIC LENS



EASY CLICK ADAPTERS



DRIP PROOF UPPER CONTOUR



ANTI-INTRUSION GUARDS



COMPATIBLE WITH GLASSES

ZENITH X | PRIMERO KIT

MOUNT KIT

WKI00009 | MOUNT KIT ZEN FF/MM/PM/FS



KIT INCLUDES



=



WAC00010
VISOR CARRIER

+



WAC00009
ADAPTERS

ORDER LOGISTICS

MASTERBOX	pieces	20
DIMENSIONS	cm	54 x 82 x 47
WEIGHT	kg	7

COMPATIBLE WITH SERIES



WKI00012 | BRIM KIT



KIT INCLUDES



=



WAC00010
VISOR CARRIER

+



WAC00009
ADAPTERS

+



WVI00011
BRIM

ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	49 x 79 x 52
WEIGHT	kg	4

COMPATIBLE WITH SERIES



V2 PLUS VISOR

WV100036

EN ISO 16321- EN 14458 - ANSI Z87.1



OPTIONS



WV100036-500
CLEAR



WV100036-510
SMOKE



WV100036-520
SILVER MIRROR

COMPATIBLE WITH SERIES



SUPERPLASMA SERIES

SCREW SET FOR MOUNTING IS INCLUDED IN EVERY VISOR.



WAC00005
VISOR SCREW SET

TECHNICAL DETAILS

MATERIAL
Polycarbonate

STANDARD
EN ISO 16321
EN 14458

LENGTH
110 mm

CE

WEIGHT
80 g

ANSI Z87.1
CATEGORY
II

MARKINGS

CLEAR:
CE | EN14458:2018 | KASK | V2 PLUS | MM/YY | = | BT | 2C-1,2 | -30°C+50°C | KASK | UL1,2 | DT | 1 | K | N | CH | 7 | 16321 | KASK | DT | 1-M
SMOKE:
CE | EN14458:2018 | KASK | V2 PLUS | MM/YY | = | BT | 5-1,4 | -30°C+50°C | KASK | GL1 | DT | 1 | K | N | CH | 7 | 16321 | KASK | DT | 1-M
SILVER MIRROR:
CE | EN14458:2018 | KASK | V2 PLUS | MM/YY | = | BT | 5-2,5 | -30°C+50°C | KASK | GL2 | DT | 1 | K | N | CH | 7 | 16321 | KASK | DT | 1-M

ORDER LOGISTICS

MASTERBOX	pieces	42
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	11

TECHNOLOGIES



ANTI-FOG



ABRASION
AND
SCRATCH
RESISTANCE



PANORAMIC
LENS



CUT PROOF
EDGE



DRIP PROOF
UPPER CON-
TOUR



COMPATIBLE
WITH
GLASSES



EXTREME
TEMP IMPACT
RESISTANCE

ENHANCED OPTICAL PERFORMANCE
1

SUPERPLASMA

V2 FULL FACE VISOR

WV100037

EN ISO 16321 - ANSI Z87.1



OPTIONS



WV100037-500
CLEAR



WV100037-510
SMOKE



WV100037-520
SILVER MIRROR

COMPATIBLE WITH SERIES



SUPERPLASMA SERIES

SCREW SET FOR MOUNTING IS INCLUDED IN EVERY VISOR.



WAC00005
VISOR SCREW SET

TECHNICAL DETAILS

MATERIAL
Polycarbonate

STANDARD
EN ISO 16321
CE

LENGTH
190 mm

ANSI Z87.1

WEIGHT
120 g

CATEGORY
II

MARKINGS

CLEAR:
V2 FULL FACE | MM/YY | CE | KASK | UL1,2 | ET | -5°C +55°C | K | N | CH | 9 | 16321 | KASK | ET | 1-M/1-L | -5°C +55°C | 6 | CH | 9
SMOKE:
V2 FULL FACE | MM/YY | CE | KASK | GL2 | ET | -5°C +55°C | K | N | CH | 9 | 16321 | KASK | ET | 1-M/1-L | -5°C +55°C | 6 | CH | 9
SILVER MIRROR:
V2 FULL FACE | MM/YY | CE | KASK | GL1 | ET | -5°C +55°C | K | N | CH | 9 | 16321 | KASK | ET | 1-M/1-L | -5°C +55°C | 6 | CH | 9

ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	8

TECHNOLOGIES



ANTI-FOG



ABRASION
AND
SCRATCH
RESISTANCE



PANORAMIC
LENS



COMPATIBLE
WITH
GLASSES



DRIP PROOF
UPPER CON-
TOUR

ENHANCED OPTICAL PERFORMANCE
X


SUPERPLASMA

MESH VISOR

WVI00006
EN 1731 - ANSI Z87.1



MOUNTING PARTS



TECHNICAL DETAILS

MATERIAL	STANDARD
Polypropylene and metal	EN 1731
LENGTH	CE UK
190 mm	ANSI Z87.1

WEIGHT	CATEGORY
42 g	II
LIGHT TRANSMISSION	
82-85,5%	

MARKINGS

EN 1731

TECHNOLOGIES



ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	78 x 48 x 50
WEIGHT	kg	8



PROTECTION FROM ELECTRIC ARC

— 108

SOLUTIONS FOR HIGH-RISK CONDITIONS

Built for environments that require even higher levels of protection.
Focusing on fire-resistant, fire-retardant, arc-rated equipment.



ZENITH X CLOSED SHELL | PRIMERO CLOSED SHELL

ARC VISOR CLASS 1

WVI00014
ISO 16321 - DGVV GS ET29



OPTIONS



WVI00014
CLEAR

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

ARC VISOR MOUNTS WITHOUT ANY ADAPTER.

TECHNICAL DETAILS

MATERIAL
Polycarbonate

LENGTH
245 mm

WEIGHT
300 g

STANDARD
EN ISO 16321-1
DGVV GS-ET-29

CE 1883 UK 0843

GS-ET-29 (Box-Test)
Class 1 / APC 1

CATEGORY
III

MARKINGS



16321 KASK UL1,2 E 6
GS-ET-29 8-1-0 APC 1

ORDER LOGISTICS

MASTERBOX	pieces	10
DIMENSIONS	cm	60 x 40 x 40
WEIGHT	kg	4,5

TECHNOLOGIES



ELECTRIC ARC
PROTECTION



STABLE
CARRIER



PANORAMIC
LENS



> CRI 95



COMPATIBLE
WITH
GLASSES

ZENITH X CLOSED SHELL | PRIMERO CLOSED SHELL

ARC VISOR CLASS 2 ERGO

WVI00034
ISO 16321 - DGVV GS ET29 | ASTM F2178: ATPV 12.0 cal/cm² ARC 2



OPTIONS



WVI00034
SMOKE

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

ARC VISOR MOUNTS WITHOUT ANY ADAPTER.

TECHNICAL DETAILS

MATERIAL
Polycarbonate

LENGTH
215 mm

WEIGHT
370 g

ATPV
12 cal/cm², ARC 2

STANDARD
EN ISO 16321-1
DGVV GS-ET-29

CE 1883 UK 0843

ANSI Z87.1 + ASTM F2178
CSA Z94.3

GS-ET-29 (Box-Test)
Class 2 / APC 2

CATEGORY
III

MARKINGS



16321 KASK UL2 E 6 9 / GS-ET-29 8-2-2 APC 2
ATPV 12 cal/cm² / ANSI / ISEA Z87.1 KASK Z87 + U6
CSA Z94.3 KASK 2.0

ORDER LOGISTICS

MASTERBOX	pieces	8
DIMENSIONS	cm	60 x 40 x 40
WEIGHT	kg	4,6

TECHNOLOGIES



ELECTRIC ARC
PROTECTION



STABLE
CARRIER



PANORAMIC
LENS



> CRI 95



COMPATIBLE
WITH
GLASSES



SEE-THROUGH
CHIN
PROTECTION

ZENITH X | PRIMERO

FR NECK PROTECTOR

WAC00034
EN 13688 | ASTM F1959/05 | IEC 61482/1 | ATPV 22.2 cal/cm²

OPTIONS

COMPATIBLE WITH SERIES



WAC00034-514
BLUE NIGHT



ZENITH X SERIES



PRIMERO SERIES

FR NECK PROTECTOR IS MOUNTED VIA EASY ATTACHMENT SYSTEM

TECHNICAL DETAILS

MATERIAL Double layer fabric in 93% Nomex® 5% Kevlar® 2% antistatic fiber	STANDARD EN 13688 Protective clothing - general requirement EN 11612 Heat and flame protection A1 - Limited flame spread B1 - Convective heat C1 - Radiant heat EN 13034 Protection against chemicals Type PB [6] - protection against liquid chemicals: H2SO4 - 30% dilution NaOH - 10% dilution o-Xylene – undiluted Butan-1-olo – undiluted EN1149-5 Electrostatic properties (base fabric only) Half decay time t50 <4s Shielding factor S >0.2s
WEIGHT 80,5 g	
SIZE One size	
CATEGORY III	
	CE UK CA 0624 TEST ASTM F1959/05 IEC 61482/1 ATPV 22.2 cal/cm²

TECHNOLOGIES

 FIRE RESISTANT FABRIC	Test: ASTM F1959-05 IEC 61482/1 ATPV 22.2 cal/cm² Fire-resistant Nomex® fabric. Non-melting, self-extinguishing with no flame.	 NON CONDUCTIVE	 HOOK-AND-LOOP FASTENER	 NECK AND EAR PROTECTION	 EASY ATTACHMENT SYSTEM
---	---	--	--	---	--

ORDER LOGISTICS

MASTERBOX	pieces	175
DIMENSIONS	cm	43 x 42 x 66
WEIGHT	kg	14



HEARING PROTECTION

— 112

SOUND SAFETY

A selection of non-conductive earmuffs that integrate seamlessly with helmets to reduce noise levels in high-volume environments.

KASK HEARING PROTECTION

OVERVIEW OF TECHNOLOGIES.

**CERTIFIED FOR USE WITH KASK HELMETS**

Performance tested on all KASK helmets.

**COLOR CODED PERFORMANCE LEVEL**

Color coded to indicate noise reduction performance level.

**EASY SIZE ADJUSTMENT**

Designed to adjust seamlessly for almost any headshape or size.

**NON-CONDUCTIVE**

Designed to not conduct heat or electricity.

**STANDARD 30 MM SLOT**

Designed to attach in 30 mm EURO slots.



SC1

WHP00004
EN 352-3 / ANSI S3.19



DESCRIPTION

Green-colored earmuffs used in environments with low-to-medium noise levels. Typical applications include: general industrial work areas. Compatible with all KASK helmets.

COMPATIBLE WITH SERIES



SUPERPLASMA HELMET SERIES REQUIRE EARMUFFS ADAPTERS (WAC00003) FOR MOUNTING.

TECHNICAL DETAILS

MATERIAL EAR CUPS and SPACER: ABS thermoplastic	STANDARD EN 352-3 CE UK 1974
FOAM LINER: Polyether	ANSI S3.19
WEIGHT 280 g	CATEGORY III

SNR / NRR

	SNR (EN 352-3) All KASK helmets 25 dB (A) H 27 dB - M 23 dB - L 16 dB
	NRR (ANSI S3.19) 22 dB

ORDER LOGISTICS

MASTERBOX	pieces	20
DIMENSIONS	cm	55 x 30 x 35
WEIGHT	kg	9

TECHNOLOGIES



EARMUFFS

SC2

WHP00005
EN 352-3 / ANSI S3.19



DESCRIPTION

Yellow-colored earmuffs used in environments with medium-to-high noise levels. Typical applications include: building and construction, forestry use, industrial areas, production areas, agriculture, etc. Compatible with all KASK helmets.

COMPATIBLE WITH SERIES



SUPERPLASMA HELMET SERIES REQUIRE EARMUFFS ADAPTERS (WAC00003) FOR MOUNTING.

TECHNICAL DETAILS

MATERIAL EAR CUPS and SPACER: ABS thermoplastic	STANDARD EN 352-3 CE UK 1974
FOAM LINER: Polyether	ANSI S3.19
WEIGHT 320 g	CATEGORY III

SNR / NRR

	SNR (EN 352-3) All KASK helmets 29 dB (A) H 31 dB - M 27 dB - L 20 dB
	NRR (ANSI S3.19) 24 dB

ORDER LOGISTICS

MASTERBOX	pieces	20
DIMENSIONS	cm	55 x 30 x 35
WEIGHT	kg	10

TECHNOLOGIES



EARMUFFS

SC3

WHP00006
EN 352-3 / ANSI S3.19



DESCRIPTION

Orange-colored earmuffs used in environments with high noise levels. Typical applications include: airports, car racing, while using pneumatic drills, etc.
Compatible with all KASK helmets.

COMPATIBLE WITH SERIES



ZENITH X SERIES PRIMERO SERIES SUPERPLASMA SERIES

SUPERPLASMA HELMET SERIES REQUIRE EARMUFFS ADAPTERS (WAC00003) FOR MOUNTING.

TECHNICAL DETAILS

MATERIAL	STANDARD
EAR CUPS and SPACER: EN 352-3 ABS thermoplastic	CE UK 1974
FOAM LINER: Polyether	ANSI S3.19
WEIGHT 350 g	CATEGORY III

SNR / NRR

	SNR (EN 352-3) All KASK helmets 31 dB (A) H 32 dB - M 30 dB - L 21 dB
	NRR (ANSI S3.19) 27 dB

TECHNOLOGIES

				
STANDARD 30 mm SLOT	COLOR CODED PERFORMANCE LEVEL	EASY SIZE ADJUSTMENT	NON- CONDUCTIVE	CERTIFIED FOR USE WITH KASK HELMET

ORDER LOGISTICS

MASTERBOX	pieces	20
DIMENSIONS	cm	55 x 30 x 35
WEIGHT	kg	10



WEATHER PROTECTION

— 116

CLIMATE COMFORT

Accessories that integrate with KASK helmets helping workers better handle environmental elements in comfort.



OVERVIEW OF TECHNOLOGIES.



EASY ATTACHMENT SYSTEM

Integrated helmet slots enable secure attachment of accessories.



EARMUFF COMPATIBLE

Can be used with KASK hearing protection.



FORM FITTING

Designed to integrate seamlessly with helmets without compromising fit.



ERGONOMIC FIT

Engineered with an ergonomic neck cut for optimal head movement.



CLICK-IN ATTACHMENT

Attachment system that lets padding easily snap in and out.



NECK AND EAR PROTECTION

Designed to protect the neck and ears from the weather and environmental elements.



ADJUSTABLE SIDE COVERAGE

Enables quick and easy adjustments while worn.



BREATHABLE

Designed to be breathable with increased airflow.



UNDERSURFACE SUN REFLECTION

A dark undersurface prevents sun reflection, enhancing all-day comfort.



UV PROTECTION

Treated to protect from sunlight and block ultraviolet rays.



WATERPROOF

Designed to offer rain protection up to 10 meters of water column.



WINDPROOF

Blocks wind for added comfort in different weather conditions.



WIND RESISTANT

Protects from light wind without affecting breathability.



COLD RESISTANT

Insulated accessories for enhanced comfort and protection in cold environments.



WATER RESISTANT

Engineered to provide light rain protection and water repellency.



HYDRO OIL REPELLENT

Repels water and oil infiltration.



MOISTURE-WICKING

Made with fabric that disperses sweat and moisture.



NECK SHADE

WAC00020 | HI VIZ - WAC00024
AS/NZS 4399:2017 / AATCC 183:2014



OPTIONS



WAC00020-313
GREY



WAC00024-222
ORANGE FLUO



WAC00024-221
YELLOW FLUO

COMPATIBLE WITH SERIES



SUPERPLASMA SERIES +

NECK SHADE IS ATTACHED TO THE HELMET WITH SPECIAL HOOK-AND-LOOP ADHESIVE STRIPS, INCLUDED.

TECHNICAL DETAILS

MATERIAL
79% Polyamide
21% Elastane

STANDARD
AATCC 183:2014
AS/NZS 4399:2017

SIZE
45 x 33 cm

UVA/UVB PROTECTION
UPF 50+

CARE LABELLING



ORDER LOGISTICS

MASTERBOX DIMENSIONS WEIGHT	pieces	single unit
	cm	18,5 x 10 x 1
	kg	0,04

TECHNOLOGIES



SUPERPLASMA

NECK SHIELD RW

WAC00032 | HI VIZ - WAC00033



OPTIONS



WAC00032-209
ANTHRACITE



WAC00033-222
ORANGE FLUO



WAC00033-221
YELLOW FLUO

COMPATIBLE WITH SERIES



SUPERPLASMA SERIES +

NECK SHIELD RW IS ATTACHED TO THE HELMET WITH SPECIAL HOOK-AND-LOOP ADHESIVE STRIPS, INCLUDED.

TECHNICAL DETAILS

MATERIAL
OUTER:
Synthetic fabric
MID-LAYER:
Zerowind® membrane
INNER:
Micro-fleece

SIZE
45 x 27 cm

CARE LABELLING



ORDER LOGISTICS

MASTERBOX DIMENSIONS WEIGHT	pieces	single unit
	cm	32 x 21,5 x 0,5
	kg	0,06

TECHNOLOGIES




ZENITH X | PRIMERO

NECK SHADE

WAC00013 | HI VIZ - WAC00025
AS/NZS 4399:2017 / AATCC 183:2014

OPTIONS

WAC00013-313
GREYWAC00025-222
ORANGE FLUOWAC00025-221
YELLOW FLUO

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

NECK SHADE IS MOUNTED VIA EASY ATTACHMENT SYSTEM

TECHNICAL DETAILS

MATERIAL
79% Polyamide
21% Elastane**STANDARD**
AATCC 183:2014
AS/NZS 4399:2017**SIZE**
45 x 27 cm**UVA/UVB
PROTECTION**
UPF 50+

CARE LABELLING



ORDER LOGISTICS

MASTERBOX	pieces	single unit
DIMENSIONS	cm	32 x 21 x 0,5 cm
WEIGHT	kg	0,06

TECHNOLOGIES



ZENITH X | PRIMERO

NECK SHIELD RW

WAC00030 | HI VIZ - WAC00031

OPTIONS

WAC00030-209
ANTHRACITEWAC00031-222
ORANGE FLUOWAC00031-221
YELLOW FLUO

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

NECK SHIELD RW IS MOUNTED VIA EASY ATTACHMENT SYSTEM

TECHNICAL DETAILS

MATERIAL
OUTER:
Synthetic fabric
MID-LAYER:
Zerowind® membrane
INNER:
Micro-fleece**SIZE**
45 x 27 cm

CARE LABELLING



ORDER LOGISTICS

MASTERBOX	pieces	single unit
DIMENSIONS	cm	32 x 21,5 x 0,5
WEIGHT	kg	0,06

TECHNOLOGIES



KASK

UNIVERSAL

SUN SHIELD

WAC00036 | HI VIZ - WAC00037
AS/NZS 4399:2017 / AATCC 183:2014



OPTIONS



WAC00036-209
ANTHRACITE



WAC00037-222
ORANGE FLUO



WAC00037-221
YELLOW FLUO

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES



SUPERPLASMA
SERIES

TECHNICAL DETAILS

MATERIAL
Cordura™

STANDARD
AATCC 183:2014
AS/NZS 4399:2017

SIZE

One size fits most

**UVA/UVB
PROTECTION**
UPF 50+

CARE LABELLING



TECHNOLOGIES



ORDER LOGISTICS

MASTERBOX	pieces	30
DIMENSIONS	cm	31 x 41 x 27
WEIGHT	kg	5

UNIVERSAL

WINTER BALACLAVA

WAC00069 | HI VIZ - WAC00070



OPTIONS



WAC00069-209
ANTHRACITE



WAC00070-222
ORANGE FLUO



WAC00070-221
YELLOW FLUO

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES



SUPERPLASMA
SERIES

TECHNICAL DETAILS

MATERIAL

OUTER:
Syntethic fabric
MID-LAYER:
Zerowind® membrane
INNER:
Micro-fleece

SIZE

One size fits most

CARE LABELLING



TECHNOLOGIES



ORDER LOGISTICS

MASTERBOX	pieces	100
DIMENSIONS	cm	31 x 41 x 27
WEIGHT	kg	11

UNIVERSAL

WINTER CAP

WPA00007



OPTIONS

WPA00007
BLACK

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

SUPERPLASMA
SERIES

TECHNICAL DETAILS

MATERIAL

93% Polyester
7% Polyurethane

CARE LABELLING



TECHNOLOGIES

WINDPROOF BREATHABLE WATERPROOF WIND RESIS-
TANT COLD RESIS-
TANT

SIZE

One size fits most

ORDER LOGISTICS

MASTERBOX	pieces	30
DIMENSIONS	cm	25,5 x 15,5 x 5
WEIGHT	kg	0,06

MOISTU-
RE-WICKING FORM
FITTING HYDRO OIL
REPELLENT

ZENITH X

MERINO CAP

WPA00009



OPTIONS

WPA00009
BLACK

COMPATIBLE WITH SERIES



ZENITH X SERIES

FRONTAL CLICK-IN SYSTEM ALLOWS MOUNTING.

TECHNICAL DETAILS

MATERIAL

OUTER:
100% Polyester
INNER:
Merino Wool mix

CARE LABELLING



TECHNOLOGIES

WINDPROOF BREATHABLE WATERPROOF WIND RESIS-
TANT COLD RESIS-
TANT

SIZE

One size fits most

ORDER LOGISTICS

MASTERBOX	pieces	100
DIMENSIONS	cm	42 x 66 x 43
WEIGHT	kg	7

MOISTU-
RE-WICKING ERGONOMIC
FIT CLICK-IN AT-
TACHMENT

HEADLAMPS

— 124

ILLUMINATING SOLUTIONS

Lighting accessories that attach to KASK helmets to brighten worker sight lines in low-light conditions.





OVERVIEW OF TECHNOLOGIES.



ADVANCED FOCUS SYSTEM®

Patented technology that allows a seamless transition from broad low beam to sharply focused high beam.



DUAL POWER SOURCE

Equipped with two battery types; a rechargeable lithium-ion battery and regular AA alkaline battery, to provide flexibility in a variety of applications.



OPTISENSE® TECHNOLOGY

Technology that automatically adapts to the present light conditions – controlling the luminosity based on the reflecting surrounding light to avoid glare.



RAPID FOCUS

Mechanism that allows the light beam to be adjusted quickly.



TEMPERATURE CONTROL SYSTEM

Technology that automatically lowers the output to protect from overheating.



COOLING TECHNOLOGY

Dissipates heat generated by extended headlamp use.



TRANSPORTATION LOCK

Prevents the light from being turned on inadvertently.



BLUE LIGHT

Equipped with a blue LED light for use in fog and smoky conditions.



GREEN LIGHT

Equipped with a green LED light for increased run time and nighttime visibility.



RED READING LIGHT

Equipped with a red LED light for better nighttime visibility and emergency situations.



EMERGENCY LIGHT

Designed to turn on automatically when the power goes out and the headlamp is on its charging station.



BLUETOOTH®

Designed with Bluetooth® smartphone connection via app for personalized settings, timer, etc.



MAGNETIC CHARGE SYSTEM

Easily recharge the headlamp via a magnetic USB cable.



KL-1

WLA00001



TECHNICAL DETAILS

Weight incl. Battery	98 g
Light output max - min	400 lm 20 lm
Runtime min - max	4 h 35 h
Battery	1* Li-ion (included) or 1*AA Alkaline 1.5V/ 1*AANiMH1.2V (not included)
IP class	IP54
Charging time	150 min (according to hardware used)
Light functions	Power, low power
Functions	Low battery warning, charge indicator, battery indicator, rapid focus, red reading light


COMPATIBLE WITH SERIES



INCLUDES

Headlamp + elastic band
Overhead-band
Charging cable
Battery (to be installed)

TECHNOLOGIES



ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	40 x 40 x 35
WEIGHT	kg	10

HEADLAMPS

KL-2

WLA00002



TECHNICAL DETAILS

Weight incl. Battery	139 g
Maximum light output boost	600 lm for 10"
Light output max - min	400 lm 170 lm 20 lm
Runtime min - max	7 h 10 h 60 h
Battery	1* Li-ion (included) or 2*AA Alkaline 1.5V/ 2*AANiMH1.2V (not included)
IP class	IP54
Charging time	270 min (according to hardware used)
Light functions	Low power, mid power, power, blink, boost
Functions	Low battery warning; charge indicator; battery indicator; rapid focus; transport lock; red green and blue light (also fix bad break so battery doesn't break across the line.)


COMPATIBLE WITH SERIES



INCLUDES

Headlamp + elastic band
Overhead-band
Charging cable
Battery (to be installed)

TECHNOLOGIES



ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	40 x 40 x 35
WEIGHT	kg	10

HEADLAMPS

KL-3

WLA00001



TECHNICAL DETAILS

Weight incl. Battery	179 g
Maximum light output boost	1000 lm for 10"
Light output max - min	750 lm* 300 lm 10 lm
Runtime max - min	4 h 8 h 100 h
Battery	* 1 Li-ion (included) or ICR Li-ion 3.7V (not included)
IP class	IP54
Charging time	420 min (according to hardware used)
Light functions	Low power, mid power, power, boost, blink, SOS, strobe
Functions	Low battery warning; charge indicator; battery indicator; rapid focus; transport lock; red, green, and blue light; Bluetooth; automatic brightness adjustment

COMPATIBLE WITH SERIES




INCLUDES

Headlamp + elastic band
Overhead-band
Charging cable
Battery (to be installed)


ORDER LOGISTICS

MASTERBOX	pieces	24
DIMENSIONS	cm	40 x 40 x 35
WEIGHT	kg	10


TECHNOLOGIES



MOUNTING

ZENITH X, PRIMERO, SUPERPLASMA
MOUNTING WITH ELASTIC BANDZENITH X, PRIMERO
ASSEMBLY VIA FRONT ATTACHMENT POINT ADAPTERZENITH X, PRIMERO
OVERHEAD-BAND MOUNTINGZENITH X, PRIMERO
OVERHEAD-BAND MOUNTING WITH EARMUFFSSUPERPLASMA
OVERHEAD-BAND MOUNTINGSUPERPLASMA
OVERHEAD-BAND MOUNTING WITH EARMUFFS

Headlamps spare parts are at page 127



— 130

OTHER ACCESSORIES

SMART SOLUTIONS

Securely attached accessories that allow working activities to be fast and practical.

ZENITH X | PRIMERO

BADGE HOLDER

WAC00048

OPTIONS

WAC00048
CLEAR

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

TECHNICAL DETAILS

MATERIAL

PC - transparent
PA - black

SIZE

58 x 95 mm

DESCRIPTION

Attachment designed to securely connect badge to front attachment point of helmet while providing protection from splash risks. It is mounted by removing frontal point cover and inserting badge slot.

ORDER LOGISTICS


MASTERBOX	pieces	30
DIMENSIONS	cm	17,5 x 25 x 17,5
WEIGHT	kg	1

UNIVERSAL

BADGE HOLDER LIGHT

WAC00042 | WAC00047

OPTIONS

WAC00042
SUPERPLASMAWAC00047
ZENITH X
PRIMERO

COMPATIBLE WITH SERIES



ZENITH X SERIES



PRIMERO SERIES

SUPERPLASMA
SERIES

TECHNICAL DETAILS

MATERIAL

Badge Holder:
Transparent PE

Elastic band:
75% polyester
25% natural rubber

SIZE

58 x 95 mm

DESCRIPTION

Attachment for connecting badge via lamp clips to the front or back of helmet. It is mounted by fixing elastic band loop to helmet lamp clips.

ORDER LOGISTICS

MASTERBOX	pieces	70
DIMENSIONS	cm	17,5 x 25 x 17,5
WEIGHT	kg	1,5



CUSTOM PRINTING AS EASY AS 1, 2, 3.

With high-quality printing and flexible order options, KASK helmets can be customized to outfit any team.

- High-quality graphics in up to seven colors
- Applied to standard or custom print areas
- Low minimum order quantities

Contact a KASK sales representative to learn about custom printing your helmets. Standard and Hi-Viz decal customization available.

— 132

1

CHOOSE YOUR HELMET



ZENITH X SERIES

ZENITH X



ZENITH X HI VIZ



PRIMERO SERIES

PRIMERO



PRIMERO HI VIZ



SUPERPLASMA SERIES

SUPERPLASMA



SUPERPLASMA HI VIZ



2 CHOOSE YOUR PRINTING AREA



FRONT
80 mm x 46 mm



FRONT
80 mm x 55 mm



FRONT
80 mm x 55 mm



SIDES
55 mm x 24 mm



SIDES
65 mm x 35 mm



SIDES
65 mm x 35 mm



BACK
60 mm x 35 mm
80 mm x 33 mm



BACK
50 mm x 24 mm
34 mm x 40 mm



BACK
80 mm x 25 mm
80 mm x 18 mm

Every KASK helmet can be customized.

These are typical guidelines for graphic placement on KASK helmets.

KASK will work with you to help achieve your vision for your helmets.



3 CHOOSE YOUR GRAPHICS



PAD PRINTING

- High-quality color matching
- Each side can be a unique graphic
- Print in standard areas, or request custom print areas
- Durable in time

DECALS

- High-quality color matching
- Each decal can be customized
- Replaceable

SPARE PARTS.

HELMETS

ZENITH X



**ZENITH X INTERNAL
PADDING**
WPA00010



**ZENITH X FRONT
PADDING**
WPA00011



**ZENITH X COMFORT
FIT FRONT PADDING**
WPA00012



**ZENITH X REFLECTI-
VE DECALS**
WAC00062-252



**LAMP CLIPS
BLACK**
WAC00061-210



**LAMP CLIPS
LUMINESCENT**
WAC00061-236



**ZENITH X MAX
INTERNAL PADDING**
WPA00023




**ZENITH X MAX
FRONT PADDING**
WPA00024



**ZENITH X MAX
COMFORT FIT PADDING**
WPA00025



**ZENITH X REFLECTI-
VE DECALS**
WAC00088-252



**CLEAR
STICKERS**
WAC00023



**BADGE
HOLDER**
WAC00048 | WAC00047



**EASY CLICK
ADAPTERS**
WAC00009



**FULL FACE VISOR
CARRIER**
WAC00010



BRIM
WVI00011



**ADAPTIVE FIT SY-
STEM WHEEL KIT**
WAC00086

134

HELMETS

PRIMERO



**INTERNAL
PADDING**
WPA00019



**FRONT
PADDING**
WPA00020



**COMFORT FIT
FRONT PADDING**
WPA00013




**LAMP CLIPS
BLACK**
WAC00082-210



**LAMP CLIPS
LUMINESCENT**
WAC00082-236



**REFLECTIVE
DECALS**
WAC00083-252



**CLEAR
STICKERS**
WAC00023



**BADGE
HOLDER**
WAC00048 | WAC00047



**EASY CLICK
ADAPTERS**
WAC00009



**FULL FACE VISOR
CARRIER**
WAC00010




BRIM
WVI00011



**QUICK/ERGO FIT
SYSTEM GEAR KIT**
WAC00085

HELMETS

SUPERPLASMA



**SUPERPLASMA AQ
PADDING**
WPA00002



**SUPERPLASMA HP
PADDING**
WPA00005



**SUPERPLASMA
PL PADDING**
WPA00003



**CLEAR
STICKERS**
WAC00018



**SUPERPLASMA AQ
REFLECTIVE STICKERS**
WAC00001

- 202 YELLOW
- 204 RED
- 205 GREEN
- 252 SILVER



**BADGE HOLDER -
LIGHT**
WAC00042



**VISOR
SCREW SET**
WAC00005



**EARMUFF
ADAPTERS**
WAC00003



**MESH VISOR
CARRIER**
WV100005



**MESH VISOR
ADAPTERS**
WAC00008



**QUICK/ERGO FIT
SYSTEM GEAR KIT**
WAC00085

ACCESSORIES

HEADLAMPS



**KL-1 FRONT
ATTACHMENT**
WAC00064
(ZENITH X | PRIMER0)



**KL-2 FRONT
ATTACHMENT**
WAC00065
(ZENITH X | PRIMER0)



**KL-3 FRONT
ATTACHMENT**
WAC00066
(ZENITH X | PRIMER0)



**OVERHEAD-BAND
KL-1/KL-2/KL-3**
WAC00049



**HEADBAND
KL-1**
WAC00053



**HEADBAND
KL-2/KL-3**
WAC00054



**USB MAGNETIC
CHARGING CABLE**
WAC00059



**BASE PLATE
KL-1**
WAC00055



**BASE PLATE
KL-2**
WAC00056



**BASE PLATE
KL-3**
WAC00057



**BATTERY COVER
KL-1**
WAC00050



**BATTERY COVER
KL-2**
WAC00051



**BATTERY COVER
KL-3**
WAC00052



**BATTERY
KL-3**
WAC00058

ACCESSORIES

EARMUFFS



**HEARING
PADDING SC1+SC2**
WAC00006



**HEARING
PADDING SC3**
WAC00007



**EARMUFF
ATTACHMENT ARMS**
WAC00022

SALES SUPPORT.

PRINTED SUPPORT



CATALOGUE

SAFETY COLLECTION:
XDI00034-2025-EN | IT | DE | FR | ES-



PRODUCT FLYER

ZENITH X:
XDI00017-ZENITH-X-EN | IT | DE | FR | ES-2024-

PRIMERO:
XDI00017-PRIMERO-EN | IT | DE | FR | ES-2023-

SUPERPLASMA:
XDI00017-SUPERPLASMA-EN | IT | DE | FR | ES-2023-

COLORBOOK



**HELMET SHELL
COLORBOOK PP**
XDI00135-PP



**HELMET SHELL
COLORBOOK ABS**
XDI00135-ABS



**REFLECTIVE DECALS
COLORBOOK**
XDI00136



**WINDOW
STICKERS**
(21 x 8 cm) | XME00127-213

DISPLAY



**STAND & HANG
HELMET DISPLAY**
(75 x 33 x 180 cm)
XDI00077



**4-HELMET
DISPLAY**
(28 x 40 x 183 cm)
XDI00119



**SINGLE HELMET
DISPLAY**
(50 x 30 x 37 cm)
XDI00032



**FLYER
DISPLAY**
(25 x 8 x 27 cm)
XDI00031



**WINDOW
DISPLAY**
(42 x 30 cm)

ZENITH X:
XDI00179- EN | IT | DE | FR | ES-

PRIMERO:
XDI00179- EN | IT | DE | FR | ES-

SUPERPLASMA:
XDI00181- EN | IT | DE | FR | ES-

SLAT WALL KIT



**KASK
HANGER**
XDI00188




**SLAT WALL
BANNER**
XEV00020

ROLL UP



**ROLL UP
INDUSTRIAL**
(200 x 80 cm)
XEV00016-501-2023-



**ROLL UP
ROPE ACCESS**
(200 x 80 cm)
XEV00016-505-2023-



**ROLL UP
CONSTRUCTION**
(200 x 80 cm)
XEV00016-506-2023-



**ROLL UP
TREE CLIMBING**
(200 x 80 cm)
XEV00016-504-2023-



HELMET BAGS



**DRAWSTRING
BAG SMALL**
WAC00026



**DRAWSTRING
BAG LARGE**
WAC00071



**REINFORCED
BAG**
WAC00029



**SELECTION
BAG**
UAC00007



**KASK BAG
SMALL**
UAC00006



**KASK BAG
BIG**
UAC00004

CLEANERS



LINER REFRESHER
100ML/3.4 FL OZ
SINGLE UNIT
WAC00040



LINER REFRESHER
100ML/3.4 FL OZ
8 PCS BOX
WAC00044



HELMET CLEANER
100ML/3.4 FL OZ
SINGLE UNIT
WAC00063



HELMET CLEANER
100ML/3.4 FL OZ
8 PCS BOX
WAC00072

KASK SERIES: THE FULL RANGE

— 138


PRODUCT OVERVIEW

Overview of all helmets and accessories that complete every KASK series - Zenith X, Primero and Superplasma.



ZENITH X FULL RANGE.

ZENITH X




All colors are available as made-to-order with Longer Chinstrap ($\longleftrightarrow$ +10 cm): WHE00125 - Zenith X LC
All colors are also available as **ZENITH X MAX** version: **WHE00130**

ZENITH X HI VIZ



All colors are available as made-to-order with Longer Chinstrap ($\longleftrightarrow$ +10 cm): WHE00126 - Zenith X LC HI VIZ
*Selected colors are also available as **ZENITH X MAX HI VIZ** version: **WHE00131**

ZENITH X AIR



All colors are available as made-to-order with Longer Chinstrap ($\longleftrightarrow$ +10 cm): WHE00127 - Zenith X AIR LC All colors are also available as **ZENITH X MAX AIR** version: **WHE00132**

ZENITH X AIR HI VIZ



All colors are available as made-to-order with Longer Chinstrap ($\longleftrightarrow$ +10 cm): WHE00128 - Zenith X AIR LC HI VIZ
*Selected colors are also available as **ZENITH X MAX AIR HI VIZ** version: **WHE00133**

ZENITH X PL



ZENITH X PL HI VIZ



ZENITH X COMBO



ZENITH X AIR COMBO



ZENITH X PL COMBO



EYE & FACE PROTECTION

ZEN VISOR



ZEN FF VISOR



ZEN MM | PM



ZEN FOAM



ZENITH X KIT



ZEN PLUS VISOR



ZEN FF PLUS VISOR



FR PROTECTION KIT



PROTECTION FROM ELECTRIC ARC

ARC VISOR CLASS 1



ARC VISOR CLASS 2 ERGO



FR NECK PROTECTOR



WEATHER PROTECTION

NECK SHADE | HI VIZ



NECK SHIELD RW | HI VIZ



WINTER BALACLAVA | HI VIZ



SUN SHIELD | HI VIZ




MERINO | WINTER CAP



HEADLAMPS

HEADLAMPS




LAMP FRONT ATTACHMENT



HEARING PROTECTION

EARMUFFS



HYGENE KIT



SPARE PARTS & SAFETY ACCESSORIES

ZENITH X SPARE PARTS



PRIMERO FULL RANGE.

PRIMERO



PRIMERO HI VIZ



PRIMERO AIR



PRIMERO AIR HI VIZ



PRIMERO PL



PRIMERO PL HI VIZ



EYE & FACE PROTECTION

ZEN VISOR



ZEN FF VISOR




ZEN MM | PM



ZEN FOAM



PRIMERO KIT



ZEN PLUS VISOR



ZEN FF PLUS VISOR



FR PROTECTION KIT



PROTECTION FROM ELECTRIC ARC

ARC VISOR CLASS 1



ARC VISOR CLASS 2 ERGO



FR NECK PROTECTOR



WEATHER PROTECTION

NECK SHADE | HI VIZ



NECK SHIELD RW | HI VIZ



WINTER BALACLAVA | HI VIZ



SUN SHIELD | HI VIZ




WINTER CAP



HEADLAMPS

HEADLAMPS




LAMP FRONT ATTACHMENT



HEARING PROTECTION

EARMUFFS



HYGIENE KIT



SPARE PARTS & SAFETY ACCESSORIES

PRIMERO SPARE PARTS



SUPERPLASMA FULL RANGE.

SUPERPLASMA AQ



SUPERPLASMA AQ HI VIZ



SUPERPLASMA HP




SUPERPLASMA HP VISOR



SUPERPLASMA PL



SUPERPLASMA PL HI VIZ



EYE & FACE PROTECTION

V2 PLUS VISOR



WV100036-500 CLEAR
WV100036-510 SMOKE
WV100036-520 SILVER MIRROR

VISOR FULL FACE



WV100037-500 CLEAR
WV100037-510 SMOKE
WV100037-520 SILVER MIRROR

MESH VISOR



WV100006 METAL MESH

WEATHER PROTECTION

NECK SHADE | HI VIZ



WAC00020-313 GREY
WAC00024-222 ORANGE FLUO
WAC00024-221 YELLOW FLUO

NECK SHIELD RW | HI VIZ



WAC00032-209 ANTHRACITE
WAC00033-222 ORANGE FLUO
WAC00033-221 YELLOW FLUO

WINTER BALACLAVA | HI VIZ



WAC00069-209 ANTHRACITE
WAC00070-222 ORANGE FLUO
WAC00070-221 YELLOW FLUO

SUN SHIELD | HI VIZ



WAC00036-209 ANTHRACITE
WAC00037-222 ORANGE FLUO
WAC00037-221 YELLOW FLUO

WINTER CAP



WPA00007 WINTER CAP

HEADLAMPS

HEADLAMPS



WLA00001 KL-1
WLA00002 KL-2
WLA00003 KL-3

HEARING PROTECTION

EARMUFFS



WHP00004 SC1 - GREEN
WHP00005 SC2 - YELLOW
WHP00006 SC3 - ORANGE

HYGENE KIT



WAC00006-7 HYGIENE KIT EARMUFFS

SPARE PARTS & SAFETY ACCESSORIES

SUPERPLASMA SPARE PARTS



WPA00002 SUPERPLASMA AQ PADDING
WPA00005 SUPERPLASMA HP PADDING
WPA00003 SUPERPLASMA PL PADDING
WAC00001 REFLECTIVE STICKERS
WAC00005 VISOR SCREW SET
WAC00003 EARMUFFS ADAPTERS
WAC00008 MESH VISOR ADAPTER
WV100005 MESH VISOR CARRIER
WAC00085 QUICK/ERGO FIT SYSTEM GEAR KIT
WAC00018 CLEAR STICKERS

BADGE HOLDER LIGHT



WAC00042

CLEANERS



WAC00040 LINER REFRESHER
WAC00063 HELMET CLEANER



Reproduction forbidden. All rights reserved. Some of the products shown may differ from products supplied. Kask spa. reserves the right to make variations/ improvements of any of the product or data shown at any time, without notice. All the products are designed and engineered by Kask spa. Italy. The illustrations, descriptions and dimensions shown in this catalog are indicative. KASK reserves the right to modify or improve them in any moment. The colors have been reproduced with the accuracy allowed by the process of printing. KASK products are guaranteed not to involve child labor.



KASK S.p.A

Via Firenze, 5
24060 Chiuduno (BG) - Italy
T. +39 035 4427497
F. +39 035 4427704

info@kask.com

   
kask-safety.com

DISTRIBUTED BY

