

# RP303 HALO Rigging Plate- Medium

## Data Sheet



climb. work. rescue.

**I|S|C**  
Solutions in Metal

HALO Rigging Plates are machined from superior grade Aluminium.

HALO Plates feature a central hole, surrounded by six equi-spaced apertures, each of which is capable of accommodating multiple Karabiner connections. This allows the user multiple loading options. All holes have radiussed edges, to reduce rope/webbing wear and also to reduce wear from loads which are applied by Karabiners.

<b>Outer Diameter</b>	144mm (5 <sup>10</sup> / <sub>16</sub> "
<b>Central Hole Diameter</b>	39mm (1 <sup>1</sup> / <sub>2</sub> "
<b>Aperture Size (approx.)</b>	36mm x 24mm (1 <sup>7</sup> / <sub>16</sub> x <sup>15</sup> / <sub>16</sub> "
<b>Minimum Breaking Strength (MBS)</b>	50kN (11240lbf)
<b>Unit Weight</b>	221g (8oz)
<b>Material</b>	Aluminium (Anodised)
<b>Standards</b>	Approved to CE 0120. Meets: NFPA 1983 (17ED)G, PD CEN/TS 16415:2013 (Personal fall protection equipment – Anchor devices – Recommendations for anchor devices for use by more than one person simultaneously).