

Dynamic rope lanyard with stitched eyes at the ends for work positioning and anchoring at the tree care.

DESCRIPTION

Dynamic rope Ø 11 mm guarantees smooth adjustment and in case of fall higher impact force absorption.

Suitable to use with the mechanical adjustment devices and also with friction hitches (Prusik knot).

Available in 3 versions, with light alloy ring, steel ring or without a ring.



Suitable also for other work at height as the anchor device.

Strength stitching is covered with plastic cover for higher abrasion resistance and easier pulling from the tree top.







KEY FEATURES

light

dynamic

long lifetime

STANDARDS

C€ 1019 EN 795B

EN 354

FEATURES



1 person only



22 kN



60-550 cm



105-540 g (see the table) (see the table)



warranty

MATERIALS

PATRON LANYARD ALU RING

84% PA 15% light alloy 1% PVC




PATRON LANYARD STEEL RING

84% PA 15% steel 1% PVC




99% PA 1% PVC

TECHNICAL DATA



steel ring





TYPES AND LENGTHS

	[cm]	[g]	kód
PATRON LANYARD	60	105	W2113Y060
PATRON LANYARD	80	120	W2113Y080
PATRON LANYARD	120	155	W2113Y120
PATRON LANYARD	150	185	W2113Y150
PATRON LANYARD	350	345	W2113Y350
PATRON LANYARD	550	540	W2113Y550
PATRON LANYARD ALU RING	125	215	W2111Y125
PATRON LANYARD ALU RING	150	235	W2111Y150
PATRON LANYARD STEEL RING	125	292	W2112Y125
PATRON LANYARD STEEL RING	150	315	W2112Y150



PATRON LANYARD



PATRON LANYARD ALU RING

30°C



PATRON LANYARD STEEL RING

MAINTENANCE

Lifetime of this product depends on the frequency and the environment (salt, sand, moisture, chemicals, etc.) in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 15 years from the date of production and 10 years from the date of the first use.

However mechanical damage can occur during the first use, which can limit the lifetime of this products only to its first use.



beware of beware of salt UV



beware of washing chemicals





ying read instructions

RELATED PRODUCTS				
	PULLEY SLING W2603YB00	RING SLING W2604RR00	PRUSIK SLING W2601R085	TREE ANCHOR W2114
LENGTH	40 cm	40 cm	38 cm	500 cm
ROPE DIAMETER	10 mm	10 mm	8 mm / 10 mm	11 mm
WEIGHT	160 g	115 g	48 g / 70 g	525 g

Note Section 1. Substitute 1.

