singing rock®

PROFESSIONAL

CATALOGUE **2023/24** | EN

SINGING ROCK was founded in 1992. During its existence, Singing Rock has established itself as a professional and innovative producer and supplier of personal fall protective equipment. Nowadays SINGING ROCK is one of the world leaders on the market of professional protective equipment for work at height, military and rescue. All of the high-performance and innovative products are developed and produced in Czech Republic, Europe. Our products are certified are certified and fully comply with the international industrial safety standards. Our products are innovative, modern and easy to use, with great strength and with maximum comfort.

www.singingrock.com

Thanks to the innovated technologies and smart solutions, SINGING ROCK can offer a full range of safety harnesses covering all areas of working applications.
SINGING ROCK harnesses are exclusively manufactured in Czech Republic.



INNOVATION

It is not necessary to talk too much about the innovation as it is inherently present in all our products.

TESTING

Meeting minimum requirements is obvious – but we go further by performing tests to simulate all kind of usage as the basis for further development.

TECHNOLOGY

Appropriate technology and tools are essential to produce first-class products.

Shopping mall Teplice, Czech republic Photo: Ondřej Vítko

KNOWLEDGE & EXPERIENCE

Our products and techniques are thoroughly validated in our own testing and training centers. We are pleased to share all this with our customers – you get a complex solution.

INVOLVEMENT

We are climbers and we love climbing. Enthusiasm drives our innovations and improvements.

PERFORMANCE

Do your job efficiently, safely and comfortably – we are here to give you the tools to do this. Enjoy your work.

eoca european outdoor conservation association

TRADITION & STABILITY

We draw on 30 years of our own experience and we are proudly inspired by vast knowledge and experience of climbers from our region.

EFFICIENCY

We run lean management system with horizontal organization structure. Thanks to this we are able to react immediately and customize our products and services for your specific needs.

ENVIRONMENT

We bear the responsibility to keep our planet green and to preserve its riches for our kids. SINGING ROCK is member of the European Outdoor Conservation Association.

Building painting, Brno, Czech republic. Photo: Pavel Nesvadba

HARNESSES

ROPE ACCESS
FALL ARREST
FULL BODY
CHEST
SIT HARNESSES
ARBORICULTURE
RESCUE
ACCESSORIES

ROCK &LOCK

patented smart buckle system

Easy to lock and open: Only a small amount of finger pressure is needed to lock and to open.

- Fast lace-through: Make the loop, put it through the buckle frame, hook the loop on the cross bar and tighten. It's as easy as that.
- Smart function: Rock&Lock allows you to put on your harness very quickly
- Double safety: Webbing cannot slip through Rock&Lock due to a safety loop at the end of the webbing Spontaneous opening of Rock&Lock is virtually impossible.
- Lightweight and extra strong.
- Excellent operation in all-season conditions: Operation guaranteed even when webbing is wet or frozen.

EASY-LOCK BUCKLE

smooth adjusting

Unique buckle with a sliding captive bar matches strict American standards (ANSI, CSA). Its minimum strength is 17.2 kN. No webbing slippage in a buckle. Its construction ensures longtime operation and efficiency (easy releasing and fastening even when dirty and tough webbing). Corrosion resistance is tested by spraying in a salty chamber for a period of 48 hours.

SPEED BUCKLE

1 second buckle

SINGING ROCK SPEED buckle is the side quick release buckle.

- Easy operation
- Durable and adjustable
- Made from steel
- Matches strict American standard ANSI
- Impossible opening under the loading
- Impossible to lock when the strap is twisted
- Strap width up to 45 mm
- Black coated
- Strength 18 kN

Chimney demolition, Frýdlant nad Ostravicí, Czech republic Photo: Petr Piechowicz



These icons will help you to choose the proper harness regarding the most common and most suitable use:

rope acces | **rescue** | **work restraint** | **fall arrest** | **intervention** | **rope park** | **tree care**

EXPERT 3D / SPEED

W0079DR
black version – W0079DB

Fully adjustable harness for a rope access with wide padded waist belt, leg loops and shoulder straps. Suitable also for work positioning, fall arrest and work restraint situations.

- shoulder straps can be totally removed and the harness can be used as a sit harness only
- super comfortable wide waist belt padding provides maximum comfort when working at height
- strength webbing on the waist belt is stitched in the way that at normal working situation the body weight is absorbed by the padding only
- reflective strap and printing on the waist belt and shoulder padding increase the visibility in dark working conditions
- anatomic leg loops and waist belt are covered with strong PES fabric providing high abrasion resistance
- SPEED buckles enable fluent and fast adjustment to fit a user´s body
- OXY triple lock carabiner used for connection of shoulder straps to the main point to increase the space for chest ascender attachment
- chest ascender smart fixation system with plastic cover on the OXY carabiner increasing the durability of the webbing
- shoulders straps and leg loops are independently adjustable
- narrowed padding and webbing on the shoulder straps in a neck area enhance a comfortable work
- front and back attachment points for fall-arrest according to EN 361 marked with additional "A" marking
- rear lower attachment point according to EN 813
- flat rear attachment point does not bear on users back when carrying backpack or breathing apparatus
- front lower attachment point for descender placement or work positioning according to EN 813, EN 358
- 2 side attachment points for work positioning according to EN 358
- heavier items up to 35 kg can be attached to the webbing on the waist belt
- all steel components finished with E coating for higher corrosion resistance
- 4 ergonomic braided gear loops with a bearing capacity 5 kg
- additional loops on the waist belt and leg loops with a bearing capacity of 5 kg offer additional space for the gear and better gear orientation
- wide elastic band on left shoulder strap for the gear attachment (f.e. transmitter)
- slots on the waist belt for PORTER tool holder to carry your industrial tools

Size: S, M/L, XL
Weight: (M/L) 2415 g• 85.19 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813 • EN 361 • EN 1497

EXPERT 3D / STANDARD

W0078DR
black version – W0078DB

- standard easy-lock buckles enable smooth adjustment
- super comfortable wide waist belt padding provides maximum comfort even during prolonged suspension

Size: S, M/L, XL
Weight: (M/L) 2110 g • 74.43 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813 • EN 361 • EN 1497

EXPERT 3D / SPEED STEEL

W0080DR

The variant of EXPERT 3D harness according to the North American standards ANSI and NFPA with SPEED buckles, metal elements made of steel, fall indicators and lanyard keepers.

- harness certified according to the newest North American standards ANSI Z359.11-2014 and NFPA 1983 Class III
- ergonomic and removable lanyard keepers on the shoulder straps allow user to store lanyard connectors when not in use - in the event of a fall, the connector is released so that the shock absorber can be safely deployed
- for easier inspection, the harness is equipped with fall indicators placed close to dorsal attachment point which are activated in case of a fall - red label indicates that the harness must be retired

Size: S, M/L, XL
Weight: (M/L) 2830g • 99.83 oz
Max. rated load: 150 kg (140 kg/310 lbs according to ANSI)
ANSI Z359.11-2014 • NFPA 1983 Class III • CE 1019 • EN 358 • EN 813 • EN 361 • EN 1497

 Czech Police Special Forces, Photo: Artsiom Hasiankou

PROFI WORKER 3D / SPEED

W0082DR
black version – W0082DB

Fully adjustable harness for a rope access with wide padded waist belt, leg loops and shoulder straps. Suitable also for work positioning, fall arrest and work restraint situation.

- super comfortable wide waist belt padding provides maximum comfort when working at height
- strap that connects the legs loops and shoulders at the back passes freely through the waist belt, which brings increased mobility
- strength webbing on the waist belt is stitched in the way that at normal working situation the body weight is absorbed by the padding only
- reflective strap and printing on the waist belt and shoulder padding increase the visibility in dark working conditions
- anatomic leg loops and waist belt are covered with strong PES fabric providing high abrasion resistance
- SPEED buckles enable fluent and fast adjustment to fit a user´s body
- narrowed padding and webbing on the shoulder straps in a neck area enhance a comfortable work
- leg loops connection straps made from durable PES webbing for better abrasion resistance
- front and back attachment points for fall-arrest according to EN 361 marked with additional „A" marking
- rear lower attachment point according to EN 813
- flat rear attachment point does not bear on users back when carrying backpack or breathing apparatus
- front lower attachment point for descender placement or work positioning according to EN 813, EN 358
- 2 side attachment points for work positioning according to EN 358
- heavier items up to 35 kg can be attached to the webbing on the waist belt
- 4 ergonomic braided gear loops with a bearing capacity 5 kg
- additional loops on the waist belt and leg loops with a bearing capacity of 5 kg offer additional space for the gear and better gear orientation
- wide elastic band on left shoulder strap for the gear attachment (f.e. transmitter)
- slots on the waist belt for PORTER tool holder to carry your industrial tools

Size: S, M/L, XL •
Weight: (M/L) 2075 g • 73.19 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813 • EN 361 • EN 1497

PROFI WORKER 3D / STANDARD

W0081DR
black version – W0081DB

Fully adjustable harness for a rope access with wide padded waist belt, leg loops and shoulder straps. Also suitable for work positioning, descent, ascent and rescue situations

- standard easy-lock buckles enable smooth adjustment
- super comfortable wide waist belt padding provides maximum comfort even during prolonged suspension

Size: S, M/L, XL •
Weight: (M/L) 1777 g • 62.68 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813 • EN 361 • EN 1497

Work at height at night, Kladno, Czech republic Photo: Jiří Bošek

TECHNIC

STANDARD – W0063BB
SPEED – W0064BB

TECHNIC STANDARD

TECHNIC SPEED

Fully adjustable full body harness for rope access, work positioning and fall arrest with Easy-Lock or SPEED buckles and steel components.

- front large attachment point for attaching descender or work positioning devices (EN 813, EN 358)
- steel side positioning points according to EN 358 with position adjustment are placed symmetrically and do not interfere at work
- front and rear attachment points for fall arrest (EN 361)
- rear attachment point does not interfere with carrying a backpack or breathing apparatus
- attachment of the CAM CLEAN chest ascender by a mailon and the CAM CLEAN strap
- 2 braided gear loops with a bearing capacity of 5 kg
- additional slots on the waist belt allow you to safely hang expensive equipment (chainsaw, drill...)
- the corrosion resistance of the steel components is tested by spraying in a salt chamber for 48 hours

Size: S, M/L, XL
Weight: (M/L) 2045 g • 72 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813 • EN 361

TECHNIC ANSI

STANDARD – W0103BB
SPEED – W0104BB

TECHNIC STANDARD ANSI

TECHNIC SPEED ANSI

Fully adjustable full body harness for rope access, work positioning and fall arrest with SPEED buckles, steel components, fall indicator and connector keepers.

- harness is certified to the latest American Standards ANSI Z359.11-2021 and NFPA 1983 Class III
- ergonomic and removable BIG/GIGA connector keepers on the shoulder straps allow you to store the fall arrest connectors when not in use. In case of a fall, the loops will release to allow the shock absorber can be safely deployed.
- for easy inspection, the harness is equipped with a fall indicator in the area of the back attachment point which is activated as a result of a fall, a red label indicates the harness must be retired
- front large attachment point for attaching descender or work positioning devices (EN 813, EN 358)
- steel side positioning points according to EN 358 with position adjustment are placed symmetrically and do not interfere at work
- front and rear attachment points for fall arrest (EN 361)
- attachment of the CAM CLEAN chest ascender by a mailon and the CAM CLEAN strap
- SPEED buckles allow smooth and quick donning and adjustment of the harness with maximum comfort
- the corrosion resistance of the steel components is tested by spraying in a salt chamber for 48 hours
- 2 braided gear loops with a bearing capacity of 5 kg
- additional slots on the waist belt allow you to safely hang expensive equipment

Size: S, M/L, XL
Weight: (M/L) 2085 g • 73.55 oz
Max. rated load: 150 kg (140 kg/310 lbs according ANSI)
ANSI Z359.11-2021 • NFPA 1983 Class III • CE 1019 • EN 358 • EN 813 • EN 361

ROOF MASTER

W0091BY

NEW

You want freedom of movement when working on the roof, and the ROOF MASTER harness with its many features and unique Singing Rock MOTION SYSTEM guarantees it. Its movable attachment point is openable, which makes it easy to connect a chest ascender or detach the shoulder straps. So, you can choose between a full-body and a sit harness, it's up to you.

- Singing Rock MOTION SYSTEM guarantees freedom of movement without being restricted by a working rope or a fall arrest system
- in the front, part of the MOTION SYSTEM is the light alloy RINGO ring which forms a movable attachment point and a flexible connection between the waist belt and shoulder straps
- RINGO ring is openable, which allows easy attachment of the CAM CLEAN chest ascender or detachment of the shoulder straps and conversion of the full-body harness into the sit harness
- on the back of the harness, the MOTION SYSTEM consists of a classic light alloy ring that works as a flexible connection between the dorsal strap and the back of the waist belt
- this rear light alloy ring is equipped with a grey textile loop with a capacity of 100 kg for heavier work tools
- in the back of the shoulder straps there is a red EN 361 textile attachment point for fall arrest
- front EN 361 fall arrest point (the red light alloy D-ring) is positioned lower than usual and takes full advantages of the front part of the MOTION SYSTEM
- MOTION SYSTEM allows to use this point also for work positioning without restricting the user's movement or work - thus one point serves both for fall arrest and positioning at the same time
- red D-ring can also be used as EN 813 because it functions as an extension of the front attachment point
- SPEED buckles on the leg loops and on the left side of the waist belt ensure easy adjustment and comfortable putting on of the harness
- side textile EN 358 loops for work positioning are highlighted with red stitching and designed to prevent accidental catching during work
- 3D waist belt is equipped with a rubberized strength fabric with a number of attachment holes - you can thread an auxiliary cord through the holes to create additional loops or you can clip auxiliary carabiners into the holes to connect a tool bag (each hole has a bearing capacity of 10 kg)
- waist belt is also equipped with two standard textile loops with a bearing capacity of 5 kg
- ring-shaped leg loops are lightweight, yet very comfortable, their size can be easily adjusted with SPEED buckles, they are connected to the waist belt at the back by adjustable elastic straps
- neoprene pocket on the right leg loop is suitable for small items
- reflective printing on the waist belt increases the visibility of the harness
- identification label on the back of the shoulder straps ensures that you can always find yours in a pile of harnesses

Weight: (M/L) 1830 g • 64.55 oz
Max. rated load: 150 kg
Size: S, M/L, XL
CE 1019 • EN 358 • EN 813 • EN 361

TACTIC MASTER

W0096BB

Lightweight and fully adjustable fullbody safety harness intended mainly for special forces featuring the MOLLE system and a possibility to wear the harness above the bullet-proof vest. The unique Singing Rock MOTION SYSTEM with the openable RINGO O-ring gives the user freedom of movement without being restricted by a working rope or a fall arrest system. An ideal solution for working at heights where the precise positioning and free movement are important.

- frontal textile A point according to EN 361 is vertically adjustable, allowing to use the same harness with and without the bullet-proof vest
- abseil rope clipped through a connector, attached to A point, can help the user to stay in an upright position even with a heavy load on the back
- part of the EN 813 MOTION SYSTEM is the openable RINGO O-ring, which allows the user to disconnect the chest part and leg loops or put the chest ascender along with other devices directly to RINGO
- shoulder straps and leg loops are fully removable, the harness can be used as a sit harness or positioning (tactical) belt only
- textile loops for work positioning according to EN 358 designed in a way that prevents accidental capture during a work
- during the fall arrest to the dorsal textile attachment point EN 361, the MOTION SYSTEM efficiently splits the energy of the fall to the harness
- harness can be easily supplemented with the CAM CLEAN chest ascender
- shoulder connection for confined space rescue
- MOLLE system on the waist belt, leg loops and right shoulder strap to attach the pouch or other gear
- speed buckles for quick and easy put on/off
- rear light alloy ring is equipped with grey textile loop for heavier tools with a load capacity 100 kg

Size: S, M/L, XL
Weight: (M/L) 1740 g • 61.38 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813 • EN 361 • EN 1497

SEAMASTER 3D STAINLESS STEEL

W0074DR

Fully adjustable harness for rope access with a padded wide waist belt, leg loops and shoulder straps. Suitable for work positioning, fall arrest and work restraint situations.
This harness is specially intended for workers at offshore oil platforms.

- stainless steel components make the harness ultimate choice for offshore operations
- padded waist belt, shoulder straps and leg loops
- wide waist belt provides maximum comfort when working at height
- narrowed padding and webbing on the shoulder straps in a neck area enhance comfortable work
- reflective printing on the waist belt increases the visibility in dark working conditions
- front attachment point for fall-arrest according to EN 361
- front lower attachment point for descender placement or work positioning according to EN 813
- side attachment points for work positioning according to EN 358
- 3 braided gear loops with a bearing capacity of 5 kg
- heavier items up to 35 kg can be attached to the webbing on the waist belt
- additional loops with a bearing capacity of 5 kg offer additional space for the gear and better gear orientation
- combination of standard and SPEED buckles enable fluent and fast adjustment to fit the users body
- special construction of central loop provides excellent comfort when hanging in the harness
- easy fixing CAM CLEAN ascender in vertical position is provided by stitched strap between lower front attachment point and front tie-in point
- different color webbing stitched in the buckle simplify adjusting and size selection

Weight: (M/L) 1870 g • 66 oz
Max. rated load: 150 kg
Size: S, M/L, XL
CE 1019 • EN 361 • EN 358 • EN 813

Oil platform, Photo: archive Singing Rock

ANTISHOCK I

W0086B0

Full body harness for rope access, work positioning, fall arrest. The Antishock I is the perfect solution for work at height in explosive atmospheres. It is particularly suitable for energetics, petrochemical and mining environments.

- all metal and alloy parts are overmolded with colored plastic with an electrical puncture resistance of 10 kV and antistatic finishing
- harness certified according to the newest North American standards ANSI Z359.11-2014 and NFPA 1983 Class II
- ergonomic and removable lanyard keepers on the shoulder straps allow user to store lanyard connectors when not in use - in the event of a fall, the connector is released so that the shock absorber can be safely deployed
- for easier inspection, the harness is equipped with fall indicators placed close to dorsal attachment point which are activated in case of a fall - red label indicates that the harness must be retired
- shoulder attachment points for confined space rescue according to EN 1497 2
- side attachment points for work positioning according to EN 358
- front lower attachment point for descender placement or work positioning according to EN 813
- narrowed padding and webbing on the shoulder straps in a neck area enhance a comfortable work
- chest ascender smart fixation system
- chest ascender maillon slot (recommended maillon big D, EN 362)
- 2 large braided gear loops with a bearing capacity of 5 kg
- name tag for easier recognition of the harness

Size: S, M/L, XL
Weight: (M/L) 2430 g • 85.72 oz
Max. rated load: 150 kg (140 kg/310 lbs according to ANSI)
ANSI Z359.11-2014 • NFPA 1983 Class III • CE 1019 • EN 358 • EN 813 • EN 361 • EN 1497

TARZAN

W0050

Fully adjustable full body harness intended for rope courses and adventure parks.

- attachment point for work in hanging position, rappelling according to EN 813.
- anatomic waist belt and leg loops padding
- speed buckle connecting shoulder straps with waist belt. Increased comfort when putting the harness on.
- buckle with a captive bar matches strict American standards (ANSI). Its minimum strength is 17.2 kN. No webbing slippage in a buckle. Its construction ensures longtime operation and efficiency (easy releasing and fastening even when dirty and tough webbing).
- Shoulder webbing has different colour for easy manipulation
- Left leg loops with red colour inside helps to put the harness on
- Different colour of rear plate for each size.
- Dorsal attachment point according EN 361. Steel D-ring with a bearing capacity of 15 kN. This D-ring is flat and settled on a padding.
- Webbing strap stitched in the buckle simplify handling with buckle

Size: XS – S, M – XL
Weight: 1530 g (M – XL) ±15 g • 54 oz
CE 1019 • EN 813 • EN 361

TARZAN ECONOMIC

W0059BR

Fully adjustable full body harness intended for rope courses and adventure parks.

- front attachment point for belaying and rappeling according to EN 12277 type C
- waist belt and leg loops without the padding enables to put a harness to every person
- rear steel D-ring with a bearing capacity of 15 kN according EN 361
- shoulder straps, waist belt and leg loops are easily adjustable with Easy Lock buckles
- all steel components are finished with E coating technology for higher corrosion resistance
- left leg loop with red colour helps to put the harness on
- webbing strap stitched in the buckle simplify handling with a buckle
- dorsal plastic plate with different color according the size of the harness (S – yellow, UNI – red)

Size: S (110 – 150 cm), UNI (150 – 200 cm)
Weight: 1050 g • 34 oz (UNI)
CE1019 • EN 12277 • EN 361

ROPEDANCER II

W0087BY

Fully adjustable full body harness with various attachment points intended for rope courses and adventure parks

- easy to put on and off,
- easy to adjust, thanks to 5 double buckles and 1 SPEED buckle
- bright color font lower attachment point for rappelling and belaying •waist belt in different (black) color for better orientation within the harness
- front and rear attachment points
- 2 gear loops with a bearing capacity of 5 kg
- max. rated load of the harness 150 kg
- different color of the rear triangle for each size
- suitable also for working at height

Weight: (S/M/L) 1195 g • 42.15 oz
CE 1019 • EN 12277

BODY II STANDARD

W0068BR
black version – W0068BB

Fully adjustable fall-arrest harness with various attachment points.

- two fall-arrest attachment points according to EN 361
- harness is compact and light-weight, thus suitable for horizontal or inclined space. It also allows temporary hanging in.
- intended for working in places with the risk of fall
- flat rear attachment point does not affect comfort when wearing the backpack or breathing apparatus
- shoulder and leg loops webbings are colour distinguished for easy manipulation
- webbing stitched in the buckle simplify handling
- two gear loops with max. load 5 kg
- easy to adjust, easy to put on and off
- suitable also for rope courses and adventure parks
- different colour of rear triangle for each size (S/M/L- grey, XL/XXL- yellow)
- 2 sizes fit whole size range from 150 to 210 cm

Size: S/M/L, XL/XXL, XXXL
Weight: 1025 g • 36.16 oz (size S/M/L)
CE 1019 • EN 361

BODY II SPEED

W0071BY
black version – W0071BB

Fully adjustable fall-arrest harness with various attachment points.

- version with Speed buckles on the leg loops enables easy putting the harness on
- easy to adjust, easy to put on and off
- webbing stitched in the buckle simplify handling

Size: S/M/L, XL/XXL, XXXL
Weight: 1185 g • 41.8 oz (size S/M/L)
CE 1019 • EN 361

BODY II ENERGY SPEED

W0093SY

Fully adjustable work-positioning harness with various attachment points, speed buckles and comfortable padding.

- suitable for working situations whith maximum freedom of movement during work positioning
- stitched waist belt padding allows horizontal or vertical movement of the padding thus providing maximum comfort during a work.
- side attachment points for work positioning according EN 358
- front and rear attachment points according EN 361 marked with „A" label
- removable and washable shoulder and leg loops padding provides great comfort
- shoulder padding with reflective straps and integrated loops for hooks storage
- webbing stitched in the buckles simplify handling
- two gear loops with max. load 5 kg
- 4 additional plastic hooks for light gear attachment
- different colour of rear triangle for each size (S/M/L- grey, XL/XXL- yellow)
- 2 sizes fit whole size range from 150 to 210 cm

Size: S/M/L, XL/XXL, XXXL
Weight: 2250 g • 79.44 oz (size S/M/L)
CE 1019 • EN 361 • EN 358

Power supply maintenance, Ponikla, Czech republic Photo: Jiří Bošek

BASIC LIGHT

W0090SY

Fully adjustable fall-arrest harness with a rear dorsal attachment point.

- dorsal rear D-ring attachment point according to EN 361
- one gear loop with max load of 5 kg
- easy to adjust thanks to 4 easy-lock buckles, easy to put on and off
- different color of the rear webbing for each size (S/M/L grey, XL/XXL yellow)
- all steel components finished with E-coating for higher corrosion resistance
- 2 sizes fit whole size range from 150 to 210 cm
- suitable for use with a range of accessories like Pole, Harness Padding, Suspension Trauma Safety Strap

Size: S/M/L, XL/XXL
Weight: 760 g • 26.81 oz / 810 g • 28.5 oz
CE 1019 • EN 361

BASIC

W0089SY

Fully adjustable fall-arrest harness with rear dorsal and front sternum attachment points.

- dorsal rear D-ring and front textile twin loops attachment points according to EN 361
- one gear loop with max load of 5 kg
- easy to adjust thanks to 4 easy-lock buckles, easy to put on and off
- different color of the rear webbing for each size (S/M/L grey, XL/XXL yellow)
- all steel components finished with E-coating for higher corrosion resistance
- 2 sizes fit whole size range from 150 to 210 cm
- suitable for use with a range of accessories like Pole, Harness Padding, Suspension Trauma Safety Strap

Size: S/M/L, XL/XXL
Weight: Weight: 820 g • 29 oz / 885 g • 31 oz
CE 1019 • EN 361

FAVORABLE COMBINATIONS

Singing Rock also offers favorable combinations of the fall-arrest harnesses and range of accessories:

Harness / Accessory	w/ Padding	w/Pole II	w/ Padding and Pole II
Basic Light	M0023DX	M0023PX	M0023XX
Basic	M0024DX	M0024PX	M0024PX
Body II standard	M0025DX	M0025PX	M0025XX
Body II speed	M0026DX	M0026PX	M0026XX

POLE II

W0073

Belt for work positioning and prevention against the falls from a height.

- anatomic padded waist belt ensures minimal bruising and enough comfort in the waist area
- two side "D" ring for work positioning according to EN 358, tested for 15 kN strength
- two braided gear loops with a bearing capacity of 5 kg
- slots designed for a secure hanging of expensive equipment (such as power saw, drilling machine,..) with a capacity of 1 kN
- speed buckles allow easy manipulation when dressing up and undressing

Recommended use:

- for work positioning and prevention of falls from a height
- possible combination with fullbody fall-arrest harness BODY II

Size: S/M/L, XL/XXL, XXXL
Weight: (S/M/L) 575 g • 20.3 oz
CE 1019 • EN 358

HARNESS PADDING

W0092BB

Removable shoulder and leg padding intended for Body II, Basic and Basic Light harnesses.

- durable and soft material spreads the tension to a bigger surface to increase the comfort of wearing the harness
- reduces the effects of suspension trauma after a fall
- integrated loops on shoulder padding for hooks storage
- removable and washable padding

Size: S/M/L, XL/XXL
Weight: 236 g • 8.33 oz (S/M/L)

TECHNIC PADDING

W0097BB00

Removable shoulder padding for TECHNIC harnesses

- durable and soft material spreads the tension to a bigger surface to increase the comfort of wearing the harness
- integrated loops for hooks storage
- removable and washable

Weight 100 g (3.5 oz)
Size UNI

CONNECTION STRAP

W2020X080

Extremely light and durable sling intended mainly for connection between rear dorsal attachment point and self-retractable lifelines.

- allows an easy self-connection to the rear EN 361 D-ring
- made out of dyneema
- 15 cm and 5 cm long loops are on both ends of a sling
- big loop is overturned to make a Girth Hitch knot over a D ring

Length: 80 cm
Width: 13 mm
Weight: 40 g • 1.41 oz
CE 1019 • EN 354

REFLECT VEST

W9804YX

Fluorescent-colored vest with reflective strips certified accorsding to EN ISO 20471:2013. Suitable for all Singing Rock fall arrest harnesses with or without padding which can also be equipped with the Pole II positioning belt.

- Öko-Tex® certified 240 g/m² fabrics made of PES and cotton combination for improved comfort of the user
- stitched retroreflective stripes with microscopic glass beads
- reinforced holes with hook-and- loop fixation of straps, positioning attachment points and gear loops
- size adjustment system using hook-and--loop fixation on a flap
- fits to Basic Light, Basic, Body II, Body II Energy harnesses with or without attached padding and the Pole II positioning belt
- fulfils the requirements of EN ISO 13688:2013 Protective clothing and EN ISO 20471:2013 High visibility clothing
- Material: cotton, PES, glassWeight: 375 g • 13.23 ozSize: S/M/L, XL/XXL, XXXL

EN ISO 20471:2013 · EN ISO 13688:2013

HOOK PARKING LOOP

W0102YB00

Removable connector keepers for accommodating shock absorber lanyards on shoulder straps of a full-body harness.

- in case of a fall, a parked connector is released so that a shock absorber can be safely deployed
- suitable for most of Singing Rock full-body harnesses
- marking according to ANSI Z359.11-2014
- loop is reinforced with a plastic cover
- attachment using velcro
- sold as 2 pcs.

Weight: 14 g • 0.5 oz (a piece)

SUSPENSION TRAUMA SAFETY STRAP

W1029BX00

Auxiliary sling preventing effects of suspension trauma after a fall.

- helps to relieve pressure in the groin area while a worker is awaiting rescue
- easy to attach to a harness using a girth hitch and velcro strap
- plastic cover increases resistance during normal working activities
- patented Rock&Lock buckle ensures easy length adjustment
- colored stepping loop
- suitable for Body II, Basic and Basic Light harnesses

Weight: 63 g • 2.2 oz
Material: polyamide

Telecommunication site inspection, Vislanda, Sweden Photo: Jan Špiroch

SIT WORKER 3D / SPEED

W0076DR
black version – W0076DB

Fully adjustable sit harness for work positioning. The new design of this sit harness is characterized by perfect functionality, great comfort and lightness. Intended for all vertical activities without any risk of the fall.

- super comfortable wide waist belt padding provides maximum comfort when working at height
- strength webbing on the waist belt is stitched in the way that at normal working situation the body weight is absorbed by the padding only
- anatomic leg loops and waist belt are covered with strong PES fabric providing high abrasion resistance
- SPEED buckles enable fluent and fast adjustment to fit a user´s body
- side attachment points for work positioning according to EN 358
- front attachment point for descender placement or work positioning according to EN 813, EN 358
- reflective strap and printing on the waist belt increase the visibility in dark working conditions
- 4 ergonomic braided gear loops with a bearing capacity 15 kg
- additional loops on the waist belt and leg loops with a bearing capacity of 5 kg offer additional space for the gear and better gear orientation
- slots on the waist belt for PORTER tool holder to carry your industrial tools

Size: S, M/L, XL
Weight: (M/L) 1515 g • 53.44 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813

SIT WORKER 3D / STANDARD

W0075DR
black version – W0075DB

Fully adjustable sit harness with easy-lock buckles for work positioning.

- thermo finished webbing in a waist belt for easy handling and higher durability
- all steel components finished with E coating for higher corrosion resistance
- super comfortable wide waist belt padding provides maximum comfort when working at height
- side attachment points for work positioning according to EN 358

Size: S, M/L, XL
Weight: (M/L) 1195 g • 42.15 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813

SIT WORKER 3D / SPEED STEEL

W0077DR

Fully adjustable sit harness for work positioning with the stainless steel components and SPEED buckles.

- SPEED buckles enable fluent and fast adjustment to fit a user´s body
- the harness is made in an accordance with a strict American standards (NFPA)
- 4 ergonomic braided gear loops with a bearing capacity 15 kg
- super comfortable wide waist belt padding provides maximum comfort when working at height
- side attachment points for work positioning according to EN 358

Size: S, M/L, XL
Weight: (M/L) 1650 g • 58.2 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813
NFPA Class II

URBAN II

W0022BB

Sit harness for work positioning

- anatomic waist belt and leg loops padding perfectly fits to man anatomy
- textile attachment point for work in hanging position, rappelling according to EN 813.
- textile positioning points according to EN 358 are placed symmetrically, tested for 15 kN strength.
- 2 braided gear loops with a bearing capacity of 10 kg provide enough space for 10 pieces of HMS carabiners
- additional loops with a bearing capacity of 5 kg offer additional space for the gear and better gear orientation
- slots designed for a secure hanging of expensive equipment (such as power saw, drilling machine,...)

Size: S, M/L, XL
Weight: M/L 850 g (±15g) • 30 oz
Max. rated load: 150 kg
CE 1019 • EN 358 • EN 813

FRANKLIN

W0010YB
black version – W0010BB

Work positioning seat provides more comfort when hanging in the harness.

- intended for use with our fall arrest or work positioning harnesses
- easy to adjust with Rock&lock buckles. Attachment straps are shorter to fit better to thinner users
- inside padding is made of aluminium which allows long term use without any deformation
- wider sitting area ensures good stability and allows comfortable suspension as well as standing at work positioning
- suspension straps do not press on your thighs
- three D-rings (bearing capacity 50 kg) for bucket or other gear suspension

Max. load of seat: 150 kg
Weight: 1615 g • 57 oz

Tree cutting, Poníkla, Czech Republic Photo: Marta Menaříková

ALADIN

C5056

Chest harness
- designed to be used together with a sit harness
- optimising body positon while hanging or falling
- made from lightweight wide nylon webbing
- very durable and affordable to all climbers

Must be worn with sit harness.
Do not use chest harness alone!

Size: UNI
Weight: 240 g • 8.5 oz
CE 1019 • EN 12277 •

RL CHEST

W0200BB

Fully adjustable chest harness
- non-padded
- Rock&Lock buckles on shoulder straps
- two D-rings with bearing capacity of 50 kg
- together with SIT WORKER 3D compose fully adjustable full body harness in conformity with EN 361

Do not use separately - use only in combination with a sit harness!

Size: UNI
Weight: 600 g • 21.2 oz
CE 1019

ARBO CHEST

W0108BR00

Padded chest harness designed for the ARBO MASTER arborist harness.
- offers the user greater comfort when loading the harness with heavier equipment and a more comfortable ascent
- for comfortable donning, equipped with a trident with a whistle at the front
- in the shoulder padding, there is a tunnel on each side for threading a pull-on elastic band, which is specially designed for SRT technique
- loops on the front side for possible attachment of additional equipment and height adjustment for attaching a chest ascender
- the chest harness can be used with any harness equipped with three fixing eyes

The chest harness cannot be used alone!

Size: UNI
Material: PAD, EVA foam, PES, Polyethylene, PP, Elastane
Weight: 160 g / 5.6 oz

ARBO MASTER

W0105BR

Fully adjustable work positioning harness with unique motion system at front attachment points, specially invented for professional arborists allowing freedom of movement at the tree top.

- super comfortable wide waist belt made of 3 inside webbings and wide leg loops made of 2 inside webbings provide maximum comfort when working in the harness
- removable and exchangeable bridge connecting the leg loops for variability of work at the tree top
- double rope connection bridge for two independent attachment points (EN 813) with a strength 15 kN
- knots on the connection bridge allow the length adjustment and replacement
- moveable O ring at the connection bridge as an attachment point (EN 813)
- adjustable red side D buckles between the leg loops and waist belt for the attachment point, used in a pair according to EN 813 with a strength 15 kN
- adjustable side positioning D rings possible to fold in when not in use
- replaceable adjusting webbing for D rings
- speed buckles enable fluent and fast adjustment of the waist belt and the leg loops, keep the adjusted size
- flexible rear rubber bands for adjusting the position of the leg loops
- 4 gear loops with a bearing capacity of 5 kg provide enough space for your gear
- rear loop for hanging heavy tools such as a chainsaw, etc. with a load capacity of 35 kg
- 2 red textile loops with a load capacity of 5 kg for attaching a hand saw
- 2 small steel rings with a load capacity of 10 kg for attaching the chainsaw on the left and right side
- small textile loops to create your own additional gear loops with a load capacity of 5 kg
- loops at the waist belt for the possibility of attaching a chest harness

- slots for PORTER tool holder to carry your industrial tools
- wide rubber band for attaching the first aid kit to the harness
- neoprene pocket on the leg loop for small items
- identification and methodological label

Size: S/M/L, XL
Max. rated load: 120 kg
Weight: 1680 g • 59.3 oz (S/M/L), 1760 g • 62 oz (XL)
CE 1019 • EN 358 • EN 813

SPARE PARTS:

W0109RX00	ARBO MASTER BRIDGE
W0110RX00	ARBO MASTER ADJUSTABLE WEBBING

Tree care, Paseky nad Jizerou, Czech Republic Photo: Ondřej Vítko

EVACUATION TRIANGLE SIT II

W8201BY00

Evacuation triangle for a person to rescue from a chair lift or a cable car.

- chest plastic buckle for easy putting on the triangle
- durable steel attachment points
- easy to put on and take off
- adjustable crotch webbing
- made from durable ripstop material

Only for rescue purposes.
Size: UNI • Weight: 800 g • 1.8 lb
EN 1498

EVACUATION TRIANGLE COMBI II

W8211BY00

Evacuation triangle with shoulder straps for a person to rescue from a chair lift or a cable car.

- special shoulder straps for better fixing a person in evacuation triangle
- straps are made from different color for better attachment management
- durable steel attachment points
- easy to put on and take off
- adjustable crotch webbing
- made from durable ripstop material

Only for rescue purposes.
Size: UNI • Weight: 880 g • 1.9 lb
CE 1019 • EN 1497 • EN 1498

LAIKA

W0005YBO9
black version – W0005BB09

Dog harness intended for transport of the dog from a helicopter.

- side light-alloy reinforcements
- easy and quick fastening with velcro
- max. load 150 kg

Size: UNI • Weight: 800 g • 1.8 lb

BABY RESCUE BAG

W8220

Rescue bag for the children evacuation.

- designed for rescue transporting of the children (height 40-110 cm, max. weight 25 kg)
- safety fixation by 3 belts with Velcro and with the safety straps led to cross during the transporting.
- inner padding is very comfortable and fully removable and washable
- top cover with full zipper and ventilation hole
- stabilization strap of the top cover to prevent the camber of the cover to the face of the child during the transport by the helicopter
- colored loops for the carabiner fixation and adjusting the position of the bag
- side ventilation holes covered by PVC net
- durable material with the reflection elements
- hygienic inner textile cover included
- fulfils EN 1498 requirements

Size: 80x45x35 cm
Weight: 3300 g
Max. load: 25 kg
Material:
PVC, PAD, PES,
PES / cotton

CE

Chair lift evacuation, Jánské Lázně, Czech Republic Photo: Ondřej Vítko

	type	black version	code	size	weight M/L [g]	waist [cm/in]	leg loops [cm/in]	height [cm]
EXPERT 3D	standard	yes	W0078DR02	S		65–80 / 25–31	45–60 / 18–24	150–170
		yes	W0078DR03	M/L	2110	75–100 / 29–39	50–75 / 19–29	160–180
		yes	W0078DR05	XL		85–130 / 33–51	50–75 / 19–29	175–205
	speed	yes	W0079DR02	S		65–80 / 25–31	45–60 / 18–24	150–170
		yes	W0079DR03	M/L	2415	75–100 / 29–39	50–75 / 19–29	160–180
		yes	W0079DR05	XL		85–130 / 33–51	50–75 / 19–29	175–205
	speed steel	no	W0080DR02	S		65–80 / 25–31	45–60 / 18–24	150–170
		no	W0080DR03	M/L	2685	75–100 / 29–39	50–75 / 19–29	160–180
		no	W0080DR05	XL		85–130 / 33–51	50–75 / 19–29	175–205
PROFI WORKER 3D	speed	yes	W0081DR02	S		65–80 / 25–31	45–60 / 18–24	150–170
		yes	W0081DR03	M/L	1777	75–100 / 29–39	50–75 / 19–29	160–180
		yes	W0081DR05	XL		85–130 / 33–51	50–75 / 19–29	175–205
	standard	yes	W0082DR02	S		65–80 / 25–31	45–60 / 18–24	150–170
		yes	W0082DR03	M/L	2075	75–100 / 29–39	50–75 / 19–29	160–180
		yes	W0082DR05	XL		85–130 / 33–51	50–75 / 19–29	175–205
TECHNIC	standard	no	W0063BB02	S		65–80 / 25–31	45–60 / 18–24	150–170
		no	W0063BB03	M/L	1725	75–100 / 29–39	50–75 / 20–29	160–180
		no	W0063BB05	XL		85–130 / 33–51	50–75 / 20–29	175–205
	speed	no	W0064BB02	S		65–80 / 25–31	45–60 / 18–24	150–170
		no	W0064BB03	M/L	2045	75–100 / 29–39	50–75 / 20–29	160–180
		no	W0064BB05	XL		85–130 / 33–51	50–75 / 20–29	175–205
TECHNIC ANSI	standard	no	W0103BB02	S		65–80 / 25–31	45–60 / 18–24	150–170
		no	W0103BB03	M/L	1805	75–100 / 29–39	50–75 / 20–29	160–180
		no	W0103BB05	XL		85–130 / 33–51	50–75 / 20–29	175–205
	speed	no	W0104BB02	S		65–80 / 25–31	45–60 / 18–24	150–170
		no	W0104BB03	M/L	2085	75–100 / 29–39	50–75 / 20–29	160–180
		no	W0104BB05	XL		85–130 / 33–51	50–75 / 20–29	175–205
ROOF MASTER		no	W0091BY02	S		65–80 / 25–31	45–60 / 18–24	
		no	W0091BY03	M/L	1570	75–100 / 29–39	50–75 / 19–29	160–180
		no	W0091BY03	XL		85–130 / 33–51	50–75 / 19–29	175–205
TACTIC MASTER		yes	W0096BB02	S		70-85 / 27-33	45–60 / 18–24	150–170
		yes	W0096BB03	M/L	1740	80-100 / 31-39	50–75 / 20–29	160–180
		yes	W0096BB05	XL		90-130 / 35-51	50–75 / 20–29	175–205

	type	black version	code	size	weight M/L [g]	waist [cm/in]	leg loops [cm/in]	height [cm]
SEAMASTER 3D		no	W0074DR03	S		65–80 / 25–31	45–60 / 18–24	150–170
		no	W0074DR03	M/L	1870	75–100/29–39	50–75/19–29	160–180
		no	W0074DR05	XL		85–130/33–51	50–75/19–29	175–205
ANTISHOCK I	standard	no	W0086B002	S		65–80 / 25–31	45–60 / 18–24	150–170
		no	W0086B003	M/L	2430	75–100 / 29–39	50–75 / 20–29	160–180
		no	W0086B005	XL		85–130 / 33–51	50–75 / 20–29	175–205
TARZAN		no	W0050BR02	XS–S	1530	50–80 / 20–31	45–60 / 18–24	145–165
		no	W0050BR05	M–XL		70–130 / 27–51	50–75 / 19–29	160–205
TARZAN ECONOMIC			W0059BR	UNI	1050	UNI	59–78	150–200
				S			43–78	110–150
ROPEDANCER II		no	W0087BY01	XS		UNI	UNI	125–155
		no	W0087BY03	S/M/L	1195	UNI	UNI	150–185
		no	W0087BY05	XL/XXL		UNI	UNI	180–210
BODY II	standard	yes	W0068BR03	S/M/L	1025	UNI	45–70 / 18–27	150–185
		yes	W0068BR05	XL/XXL		UNI	45–85 / 18–33	180–210
		yes	W0068BR07	XXXL		UNI	45–95 / 18–39	180–210
	speed	yes	W0071BR03	S/M/L	1185	UNI	45–70 / 18–27	150–185
		yes	W0071BR05	XL/XXL		UNI	45–85 / 18–33	180–210
		yes	W0071R07	XXXL		UNI	45–95 / 18–39	180–210

	type	black version	code	size	weight M/L [g]	waist [cm/in]	leg loops [cm/in]	height [cm]
BODY II ENERGY SPEED	speed	no	W0093SY	S/M/L	2250	75–125 / 29–49	55–70 / 22–28	150–185
		no		XL/XXL		85–140 / 33–55	65–90 / 25–35	180–210
				XXXL		85–155 / 33–61	65–105 / 25–41	180–210
BASIC		no	W0089SY03	S/M/L	820	UNI	45–70 / 18–27	150–185
		no	W0089SY05	XL/XXL		UNI	45–85 / 18–33	180–210
BASIC LIGHT		no	W0090SY05	S/M/L	760	UNI	45–70/18–27	150–185
		no	W0080SY05	XL/XXL		UNI	45–85/18–33	180–210
POLE II		yes	W0073BR02	S/M/L		75–100 / 29–39		
		yes	W0073BR03	XL/XXL	575	85–130 / 33–51		
		yes	W0073BR05	XXXL		95–150 / 37–59		
SIT WORKER 3D	standard	yes	W0075DR02	S		65–80 / 25–31	45–60 / 18–24	
		yes	W0075DR03	M/L	1195	75–100 / 29–39	50–75 / 19–29	
		yes	W0075DR05	XL		85–130 / 33–51	50–75 / 19–29	
	speed	yes	W0076DR02	S		65–80 / 25–31	45–60 / 18–24	
		yes	W0076DR03	M/L	1515	75–100 / 29–39	50–75 / 19–29	
		yes	W0076DR05	XL		85–130 / 33–51	50–75 / 19–29	
	speed steel	no	W0077DR02	S		65–80 / 25–31	45–60 / 18–24	
		no	W0077DR03	M/L	1650	75–100 / 29–39	50–75 / 19–29	
		no	W0077DR05	XL		85–130 / 33–51	50–75 / 19–29	
URBAN II	standard	yes	W0022BB02	S		65–80 / 25–31	45–60 / 18–24	
		yes	W0022BB03	M/L	850	75–100 / 29–39	50–75 / 19–29	
		yes	W0022BB05	XL		85–130 / 33–51	50–75 / 19–29	

	type	black version	code	size	weight M/L [g]	waist [cm/in]	leg loops [cm/in]	height [cm]
ALADIN		yes	C5056	UNI	240			
RL CHEST		yes	W0200BB	UNI			chest max. 125/49	
ARBO CHEST		no	W0108BR00	UNI	160			150–210
ARBO MASTER	speed	no	W0105BR02	S/M/L	1680	65–100 / 25–39	45–65 / 18–25	
		no	W0105BR05	XL	1760	85–130 / 33–51	55–75 / 22–29	

Telecommunication site installation, Norvay Photo: Pavel Nesvadba

Building painting, Brno, Czech Republic Photo: Pavel Nesvadba

ROPES

STATIC
DYNAMIC
SPECIAL
SPELEO
CORDS
ACCESSORIES



ROUTE 44

experience the touch of the future
Route 44 is unique technology invented and patented by Singing Rock. Route 44 technology allows blending of properties that were considered impossible before. Rope braided by using Route 44 technology is more compact, softer and above all it is more durable than conventional rope. All that is achieved by making no compromises in using correct sheath thickness, which is round-braided by 44 carriers. These features combine to give you better rope.

ULTRASONIC

ULTRASONIC ending is an excellent way of rope ending.
All SINGING ROCK ropes are ended by a unique technology ULTRASONIC.
The load-bearing core and the protective sheath are joined into a compact unit in the last 15 mm of the rope which eliminates the sheath slippage.

STITCHED EYE

Selected SINGING ROCK static ropes which are marked with Stitched eye icon are possible to produce with one or two stitched eyes at the end of the rope.

STATIC R44 11.0

L0450WG – white
L0450RR – red
L0450BB – black
L0450OO – orange

Excellent quality static rope intended for rope access, work positioing, rescue or manipulation with the objects.

- type A rope – low stretch kernmantel rope designed for general use with patented rope-braiding technology ROUTE 44
- sheath is made on 44 carrier machine thus the core/sheath ratio is ideal with reference to the strength of the rope and strength of the rope with knots
- sheath is braided more densely which provides better protection of the core against dirt and dust
- rope is running smoother through belay/rappel devices with lower risk of core prolapse through the sheath when is bent over small diameters
- meets the requirements that the rescuers, firemen, specialists working at height and other professionals require when working every day
- ultrasonic ending eliminates the sheath slippage
- possible to be produced with one or two stitched eyes at the end of the rope

Weight: 77 g/m
Strength: 34.9 kN
Diameter: 11.0 mm
Length: pack: 30, 40, 50, 60, 70, 80, 100 m
spool: 100, 200 m
CE 1019 • EN 1891 • UIAA

STATIC R44 10.5

L0430WR – white
L0430RR – red
L0430BB – black
L0430KK – khaki



Low stretch kernmantel rope type A designed for general use with patented rope-braiding technology ROUTE 44

- intended for rope access, work positioning, rescue or manipulation with the objects
- sheath is made on 44 carrier machine thus the core/sheath ratio is ideal with reference to the strength of the rope and strength of the rope with knots
- sheath is braided more densely which provides better protection of the core against dirt and dust
- rope is running smoother through belay/rappel devices with lower risk of core prolapse through the sheath when is bent over small diameters
- ultrasonic ending eliminates the sheath slippage
- possible to be produced with one or two stitched eyes at the end of the rope

Weight: 72 g/m
Strength: 31.5 kN
Diameter: 10.5 mm
Length: pack: 30, 40, 50, 60, 70, 80, 100 m
spool: 100, 200 m
CE 1019 • EN 1891 • UIAA

STATIC 11.0

L0250WR – white
L0250RR – red
L0250BB – black

Static rope for workers at height, rescuers, firemen, cavers and other professionals when working every day.

- low stretch kernmantel rope type A intended for rope access, work positioning, rescue, caving or manipulation with the objects
- ultrasonic ending eliminates the sheath slippage
- possible to be produced with one ro two stitched eyes at the end of the rope
- available in 3 colors

Color: white, red, black
Weight: 80 g/m
Strength: 34.5 kN
Diameter: 11 mm
Length: pack: 30, 40, 50, 60, 70, 80, 100 m
spool: 100, 200 m
CE 1019 • EN 1891 • UIAA

STATIC 10.5

L0230WR – white
L0230RR – red
L0230BB – black
L0230KK – khaki



Low stretch kernmantel rope type A intended for rope access, work positioning, rescue, caving or manipulation with the objects.

- meets the requirements that the rescuers, firemen, specialists working at height and other professionals require when working every day
- ultrasonic ending eliminates the sheath slippage
- possible to be produced with one ro two stitched eyes at the end of the rope
- available in 4 colors

Color: white, red, black, khaki
Weight: 77 g/m
Strength: 30.4 kN
Diameter: 10.5 mm
Length: pack: 30, 40, 50, 60, 70, 80, 100 m
spool: 100, 200 m
CE 1019 • EN 1891 • UIAA

Telecommunication site inspection, Guvstavsberg, Sweden Photo: Jan Špiroch

STATIC R44 NFPA 10.5

black – R0430BB
khaki – R0430KK

red – R0430RR
white – R0430WR

Excellent static rope designed for technical use for rope access, rescue and for manipulation with the objects. Meet NFPA 1983 Technical Use requirements that the rescuers, firemen, specialists working at height and other professionals require when working every day.

Weight: 72 g/m • Strength: 32 kN

Length: pack: 150, 200, 300 ft / 46, 61, 92 m
spool: 330, 600, 660 ft / 100, 183, 200 m
Diameter: 10.5 mm

Static elongation: 3.5 % (at 3.5 kN, 300 lbs)
7.2 % (at 2.7 kN, 600 lbs) • 9.9 % (at 4.4 kN, 1000 lbs)
NFPA 1983 Technical Use • EN 1891 • CE 1019 • EN 1891 • UIAA

STATIC R44 NFPA 11.0 (7/16")

black – R0450BB
orange – R0450OO

red – R0450RR
white – R0450WG

Excellent static rope, meet NFPA 1983 Technical Use requirements that the rescuers, firemen, specialists working at height and other professionals require when working every day. Manufactured by patented rope-braiding technology ROUTE 44 with ultrasonic ending.

Weight: 77 g/m • Strength: 33.5 kN
Length: pack: 150, 200, 300 ft / 46, 61, 92 m
spool: 330, 600, 660 ft / 100, 183, 200 m
Diameter: 11.0 mm • 7/16 in

Static elongation 3.0 % (at 1.35 kN, 300 lbs)
6.8 % (at 2.7 kN, 600 lbs)
10.8 % (at 4.4 kN, 1000 lbs)
NFPA 1983 Technical Use • EN 1891 • CE 1019 • UIAA

STATIC R44 NFPA 13.0 (1/2")

R0460WB



Excellent static rope for everyday work at height designed for general use for rope access, rescue and for manipulation with the objects. Meet NFPA 1983 General Use requirements.

Weight: 108.7 g/m
Strength: 47 kN
Length: pack: 150, 200, 300 ft / 46, 61, 92 m
spool: 330, 600, 660 ft / 100, 183, 200 m

Diameter: 13.0 mm • 1/2 in

Static elongation: 3.4 % (at 1.35 kN, 300 lbs)
5.4 % (at 2.7 kN, 600 lbs)
7.6 % (at 4.4 kN, 1000 lbs)
NFPA 1983 General Use

STATIC 9.0

L0220WR – white
L0220BB – black



Static rope type B. Low stretch kernmantel rope of a lower performance than type A ropes, requiring greater care in use.

- smaller diameter provides easier handling and lower weight
- recommended use: back-up rope, hauling and lowering, expeditions
- ultrasonic ending eliminates the sheath slippage
- available in 2 colors

Color: white, black
Weight: 54 g/m
Strength: 24.4 kN
Diameter: 9 mm
Length: pack: 30, 40, 50, 60, 70, 80, 100 m
spool: 100, 200 m
CE 1019 • EN 1891 • UIAA

CONTRA 10.5

L026



All-purpose static rope providing a balance between flexibility and abrasion resistance.

- intended for rope access, work positioning, rescue or manipulation with the objects
- ultrasonic ending eliminates the sheath slippage
- white color makes the rope easy to spot in the dark conditions

Color: white
Weight: 69 g/m
Strength: 30 kN
Diameter: 10.5 mm
Length: pack: 30, 40, 50, 60, 70, 80, 100 m
spool: 100, 200 m
CE 1019 • EN 1891 • UIAA

TILIA 11.5

L0460OV00
spliced loop - L0468O

Static rope specially invented for professional tree care operations.

- sheath construction guarantees higher abrasion resistance and longer lifetime
- rope has high static strength and low elongation which provides efficient work at the tree top
- works perfectly with the friction knots as well with mechanical devices
- small diameter ensures very good performance in terms of flexibility and weight
- available with a splice at one end for optimal rope glide through devices like a cambium saver or pulley

Diameter: 11.5 mm • Weight: 90 g/m
Number of falls: 20 • Strength: 30 Kn
Min. strength with a knot: 18 kN
Percentage of sheath: 54 %
Sheath slippage: 0.5 % • Static elongation: 3 %
Shrinkage: 1 %Material: PES/PA
CE 1019 • EN 1891

SPELEO R44 10.5

L0440WR



Static rope with patented rope-braiding technology ROUTE 44 developed especially for cave exploring.

- sheath is made on 44 carrier machine thus the core/sheath ratio is ideal with reference to the strength of the rope and strength of the rope with knots
- rope is running smoother through belay/rappel devices with lower risk of core prolapse through the sheath when is bent over small diameters
- white color makes the rope easy to spot in the dark
- ultrasonic ending eliminates the sheath slippage

Color: white
Weight: 72 g/m
Strength: 33.4 kN
Diameter: 10.5 mm
Length: pack: 30, 40, 50, 60, 70, 80, 100 m
spool: 100, 200 m
CE 1019 • EN 1891 • UIAA

SPELEO

L0240WR

Static rope developed especially for cave explorers.

- all-purpose rope providing a balance between flexibility and abrasion resistance that is ideal for your explorations
- great rope for wet and muddy conditions
- white color makes the rope easy to spot in the dark
- ultrasonic ending eliminates the sheath slippage

Color: white
Weight: 71 g/m
Strength: 29.4 kN
Diameter: 10.5 mm
Length: pack: 30, 40, 50, 60, 70, 80, 100 m
spool: 100, 200 m
CE 1019 • EN 1891 • UIAA

DNA DRY 8.9

L3060CX

NEW

One rope for all your climbing activities. Suitable for sport climbing at the top level and also for mountaineering and glacier tours thanks to its lightness and water resistance.

- certificated as a single, twin and half rope for the widest range of use
- extremely lightweight, ideal rope for onsight, flash or redpointing your climbing projects where every small detail matters
- great rope for mountaineering, glacier tours or trad climbing
- rope is soft and easy to manipulate in all belay devices
- UIAA water repellent treatment achieved by revolutionary nanotechnology, this treatment gives the rope longer lifetime and water resistance
- thermotransfer end marking
- middle marking
- ultrasonic ending

CE 1019 • EN 892 • UIAA • 1 1/2 ∞

ICON DRY 9.3

L0384RX

Excelent single rope for high-level climbers or glacier/mountain usage thanks to its lightness and water resistance.

- extremely lightweight and robust; it is ideal for hard routes onsight, flash or redpointing where every gram counts
- produced on 44-carrier machine, Route 44, Singing Rock's patented technology
- with our special UIAA water repellent treatment Icon 9.3 Dry is ideal for rock climbing, pumpy routes or extreme ascents in the mountains
- TEFLON® is applied on the ropes by revolutionary nanotechnology
- the sheath is more resistant against breakage, but on the other hand it is smoother
- Teflon® Treatment
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

ICON 9.3

L0380YX

Excelent single rope for high-level climbers.

- extremely lightweight and robust; it is ideal for hard routes onsight, flash or redpointing where every gram counts
- produced on 44-carrier machine, Route 44, Singing Rock's patented technology
- this unique technology gives to the rope great handling, low-weight and high durability
- the sheath is more resistant against breakage, but on the other hand it is smoother
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

HERO DRY 9.6

L0524GW



A top-class single rope with low weight and great handling qualities for high-level climbers.

- Single Tech construction provides increased resistance to abrasion and great handling qualities
- rope is soft and easy to manipulate in the belay devices
- although having a small diameter, this rope provides long lifespan
- special UIAA water repellent treatment provides longer lifetime during the usage
- TEFLON® is applied on the ropes by revolutionary nanotechnology
- ideal for sport climbing and single pitch ice climbing
- Teflon® Treatment
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

HERO 9.6

L0520GW

NEW



Excellent single rope for sport climbers.

- Single Tech construction provides increased resistance to abrasion, low weight and great handling qualities
- rope is soft and easy to manipulate in the belay devices
- even with a small diameter, this rope provides long lifespan
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

KATA DRY 9.7

UIAA WATER REPELLENT

L0580AA



High-end climbing single rope with high safety factors and extremely high durability. Suitable for both experienced climbers and beginners.

- the unique patented InterCore technology provides maximum safety even in case of a damaged sheath
- narrow diameter and great handling provide easy manipulation in all belay devices
- thanks to the sandwich-type construction of braided layers and the use of specially developed staple fibres the rope has super high resistence to abrasion.
- special UIAA water repellent treatment provides longer lifetime during the usage. Treatment is applied on the core and sheath by revolutionary nanotechnology.
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

KATA 9.7

L057AA

High-end climbing single rope with high safety factors and extremely high durability. Suitable for both experienced climbers and beginners.

- narrow diameter and great handling provide easy manipulation in all belay devices
- the unique patented InterCore technology provides maximum safety even in case of a damaged sheath
- thanks to the sandwich-type construction of braided layers and the use of specially developed staple fibres the rope has super high resistence to abrasion.
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

STORM DRY 9.8

UIAA WATER REPELLENT

L3044AG00



Single rope with great balance in weight, durability and use. Perfect choice for all-round climbing.

- this rope provides great handling, low-weight and high durability
- special Teflon® Eco treatment provides longer lifetime during the usage
- special UIAA water repellent treatment is applied on the ropes by revolutionary nanotechnology which makes the top of the line impregnated ropes
- narrow diameter and higher UIAA fall rating (UIAA falls 9) help you to improve your climbing achievements
- ideal for all-round climbing, training hard routes and RP ascents.
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

STORM 9.8

L3040GA00

Single rope with great balance in weight, durability and use. Perfect choice for all-round climbing.

- narrow diameter and higher UIAA fall rating (UIAA falls 9) help you to improve your climbing achievements
- this rope provides great handling, low-weight and high durability
- the rope is very compact, durable and pleasant to use
- ideal for all-round climbing, training hard routes and RP ascents.

- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

GYM 10.1

L3050RY00

Single rope specially invented for the climbing gyms, adventure parks or rope courses.

- this rope is designed for heavy usage with high safety factors and extremely high durability
- special technology of braided core gives the rope great resistance parameters
- braided core and compact sheet minimize the inter-fiber friction which give the result of the increased resistance to abrasion mainly when top-roping

- narrow diameter and great handling provide easy manipulation in all belay devices
- ideal for climbing schools, gyms, adventure parks and rope courses.
- thermotransfer end marking
- ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

SCORE DRY 10.1

L0364LA00

NEW

General use rope for your climbing activities. Suitable for climbing gyms or sport climbing.

- manufactured using Singing Rock's unique patented Route 44 technology
- this technology gives the rope excellent handling, low weight and long lifetime
- easy to tie and untie knots, pleasant to work with.
- rope is soft and easy to manipulate in all belay devices

- UIAA water repellent treatment achieved by revolutionary nanotechnology, this treatment gives the rope longer lifetime and water resistance
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

SCORE 10.1 ROUTE 44

L0360GG

Great rope for sport climbing with excellent visibility.

- made by Singing Rock patented technology R44, which gives to the rope well – balanced rate of weight and diameter
- this unique technology gives to the rope great handling, low-weight and high durability
- rope is very compact, durable and pleasant to use
- suitable for all belay devices on the market
- Thermotransfer end marking

- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1

DURAN 10.4

L0340AX



Ideal rope for indoor climbing and crags with rough rocks.

- made by Singing Rock patented technology R44, which gives to the rope well – balanced rate of weight and diameter
- rope is very compact, durable and pleasant to use
- rope has thicker sheath with perfect abrasion resistance still keeping good handling characteristics
- suitable for the most types of belay devices on the market
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • ①

PATRON 11.0

L0540YX
black – L0540BB00



Dynamic single rope with high safety factor and great durability.

- designed for heavy usage in rope training centres, climbing schools and rescue situations
- rope has thicker sheath with perfect abrasion resistance
- suitable for the most types of the belay devices on the market
- Thermontransfer end marking
- Middle marking
- Ultrasonic ending
- suitable for IRATA cow´s tails

CE 1019 • EN 892 • UIAA • ①

ACCORD DRY 8.3

L0514



Half and twin rope with excellent durability and special Teflon® treatment.

- tested and certified according to the EN 892 standard requirements for half ropes and twin ropes.
- with our special UIAA water repellent treatment is ideal for ice climbing or wet conditions in the mountains
- UIAA water repellent treatment is applied on ropes by revolutionary nanotechnology.
- weight, diameter and number of falls are balanced in such a way that can be used as a half and twin rope.
- used in pairs, the climber can choose between the twin rope technique or half rope technique. Whatever technique is required at the time.
- Thermotransfer end marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • ①/② ∞

ACCORD 8.3

L0510



Half and twin rope with excellent durability and lightness.

- compact rope which has minimal interfiber friction, thereby increasing durability.
- tested and certified according to the EN 892 standard requirements for half ropes and twin ropes
- weight, diameter and number of falls are balanced in such a way that can be used as a half and twin rope
- used in pairs, the climber can choose between the twin rope technique or half rope technique. Whatever technique is required at the time.
- Thermotransfer end marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • ①/② ∞

GEMINI DRY 7.9

L3020

Half and twin rope for those who count every gram.

- lightweight rope with top parameters allows wide use: ice climbing, mix routes, glacier tours or mountaineering
- tested and certified according to EN 892 standard requirements as half rope and twin rope
- with our special UIAA water repellent treatment Gemini 7.9 is ideal for ice climbing or extreme ascents in the mountains
- UIAA water repellent treatment is applied on ropes by revolutionary nanotechnology
- used in pairs, the climber can choose between the twin rope technique or half rope technique. Whatever technique is required at the time
- TEFLON® Treatment
- Thermotransfer end marking
- Ultrasonic ending

CE 1019 • EN 892 • UIAA • 1/2 ∞

Camera traps installation, Mentawai Islands, Indonesia Photo: Tomáš Ouhel

THERMOCUTTER

X0004GB

The ideal machine for cutting the ropes and accessory cords. Compact hand-held.
The blade heats quickly. For save and fast cutting the ropes.

ROPEMARKER

E0015XX

When you need to mark your rope, use SINGING ROCK Rope Marker

- with dark ink and easy-to-use design, you'll never be left wondering in those unsure situations
- when the middle marking fades you can mark it again with this specially formulated rope marker
- you can mark the center of ropes or any other part of the harness or sling

For use with: PA, PP, PES, PE.

COW´S TAIL

L0540C450
black – L0540B450

4,5 m long piece of 11mm dynamic rope to create lanyards using figure eight knots according to IRATA recommendations.

Length: 4.5 m
Rope diameter: 11 mm
CE 1019 • EN 892 •



HAMMER CORD

2 mm – L0002
3 mm – L0003

Durable, strong, easy to tie, for example for securing climbing equipment, backpack, tools or laces. Suitable for climbing purposes, guiding or work at height.

Strength: 1.2 kN / 1.9 kN

ACCESSORY CORD

L0041 – L0081

Suitable for a multitude of uses, SINGING ROCK accessory cords are strong and supple.

- easy handling
- strong
- multitude of uses

Diameters: 4, 5, 6, 7 and 8 mm

CE 1019 • EN 564 •

THROW LINE

L9031YX10

Perfect throwline providing high levels of efficiency to tree climbers.

- excellent sheath-core bond maintains a round cross-section, ensuring good rope glide through the tree
- high visible yellow color for better orientation in the treetop

Diameter: 3mm
Weight: 2,5 g/m
Strength: 0,8 kN
Material: PE (Polyethylen)

ATIKA ROPE PROTECTOR

RK900PP00

Very stable rope protector.

- made of stainless steel
- rubber layer on the lower side eliminates unwanted movement
- ensures safe work at height and load lifting over sharp edges

Weight: 1450 g / 51 oz
Material: stainless steel + rubber

ROPE PROTECTOR

W8100B

Protects rope sheath against abrasion on rough surfaces.

50/70/100/120 cm • 20/28/40/48 in
Material: PVC
Colour: mix colours

DEFENDER

W1027B

Protects rope sheath against abrasion on rough surfaces.
Allows to put 2 ropes in.

80/120 cm • 32/48 in
Material: Cortex

EDGE ROLLER

set – K0050OS03

Compact light edge roller for rope protection made from aluminium alloy.

- suitable for working on the sharp edges
- protects a moving rope againts the abrasion.
- fully adjustable to any work situation
- intended for safe work at height or heavy weights hauling
- parts are connected by maillons. Number of parts can be added as needed
- modular perfectly copy the terrain
- anodized side plates
- set includes 3 parts of edge roller and 4 maillons

Weight: 777g • 27.41 oz

EDGE ROLLER – PART

K0050OS01

- it is possible to extend the size of Edge Roller set by adding the separate moduls

Weight: 232g • 8.18 oz

DYNAMIC ROPES

	code	colour	length [m]	diameter [mm]	weight [g/m]	static elong. [%]	dynamic elong. [%]	falls	impact force [kN]	type
DNA DRY 8.9	L3060CX	pink	30 – 80, 100, 200	8,9	51	5 / 4	30 / 27 / 25	6 / 15 / 30	9,9 / 7,2 / 11,5	single/ half/twin
ICON DRY	L0384RX	red	30 – 80, 100, 200	9.3	56	7.5	34	5	8.6	single
ICON	L0380YX	yellow	30 – 80, 100, 200	9.3	56	7.5	34	5	8.6	single
HERO DRY	L0524GW	blue	30 – 80, 100, 200	9.6	59	5.1	35	8	7.9	single
HERO	L0520GW	white	30 – 80, 100, 200	9.6	59	5.1	35	8	7.9	single
KATA DRY	L0580AA	azul	30-200	9.7	61	9.0	30	5	7.7	single
KATA	L057AA	azul	30-200	9.7	61	9.0	30	5	7.7	single
STORM DRY	L3044AG	blue	30 – 80, 100, 200	9.8	65	7.9	35	9	9.1	single
STORM	L3040GA	green	30 – 80, 100, 200	9.8	65	7.9	35	9	9.1	single
GYM	L3050RY	red	30 – 80, 100, 200	10.1	68	8.4	35	7	8.7	single
SCORE DRY	L0364LA00	mint	30 – 80, 100, 200	10,1	66	7	32	8	9,1	single
SCORE	L0360GG	green	30 – 60, 80, 100, 200	10.1	66	7	32	8	9.1	single
DURAN	L0340AX	blue	30 – 60, 80, 100, 200	10.4	70	7.1	31	9	9.1	single
PATRON	L0540YX	yellow	30 – 80, 100, 200	11.0	79	5.3	31	16	9.1	single
ACCORD DRY	L0514OG	orange	30 – 70, 100, 200	8.3	43	11 / 6.4	33 / 34	5 / 15	6.3 / 9.7	half / twin
	L0514GO	green	30 – 70, 100, 200	8.3	43	11 / 6.4	33 / 34	5 / 15	6.3 / 9.7	half / twin
ACCORD	L0510AG	blue	30 – 70, 100, 200	8.3	43	11 / 6.4	33 / 34	5 / 15	6.3 / 9.7	half / twin
	L0510GA	green	30 – 70, 100, 200	8.3	43	11 / 6.4	33 / 34	5 / 15	6.3 / 9.7	half / twin
GEMINI DRY	L3020	red	30 – 70, 100, 200	7.9	39	10.5/8	38/33	5/16	5.1/7.9	half / twin
	L3020	yellow	30 – 70, 100, 200	7.9	39	10.5/8	38/33	5/16	5.1/7.9	half / twin

CE • EN 892 • UIAA • packaging dynamic ropes: pack – 30. 40. 50. 60. 70. 80. 100 m • spool – 200 m

STATIC ROPES

	code	strength [kN]	knot breaking force [kN]	stitched eye strength [kN]	static elongation [%]	number of falls	weight [g/m]	type
STATIC R44 11.0	L0450	34,9	22,3	28,5	3,2	>20	77	A
STATIC R44 10.5	L0430	31,5	19,8	27,7	3,4	>15	72	A
STATIC 11.0	L0250	34,5	22,0	28,1	3,3	>20	80	A
STATIC 10.5	L0230	30,4	18,6	24,3	3,3	>10	69	A
STATIC R44 NFPA 10.5	R0430	32	–	–	3,5 / 7,2 / 9,9	–	72	general use
STATIC R44 NFPA 11.0	R0450	33,5	–	–	3 / 6,8 / 10,8	–	77	technical use
STATIC R44 NFPA 13.0	R0460	47	30	–	3,4 / 5,4 / 7,6	–	108,7	technical use
STATIC 9.0	L0220	24,4	13,6	–	3,3	>15	54	B
CONTRA 10.5	L026	30	18	-	2	>20	69	A
TILIA 11.5	L0460	30	18	15	3	20	90	A

CE • EN 1891 • UIAA • packaging static ropes: pack – 30. 40. 50. 60. 70. 80. 100 m • spool – 100. 200 m

Static rope characteristic
Type A rope – low stretch kernmantel rope designed for general use by persons in rope access including all kinds of work positioning and restraint; in rescue and in caving Type B rope – low stretch kernmantel rope of a lower performance than type A ropes, requiring greater care in use (standard does not content other specification).

Static strength defined in the standard
22 kN for the ropes of type A • 18 kN for the ropes of type B
Another standard requirement says, the material used for rope production shall have the melting point higher than 195 °C, so polyethylene or polypropylene are not suitable for the production of the ropes.

Rope elongation
The rope elongation shall not be higher than 5%, tested by loading the rope for 3 min with 150kg load (pretension 50 kg)

Dynamic performance
Fall test with two meters long rope terminated with figure-eight knots; fall factor 1. The testing mass 100 kg for type A ropes, 80 kg for type B ropes.

SPELEO ROPES

	strength [kN]	knot breaking force [kN]	static elongation [%]	number of falls	weight [g/m]
SPELEO R44 10.5	33.4	20	3.3	>15	72
SPELEO 10.5	29.4	17.2	4.5	>10	71

CE • EN 1891 • UIAA packaging speleo ropes: pack – 30. 40. 50. 60. 70. 80. 100 m • spool – 100. 200 m

ACCESSORY CORDS

coil	diameter [mm]	weight [g/m]	strength [kN]	length [m]	ft
L0021	2	2.8	1.2	100	328
L0031	3	6.5	1.9	100	328
L0041	4	12.6	3.2	100	328
L0051	5	18.7	5	100	328
L0051BB	5	18.7	5	100	328
L0061	6	23.2	9	100	328
L0061BB	6	23.2	9	100	328
L0071	7	35.1	11.5	100	328
L0081	8	39.8	16	100	328

CE 1019 • EN 564 • UIAA • note: Hammer Cords L0002. L0003 do not fulfill EN standards and CE.



Telecommunication site inspection, Sweden Photo: Pavel Nesvadba

singingROCK

HECTOR / SCREW
HECTOR / TRIPLE LOCK

screw – K0114EE00
screw black – K0114BB00
triple lock – K0121EE00
triple lock black – K0121BB00

Large versatile pear-shaped HMS carabiner with screw/triple lock gate designed for multiple uses mainly for belaying or anchoring when working at height. Due to high strength and large gate opening it is mainly used as a central carabiner when anchoring.

- pear-shaped basket facilitates belaying with the Münter hitch or other belay devices
- angled snag free Keylock nose for smooth clipping and unclipping maneuvers
- rough notches on the screw/triple locking sleeve for easy manipulation even with gloves
- each carabiner is individually tested for a strength of 10 kN
- large rope bearing area for better rope glide and reduced wear on the carabiner
- gate opening and basket area are large enough to easily accommodate a big anchor point or more slings
- hot-forged I-beam construction makes the carabiner extremely strong, stiff and light
- excellent ergonomic provides perfect handling with the carabiner
- anodized finishing increases corrosion resistance
- unique production number for better traceability and inspection

Strength: ↔ 30 ↕ 9 ⟲ 8 kN
Gate opening (d): 26 mm
Weight: screw – 83 g / 2.9 oz
triple – 89 g / 3.1 oz

CE 1019 • EN 12275 • EN 362

HECTOR BC / SCREW
HECTOR BC / TRIPLE LOCK

screw BC – K0114EC00
screw BC black – K0114BC00
triple BC – K0121EC00
triple BC black – K0121BC00

Large versatile pear-shaped HMS carabiner with screw/triple lock gate and removable captive bar designed especially as a fixed connector in anchor systems or lanyards.

- captive bar keeps the carabiner in its proper orientation
- bar is easily removable with an Allen key no. 3
- this carabiner keeps your gear well-a-rranged and minimizes the chance of cross loading
- unique production number for better traceability and inspection

Strength: ↔ 30 ↕ 9 ⟲ 8 kN
Gate opening (d): 26 mm
Weight: screw – 85 g / 3 oz
Triple – 91 g / 3.2 oz

CE 1019 • EN 12275 • EN 362

BORA / SCREW, BORA / TWL
BORA / TRIPLE LOCK

screw – K0107EE00
screw black – K0107BB00
TWL – K0108EE00
TWL black – K0108BB00
triple lock – K0119EE00
triple lock black – K0119BB00

BORA screw

Bora TWL

Versatile pear–shaped HMS locking biner designed for belaying, rappelling and anchor building.

- hot-forged I-beam construction makes the carabiner extremely strong, stiff and light
- large rope bearing area for better rope glide and reduced wear on the carabiner
- pear–shaped basket facilitates belaying with the Münter hitch or other belay devices
- angled snag free Keylock nose for smooth clipping and unclipping maneuvers
- opening and basket area are large enough to easily accommodate the clove hitch
- available with screw, twist and triple lock gate, all of them easy to handle
- for better gear management the screw gates are in different colors
- each carabiner is individually tested for the strength 10 kN
- unique production number for better traceability and inspection

Strength: ↔ 23 ↕ 8 ⟲ 8 kN
Gate opening (d): 22 mm
Weight:
Screw 63 g / 2.22 oz
TWL/Triple lock 68 g / 2.4 oz
CE 1019 • EN 12275 • EN 362 •

Bora triple

BORA GP / SCREW

K0107EP00
black – K0107BP00

HMS carabiner designed specifically to eliminate the dangers of cross loading.

- safety wire gate keeps the carabiner in its proper orientation
- hot-forged I-beam construction offers an improved strength/weight ratio
- large rope bearing area for better rope glide and reduced wear on the carabiner
- screw locking sleeve for great handling and effective locking
- very popular for climbing gyms and ropes centres
- each carabiner is individually tested for the strength 10 kN
- unique production number for better traceability and inspection

Strength: ↔ 23 ↕ 8 ⟲ 8 kN
Gate opening (d): 22 mm
Weight: 64 g / 2.26 oz
CE 1019 • EN 12275 • EN 362 •

COLT / SCREW

K0112EE00
black – K0112BB00

Our smallest, super light locking carabiner. Ideal for belaying and anchor building on trad and alpine climbs.

- hot-forged I-beam construction makes the biner very light and still extremely strong with 11 kN gate open rating
- angled snag free Keylock nose for smooth clipping and unclipping maneuvers
- ergonomic shape and gate position designed to provide large opening and large basket area
- screw locking sleeve for great handling and effective locking
- for better gear management the screw gates are in different colors
- each carabiner is individually tested for the strength 10 kN
- unique production number for better traceability and inspection

Strength: ↔ 26 ↕ 8 ⊂⊃ 11 kN
Gate opening (d): 18 mm
Weight: 48 g / 1.69 oz
CE 1019 • EN 12275 • EN 362 • UIAA

COLT SCREW 3PACK

K0112XX30

Three super light and small locking carabiners for belaying and anchoring for reduced price.

- screw locking sleeve for great handling and effective locking
- for better gear management the screw gates are in different colors
- each carabiner is individually tested for the strength 10 kN

Strength: ↔ 26 ↕ 8 ⊂⊃ 11 kN
Gate opening (d): 18 mm
Weight: 48 g / 1.69 oz
CE 1019 • EN 12275 • EN 362 • UIAA

OXY / SCREW, OXY / TWL, OXY / TRIPLE LOCK

Screw – K0122EE05
Screw black – K0122BB05
TWL – K0122EE06
TWL black – K0122BB06
Triple lock – K0122EE07
Triple lock black – K0122BB07

Hot-forged light alloy oval carabiners designed to be used especially with pulleys, ascenders and descenders.

- hot-forged I-beam construction makes the carabiner extremely strong, stiff and light
- rough notches on the locking sleeve for easy manipulation
- angled snag free HYPERLINK „http://www.singingrock.com/Keylock" Keylock nose for smooth clipping and unclipping
- almost oval shape makes the carabiner easy to turn around in device´s attachment points, anchors or slings
- thanks to the oval shape, pulleys attached are loaded symmetrically
- large rope bearing area for better rope glide and reduced wear of the carabiner
- each carabiner is individually tested for a strength of 10 kN
- anodized finishing increases the corrrosion resistance
- unique production number

Strength: ↔ 26 ↕ 8 ↻ 7 kN
Gate opening (d): 21 mm
Weight:
Screw: 74 g • 2.61 oz
TWL/Triple lock: 81 g • 2.86 oz
CE 1019 • EN 12275 • EN 362

OXY BC / SCREW, OXY BC / TWL OXY BC / TRIPLE LOCK

Screw – K0123EC05
Screw black – K0123BC05
TWL – K0123EC06
TWL black – K0123BC06
Triple lock – K0123EC07
Triple lock black – K0123BC07

Hot-forged light alloy oval carabiner with a removable captive bar.

- captive bar keeps the carabiner in its proper orientation
- the bar is easily removable with an Allen key no. 2
- this carabiner keeps your equipment well-arranged and minimizes the chance of cross loading
- missing captive bar does not affect the strength of the carabiner and it is allowed to use the carabiner without a bar
- serial unique number for better traceability and inspection

Strength: ↔ 26 ↕ 8 ↻ 7 kN
Gate opening (d): 21 mm
Weight:
Screw: 76 g • 2.68 oz
TWL/Triple lock: 83 g • 2.93 oz
CE 1019 • EN 12275 • EN 362

Telecommunication site installation, Czech republic, Photo: Pavel Nesvadba

OZONE / SCREW, OZONE / TWL, OZONE / TRIPLE LOCK

screw – K0016AA00
screw black – K0016BB00

twist lock – K0017AA00
twist lock black – K0017BB00
triple lock – K0018AA00
triple lock black – K0018BB00

OZONE SCREW

OZONE TWISTLOCK

Oval carabiner with screw/twist/triple lock gate designed to be used with pulleys, ascenders and descenders.

- almost oval shape makes the carabiner easy to turn around in device´s attachment points, anchors or slings
- angled snag free Keylock nose for smooth clipping and unclipping
- each carabiner is individually tested for a strength of 10 kN
- unique production number

Strength: ↕26 kN↔10 kN ⟲7 kN
Gate opening (d): 21 mm
Weight: 80 g – screw, 85 g – TWL, triplelock
CE 1019 • EN 362 • EN 12275

OZONE TRIPLELOCK



Polygon Workshop, Polygon Hlubina, Ostrava, Foto: Ondřej Vítko

MAILLON MINI OVAL K82006Z

D 6 mm • 4 kN
gate opening 7,5 mm
zinc-plated • 33 g

MAILLON SMALL OVAL K82008Z

D 8 mm • 35 kN
gate opening 11 mm
zinc-plated • 77 g
CE 0082 • EN 12275
• EN 362 •

MAILLON SMALL DELTA K82207Z

D 7 mm • 4 kN
gate opening 8.5 mm
zinc-plated • 58 g

MAILLON BIG D K82310Z

D 10 mm • 45 kN
gate opening 10 mm
zinc-plated • 153 g
CE 0082 • EN 12275
• EN 362 •

MAILLON BIG DELTA K82210Z

D 10 mm • 45 kN
gate opening 12 mm
zinc-plated • 153 g
CE 0082 • EN 12275
• EN 362 •

BIG SQUARE K82410Z

D 10 mm • 45 kN
gate opening 12 mm
zinc-plated • 166 g • 5.86 oz
CE 0082 • EN 12275
• EN 362 •

BIG TWIST K82508Z

D 8 mm • 32 kN
gate opening 17,5 mm
zinc-plated • 106 g • 3.74 oz
CE 0082 • EN 12275
• EN 362 •

SMALL CONNECTOR K3702PP
steel – K3690ZO

Small connector with double trigger
automatic locking
gate opening 21 mm • 25 kN
polished, Al • 150 g • 5.29 oz
unique production number
CE 0333 • EN 362

D STEEL / SCREW K4080ZO

D steel conector / screw
with screw gate, key lock, zinc plated
◂▸50 kN ▴▾13 kN ⟲20 kN
gate opening (d) 25 mm • 255 g • 9 oz
unique production number
CE 1019 • EN 362

D STEEL / TRIPLE LOCK K4081ZO

D steel connector /triplelock
with triplelock gate, key lock, zinc plated
◂▸50 kN ▴▾13 kN ⟲20 kN
gate opening (d) 25 mm • 267 g • 9 oz
unique production number
CE 1019 • EN 362

OVAL STEEL / TRIPLE LOCK K4241ZO07

Oval steel connector /triplelock
with key lock and triplelock gate
◂▸30 kN ▴▾9 kN ⟲8 kN
gate opening (d) 18 mm • 195 g • 6.9 oz
unique production number
CE 1019, EN 362

PALM CONNECTOR

yellow – K0124SY09
grey – K0124ST09

Light alloy double action carabiner designed to be used especially on Via Ferrata routes, also certified as an industrial termination connector.

- hot forged gate
- double action opening system
- wear indicator shows when to retire the carabiner from use
- anodized finishing increases corrosion resistance
- carabiner is available in two color versions (with yellow or grey gate)
- each carabiner is individually tested for a strength of 10 kN
- unique serial number

Weight: 117 g / 4.1 oz
Material: aluminum alloy, plastic, stainless steel
Strength: ◂▸ 28 kN ▴▾ 14 kN ⟲ 7 kN
Gate opening (d): 28 mm
CE 1019 • EN 362/T • EN 12275/K

OVAL STEEL / SCREW K4241ZO05

Oval steel connector / screw
with screw gate, key lock, zinc-plated
◂▸30 kN ▴▾9 kN ⟲8 kN
gate opening (d) 18 mm
176 g • 6,21 oz
unique production number
CE 1019 • EN 362

CONNECTOR GIGA K3550PP00

with double trigger
automatic locking
gate opening 110 mm • 25 kN
polished, Al • 965 g • 34.04 oz
unique production number
CE 0321 • EN 362

BIG CONNECTOR K3536PP00

with double trigger
automatic locking
gate opening 60 mm • 28 kN
polished, Al • 450 g • 15.87 oz
unique production number
CE 0321 • EN 362

PORTER

K9000BB03

Plastic holder for racking ice screws, pitons and industrial tools.

- for racking ice screws, pitons and industrial tools on the harness
- easy clipping and un-clipping
- the nose on the upper part allows to set away some stuff in order to access stuff on the bottom.
- rubber part fixes the Porter on place and prevent it from rotation

WARNING: NOT FOR CLIMBING!
The Porter is NOT load-bearing!
It is not designed to hold human´s weight. Do not use it for protection or belaying.
Gate opening: 23 mm
Max. load: 5 kg
Weight: 32 g • 1.13 oz

MINI PEAR

K5052EE00

accessory carabiners
mix colour • 16 g • 0.56 oz • gate opening (d) 11 mm
Not for climbing.

MINI D

K5182EE00

accessory carabiners
mix colour • 25 g • 0.88 oz • gate opening (d) 14 mm
Not for climbing.

MINI D SCREW

K0027BY00

accessory carabiners
black colour • 28 g • 1 oz
gate opening (d) 13 mm
3 kN
Not for climbing.

SAFETY FIRST



TECHNOLOGY

KEYLOCK

for easy manipulation

Key lock is an extremely simple and ingenious locking system that solves the problems associated with the traditional design of carabiners. It eliminates any risk of ropes or slings becoming entangled in the gate or in the carabiner nose when it is being connected or released. Neither the gate, which is completely cylindrical, nor the nose has any sharp edges. Ropes and slings do not, therefore, come into the contact with any cutting edges.

HOT FORGING

the latest technology in manufacturing of light alloy hardware

Aluminum alloy is heated state when being forged into the final shape. This allows the metal to be formed more easily so it can be moved to areas where it is needed and removed from the areas where it is not needed.
In comparison with cold forged binners, the hot forged binners are lighter, more durable and stronger.

UNIQUE PRODUCTION NUMBER

identification of metal parts

For better traceability and inspection recording the Singing Rock metal parts are marked with the unique production number. Singing Rock metal parts marked with the unique production number are in this catalogue indicated with text "unique production number".

type	preview	code	colour / surface	material	EN12275 sport	EN362 work	↔ kN	↕ kN	⊂⊃ kN	gate open. [mm]	weight [g]	oz
D STEEL / SCREW		K4080ZO	zinc-plated	steel	×	✓	50	13	20	25	255	8.93
D STEEL / TRIPLE LOCK		K4081ZO	zinc-plated	steel	×	✓	50	13	20	25	267	9.35
OVAL STEEL / SCREW		K4241ZO05	zinc-plated	steel	×	✓	30	9	8	18	176	6.21
OVAL STEEL / TRIPLE LOCK		K4241ZO07	zinc-plated	steel	×	✓	30	9	8	18	195	6.9
COLT / SCREW		K0112EE00	mix	AL alloy	✓	✓	26	8	11	18	48	1.7
		K0112BB00	black	AL alloy	✓	✓	26	8	11	18	48	1.7
BORA / SCREW		K0107EE00	mix	AL alloy	✓	✓	23	8	8	22	63	2.2
		K0107BB00	black	AL alloy	✓	✓	23	8	8	22	63	2.2
BORA / TWL		K0108EE00	grey	AL alloy	✓	✓	23	8	8	22	68	2.4
		K0108BB00	black	AL alloy	✓	✓	23	8	8	22	68	2.4
BORA / TRIPLE LOCK		K0119EE00	orange	AL alloy	✓	✓	23	8	8	22	68	2.4
		K0119BB00	black	AL alloy	✓	✓	23	8	8	22	68	2.4
BORA GP / SCREW		K0107EP00	grey	AL alloy	✓	✓	23	8	8	22	64	2.3
		K0107BP00	black	AL alloy	✓	✓	23	8	8	22	64	2.3
HECTOR / SCREW		K0114EE00	blue	AL alloy	✓	✓	30	9	8	26	83	2.9
		K0114BB00	black	AL alloy	✓	✓	30	9	8	26	83	2.9
HECTOR / TRIPLE LOCK		K0121EE00	blue	AL alloy	✓	✓	30	9	8	26	89	3.1
		K0121BB00	black	AL alloy	✓	✓	30	9	8	26	89	3.1
HECTOR BC / SCREW		K0114EC00	blue	AL alloy	✓	✓	30	9	8	26	85	3
		K0114BC00	black	AL alloy	✓	✓	30	9	8	26	85	3
HECTOR BC / TRIPLE		K0121EC00	blue	AL alloy	✓	✓	30	9	8	26	91	3.2
		K0121BC00	black	AL alloy	✓	✓	30	9	8	26	91	3.2
OXY SCREW		K0122EE05	golden	AL alloy	✓	✓	26	8	7	21	74	2.6
		K0122BB05	black	AL alloy	✓	✓	26	8	7	21	74	2.6
OXY TWL		K0122EE06	golden	AL alloy	✓	✓	26	8	7	21	81	2.9
		K0122BB06	black	AL alloy	✓	✓	26	8	7	21	81	2.9

OXY TRIPLE LOCK		K0122EE07	golden	AL alloy	✓	✓	26	8	7	21	81	2.9
		K0122BB07	black	AL alloy	✓	✓	26	8	7	21	81	2.9
OXY BC SCREW		K0123EC05	golden	AL alloy	✓	✓	26	8	7	21	76	2.7
		K0123BC05	black	AL alloy	✓	✓	26	8	7	21	76	2.7
OXY BC TWL		K0123EC06	golden	AL alloy	✓	✓	26	8	7	21	83	2.9
		K0123BC06	black	AL alloy	✓	✓	26	8	7	21	83	2.9
OXY BC TRIPLE LOCK		K0123EE07	golden	AL alloy	✓	✓	26	8	7	21	83	2.9
		K0123BB07	black	AL alloy	✓	✓	26	8	7	21	83	2.9
OZONE / SCREW		K0016AA00	blue	AL alloy	✓	✓	26	10	7	21	80	2.82
		K0016BB00	black	AL alloy	✓	✓	26	10	7	21	80	2.82
OZONE / TWL		K0017AA00	blue	AL alloy	✓	✓	26	9	7	21	85	3
		K0017BB00	black	AL alloy	✓	✓	26	9	7	21	85	3
OZONE / TRIPLE LOCK		K0018AA00	blue	AL alloy	✓	✓	26	9	7	21	85	3
		K0018BB00	black	AL alloy	✓	✓	26	9	7	21	85	3
SMALL CONNECTOR		K3702PP	silver	AL alloy	✕	✓	25			21	150	5.29
		K3690ZO	zinc-plated	steel	✕	✓	25			244	244	8.6
BIG CONNECTOR		K3536PP	silver	AL alloy	✕	✓	28			60	450	15.87
GIGA CONNECTOR		K3550PP	silver	AL alloy	✕	✓	25			110	965	34.04
PALM CONNECTOR		K0124SY09	yellow	AL alloy	✓	✓	28	14	7	28	117	4.1
		K0124ST09	grey	AL alloy	✓	✓	28	14	7	28	117	4.1

Tree care, Paseky nad Jizerou, Czech Republic Photo: Ondrej Vitko

singing rock
Safe 2
Helberg
FLEX

FLASH

Professional protective helmets designed with emphasis to comfortability and durability. Helmets are available in two models depending on the user´s choice according the working situation.

- helmet construction with shock resistant ABS/PC shell and without EPS lining provides great ventilation and comfort for user
- fully adjustable headband with two side and two rear adjusting sleeves to regulate the length of the chin straps
- fast, easy and durable size adjustment mechanism on the back of the helmet with UNI size 53–63 cm
- suspension straps easily adjustable to 3 depth levels
- four head lamp holders for any head lamp available on the market
- inner padding fully removable and hand or machine washable at 30 °C (86 °F)
- helmets can be safely used in the temperatures ranging from –30 to +50 °C (–22 to 122 °F)
- universal 30 mm accessory slot is compatible with most of the visors and hearing protectors on the market
- certified with Hellberg safety ear muffs
- reflective stickers included
- unique number marking

Bouldering hall Teplice, Czech Republic Photo: Ondřej Vítko

FLASH INDUSTRY

red – W9601RX00
white – W9601WX00
yellow – W9601YX00
black – W9601BB00
high visible – W9601QX00

Professional safety helmet for industrial work and construction sites. Its main purpose is to protect the user against falling objects and voltage.

- safety chin strap in compliance with EN 397 is released at a load ranging between 15 and 25 daN (approx. 15–25 kg), which eliminates the risk of strangling
- suitable for working situations where, in case of fall, the risk of strangling is higher than risk of dropping the helmet
- fulfils EN 397 optional requirements: low temperature (–30°C), lateral deformation, electrical insulation (440V a.c.)
- five color variants
- fulfils side impact force requirements according to EN 12492

Weight: 455 g • 16.05 oz
Material: ABS/PC
Size: UNI (53–63 cm)
Color: yellow, white, red, black, high-visibility yellow
CE 1015 • EN 397 (LD, 440V a.c., -30 °C)

FLASH ACCESS

red – W9603RX00
high visible yellow – W9603QX00

Protective helmet for work at heights, and rescue purposes. It is primarily intended for protection against falling objects and to protect against voltage.

- helmet has a solid chin strap that will withstand a load of at least 50 kg, which prevents the possibility of dropping the helmet in case of fall
- suitable for work at heights activities where, in case of fall, the risk of dropping the helmet is higher than risk of strangling
- partly meets the requirements the requirements of EN 397 and EN 12492
- fulfils EN 397 optional requirements: low temperature (–30°C), lateral deformation, electrical insulation (440V a.c.)
- fulfils side impact force requirements according to EN 12492

Weight: 455 g • 16.05 oz
Material: ABS/PC
Size: UNI (53–63 cm)
Color: red, high-visibility yellow
CE (LD, 440V a.c., -30 °C)
CE 1015

FLASH AERO

red – W9602RX00
high-visibility yellow – W9602QX00

Protective well ventilated helmet for work at heights, and rescue purposes. Suitable for physically hard working persons. Its main purpose is to protect the user against falling objects.

- helmet has a solid chin strap that will withstand a load of at least 50 kg, which prevents the possibility of dropping the helmet in case of fall
- suitable for work at heights activities where, in case of fall, the risk of dropping the helmet is higher than risk of strangling
- partly meets the requirements the requirements of EN 397 and EN 12492
- fulfils ventilation requirements according to EN 12492 which ensures better ventilation for physically hard working persons and persons working in excessively warm environments
- fulfils side impact force requirements according to EN 12492

Weight: 455 g • 16.05 oz
Material: ABS/PC
Size: UNI (53–63 cm)
Colors: red, high-visibility yellow
CE

PENTA

C0091

NEW

The second generation of the popular, lightweight, comfortable and ventilated climbing helmet. Due to its comfort and lightweight construction, it is ideal for sport climbing, trad climbing, mountaineering and via ferratas.

- the first climbing helmet on the market in three sizes (S 48-54 cm, M/L 52-58 cm, XL 56-62 cm) for the widest range of users
- 30 % larger vent area than the first generation ensures excellent ventilation even on the hottest summer days
- weight under 200 g (size M/L) ensures comfort for all-day climbing
- compact upper protects the user from falling objects, yet maintains a low profile
- hard PC shell protects against sharp objects, while PS foam absorbs the impact force
- thanks to its low profile, the helmet does not get in the way when climbing and fits neatly on the head
- comfortable and easy size adjustment system with straps that don't squeeze even after a full day of climbing
- soft and wide chin strap ensures maximum comfort and its length allows a scarf or hat to be worn under the helmet
- clips for attaching the head lamp are recessed to avoid catching them when removing the slings or hood from the jacket
- inner padding is in one piece to prevent the loss of smaller parts, holds better, is completely removable and washable
- available in 4 colors with a modern look

C0091YX02	PENTA S yellow gold
C0091YX03	PENTA M/L yellow gold
C0091YX05	PENTA XL yellow gold
C0091GX02	PENTA S mint green
C0091GX03	PENTA M/L mint green
C0091GX05	PENTA XL mint green
C0091SX02	PENTA S olivine gray
C0091SX03	PENTA M/L olivine gray
C0091SX05	PENTA XL olivine gray
C0091FX02	PENTA S spruce blue
C0091FX03	PENTA M/L spruce blue
C0091FX05	PENTA XL spruce blue

CE, EN 12492
Color: yellow gold, mint green, olivine gray, spruce blue
Weight: S 185 g • 6.5 oz,
M/L 195 g • 6.9 oz,
XL 205 g • 7.2 oz
Size: S (48-54 cm • 19-21 in),
M/L (52-58 cm • 20.5–23 in),
XL (56-62 cm • 22-24.5 in)
Materiál: PC, EPS, PA, POM, PE foam, rubber

PENTA JUNIOR

C0091JY02

NEW

Lightweight, comfortable and fully ventilated helmet for the smallest climbers. For its comfort and lightweight construction, it is ideal for sport climbing, mountaineering and via ferratas.
designed for child users with a small head circumference (48-54 cm)
with a weight of 185 g, your child will not know he/she is wearing a helmet
large vent area guarantees excellent ventilation even on the hottest summer days
compact top protects children from falling objects, yet maintains a low profile
hard PC shell protects against sharp objects, while PS foam absorbs the impact force
thanks to its low profile, the helmet does not get in the way when climbing and fits neatly on the head
soft, wide chin strap ensures maximum comfort and its length allows a scarf or hat to be worn under the helmet
comfortable and easy size adjustment system with straps that do not squeeze even after a full day of wear
inner padding is in one piece to prevent the loss of smaller parts, holds better, is completely removable and washable
recessed clips for attaching any head lamp on the market
comes with stickers for your child to create their own unique design

Color: arnica yellow / dark teal
Hmotnost: 185 g · 6.5 oz
Size: UNI (48-54 cm)
Material: PC, EPS, PA, POM, PE foam, rubber
CE • EN 12492

Via ferrata Slaný, Česká republika Foto: Jan Zámečník

HEX

Durable, fully ventilated helmet for climbing, mountaineering and other rope activities. Due to its durability, ventilation and versatility, it is suitable for both sport and trad climbing, via ferrata or rope parks.

- durable EPP + ABS shell protects against falling objects and guarantees a high degree of protection against impact force, including repeated impact force
- the „OPEN CELL" construction with 35 ventilation holes with a total area of 108 cm^2 guarantees maximum ventilation
- easy and quick size adjustment mechanism in the back of the helmet
- chin strap made of a soft and wide webbing provides maximum comfort
- inner padding is made as one piece, which prevents the loss of smaller parts and holds better
- inner padding is removable and washable
- integrated „EASY CLIP" front clips for reliable attachment of a headlamp, their shape prevents jamming of a hood / slings
- the „UNI FIX" elastic system on the backside simply attaches any headlamp or ski goggles
- available in two sizes (M 52/58cm a L 55/61cm)
- modern design and 5 colors

Size M (52-58 cm):	
ice white	C0900WX03
arnica yellow	C0900YX03
garish blue	C0900MX03
mountain lake azure	C0900AX03
fox red	C0900RX03
Size L (55-61 cm):	
ice white	C0900WX04
arnica yellow	C0900YX04
garish blue	C0900MX04
mountain lake azure	C0900AX04
fox red	C0900RX04

Weight: M 300 g • 10.6 oz,
L 330 g • 11.6 oz
CE • EN 12492

Rope park Rokytnice nad Jizerou, Czech Republic Photo: Jan Zámečník

PENTA

blue – C0071AA00
red – C0071RR00
grey – C0071SS00
white – C0071WW00

Extremely lightweight, super-comfortable and fully ventilated climbing helmet. All this combined with a maximum head protection. For its comfort and lightweight design is ideal for sport climbing, mountaineering, trad climbing or via ferrata.

- Co-molded expanded polystyrene foam and hard polycarbonate shell engineered to ensure maximal head protection and still keep lightweight and low profile
- Narrow straps of retention system are very soft and light and do not press as standard hard-plastic headbands
- Soft (webbing made) rear adjustment system (headband) conforms better to the head and provides compact storage in the backpack
- Extended chin strap length allows to wear a hat under the helmet
- 4 headlamp clips are imbedded to avoid snagging, robust for easy handling and secure attachment of any headlamp on the market
- 11 vents and air channels built in the foam facilitate excellent ventilation
- Inside padding is fully removable and washable
- Available in 4 color versions

Weight: 205 g • 7.23 oz
Color: blue, grey, red, white
Size: UNI (51–60 cm)
CE • EN 12492 • UIAA



HELMETS

	name	code	color	head circumference (cm)	weight (g)	EN 397	EN 12492	CE						
	FLASH INDUSTRY	W9601	yellow, white, red, black, high-visibility yellow	53–63	455	✓	×	CE 1015	15–25 kg	440V a.c.	×	–30 °C	✓	✓
	FLASH ACCESS	W9603	red, high visible yellow	53–63	455	×	×	CE 1015	min. 50 kg	440V a.c.	×	–30 °C	✓	✓
	FLASH AERO	W9602	red, high visible yellow	53–63	455	×	×	CE	min. 50 kg	×	✓	–10 °C	×	✓
	PENTA	C0071	blue, red, grey, white	51–60	205	×	✓	CE	min. 50 kg	×	✓	–10 °C	×	✓
	PENTA	C0091	yellow gold, mint green, olivine gray, spruce blue	48–54 / 52–58 / 56–62	185 / 195 / 205	×	✓	CE	min. 50 kg	×	✓	–10 °C	×	✓
	PENTA JUNIOR	C0091JY02	arnica yellow, dark teal	48–54	185 g	×	✓	CE	min. 50 kg	×	✓	-10 °C	×	✓
	HEX	C0900	ice white, arnica yellow, garish blue, mountain lake azure, fox red	52–58 / 55–61	300 / 330	×	✓	CE	min. 50 kg	×	✓	-10 °C	×	✓

SAFE PC ELECTRIC ARC VISOR X0049XX00

Visor providing protection against electric arc up to 400 volts.

- approved to medium impact and suitable for electrical work
- visor is possible to attach with or without the earmuffs
- for attaching to the FLASH helmet SAFE 2 FLEX CARRIER and SECURE earmuffs or CLASSIC ADAPTOR are needed

Material: PC
Length: 200mm • Weight: 116g
Thickness: 1,5mm
CE • EN 166/1B389 • EN 170/2-1,2

SAFE NYLON MESH VISOR X0051XX00

Light weight and non-conductive visor which stays close to your face for great coverage.

- gives a comfortable airflow
- approved to low impact
- visor is possible to attach with or without the earmuffs
- for attaching to the FLASH helmet SAFE 2 FLEX CARRIER and SECURE earmuffs or CLASSIC ADAPTOR are needed

Light transmisson 58–61%
Length: 185mm
Weight: 36g
CE EN 1731/F • ANSI Z87

SAFE STEEL MESH VISOR X0050XX00

The unique hexagon shaped etching provides superior light transmission for added safety in low-light conditions.

- stays close to your face for great coverage
- gives comfortable airflow
- approved to low impact and suitable for applications such as forestry work and grass/bush trimming
- visor is possible to attach with or without the earmuffs
- for attaching to the FLASH helmet SAFE 2 FLEX CARRIER and SECURE earmuffs or CLASSIC ADAPTOR are needed

Weight: 52 g • Material: steel
Light transmission: 82–85,5 %
Length: 185mm
CE • EN 1731/F • ANSI Z87

SAFE 2 FLEX CARRIER X0052XX00

Intended for attachment of the visors to helmet using earmuffs or adaptors.

- Compatible with Flash helmets.

CE • EN 166/1731 • ANSI Z87+

CLASSIC ADAPTOR (PAIR) X0053XX00

Allows attachment of the flex carrier for face shield without earmuffs.

- compatible with Flash helmets
- sold in pair

COVER

W9605XX00

Protective visor suitable for industrial work and construction sites. Its main purpose is to protect the user against fast-moving particles.

- durable positioning mechanism with two positions
- knurled screw for easy manipulation
- robust visor body with excellent optical performance area with anti scratch film
- fulfills EN 166 / 1 / F (1 - First optical quality
- F - Increased resistance against fast flying particles)
- visor is clear and do not have any protection against UV radiation
- compatible with the Singing Rock FLASH helmet family. Cannot be used separately or with another helmets.

Height: 100 mm
Thickness: 2.25 mm
Material: PC
Weight: 100 g • 3.5 oz
CE • EN 166 1 F

SECURE EARMUFFS

1 C – X0048XX25
2 C – X0048XX29
3 C – X0048XX31

SECURE EARMUFFS 1C
The cap mounted earmuff is the ideal choice for any work that requires head and hearing protection.

- durable construction withstands rough environments
- slim design reduces the risk of snagging in confined areas
- available in three protection levels, clearly indicated with bright safety colours for easy identification and selection
- fully compatible with Safe Visor System
- universal 30 mm euro slot adaptor is compatible with most helmets on the market
- non-conductive
- smooth telescopic size adjustment
- certified with Flash helmets

Size: UNI • Weight: 250 g
SNR: 25 • NRR: 22 • SLC (80): 25
Suitable for: construction sites, engineering, forestry work, agriculture, mining
CE EN 352-3:2002

SECURE EARMUFFS 2C
Great choice for long term use in middle noise environment or for shorter use with high noise level.
The best choice for high frequency noise.
Weight: 271 g
NRR: 24 • SLC (80): 28
Suitable for: construction sites, engineering, forestry work, agriculture, mining
CE EN 352-3:2002

SECURE EARMUFFS 3C
Earmuffs suitable for extremely high noise environment.
The best choice for low oscillation frequency.

Weight: 300 g
SNR: 31 • NRR: 27 • SLC (80): 31
Suitable for: mining, car racing
CE EN 352-3:2002

XSTREAM LD

X0062XX00

Hellberg hearing protection with Bluetooth for music streaming. Your hearing is protected while you enjoy your favourite music with excellent sound quality, and the built-in speech microphone allows you to make phone calls.

- level dependent Active Listening micro-phones
- waterproof to IPX4
- easy to operate with push buttons
- voice assistant support
- USB charging
- battery power-save function
- fully compatible with Hellberg Safe Visor System
- certified with FLASH helmets

Technical data

- SNR: 28; NNR: 25; HML: 31-26-18
- operation temperature: -20°C / +55°C
- battery type: Li-Ion
- weight: 416 g (14.67 oz)
- Bluetooth® version: 4.1, A2DP 1.2, HSP 1.1, HFP 1.6
- run-time: 50 hours
- stand-by time: 100 hours
- charging time: 3 hours

1974 EN352-3, 4, 6, 8 • ANSI S-3.19-1974 • CSA Z94.2-02 ROHS • REACH • WEEE

LAMPFIX

W9606SX00



Lamp holder on the side of the working helmet.

- fits into universal 30 mm slot on the helmet
- suitable for the lamps with a diameter 18–23 mm (lamp not included)
- ideal with Flash helmet, compatible also with Petzl, Kask and other helmets on the market
- compatible with Hellberg hearing protection
- compatible with Cover protective eye shield also in combination with Hellberg hearing protection

Weight: 15 g • 0.53 oz
Material: PA, rubber

FLASH PADDING

W9604BX00

Replacement foam padding for FLASH helmets.
- easy maintenance and replacing the padding

Weight: 6 g • Material: PE

HEX PADDING

C0901SB

Replacement padding for the HEX helmet
- easy maintenance and replacing
- washable by hand or in a washing machine at 30° C

Weight: 10 g • Size: M, L • Material: PES

PENTA PADDING

C0092XX

Replacement padding for the PENTA helmets
- easy maintenance and replacing
- washable by hand or in a washing machine at 30° C

Size: S, M/L, XL
Weight: 10 g (M/L)
Material: PES

Power cable installation, Cableway Zugspitze, Germany Photo: Gábor Berta

HARDWARE

ANCHOR AND BELAY DEVICES
ASCENDERS
DESCENDERS
PULLEYS
SELF BRAKING DEVICES
RETRACTABLE
FALL ARRESTERS

SIR

K032SIR00

Robust multifunctionality device for use in industrial rope access. Its functionality spans the range from rope descender and abseiling device through fall-arrest device to work positioning device for use on roofs and edges.

- unimpeded movement of the cam
- by pulling onto the working end of the rope the cam engages and jams the rope
- by pulling the lever the cam gradually releases the rope. If the lever is pulled down to its terminal position the double--stop function is triggered which blocks the rope again
- spring loaded pin for impeded swinging of the cam
- easy and intuitive installation of the device onto the rope. (watch the pictograms and read the instruction of use)
- no hidden mechanisms for easy inspection
- metal lever under all industrial conditions tested for 225 Kg according to EN 12841(rope access)

Weight: 365g • 12.88 oz
Rope diameter: 10–12 mm
Working load: 225 kg

EN 341-A Singing Rock static rope
R 44 11 mm
EN 12841-C static rope 10–12 mm
CE 0123

DOUBLE STOP PLUS

K031DSD00

Descender with anti-panic system in case of accidental loss of descent control.

- the descender doesn't have movable flanges. This makes it a robust and mistake-resilient device (quick insertion and release, no need to unclip it for rope insertion)
- new cam tested for higher loads – enhanced braking in both stop positions
- unique way of rope insertion. Diminished possibility of incorrect insertion of the rope. Even incorrect insertions will not result in a fall as the rope is blocked.
- sensitive and longer handle enables smooth descent without harmful rope twisting, gentle and progressive braking (enhanced press stop braking mode)
- rubberized handle provides pleasant feeling, non slip and thermal insulation.
- ergonomically improved curved edges and longer flanges provide the user with a comfortable grip with the handle
- integrated wear indicator
- high strength plain bearing added to the pivoting cam
- all parts in contact with the rope are made of stainless steel – minimum possible wear
- rope diameter: 9–12mm
  9 mm – max. rated load 130 kg
  10–12 mm – max. rated load 200 kg

Weight: 421 g • 14.85 oz • Breaking loads in excess of 22 kN.
Increased maximum rated load to 200 kg.
Reduced slippage of the rope to 600 daN.
Reduced force required on the handle.
CE 0123 • EN 12841 TypeC

INDY EVO PLUS

K0101BX00

Manually operated descender device with double auto-locking system,that locks both when the lever is released or when it is pressed.
INDY EVO is also a descender device (conform to EN 12841 type C) for working rope and it allows a descent at a controlled speed and stop at any time, hands free, on a static rope (EN 1891) or dynamic rope (EN 892).
It allows the lowering of two people at the same time.

Dimensions: 212x58x38 mm
Weight: 480 g • 16.9 oz
Rope Ø 10-12 mm (100 kg)
Rope Ø 11-12 mm (200 kg)
NFPA 1983 (2012 ED)
Rope Ø 10-13 mm (one person only)
CE 0426 • EN 341 • EN 12841

RAMA

grey – K0043SX00
orange – K0043OX00

Intuitive single rope belay device with enhanced braking feature. Designed for gym or single pitch sport climbing.

- reliable locking geometry provides added level of safety to your belay
- operating is very simple, as it works without any moving parts or lever
- large clipping area for most common carabiner shapes, works best with BORA or OXY carabiner
- durable stainless steel braking surface provides longer lifetime and the smooth and secure control for gradual lowering
- functionality is according to the tube principle and is therefore suitable for lead and top-rope climbing
- compact geometry makes paying out rope even faster and easier, while the handle has a comfortable and firm grip.

Weight: 84 g • 3 oz
Rope diameter: 8.7 – 11 mm
Material: Light alloy, steel, plastic
EN 15151-2

RAMA SET

M0201XX00

Single rope belay device with enhanced braking feature and hot-forged light alloy oval carabiner OXY TWL create a perfect set for lead or top-rope climbing.

Weight: 165 g • 5.82 oz
Rope diameter: 8.7 – 11 mm
Material: Light alloy, steel, plastic

SHUTTLE

K6140EE00
black matt – K6140BB00

Belay and rappel device
One device to do it all, the Shuttle offers maximum versatility. It has a groove, designed and shaped to provide equal friction for both thin and thick ropes.
When you're belaying from above, the "guide mode" lets you bring up one or two seconding climbers under control. For lowering, it has a small secondary hole that you can clinch carabiner or sling to release the device.

- designed for twin, half and single ropes
- lightweight and compact
- V-grooves for high friction when belaying the leader or rappeling
- only 65 g – one of the lightest belay devices on the market
- self locking function when belaying the second
- eye for releasing the weight
- possibility of simultaneous belaying two climbers
- weight: 65 g • 2.29 oz
- material: light alloy

Rope diameter:
1/2 ∞ 7,8 – 10,5 mm
1 9 – 10,5 mm
EN 15151-2

BUDDY

K6132EE
black matt – K6132BB

Light and compact belay tube.
For all-round climbers.
Designed for ropes 7,8 – 11 mm
mix color • 54g • 1.91 oz

EN 15151-2

SAFETY FIRST

FIGURE 8 L

K6031EE
black matt – K6031BB

Designed for ropes of bigger diameters.
30 kN • color mix • light alloy • 125 g • 4.41 oz
- for ropes of various diameters
- easy rappelling
- effective heat distribution

EN 15151-2

FIGURE 8 M

K6021EE
black matt – K6021BB

Designed for ropes of smaller diameters.
25 kN • color mix • light alloy • 104 g • 3.67 oz

EN 15151-2

RESCUE FIGURE EIGHT

light alloy – K6180BB

Special figure eight for the rescue situations and fast rappeling
Strength: 40 kN
Material: light alloy
Weight: 154 g • 5.43 oz

LIFT

LEFT – RK804BX0L
RIGHT – RK804BX0R

LIFT open

Hand ascender for safe and smooth ascent. Extra wide handle and attachment point for two carabiners will fit everyone from bigwall climbers to workers at height or special forces.

- available in two variants – for left and right hand
- stainless steel toothed cam for higher corrosion resistance and for any conditions (frozen or dirty ropes)
- overmolded grip and ergonomic upper part for a comfortable and powerful grip
- wide lower hole allows to connect two standard carabiners
- upper hole for clipping a carabiner around the rope
- trigger with a short descent feature

Weight: 190 g • 6.7 oz
Material:
body – light alloy
cam – stainless steel
trigger – plastic

EN 12841 Static rope Ø 10–13 mm
EN 567 Rope Ø 8–13 mm
CE 1019 • EN 567 • EN 12841 type B

FOOT LIFT

Left – RK807BX0L
Right – RK807BX0P

Foot ascender to improve rope ascending in a rope access. Used in conjunction with LIFT and CAM CLEAN.

- stainless steel toothed cam for higher corrosion resistance and for any conditions (frozen or dirty ropes)
- cam / lever mechanism fully integrated into the body
- durable construction with stainless cast steel
- fully adjustable webbing to achieve the best comfort of use
- lower part is reinforced with tubular webbing for longer use
- quick and easy to adjust with O ring
- marked with unique production number
- for use with Ø 8-13 mm ropes, static and dynamic
- available in left and right version
- Foot Lift is not a PPE

Weight: 160 g • 5.6 oz
Working load: 120 kg
Material: light alloy, steel, plastic

CAM CLEAN

RK805BX00

Compact and lightweight chest ascender for safe and smooth rope ascent, rescue and special rope techniques.

- simple and quick manipulation
- lower hole angled to keep flat position on the harness
- stainless steel toothed cam for higher corrosion resistance and for any conditions (frozen or dirty ropes)
- Upper hole for attaching a PULLER shoulder strap to keep the rope clamp in a correct position
- trigger with a short descent feature

Weight: 125 g • 4.4 oz
Material:
body – light alloy
cam – stainless steel
trigger – plastic

EN 12841 Static rope Ø 10–13 mm
EN 567 Rope Ø 8–13 mm
CE 1019 • EN 567 • EN12841 type B

STRAP FOR CAM CLEAN

W0085BB00

Strap for CAM CLEAN attachment to full body harnesses including plastic cover on the carabiner.
Weight: 15 g • 0.53 oz

PULLER

S1100BY

Accesory webbing for chest ascender fixation

- fixes chest ascender in right position
- fixed by accessory sling or a mailon carabiner to front/back
- attachment point on the harness

Color: black
Size: UNI
Width: 25 mm

LOCKER

W1010BB09

Guided type fall arrester and work positioning device for 11 mm textile ropes (recommended Singing Rock Static 11).

- Construction of the device allows to release it even when it is loaded
- parking cam for blocking in required position
- unopenable version together with 11 mm sewn-in rope available as SITE – work positioning lanyard
- unique production number

Color: black matt
Weight: 240 g • 8.5 oz
CE 1019 • EN 353-2 • EN 12841

LOCKER SLING

W1015B020

Certified sling for connection the LOCKER with your harness
Length: 20 cm • Width: 20 mm
Strength: 22 kN

CE 1019 • EN 354 • EN 566

BACK-UP

K04000BB

Fall arrester that follows the user in both directions and stops the possible fall

- safe and simple to use with one hand only
- shifting the special buton on the lock mode, it can be used also as a positioning device or a normal locking device
- supports also the strongest stress in semi dynamic way and it avoids the shocking effects on the ropes caused by the tradi-tional self-locking devices wit thoothed cams
- connector included
- it can be used also as a positioning device or a normal locking device by shifting the special button on the lock mode.

Weight: 205 g • 7.23 oz (without connector), 420 g • 14.82 oz (connector included)
Rope diameter: 10-12 mm
EN 353-2 • EN 358 • EN 567 • EN 12841 A/B
CE 0426

PULLEY TWIN

RK802EE00
black version – RK802BB00

Large double pulley for textile ropes for those who need great hauling efficiency, durability and still lightweight pulley.

- designed and optimized for use with a Prusik friction knot or any clamps
- sealed ball bearing and large diameter of the sheave provides great efficiency 94%
- top attachment point accepts up to three carabineers
- durable and lightweight high-efficiency single pulley for industrial use and hauling systems
- formed side plates provides protection of rope against contact with a surrounding
- fixed-by-forging sheave and anti dust cover of ball bearing provides great lifespan
- side plate holes enable cleaning of the ball-bearing surrounding

bottom attachment point: 12 kN
strength: 36 kN
working load: 4x3 kN
max. Ø rope: 13 mm
static and dynamic ropes
sheave: aluminium alloy
side plates: aluminium alloy
sealed ball bearing: steel
axle: stainless steel
weight: 421 g • 14.9 oz
unique production number
CE 1019 • EN 12278

PULLEY EXTRA

RK801EE00
black version – RK801BB00

Large single pulley for textile ropes for those who need great hauling efficiency, durability and lightweight pulley.

- durable and lightweight high-efficiency single pulley for industrial use and hauling systems
- sealed ball bearing and large diameter of the sheave provides great efficiency 94%
- designed and optimized for use with a Prusik friction knot or any clamps
- top attachment point accepts up to three carabineers
- formed side plates provides protection of rope against contact with a surrounding
- fixed-by-forging sheave and anti dust cover of ball bearing provides great lifespan
- side plate holes enable cleaning of the ball-bearing surrounding

strength: 32 kN
working load: 2x3 kN
max. Ø rope: 13 mm
static and dynamic ropes
sheave: aluminium alloy
side plates: aluminium alloy
sealed ball bearing: steel
axle: stainless steel
weight: 257 g • 9.1 oz
unique production number
CE 1019 • EN 12278

PULLEY EXTRA PLUS

RK808OS00
black version – RK808BB00

Large pulley for those who need great hauling efficiency, durability and light weight.

- durable and lightweight single pulley for industrial use and hauling systems
- for use with static and dynamic textile ropes
- sealed ball bearing and large diameter of the sheave provide great efficiency 94%
- designed and optimized for use with Prusik friction knot or any clamps
- top attachment point accepts up to three carabiners
- formed side plates provide protection of rope against contact with a surrounding
- fixed-by-forging sheave and anti dust cover of ball bearing provide great lifespan
- side plate holes enable cleaning of ball bearing surrounding
- bottom attachment point strength 32 kN
- unique production number marking

Strength: 32 kN
Working load: 2x3 kN
Material Composition: 78% Light alloy, 21% steel, 1% plastic
Max. Ø rope: 13 mm static and dynamic ropes
Sheave: aluminium alloy
Side plates: aluminium alloy
Sealed ball bearing: steel
Axle: stainless steel
Weight: 276 g • 9.7 oz
CE 1019 • EN 12278

TANDEM PULLEY

RK803BB00

Double pulley for Tyrolean traverses and zip-lines with two stainless steel sheaves for both textile ropes (13 mm) and steel wire cables (12 mm).
Each sheave is equiped with a pair of sealed ball bearings for great durability.
Hard aluminium alloy body is balck anodized and protects the sheaves from damage.
Large attachment point can accommodate up to theree carabiners.
Second attachment point for back-up carabiner or tackle systems building.

strength: 25 kN
max. Ø rope: 13 mm
static and dynamic ropes
12 mm steel cable
Sheave: stainless steel
side plates: aluminium alloy
sealed ball bearing: steel
axle: stainless steel
weight: 290 g • 10.2 oz
unique production number

CE 1019 • EN 12278

PULLEY SMALL

RK800EE00
black version – RK800BB00

Small pulley for textile ropes for those who occasionally need to build simple hauling systems or manipulate with the objects.

- lightweight single pulley for hauling and rescue
- brass self lubricating bearing ensures reliable efficiency up to 81 %
- suitable for use with a Prusik friction knot

strength: 22 kN
max. Ø rope: 13 mm
static and dynamic ropes
sheave: aluminium alloy
side plates: aluminium alloy
axle: stainless steel
friction bearing: brass
weight: 92 g • 3.3 oz
unique production number
CE 1019 • EN 12278

PULLEY MIKY

RK806BB00

Lightweight pulley with two attachment holes Designed for tree climbing application. Suitable for use with Prusik friction knot.

- two attachment holes with strength 28 kN
- anodized aluminum alloy side plates
- aluminum alloy sheave for textile ropes and auxiliary cords up to 13 mm in diameter
- bronze self lubricating bearing ensures reliable efficiency up to 81 %
- unique production number marking

Weight: 105 g (3.7 oz)Material: sheave and side plates - aluminium alloy, bearing - bronze, axle - stainless steelStrength: 28 kNMax. diameter of rope: 13 mmBearing: friction
CE 1019, EN 12278

EASY LIFT

RK809SO00

Rescue pulley for cableway evacuation.

- designed to connect directly on the carrying steel cable of the cableway
- it is used during rescue operations and is used for the rescuer's crossing from the cableway support to the seat/cabin and rescued persons
- thanks to two sheaves construction it does not jump even on a rough steel cable
- lighter about 50 g than previous Easy Lift
- bigger gate opening allows to use the pulley on a thicker rope and more massive seat feet, eg. six seat cableways
- for steel rope with max. diameter 60 mm
- marked with a unique production number for better traceability and inspection

Weight: 1350 g • 3 lb
Strength: 30 kN
Max. diameter of steel rope: 60 mm
Max. speed: 2 m/s
Working load: max. 6 kN
Sheave: POM
Material: light alloy, POM, stainless steel
CE 1017

RIGGING PLATE 3/5

RK714BB00

Aluminium alloy device for multi-point anchoring.

- provides efficient force distribution at different load directions
- low profile of the plate makes the connection as short as possible
- provides plenty of attachment holes
- rounded holes allow direct attachment of the ropes and slings to the rigging plate
- all attachment points are big enough to allow locking sleeves of most carabiners passing through

Weight: 145 g • 5.1 oz
Material: light alloy
Strength: 50 kN • Thickness: 8 mm
CE 1019

RIGGING PLATE 1/3

RK713BB00

Aluminium alloy device for multi-point anchoring.

- helps to organize carabiners at the anchor point
- provides efficient force distribution at different load directions
- rounded holes allow direct attachment of ropes and slings to the rigging plate
- central attachment point can accommodate up to three carabiners
- all attachment points are big enough to allow locking sleeves of most carabiners passing through

Weight: 65 g • 2.3 oz
Material: light alloy
Strength: 36 kN • Thickness: 6 mm
CE 1019

RINGO

K7002BX46

Detachable ring for arborists and workers at height. Intended for semi-permanent connection. Can be loaded in any direction.

- strong and light body made of aluminium alloy
- minimum strength 20 kN in any direction
- inner diameter: 46 mm
- 10 mm clipping gap
- steel bolt
- unique serial number

Weight: 75 g • 2.6 oz
Strength: 20 kN
Gate opening (d): 10 mm
CE 1019 • EN 362

Spare part: K7003XX00 Bolt for Ringo (2 pcs)

RING

RK400BB

Load sharing rings used by a person for fall protection for work at height or mountaineering.

- anodized surface
- unique number marking
- two sizes, with inner diameter 28 or 46 mm

Weight: 39 g • 1,4 oz (28 mm), 57 g • 2,0 oz (46 mm)
Material: light alloy
Strength: 25 kN
CE 1019

PILOT

X0070XX34

Removable anchors, developed both for fall protection and multi-use, are safe, lightweight, and simple to employ.

- tested to meet ANSI Z359.1 and EN 795
- easy to use, simply drill the proper size hole into your concrete or rock surface, blow the dust out with compressed air, and insert the unit
- multi-directional attributes, anchors work in horizontal, vertical and overhead surfaces
- easily reusable, when your job is done, simply fill in the drilled hole if necessary and reuse at your new desired location
- removable anchors can be used in construction and industrial fields, mining, and mountaineering as well
- suitable for the drilled holes in a diameter 20 mm

Weight: 200 g • Working load: 181 kg
Size: ¾" • Strength: 22 kN
ANSI Z359.1 • EN 795 Type B • CE 0321

REDBLOCK

K0006RP00

Anchor device, that extends lifetime of the rope when toproping

- ideal partner for adventure parks, rope courses and climbing gyms
- allows to be installed in two axises
- for better traceability and inspection recording the RedBlock is marked with the unique production number

Color: red
Weight: 375 g • 13.23 oz
Material: light alloy
Sheave: stainless steel
Max. diameter of rope: 12 mm
Strength: 26 kN
CE 1019

TWISTER

K0030OG00

Innovated rotating anchor
Placed between a load and either rope or cable, the twister avoids severe rope twisting while the load turns.

Working load: 4 kN
Color: anthracite/yellow
Strength: 22 kN
Weight: 88 g • 3.1 oz
CE 0321 • EN 354

SITE

200 cm – W1011WB02
400 cm – W1011WB04

200 cm + K370 – W1012WB02
400 cm + K370 – W1012WB04



The work positioning lanyard with great handling makes your work safe and efficient.

- 11 mm rope sewn-in unopenable version of LOCKER – rope clamp (fall arrester)
- rope covered with tubular webbing
- parking cam for blocking in required position
- also available with stitched-in connector in accordance with EN 362 (K370)

Weight: 560 g (with connector), 410 g (without connector)
Length: 200 cm, 400 cm
CE 1019 • EN 358 • EN 353-2

SITE LANYARD

200 cm – W1014WB02
400 cm – W1014WB04



Spare part for SITE positioning system.

- suitable only with the LOCKER device for creating your positioning lanyard
- with an unopenable version of LOCKER certified in accordance to EN 353-2 and EN 358
- 11 mm rope covered with a tubular web-bing
- one end of the rope is ended by a sewed eye, the 2nd one must be ended by a safety knot (see instructions of use)

CE 1019 • EN 353-2 • EN 358

Telecommunication site inspection, Sweden Photo: Pavel Nesvadba

STAINLESS HANGER PLATE / WITH BOLT

10 mm RK702XX10
12 mm RK702XX12
10 mm w/bolt RK715XX10
12 mm w/bolt RK715XX12

Stainless steel hanger plates and bolts for permanent anchor points. Available in two different bolt sizes.

- recommended for outdoor, wet environment. Not recommended for aggressive environment (e.g. sea water, chlorinated pool water, chemically polluted environment, etc.)

Plate thickness: 3 mm
Bolt length: 84 mm
Length of the hole: 75 mm
Strength: 25 kN
Weight:
Hanger plate 42 g • 1.48 oz
10 mm w/bolt 112 g • 3.95 oz
12 mm w/bolt 140 g • 4.94 oz
EN 795 • EN 959

ZINC PLATED HANGER PLATE / WITH BOLT

10 mm RK704XX10
12 mm RK704XX12
10 mm w/bolt RK716XX10
12 mm w/bolt RK716XX12

Zinc plated steel hanger plates and bolts for permanent anchor points. Available in two different bolt sizes.

- recommended for indoor, dry environment

Plate thickness: 4 mm
Bolt length: 84 mm
Length of the hole: 75 mm
Strength: 25 kN
Weight:
Hanger plate 62 g • 2.19 oz
10 mm w/bolt 100 g • 3.53 oz
12 mm w/bolt 125 g • 4.41 oz
EN 795 • EN 959

GLUE IN ANCHOR

RK703XX10

Stainless steel durable permanent anchor point.

- works also in soft or pocketed stone
- smooth eye allows safe rope threading for retreat
- made of welded, grade AISI 316 stainless steel
- for drilled hole with diameter 12 mm
- recommended glue: UPM 44 or FIS 360V, resin capsule RM10

Diameter: 10 mm
Length of shaft: 80 mm
Weight: 120 g 3.18 oz
Strength: ◂▸ 30 kN ▴▾ 25 kN
EN 959 • EN 795 Type A

D – MOBILE

A0002SS01

Door or window anchor point

- an indispensable anchor point protect against sudden falls
- the safety traverse offers in connection with the rope perfect safety solution when working in wall openings and on balcony support plates
- no tools are needed to fix the traverse in doorways, the opening of which may be up to 1100 mm wide for one person for two persons can be maximum opening up to 900 mm
- fast adjustment by pressing the pawl
- star grip to clamp the safety traverse
- bearing surfaces coated with synthetic material

Strength: 22 kN • Weight: 11 kg
Dimensions: 141 x 13 x 13 cm
CE 0123 • EN 795 Type B

VERTICAL FIXED BEAM CLAMP

X0077XX00

Fixed I-beam anchor is designed to clamp onto a vertical or horizontal I-beam to create a fixed anchor point.

- zinc plated components
- stainless Steel D-Ring Mount
- static tensile strength: 22kN
- maximum capacity 140kg when used as a single point anchorage

Span: 100–350 mm
Maximum load: 140 kg
Weight: 3105 g • 109.5 oz

Strength: 22 kN
CE 0321 • EN 795:2012 • ANSI Z359.18 • ANSI Z359.7 • OSHA 1910.66/ • OSHA 1926.503

SNAKE BRACE

S 300 – W2018Y030
S 600 – W2018A060

Anchor point for through holes, designed to function as a link between the structure and the fall arrest, work positioning, rope access or rescue systems.

- intended for through holes whose minimum and maximum diameter corresponds to the type of Snake Brace in relation to the actual thickness of the current structure
- the opening need not be entirely regular but the minimum diameter must be flat. There must be a minimum space for installation behind the hole
- intended for a single user
- the maximum strength can be used only if the structure in which the anchor hole is located can withstand the load in all directions
- the minimum strength of the construction should be designed according to EN 795 (if not in accordance with EN 795, the load bearing capacity may be reduced)
- Snake Brace can be loaded in any direction only if also allowed by the construction in which is anchored
- can be used only with compatible connectors with locking mechanisms according to EN 362

Strength: 18 kN
Length: 30, 60, 90, 120 cm
Weight: (S 300) 162 g • 5.71 oz / (M 300) 395 g • 13.93 oz
Material: S – dyneema, alloy, steel / M – PAD, alloy, steel
CE 1019 • EN 795 Type B

type	strength	hole Ø min. (mm)	construction thickness (mm)						min. open space
			>5	≥ 50	≥ 100	≥ 150	≥ 200	≥ 300	behind the hole (mm)
			hole Ø max. (mm)						
S	18 kN	17,7	50	65	75	80	85	90	≥ 200
M	18 kN	22	175	195	210	225	235	255	≥ 450

Chimney demolition, Frýdlant nad Ostravicí, Czech Republic Photo: Petr Piechowicz

RETRACTABLE TYPE FALL ARRESTERS:

This part of your safety system allows you to move freely within a certain distance during your work and absorbs the impact in the event of a fall. All devices are certified according to EN 360:2002, some of them are suitable for rescue purposes according to EN 1496:2007. SRL (self-retracting lanyard) devices are self-retractable, while winches are manually operated.

IKAR line is an ultimate hi-end range with a variety of solutions to cover all possible needs. These sturdy, low-maintenance height safety devices with webbing or galvanized steel lifeline are offered mainly in aluminium case featuring a rotational attachment swivel to better ergonomics and long lifetime. IKAR devices function in any location position and have been tested in a simulated fall trial over an edge according to CNB 11.060 2008 sharp edge type A (with exception of HRA series). Connectors incorporate a fall indicator for easier inspection.

IKAR HWB

IKAR HWB 1.8 – A4000W018
IKAR HWB 2,8 – A4000W028
IKAR HWB 3.5 – A4000W035

Retractable fall arrester with webbing lifeline and built-in shock absorber featuring rotating attachment point and double action connector.

- lightweight aluminium housing with a webbing lifeline
- swivel eye attachment point
- sewn in load indicator on lifeline
- additional testing against falls over edges (r≥0,5mm)
- steel double action hook on end of lifeline
- device can be attached to an anchorage point or safety harness
- HWB 1.8 can be used as protection against falls in working cages of lifting platforms under specific conditions

Weight: 0.7 kg / 0.8 kg / 1.1 kg
Length: 1.8 m / 2.8 m / 3.5 m
Working load: 136 kg
CE 0229, EN 360, ANSI/ASSE Z359.1-2007, ANSI/ASSE Z359.14-2014, CSA Z259.2.2

IKAR HWS

IKAR HWS 6 – A4000S060
IKAR HWS 9 A4000S090
IKAR HWS 12 – A4000S120
IKAR HWS 24 – A4000S240

Self-retractable arrester featuring a rotating attachment swivel and a connector with fall indicator and double action swivel hook.

- lightweight aluminium housing with a galvanised steel cable lifeline
- swivel eye anchor attachment point
- additional testing against falls over edges (r≥0,5mm)
- steel double action hook on end of lifeline

Weight: 3 kg / 3.7 kg / 5.4 kg / 8.4 kg
Length:6 m / 9 m / 12 m / 24 m
Working load: 136 kg

CE 0229, EN 360, ANSI/ASSE Z359.1-2007, ANSI/ASSE Z359.14-2014, CSAZ259.2.2

IKAR H

IKAR H 33 – A4002BS33
IKAR H 42 – A4002BS42

Self-retractable arrester featuring a connector with fall indicator and double action swivel hook.

- lightweight aluminium housing with a galvanised steel cable lifeline
- fixed handle anchor attachment point
- additional testing against falls over edges (r≥0,5mm)
- steel double action hook on end of lifeline

Weight: 18 kg / 27.2 kg
Length: 30 m / 40 m
Working load: 136 kg

CE 0229, EN 360, ANSI/ASSE Z359.1-2007, ANSI/ASSE Z359.14-2014, CSA Z259.2.2

IKAR HRA

IKAR HRA 12 – A4004BS12
IKAR HRA 18 – A4004BS18
IKAR HRA 33 – A4004BS33

Self-retractable arrester with built in two-way rescue/ recovery mechanism. Fall arrest device with rescue lifting and lowering facility, equipped with a recovery mechanism operated by a device mounted handle. After an arrested fall, or if the user becomes incapacitated at the bottom of a shaft, the recovery mechanism can easily be engaged by a second person to raise or lower the person to a place of safety.

- lightweight aluminium housing with a galvanised steel cable lifeline
- fixed handle anchor attachment point
- equipped with a release pin and a recovery mechanism operated by a device mounted handle
- steel double action hook on end of lifeline

HRA is not suitable for use over a leading edge and has not been edge tested.
Weight: 11.5 kg / 21 kg • Length: 18 m / 33 m
Working load: 136 kg

Weight: 7 kg / 11.5 kg / 21 kg
Length: 12 m / 18 m / 30 m
CE 0229, EN 360, EN 1496, ANSI/ASSE Z359.1-2007, ANSI/ASSE Z359.14-2014, CSAZ259.2.2

PROTECTIVE SLEEVE FOR SRL

A4072YX

PVC protective covers for self-retracting lifelines.

- sealed seamless construction protects a whole SRL from precipitation or aggressive environments
- prevents scratching or damage to labels when using a SRL horizontally
- equipped with a label access transparent window for easy pre-use inspections
- available in three sizes to suit different SRLs

A4072YX02 S
IKAR HWB 1.8; HWB 2.8 and HWB 3.5 or similar
A4072YX03 M
IKAR HWS 6; HWS 9 and HWS 12 or similar
A4072YX04 L
bigger fall arresters like IKAR HWS 24 or similar

Weight: S 160 g • M 250 g • L 400 g
Size: S, M, L • Material: PVC
Dimensions: S 25x40 cm • M 30x60 cm • L 40x70 cm

Power cable installation, Cableway Zugspitze, Germany Photo: Gábor Berta

DAVIT

Davit has a modular design that allows to build a system, which would precisely fit all possible applications in every confined environment. The swivelling davit sets are free standing or attachable to walls, tanks or other entrances. A simple plug-in mechanism allows quick and purposeful installation. In order to build your davit system, order a cantilever arm, choose from a range of fixed or temporary bases and sleeves and add required consoles for IKAR HRA self-retracting lanyards or PLW winch attachment. Designed with an integrated, easy to set fall brake system and the ability to mount mechanical devices as winches and retractable fall arresters, IKAR davits provide the customer with peace of mind for years to come.

IKAR AAS-1 CANTILEVER ARM

X4005XX00

Cantilever arm with permanent angle of 49° is developed for stationary use in safety and rescue cases for two persons, as well as for lifting and lowering loads.

- built-in 3 pulley systems redirect wire ropes from attachment point of the winch and SRL to confined space entry
- Cantilever arm is made from high quality V4A stainless steel
- Suitable for fast relocation from one sleeve to another due to foldable design of 2 detachable parts – upper davit and lower mast.
- Additional attachment point provides a possibility of attaching an SRL or fall absorber with lanyard to secure a cantilever arm operator or assistant.
- Suitable for two persons with load capacity of 300 kg

Height: 2,01 m • Reach: 0,74 m
Weight: 28,7 kg
CE 0299 • EN 795:2012 Type B
CEN/TS 16415:2013

IKAR GROUND SLEEVE

X4006XX00



Sleeve is designed to be installed onto the ground with pivot bearing made of durable PA.
Sleeve can be mounted on existing concrete surfaces using the recommended composite anchor system Type MKT VMZ-AA4 145 M16-30 / 200 or steel constructions with screw connections M 16 grade 8.8.

Material: stainless steel 1.4571 (V4A), PA
Dimensions: 300 x 240 x 280 mm
(length x width x height)
Weight: 13,5 Kg
EN 795:2012 Type A
CEN/TS 16415:2013

IKAR WALL SLEEVE

X4007XX00

Sleeve is designed to be installed onto the wall with pivot bearing made of durable PA.
Sleeve can be mounted on existing concrete surfaces using the recommended composite anchor system Type MKT VMZ-AA4 145 M16-30 / 200 or steel constructions with screw connections M 16 grade 8.8.

Material: stainless steel 1.4571 (V4A), PA
Dimensions: 290 x 300 x 410 mm
(length x width x height)
Weight: 14,9 Kg
EN 795:2012 Type A • CEN/TS 16415:2013

IKAR LOWER GROUND SLEEVE

X4009XX00

Flush floor sleeve with 1 1/2" drainage pipe connection can be mounted to rebar before pouring concrete.
A concrete quality of at least B25 concrete must be ensured.

Material: stainless steel 1.4571 (V4A), PA
Dimensions: 280 x 420 mm (width x height)
Weight: 12 Kg
EN 795:2012 Type A • CEN/TS 16415:2013

IKAR LOWER GROUND SLEEVE CORE HOLE

X4010XX00

Flush floor sleeve with 3/8" drainage pipe connection to be installed to existing concrete by core-drilling and resin fix.
A suitable shrink-free grout is PCI swelling mortar with the designation „Grout 100".

Material: stainless steel 1.4571 (V4A), PA
Dimensions: 160 x 335 mm (width x height)
Weight: 4,6 Kg
EN 795:2012 Type A • CEN/TS 16415:2013

FIXING MATERIAL FOR GROUND AND WALL SLEEVE

X4008XX00

Composite anchor system Type MKT VMZ-AA4 145 M16-30 / 200 for IKAR ground and wall sleeve.

IKAR MOBILE GROUND BASE

X4011XX00

Free standing base featuring quick and easy assembling on site.
The base consists of a central socket, height adjustable pairs or front and back legs secured with ball-lock pins. Cantilever arm rotates 360°.

Material: stainless steel 1.4571 (V4A), PA
Dimensions: 1763 x 2228 x 450 mm (length x width x height)
Weight: 23,4 Kg for central socket, front leg 8,1 kg each, back leg 9,2 kg each
CE 0299 • EN 795:2012 Type B • CEN/TS 16415:2013

IKAR MOBILE ATTICS BASE

X4012XX00

Sleeve is designed to sit on the top of a concrete bund wall 200mm–400mm or container edges.
It is ideal for work areas where frequent assembly and disassembly is required.
Material: stainless steel 1.4571 (V4A)

Dimensions: 350 x 729 x 335 mm
(length x width x height)
Weight: 35 kg
CE 0299 • EN 795:2012
Type B • CEN/TS 16415:2013

IKAR WINCH CANTILEVER ARM CONSOLE

X4015XX00

Stainless steel bracket designed to fit IKAR PLW Winch to cantilever arm.
Bolts directly onto the davit's arm and comes complete with fixings and stainless--steel fixing pin for the PLW winch.

Material: aluminium
Dimensions: 200 x 130 x 82,5 mm
(length x width x height)
Weight: 2,4 kg

CANTILEVER ARM CONSOLE

IKAR HRA 12-24 – X4013XX00
IKAR HRA 33 – X4014XX00

Stainless steel bracket designed to fit IKAR HRA recovery devices to IKAR Davit's mast.
Bolts directly onto the davit' mast and comes complete with fixings and stainless--steel fixing pin for the device.

Material: stainless steel 1.4571 (V4A)
Dimensions: 264 x 162 x 250 mm
(length x width x height)
Weight: 3,5 kg (5 kg for HRA 33 version)

IKAR DB-A3 TRIPOD

X4002XX00

Portable tripod with adjustable locking legs and 3 intergated pulleys. Head construction allows a variety of leg angles and a safety-chain-free design. Ideal for economical compliance in many basic confined space, fall arrest applications and resuce.

- Up to 2,54 m high aluminium tripod with corrosion-resistant coating featuring 3 bolts-in anchor points
- 1,56 m in collapsed setup for transportation, weight is 24 kg
- 2 stage independently adjustable telescopic legs with stainless steel pins and foldable rubber shoes with spiked edges. The individually adjustable legs are advantageous as they can be used on uneven ground
- 3 pullies built into a die casted head
- Tripod is designed to be used without support safety chain, which reduces a risk of tripping
- Suitable for two persons with load capacity of 300 kg
- Console and IKAR HRA not included

Height: min. 1,43 m, max. 2,54 m
Diameter: min. 0,64 m, max. 2,19 m
Weight: 24 kg
CE 0299 • EN 795:2012-10 Typ B • CEN/TS 16415:2013

IKAR WINCH TRIPOD CONSOLE

X4004XX00



Aluminium bracket to connect an IKAR PLW Winch to IKAR DB-A3 tripod.
Dimensions: 200 x 130 x 82,5 mm
(length x width x height)
Weight: 2.0 Kg

IKAR HRA TRIPOD CONSOLE

X4003XX00

Universal aluminium bracket to connect an IKAR HRA (up to 60m) to an IKAR DB-A3 tripod.
Dimensions: 255 x 165 x 78 mm
(length x width x height)
Weight: 1.8 Kg

IKAR PLW WINCH

A4064XX30

Hand crank winch for easy and jerk-free lifting and lowering of persons and loads according to Directive 2006/42/EG with 30 m stainless steel rope of Ø 6mm (min. breaking load 18.76 kN). SWL is 300 Kg.

Material: stainless steel 1.4571 (V4A), PA
Dimensions: 230 x 336 x 200 mm (length x width x height)
Weight: 18,5 kg
CE • EN 1808:2015

Tree cutting, Poniklá, Czech Republic Photo: Pavel Nesvadba

SLINGS AND LANYARDS

MOBILE ANCHORING SYSTEM
FALL ABSORBERS

OPEN SLING 14 MM

W2005



Compact sewn loop made of two-layer material.

- minimalist, strong and durable
- constructed from two parts, where the strength core is woven into the cavity
- the outer material protects the colored core, in case of damage is visible
- sewing color according to length
- suitable for anchoring and connecting when working at heights
- available also in black only (anthracite sewing)

Width: 14 mm
Strength: 25 kN
Material: 90% PES, 10% PA
Deviation in length: 60, 80 cm +/- 2 cm;
120, 150 cm -2 / + 4 cm

code	length	sewing color
W2005Y060	60 cm	yellow
W2005A080	80 cm	blue
W2005R120	120 cm	red
W2005W150	150 cm	white
W2005B060	60 cm	anthracite
W2005B080	80 cm	anthracite
W2005B120	120 cm	anthracite
W2005B150	150 cm	anthracite

CE 1019 • EN 354 • EN 795B • EN 566

OPEN SLING

Sewn sling for creating the anchor point.
Width: 20 mm
Strength: 22 kN
Length deviation: 60, 80 cm +/- 2 cm
120, 150 cm -2/+4 cm
Material: PA

	[cm]	[in]	kN	type
W2001*060	60	24	22	
W2001*080	80	32	22	
W2001*120	120	47	22	
W2001*150	150	60	22	

CE 1019 • EN 566 • EN 795B • EN 354

EYE SLING

Sewn sling from two layers of webbing and with a wear indicator.
Width: 23 mm
Strength: 30 kN
Length deviation: 60, 80 cm +/- 2 cm
120, 150 cm -2/+4 cm
Material: PA

	[cm]	[in]	kN	type
W2004*060	60	24	30	
W2004*080	80	32	30	
W2004*120	120	47	30	
W2004*150	150	60	30	

CE 1019 • EN 354 • EN 795B

SLING LANYARD

Sewn sling from two layers of webbing and with a wear indicator.
Width: 23 mm
Strength: 22 kN
Length deviation: 60, 80 cm +/- 2 cm
120, 150 cm -2/+4 cm
Material: PA

	[cm]	[in]	kN	type
W2016*060	60	24	22	
W2016*080	80	32	22	
W2016*120	120	47	22	
W2016*150	150	60	22	

CE 1019 • EN 354 • EN 795B

LANYARD "I"

Lanyard „I" for creating the anchor point or the connection device.
Available also with sewn connectors K370 and K353.
Rope diameter: 10.5 mm
Length deviation: 60, 80 cm -2/+3 cm
120, 150 cm -3/+5 cm
Strength: 22 kN

	[cm]	[in]	kN	type
W2300*060	60	24	22	
W2300*080	80	32	22	
W2300*120	120	47	22	
W2300*150	150	60	22	
W2301*060	60	24	22	K3702PP
W2301*080	80	32	22	K3702PP
W2301*120	120	47	22	K3702PP
W2301*150	150	60	22	K3702PP
W2303*060	60	24	22	K3536PP00
W2303*080	80	32	22	K3536PP00
W2303*120	120	47	22	K3536PP00
W2303*150	150	60	22	K3536PP00

CE 1019 • EN 354 • EN 795B

LANYARD "V"



Lanyard „V" to create the connection device.
Rope diameter: 10.5 mm
Length deviation: 25/45, 25/65 cm -2/+3 cm
100/100 cm -3/+5 cm
Strength: 22 kN

	[cm]	[in]	kN	type
W2200*001	25/45	10/17	22	
W2200*002	25/65	10/30	22	
W2200*100	100/100	40/40	22	

CE 1019 • EN 354

TIMBER ACCESSORY CORD

8 mm – W2608
10 mm – W2610



With sewn eyes.
- rope diameter 8 and 10 mm
- the use of the PES/TECHNORA material combination results in a better thermal and mechanical resistance of the sheath

Length:
diameter 8 mm – 75, 80, 85, 100 cm
diameter 10 mm – 80, 85, 90, 100 cm

Strength:
18 kN (8 mm)
20 kN (10 mm)

CE 1019 • EN 795B

PRUSIK SLING

8mm – W2601R085
10mm – W2602Y085



Sewed accessory cord with a diameter 8 and 10 mm for wide use at tree care and rescue operations.
- well knotted for easier work at height and for more comfortable installation of Prusik knot
- suitable also as an anchor sling, adjustment sling and for the hauling systems

Color: red/white (8 mm), yellow/black (10 mm)
Diameter: 8 and 10 mm
Length: 38 cm • 15 in
Strength: 18 kN
Working load: max. 1 person
Material: PES, Technora
Weight: 48 g • 1.7 oz (8 mm), 70 g • 2.5 oz (10 mm)

CE 1019 • EN 795B

PULLEY SLING

W2603YB00

Prusik sling with the stitched pulley SMALL for creating the anchor point.
- sling with the pulley is suitable to use as a textile blocking device for wide use mainly at the tree care and rescue operations
- spare part for BARK PULLEY SAVER
- suitable also for other work at height as an anchor point

Strength: 18 kN
Length: 40 cm • 15.7 in
Diameter: 10 mm
Working load: max. 1 person
Material: PES, Technora, light alloy
Weight: 160 g • 5.6 oz
CE 1019 • EN 795B

RING SLING

W2604RR00

Well knotted prusik sling with stitched ring with 28 mm diameter for creating the anchor point.

- sling with the ring is suitable to use as a textile blocking device for wide use mainly at the tree care and rescue operations
- spare part for BARK RING SAVER
- suitable also for other work at height as an anchor point

Strength: 18 kN
Length: 40 cm • 15.7 in
Diameter: 10 mm, ring 28 mm
Working load: max. 1 person
Material: PES, Technora, light alloy
Weight: 115 g • 4 oz
CE 1019 • EN 795B

JINGLE II

steel ring – W1040R
ALU ring – W1041R
without ring – W1042R

Cambium saver intended for use in tree climbing as anchor device and belay anchor. The different size of the rings enables easy and quick installing and removing of the sling from the ground. As well suitable in industry as an anchor device.

- length of the slings with "O" ring – 100, 120, 150 cm
- strength 25 kN
- inside and outside diameter of "O" rings: ALU: big 46/70 mm, small 28/52 mm steel: big 58/78, small 38/57
- 3 layers of webbing sewn together
- red colour of webbing for better visibility
- available with aluminium "O" rings or without "O" rings.

CE 1019 • EN 795B

Tree care in Poniklá, Czech republic Photo: Marta Mendrická

PATRON LANYARD

W2113Y
ALU RING – W2111Y
STEEL RING – W2112Y

Dynamic rope lanyard with stitched eyes at the ends for work positioning and anchoring at the tree care.

- suitable to use with the mechanical adjustment devices and also with friction hitches (Prusik knot)
- dynamic rope 11 mm guarantees smooth adjustment and in case of fall higher impact force absorption
- strength stitching is covered with plastic cover for higher abrasion resistance and easier pulling from the tree top
- suitable also for other work at height as the anchor device
- available in 3 versions, with light alloy ring, steel ring or without a ring

Color: yellow
Strength: 22 kN
Working load: max. 1 person
Material:
PATRON LANYARD ALU RING
– PA, light alloy, PVC
PATRON LANYARD STEEL RING
– PA, steel, PVC
PATRON LANYARD – PA, PVC

Length and weight:

PATRON LANYARD ALU RING 1.25 / W2111Y125 / 125 cm • 49 in , 215 g • 7.6 oz

PATRON LANYARD ALU RING 1.50 / W2111Y150 / 150 cm • 59 in, 235 g • 8.3 oz

PATRON LANYARD STEEL RING 1.25/ W2112Y125 / 125 cm • 49 in, 292 g • 10 oz

PATRON LANYARD STEEL RING 1.50 / W2112Y150/ 150 cm • 59 in, 315 g • 11 oz

PATRON LANYARD 3.5 /W2113Y350/ 350 cm • 11.5 ft., 345 g • 12 oz

PATRON LANYARD 5.5 /W2113Y550/ 550 cm • 18 ft., 540 g • 19 oz

PATRON LANYARD 60 / W2113Y060 / 60 cm · 24 in, 105 g · 3.7 oz

PATRON LANYARD 80 / W2113Y080 / 80 cm · 31.5 in, 120 g · 4.2 oz

PATRON LANYARD 120 / W2113Y120 / 120 cm · 47 in, 155 g · 5.5 oz

PATRON LANYARD 150 / W2113Y150 / 150 cm · 59 in, 185 g · 6.5 oz

CE 1019 • EN 795B • EN 354

BARK PULLEY SAVER

W2115

Adjustable cambium saver intended for use in tree care operations.

- adjustable length and possibility to exchange the parts of the cambium saver in case of damage
- pulley sling allows smooth and fast movement in a tree top
- steel plush (22 mm diameter) with accessory cord allows to remove the cambium saver from the ground
- available in two lengths

Length: 1.25 and 1.5 m • 4 and 4.9 ft.
Weight: 470 and 495 g • 16.6 and 17.5 oz

Set includes:

- W2112 PATRON LANYARD STEEL RING
- W2603YB00 PULLEY SLING
- sheckl
- W2118XX00 retrival plaque with accessory cord

BARK RING SAVER

W2116

Adjustable cambium saver intended for use in tree care operations.

- adjustable length and possibility to exchange the parts of the cambium saver in case of damage
- removing the sling with pulling ball with a diameter 32 mm or tieing a barrel knot at the end of the rope
- available in two lengths

Length: 1.25 and 1.5 m • 4 and 4.9 ft.
Weight: 318 and 340 g • 11.2 and 12 oz

Set includes:

- W2112 PATRON LANYARD STEEL RING
- W2604RR00 RING SLING

ARBO SITE

W2117

Work positioning lanyard specially intended for tree care operations.

- allows smooth length adjustment thanks to the use of friction knots (Prusik knot) and pulleys
- the advantage of this set are two strength stitched eyes which allow to create two independent work positioning lanyards
- the set is delivered in two lengths and is ready to use
- each component is replaceable in case of damage

Work positioning set includes:

- W2117 PATRON LANYARD
- W2608 TIMBER ACCESSORY CORD
- RK806BB00 pulley MIKY
- K0122BB07 2x carabiner OXY / TRIPLE LOCK

Length: 3.5 and 5.5 m • 11.5 and 18 ft.
Weight: 638 a 860 g • 22.5 and 30 oz
CE 1019

Note: This set is not certified according to EN 358, as it consists of removable components. However, it is generally recognized according to Arboricultural Organizations (ISAs) and working practices.

TREE ANCHOR

W2114

Connection and anchor device for work at height. Multipurpose anchor device for creating the anchor point mainly on the tree. Designed for the arborists and rescue.

- static rope with a diameter 11 mm
- stitched steel ring (diameter 38 mm) at one rope end for variable use
- strength stitching is covered with plastic cover

Strength: 22 kN
Diameter: rope 11 mm, ring 38 mm
Working load: max. 1 person
Materiál: PA, steel, PVC
Length: 5 m
Weight: 525 g • 18.5 oz
CE 1019 • EN 795B • EN 354

TRACK PLUS

W1036W130

Adjustable anchoring strap and work positioning lanyard

- length adjustment from 80 to 130 cm

CE 1019 • EN 354 • EN 358 • EN 795 B

ADJUST

W1047Y100

Adjustable lanyard with steel single buckle and textile handle which allows adjusting a length under the tension.

- strong and resistant 25 mm wide webbing, eye with a protector for any EN 362 connector, big steel buckle for adjusting a length of the lanyard
- full strength textile handle for easy adjusting a length of the lanyard (guaranteed safety of this loop in case of wrong attachment)
- attachment light alloy ring with the inner diameter of 28 mm
- identification label for product traceability

Weight: 240 g • 8.5 oz
Material: PES • Strength: 22 kN
Width: 25 mm • 1 in
Length: 80–145 cm • 32-57 in
CE 1019 • EN 354 • EN 358 • EN 795 B

FLAT WEBBING

C0035AO12

- width of webbing 16 mm (0.63 in)
- made of low stretch PES
- max. length 120 m (393 ft)
- weight: 37,7 g/m
- strength: 15 kN

CE 1019 • EN 565

TUBULAR WEBBING

black – C0037BB12
red – C0037RR12



- width of webbing 20 mm (0.79 in)
- made of low stretch PES
- max. length 120 m (393 ft)
- weight: 38,2 g/m (black), 39,4 g/m (red)
- strength: 16 kN (black), 17 kN (red)

CE 1019 • EN 565

FINE LINE

MOBILE ANCHORING SYSTEM

2

S = 10 m

M = 15 m

L = 20 m

Mobile anchoring system

- colour distinction of the lengths
- allows 2 persons movement
- easy to adjust and manipulate
- manpower sufficient for fastening when installing the system
- ratchet does not damage the webbing

W1001WW10	Fine line 10 (1)
W1001WW15	Fine line 15 (1)
W1001WW20	Fine line 20 (1)
W1002WS10	Fine line bag 10 (2)
W1002WY15	Fine line bag 15 (2)
W1002WO20	Fine line bag 20 (2)

CE 1019 • EN 795 B

1

RESCUE RATCHET

W1052XX00

Quick and easy to deploy haul lanyard with ratchet for rescue purposes. It is intended to lift up the victim from the fall protection line.

Color: red
Weight: 680 g • 24 oz
Material: PES, galvanized steel
Strength: 22 kN
Width: 35 mm
Length: 25–115 cm • 31–45 in
CE 1019 • EN 354

AXILLAR

W0003BY09

Rescue sling to secure evacuated persons against accidental fall during the rescue action
(e.g. ski lift evacuation).
Weight: 385 g
EN 1498 type A

 Cableway evacuation, Krkonoše, Czech republic Photo: Ondřej Vítko

STEEL ANCHOR

300 cm – RK851XX03
500 cm – RK851XX05

Steel anchoring device ideal for tree care or welding at height.

- Steel wire cable with the diameter 6 mm is protected by thick PVC tube. Outer diameter of the tube is 13 mm.
- available in two lengths with different loop colors

Material: zinc plated steel covered by PVC
Strength: 15 kN
Length: 300, 500 cm • 9.8 ft, 16.4 ft
Weight: 730 g • 25.8 oz
1150 g • 40.6 oz
CE 1019 • EN 795B

STEEL LANYARD "I"

yellow – RK850X100
blue – RK850X130
red – RK850X180



Steel connecting and anchoring device ideal for tree care or welding at height.

- Steel wire cable with the diameter 6 mm is protected by thick PVC tube. Outer diameter of the tube is 13 mm.
- both ends finished with a fixed eye
- combination of very good strength and durability
- available in three lengths with three different loop colors
- unique production number

Material: zinc plated steel covered by PVC
Strength: 15 kN
Length: 100, 130 and 180 cm • 39, 51 and 71 in
Weight: 295 g • 10.4 oz • 350 g • 12.3 oz • 460 g •16.2 oz
CE 1019 • EN 354 • EN 795B

JACOB DYNEEMA

C2151BY00

Versatile and ultra light ladder.

- used for aid climbing and work at height
- any cell may be loaded in any directions, which can become useful in emergency situations
- strength of each loop – 22 kN
- may be also used as an open sling for the anchoring

Length: 140 cm (55 in)
Weight: 140 g • 4.9 oz
CE 1019, EN 566, EN 354

JACOB

C2150BY

Ultra light six step ladder.
Steps reinforced with a plastic to hold its shape even under the load.

Maximum load: 500 kg.
Maximum load for grab loop 100 kg.
Length: 150 cm (59 in)
Weight: 210 g • 7.4 oz

FOOTER II

W1024BX
complete – W1025BX

Ascender webbing for rope access.

- big loop for easy releasing the webbing
- small loop for the attachment to the carabiner
- reinforced step loop
- FOOTER II COMPLETE is including the mini D screw connector

Min. length: 40 cm (16 in)
Max. length: 140 cm (55 in)
Weight: 90 g • 3.2 oz / 125 g • 4.4 oz (complete)
Max. load: 150 kg

FOOTER XP

W1051BX



Lightweight ascender loop made from 6 mm accessory cord.

- webbing in the buckle simplifies the length adjustment
- XP buckle allows to adjust the length even when loaded
- big hole in the buckle for the attachment with any type of carabiner
- reinforced step loop is equipped with an elastic strap which keeps the proper position of the foot

Min. length: 30 cm (12 in)
Max. length: 170 cm (67 in)
Weight: 105 g (3.7 oz)
Max. load: 180 kg
Material: PAD, light alloy

TOOL HOLDER

W1028BY00

Elastic sling to attach the tools to the harness which makes the loss of the tool impossible.

- designed to provide comfortable work while
  working with the tools at height
- high durability and flexibility
- steel weldet eye
- length of the sling can be extended up to 130 cm

Material: PES, PAD, steel, elastic fibre
Load capacity: 25 kg
Weight: 30 g • 1.06 oz
Lenght: 70 cm, (130 cm fully extended)

Never use this sling for belaying!

TOOL HOLDER MAX

W1054BR00

Elastic sling for attaching heavier tools to the work harness.

- prevents tools from falling when working at heights
- stainless steel ring with 40 mm inner diameter for connection to the harness material carabiner (PORTER)
- suitable for chain saws and other tools up to a maximum weight of 10 kg

Length: 85–150 cm • 33,5–59 in
Weight: 95 g • 3,4 oz
Load capacity: 300 kg • 660 lb
Material: PAD, elastic fibre, steel

REACTOR 140

W4400WW00

Shock absorber used primarily by workers on a structures, ladders and pylons. Lightweight, practical shape does not restrict users at the work. Newly designed for users with a maximum weight of 140 kg (including equipment).

- designed to safely capture a person weighting 140 kg (including equipment)
- maximum active breaking length of shock absorber is 175 cm
- optional length of lanyards for diverse work
- zipper around the perimeter of the cover for easy inspection of the energy absorber
- intact, orange indicator of energy absorber activation
- any EN 362 certified connector can be sewn into the attachment loop
- orange indicator is threaded through the attaching loops and indicates an actual damage
- cover is made from black synthetic rubber and Cordura with PU coating
- oval shape for easy grip
- different webbing lengths are produced on customer´s request

Weight: 170 g • 6 oz (without any connector and lanyards)
WLL: 140 kg
CE 1019 • EN 355

Power cable installation, Cableway Zugspitze, Germany Photo: David Dani

	Typ	Kód	Karabina	Délka [cm]	Váha [g]	RFU 11.074
	„I" 85 cm	W4410W085	—	85	250	✓
		W4411W085	K370	100	400	✓
		W4412W085	K353	110	750	✓
		W4413W085	K355	120	1230	✓
	„I" 155 cm	W4410W155	—	155	290	✓
		W4411W155	K370	170	440	✓
		W4412W155	K353	180	830	✓
		W4413W155	K355	190	1270	✓
	„Y" 85 cm	W4420W085	—	85	210	✓
		W4421W085	2x K370	100	610	✓
		W4422W085	2x K353	110	1290	✓
		W4423W085	2x K355	120	2210	✓
	„Y" 155 cm	W4420W155	—	155	390	✓
		W4421W155	2x K370	170	690	✓
		W4422W155	2x K353	180	1390	✓
		W4423W155	2x K355	190	2310	✓
	EYE „Y" 155 cm	W4430W155	—	155	390	✓
		W4433W155	2x K355	190	2310	✓
	RING „Y" 155 cm	W4440W155	—	155	530	✕
		W4441W155	2x K370	170	830	✕
		W4442W155	2x K353	180	1510	✕
	ROPE "I" 85 cm	W4450X085	—	85	290	✕
		W4452X085	K353 black	110	790	✕
		W4453X085	K355 black	120	1260	✕
	ROPE "I" 155 cm	W4450X155	—	155	370	✕
		W4452X155	K353 black	180	870	✕
		W4453X155	K355 black	190	1340	✕
	ROPE "Y" 85 cm	W4460X085	—	85	400	✕
		W4462X085	2× K353 black	110	1400	✕
		W4463X085	2× K355 black	120	2340	✕
	ROPE "Y" 155 cm	W4460X155	—	155	520	✕
		W4462X155	2× K353 black	180	1520	✕
		W4463X155	2× K355 black	190	2460	✕
	ADJUST	W4470Y100	—	100–160	420	✕
		W4471Y100	1× K370	115–175	570	✕
		W4472Y100	1× K353	125–185	920	✕
		W4474Y100	1× K0124	115–175	537	✕
	FLEX "Y" 85 cm	W4480X085	—	85	330	✕
		W4482X085	2× K353 black	110	1355	✕
		W4483X085	2× K355 black	120	2255	✕
		W4484X085	2× K0124	100	565	✕
	FLEX "Y" 155 cm	W4480X155	—	155	430	✕
		W4482X155	2× K353 black	180	1425	✕
		W4483X155	2× K355 black	190	2350	✕
		W4484X155	2× K0124	170	665	✕
	FLEX RING "Y" 155 cm	W4490W155	—	155	430	✕
		W4492W155	2× K353 black	180	1425	✕
		W4493W155	2× K355 black	190	2350	✕
		W4494W155	2× K0124	170	665	✕

SMALL
K370
BIG
K353
GIGA
K355
SMALL
K370
BIG
K353
PALM
K0124
RING Y 155 cm
EYE Y 155 cm
Y 155 cm
I 155 cm
Y 85 cm
I 85 cm
ADJUST


L= max. 200 cm
LANYARD
REACTOR 140
HECTOR BC
ROPE I 155 cm
ROPE Y 155 cm
ROPE I 85 cm
ROPE Y 85 cm,
BIG
K353
GIGA
K355
FLEX RING Y 155 cm
FLEX Y 155 cm
FLEX Y 85 cm
PALM
K0124
BIG
K353
GIGA
K355

JOULE

70 cm – W4100Y070
120 cm – W4100Y120
160 cm – W4100Y160

Fall absorber
The fall absorber Joule presents optimal solution for securing persons working on horizontal constructions and roofs.
Joule is activated after reaching the load of 2 kN (200 kg).
Minimal guaranteed strength after the breaking action is 15 kN.

CE 1019 • EN 355

JOULE 70 is possible to use with the fall absorber LOCKER, for working situation which requires longer distance from the safety line.

EN 353-2, EN 355

This is not a final product, this set is necessary to set up from the separate parts.



Work at height at night, Kladno, Czech Republic Photo: Jiří Bošek

ROOFER SET

ROOFER SET 10 – M0020X1
ROOFER SET 20 – M0020X2

Roofer set is ideal for those, who are fully devoted to roofing. It allows you to position yourself on a roof with up to 45° angle to prevent a possible fall due to slippage or breaking of a structure.

Set contains:

W0091BY	ROOF MASTER
W1011WB20	SITE – Locker+Static 11mm, (ROFER SET 10 – 10 m, ROFER SET 20 – 20m)
W2016X120	Sling lanyard 120, 22 kN (double safety sling)
K0122EE07	OXY triple lock
K4241ZO07	STEEL OVAL carabiner, Triple Lock
S9000YY35	GEAR BAG 35 L YELLOW



FALL ARRESTER SET

M0022XX

Set intended for work restraint situations or attaching to anchor lines. Versatile and lightweight set contains:

Set contains:

W0089SY	BASIC HARNESS
W4100Y160	JOULE 160 Fall absorber
K4241ZO05	STEEL OVAL CARABINER, SCREW GATE 2x
W0052B010	WORKING BAG 10L



SCAFFOLDER SET

M0021XX

Scaffolder set is intended for those, who install scaffolds or work on tall structures and towers. It allows you to reach safely a place of work and position there for work.

Set contains:

W0063BB	Technic harness
W4442W155	Reactor 140 RING „Y" 155 cm + 2xK353
W1012WB02	SITE 2M + K370
K0122EE07	OXY triple lock
K4241ZO07	STEEL OVAL CARABINER, TRIPLELOCK
W1023YY00	MONTY BAG YELLOW

PPE INSPECTION SET

equipment for periodic PPE control

M0000XSET

W1023	Monty bag
X0013XX02	Wire (diameter 2 mm)
X0015XX00	Marker of textile PPE
X0016XX00	Gas Hot Knife
X0017XX00	Sliding Gauge
X0018XX00	Measuring Tape
X0023X200	Silicone oil
X0020XX00	Illuminated magnifier
X0004GB00	Thermocutter
L9991WB	Periodic control labels + plastic films
X0014XX00	File
X0021XX11	Sticker PPE inspection next control
X0022XX11	Sticker PPE inspection unsatisfactory

CABLEWAY EVACUATION SYSTEM

MK006

Complete evacuation set of personal protective equipment for work at heights for one rescue team carrying out the evacuation of persons from a chairlift or gondola.

- evacuation system is designed to be used by two rescuers
- set includes the EASY LIFT rescue pulley
- basic recommended gear is completed with optional equipment according to client´s specific needs
- adequate knowledge of the safeguards and methodologies for using the products included in the system is essential for safe ski lift evacuation
- fulfils the Regulation EP and R (EU) 2016/424

CE 1017

Set includes:

fullbody harness
fall absorber Y
small maillon oval
Giga connector
HMS carabiner
Easy Lift pulley
Maillon
Figure eight
Evacuation triangle
Sling
chest sling Axillar
Static rope 11 mm
Helmet
Gear bag
Protective gloves

Additional gear according the type of cableway:

Descender
Static rope 11 mm, 5m, 2
yeas for descender SIR
HMS carabiner
Baby Rescue Bag
Laika - dog rescue harness

Chairlift evacuation, Jánské lázně, Czech republic Photo: Ondřej Vítko

RESCUE SET

with 30 m rope – M0030X030
with 50 m rope – M0030X050
with 100 m rope – M0030X100

Rescue set is a perfect easy-to-use solution for rescuing the casualty from the fall arrest line and lowering him/her safely down.

Set contains:
- Rescue ratchet
- SIR
- Static R44 11 red with one stitched eye and one sealed rope end
- 1x Oval Steel Connector Triple Lock
- 1x Hector Triple lock black connector
- Maillon Big Delta
- STEEL LANYARD „I" 130cm
- GEAR BAG red - 35 l for 30 and 50 m rope, 50 l for 100 m rope

 Tree care, Paseky nad Jizerou, Czech Republic Photo: Ondřej Vítko

ACCESSORIES AND PROMOTIONAL

GEAR BAG

35 l black – S9000BB35
35 l yellow – S9000YY35
35 l red – S9000RR35

50 l black – S9000BB50
50 l yellow – S9000YY50
50 l red – S9000RR50

Transport bag for your gear

- waterproof, durable and washable
- very convenient to carry your gear
- takes up little space and stays dry
- transparent pocket (A4) on the top flap for your documents
- intended for speleology and working at heights
- minimum amount of seams
- main seams feature HF welding

Colors: yellow, red and black
Capacity: 35 and 50 litres
Material: PVC
Weight: 700 g • 24.7 oz – 35 l version

TARP DUFFLE

70 litres – C0046BB70
90 litres – C0046BB90
120 litres – C0046B120

Tarp duffle 120 l

Tarp duffle 70,90 l

Expedition bag 70, 90, 120 l
It's not your average duffel bag... Made from a durable laminate material, the TARP DUFFLE is an almost indestructable bag. Resilient enough to be roughed up in-flight, or to be transported up a mountain via a yak or off-road vehicle, this is one burly duffel bag. For longer trips, grab the 120 litres size so you have enough room for all your gear

- Alpine-cut shoulder straps
- Dual daisy chains
- Twin haul handles on ends
- Rugged construction with extra bartacks and double stitching
- Four compression straps
- Internal mesh pockets
- Pocket on top

Capacity: 70 l, 90 l, 120 l
Color: black
Max. load: 20 kg, 23 kg, 23 kg
Weight: 1820 g (70 l), 2270 g (90 l), 2720 g (120 l)
Material: PVC

MOVEMENT BAG

C0073BY00

Resistant traveling bag with the wheels for your climbing adventures, business trips or work at height missions.

- large u-shaped opening with heavy duty double zippers provides easy access to contents. Zippers can be easily locked with a padlock
- convenient side pocket allows you to keep e.g. footwear separate from clothing
- durable webbing straps and grab handle with reinforced stitching
- smooth rolling with all-terrain wheels for effortless mobility
- durable internally constructed push button locking handle adjusts to multiple heights for comfort whether gliding or pulling the bag
- side organization pocket for all of your travel needs
- heavy-duty PVC fabric backing
- rubberized, textured corner protectors guard agains wear and tear at critical contact points
- plastic piping reinforce high friction zones
- one internal accessory pocket provide easy packing organization

Dimension: 77 x 39 x 38 cm
• 30.3 x 15.4 x 15.0 in
Capacity: 110 litres
Max. load: 23 kg
Weight: 4600 g (10.1 lb)

CARRY BAG

C0001YY00

Practical bag intended for storage and transport of ropes as well as other gear.

- made from durable and washable material
- plastic reinforcements keep the bag self-standing
- due to its shape it is easy to store the rope and rigging tools properly
- very convenient to carry your gear
- reinforced ergonomic plastic handle to haul the bag
- loop on the bottom to shake out the gear and dirt
- water resistant
- side pocket for the accessories
- 2 steel rings for shoulder strap to carry the bag easily
- fast closing system

Color: yellow/black
Dimension: 30x40(58) cm
Max. load: 28 kg
Capacity: 28 + 10 l
Material: PVC
Weight: 940 g • 33.16 oz

DRY BAG

S9001YX40 - 40 l
S9001BX60 - 60 l

Dry bag with detachable shoulder straps intended for complete waterproof protection of your gear.

- classic rolling system with an additional guide bar
- retaining rings against unwanted opening of the closure buckle
- washable extra-durable PLASTEL® fabric, UV and waterproof resistant
- metal D-ring for safety attachment
- easily detachable foam padded shoulder straps
- color differentiation of the bag volume

Color: yellow [40 l], black [60 l]
Weight: 750 g • 26.5 oz (± 15 g • 0.5 oz) [40 l]
Material: PVC, PE
Volume: 40 or 60 litres

DRY DUFFLE

40 litrů, žlutý – S9003YY40
60 litrů, černo/žlutý – S9003YB60

Water resistant dry duffle that opens fully across its length so you can get to your compartment without having to unload half your stuff.

- Classic rolling system with additional guide bar
- Large top access to the compartment
- Quality fasteners to fix the closure and adjust the volume
- Daisy chain for fixing and attaching further gear
- Closure buckles on both sides to prevent unwanted opening
- Additional handle for short distance transfers
- Removable foam padded shoulder strap
- Colour differentiation of the bag volume

Color yellow [40 L], black/yellow [60 L]
Weight 780 g • 27.5 oz [40 L] 1040 g • 36.7 oz [60 L]
Size side Ø 27 cm, length 55 cm [40 L] side Ø 30 cm, length 70 cm [60 L]
Material PVC, PE
Volume 40 or 60 litres

RESCUE BAG

W9003RX45

Storage bag with a capacity of 30 litres

- ideal for long term storage of rescue equipment
- made of waterproof and washable material
- zippered transparent pocket on the side for documents/list of contents in A4 format
- adjustable shoulder strap
- fast opening/closing with a durable toggle

Weight: 1000 g (35.3 oz)
Material: PVC
Volume: 30 litres

PROTECTIVE CASE

17 litres – W9002XX17
46 litres – W9002XX46

Shock and water proof plastic box for your gear.
PROTECTIVE CASE 17 litres:
Outside dimensions
L x W x H: 40 x 30 x 22.3 cm
Inside dimensions
L x W x H: 34.3 x 22.3 x 20.5 cm
Lid + bottom depth: 3.9 + 16.6 cm
Weight: 1.74 kg
PROTECTIVE CASE 46 litres:
Outside dimensions
L x W x H: 60 x 40 x 27.8 cm

Inside dimensions
L x W x H: 51.8 x 31.8 x 25.9 cm
Lid + bottom depth: 4.8 + 21.1 cm
Weight: 3.44 kg

MONTY BAG

W1023

Bag for your gear and documents

- adjustable shoulder strap
- made of high resistant and durable fabric POLYMAR
- washable
- durable material
- colors: grey, yellow, orange, red

TRIPOD BAG

A4070XX00

Durable bag with a reinforced bottom to protect a tripod from mechanical damage during transport and against weather conditions.

- shoulder straps allow easy transport of a tripod to a workplace
- zippered top access into the bag
- durable material for higher mechanical resistance due to double-layer PVC sheath

Material: PES + PVC 600g/m^2
PES with double-layer PVC 1400g/m^2 (reinforced bottom)
Dimension: 160 x 30 cm
Max. load: 30 kg
Volume: 110 l
Weight: 2 kg · 4.4 lb

ROPE BAG

C0001BB

With removable sheet.

- sheet dimensions 137 x 137 cm
- hidden pocket for keys and money
- well-padde shoulder straps
- abrasion resistant material

Weight: 620 g • 21.87 oz

URNA

W1026BB

Leg rope bag

- for rappeling in the extreme conditions to have the rope under the control
- can be also used as a tool bag when working at the height
- easy to put on the user´s leg and the harnesses with the plastic buckle
- made from high quality material
- max. length of the rope 50 m of the diameter 11,5 mm
- inside loop to tie the end of the rope
- easy closing system allows to feed the rope slowly
- the bag can be completely closed to avoid loosing the tools
- side pocket for small items or for the note-book

Color: black
Capacity: 11 litres
Weight: 240 g • 8.5 oz

WORKING BAG

W0052B010
XL – W0052B012

Transport bag for working harnesses – also suitable as a gear bag for tools

- made from high abrasion resistant material PES 600 g/m2
- simple closing system with a plastic buckle
- net on the bottom for better airflow (the bag is not waterproof)
- transparent pocket for the name tag or instruction of use
- wide opening for easier putting in the harness or gear
- inside stichting covered by lace webbing
- suitable for 30m rope (10.0 mm)

Color: black
Weight: 125 g / 130 g • 4.4 oz / 4.6 oz
Material: PES
Capacity 10 / 12 litres

TOOLKIT

W9004YX00

Special bag to carry fasteners and tools for work at height.

- Belt loop to attach the toolkit to the worker at height.
- Slots for a carpenter's square.
- Closure system of the pockets to prevent falling of small items when working at heights.
- Hammer loop.
- Pockets for small items.
- Two-level loops to attach the toolkit to the harness.
- Main compartment for tools.
- Side organizer for a utility knife, a screwdriver, pencils etc.
- It is possible to carry the toolkit on a belt(belt not included).

Color: yellow-black
Dimension: 23 x 20 x 8 cm – main compartment + outside slots and pockets
Max. load: 10 kg
Weight: 650 g (23 oz)

TOOL BAG

W0008BS

Hardware carrier and organizer

- made of high resistant and durable fabric POLYMAR
- inside and outside pockets for hardware
- intended to be atached directly to the harness via carabiner or using additional waist belt
- well arranged
- easy to maintain
  maximum load – 10 kg
- dimension – 23 x 23 x 9 cm

Carabiner is not included.

Tree cutting, Poniklá, Czech Republic Photo: Marta Mendřická

FIRST AID BAG – LARGE

C0058RR00

(without the content)

- ideal for all of those who wish to choose--their own content
- bright colour increases the visibility in a bad weather or inside the backpack
- big attachment loop
- insert compartments in different sizes
- zipped big mesh pocket
- inside buckle with the emergency whistle
- high-durable material for the use in demanding conditions.

Dimension: 22 x 18 x 5 cm
material: polyamid, polyester
weight: 189 g • 6.7 oz

FIRST AID BAG

C0053RW

(without contents)
Compact and light first aid bag for minimalists

- ideal for all of those who wish to choose their own contents.
- all-round zip fastener with reflective component guarantees a good overview and easy access.
- two attachment loops;
- insert compartment in different sizes; zipped mesh pocket
- velcro attachment loop on the harness or a hip strap of backpack
- easily removable from the harness by one hand
- emergency whistle included

Dimension: 13 x 10 x 5 cm
material: polyamid, polyester
Weight: 61 g • 2.14 oz

RESCUE POLE

W8000BX00

Retractable Pole for attaching an anchor remotely

- Remote rescues
- Pole has a 3.2 m reach
- Slim fit shoulder bag with an additional pocket for heads storage
- Available with four different heads for connectors

Weight: 550 g • 19.4 oz
Length Extended: 317 cm
Length Retracted: 73 cm
Diameter: 2.8 cm
Material: fibre glass, brass bush, PVC rubber, stainless steel heads attachment

Head for connectors:
W0024XX01 – for BORA/HECTOR
W0024XX02 – for BIG CONNECTOR
W0024XX03 – for GIGA CONNECTOR
W0024XX04 - for SMALL CONNECTOR

Heads and connectors are not included.

W0024XX01

W0024XX02

W0024XX03

W0024XX04

TREEMOUSE

W9500Y

Arboristic throwing bag for tree climbing

- situable for installation of the anchor point in a treetop using cambium saver (JINGLE)
- used for dropping small branches down from the tree top
- situable for installation of the working rope to the places with comlicated access

material: high endurance synthetic fabric PES
steel welded ring of 3 cm in diameter
polyamid webbing
colour: yellow, blue/yellow, blue

TREEMOUSE 300
300 g/yellow/code: W9500Y300

TREEMOUSE 350
350 g/blue/yellow/code: W9500Y350

TREEMOUSE 400
400 g/blue/code: W9500Y400

FALCONER FULL

C0012YB

Lightweight gloves featuring great grip, dexterity and ability.

- durable double layer of artificial and split cow grade A leather on the palm
- additional reinforcement of the high-wear area between forefinger and thumb,
- breathable abrasion resistant nylon on the back
- neoprene cuff with a reinforced attachment hole

Size: 8, 9, 10, 11
EN 420

FALCONER TACTICAL

C0013YB

Lightweight gloves with uncovered tops of thumb, forefinger and middle finger making manipulation of metalwork simpler.

- durable double layer of artificial and split cow grade A leather on the palm
- additional reinforcement of the high-wear area between forefinger and thumb
- breathable abrasion resistant nylon on the back
- neoprene cuff with a reinforced attachment hole.

Size: 8, 9, 10, 11
EN 420

FALCONER 3/4

C0014YB

Lightweight gloves with removed tops of fingers making manipulation of metalwork simpler.

- durable double layer of artificial and split cow grade A leather on the palm
- additional reinforcement of the high-wear area between thumb and index finger
- breathable abrasion resistant nylon on the back
- neoprene cuff with a reinforced attachment hole
- two special pull-off half-loops on top of middle and ring fingers to secure an easy put off.

Size: 8, 9, 10, 11
EN 420

GRIPPY

C0006BH

Made out of quality leather. Reinforced palm area. Closed fingers. Abbrasion resistant.
Gloves are easy to put on thanks to special pull-on loop.

Kevlar thread • Size: 8, 9, 10, 11
EN 388, EN 420

GRIPPY 3/4

C0006HH

Made out of quality leather. Reinforced palm area and lower part of finger area.
Exposed fingertips allow you to keep your sense of touch and manipulate your gear. Gloves are easy to put on thanks to a special pull-on loop.

Kevlar thread • Size: 8, 9, 10, 11
EN 388, EN 420

Camera traps installation, Mentawa Islands, Indonesia Photo: Tomáš Ouhel

WORK KNIFE

A0031BS

Pocket knife with first class stainless steel blade.

- blade length 80 mm
- one hand operation and safety lock of opened knife
- stainless steel flexible clip for belt fixation, hole for the accessory cord fixation

Material:
blade and clip – stainless steel, plastic handle
Weight: 83 g • 2.9 oz

RESCUE KNIFE

A003OY

Special rescue knife with first class stainless steel ejection blade.

- blade length 80 mm and safety lock of opened knife
- special shape of the blade with the hook at the end for cutting of ropes or webbing
- other features: glass cutter, hammer for glass window breaking, opener of electrical cases – wrench
- stainless steel flexible clip for belt fixation

Material:
Blade and clip – stainless steel, plastic handle
Weight: 196 g • 6.9 oz

CULTER

A0050HH00

Reliable knife for daily work or emergency situations including belt cutter and window breaker.

- half-serrated 80 mm blade made of 420B stainless steel
- handle made of stainless steel and red G10 fiber
- one hand opening and closing, safety lock
- G10 line of fiber materials is not electrically conductive
- G10 fiber exhibits superior mechanical and dimensional stability and doesn't shrink, it can also resist high temperature (up to 180 °C)

Color: red
Weight: 208 g • 7.34 oz
Material: stainless steel, G10 material

OVERALL

W9803BY

Working overall combining durability, working comfort and maximum freedom of the movement. Specially intended for work at height, easy and quick to take off even without taking the shoes off.

- 21 % polyester, 70 % cotton 250 g/m2, 9 % Cordura 500D
- bright colors and reflective strips increase the worker´s visibility
- high durability even when it´s washed at high temperatures (90° C)
- full-length overall with two zippers to guarantee high comfort, practicality and a high speed when putting-on
- adjustable waist for optimum working comfort
- elastic fabric in the armpits and crotch
- two large breast pockets
- on the left sleeve pocket with compartments for mobile phone, pens, small items
- on the left leg extremely large pocket for plans, gloves, etc.
- on the right leg pocket for rescue knife supplemented by two rings of rubber for protection against falling
- on the back zipper pocket for small items
- all pockets marked with bright color for greater comfort
- pants, collar and sleeves ending with adjustable Velcro against heat loss, the penetration of dirt, snow, etc.
- pants tested in the fields of work at height, rescue, arboriculture
- made in the Czech republic

Size: S, M, L, XL • EN ISO 13688



overall			
size	chest **C** [cm/in]	height **D** [cm/ft]	lenght **E** [cm/in]
S	90/35	172/5.6	102/40
M	94/37	175/5.7	105/41
L	100/39	180/5.9	110/43
XL	106/42	185/6	115/45

note: length after sewing (is added due to shrinkage), shrinkage after washing according to the processing instruction sheet is about 4% of the length

WORKING PANTS

W9801BY

Lightweight and highly flexible pants specially intended for work at heights.

- perfect combination of durability, working comfort and maximum freedom of the movement
- contrast colours and reflective strips increase the worker´s visibility
- material ELASTAN guarantees a very high comfort during movement
- jeans low cut for comfortable fit
- higher back for comfortable fit with a working harness
- zippered pockets to secure any items needed in the pocket
- large zippered pocket for mobile phone or small tools, including a loop to secure tools against the fall
- in the side seam pockets for a knife, pencil, screw driver and other small tools
- on the back part deep pocket for any items
- loops for 50 mm wide belt
- large two loops for braces
- front part reinforced with CORDURA
- pants ending with adjustable velcro against heat loss, the penetration of dirt, snow, etc.
- pants tested in the fields of work at height, rescue, arboriculture
- bottoms of the pants are equipped with the mettalic hooks.

Color: black + yellow and reflexive strips
Size: S, M, L, XL
Material: 98% cotton/2% elastan (250 g/m²) + Cordura 500D
EN ISO 13688



working pants		
size	waist **A** [cm/in]	lenght **B** [cm/in]
S	78–82/30–32	105/41
M	82–86/32–34	110/43
L	88–94/35–37	113/44
XL	96–104/38–41	115/45

note: length after sewing (is added due to shrinkage), shrinkage after washing according to the processing instruction sheet is about 4% of the length

Tree nursery Rokle nad Jizerou Photo: Ondřej Vítko

APOLLO PANTS

C1034SS0

Men's technical pants for movement in the vertical world and for daily wear to work or school.

- the ergonomic REGULAR FIT cut with shaping at the knees and the inset gusset at the crotch guarantee maximum freedom of movement
- made of a blend of high quality cotton and spandex that guarantees breathability, durability and flexibility
- fastening of the pants with a high-quality YKK metal zipper and a metal button with the Singing Rock logo
- the possibility to tighten the width of the legs with an elastic band hidden inside the legs
- elastic band in the side seam for attaching a brush for cleaning the holds
- 2 front and 2 back comfort pockets
- the pants are finished with an enzymatic wash that makes them soft to the touch, shrunken and maximally comfortable

Size: S–XXL
Material: 96% cotton, 4% spandex
Colour: anthracite
Weight: 430 g • 15.2 oz

APOLLO SHORTS

C1035SS0

Men's technical shorts for movement in the vertical world and for daily wear to work or school.

- the ergonomic RELAX FIT cut with the inset gusset at the crotch guarantee maximum freedom of movement
- made of a blend of high quality cotton and spandex that guarantees breathability, durability and flexibility
- fastening of the shorts with a high-quality YKK metal zipper and a metal button with the Singing Rock logo
- elastic band in the side seam for attaching a brush for cleaning the holds
- 2 front and 2 back comfort pockets
- the shorts are finished with an enzymatic wash that makes them soft to the touch, shrunken and maximally comfortable

Size: S–XXL
Material: 96% cotton, 4% spandex
Colour: anthracite
Weight: 275 g • 10 oz

T-SHIRT BACKBONE

men – C1013BB
women – C1014BB

T-shirts made of 100 % cotton with short sleeves and classic round collar.

- very comfortable to wear for daily use
- made in the Czech Republic
- tag less label

Style: men/women
Size: XS – XL
Weight: 170 g/m^2

T-SHIRT ROCKET

men – C1028VX
women – C1029VX

Comfortable t-shirt made of top quality cotton with elastan, ensures the freedom of movement when climbing or wearing it everyday.

- tag less label
- relaxed fit
- made in the Czech Republic

Color: purple
Size: S, M, L, XL
Material 96 % cotton, 4 % elastan
Weight: 170 g/m^2

T-SHIRTS BLUE MOUNTAIN

men – C1032MM
women – C1033MM

Comfortable t-shirt designed by climbers for climbers. Made of top quality cotton with elastan, keeps you moving freely at the crag or at the mountains.

- tag less label
- relaxed regular fit
- classic round collar
- made in the Czech Republic

Color: blue
Size: S, M, L, XL
Material: 96 % cotton,
4 % elastan
Weight: 170 g / m^2

POLO T-SHIRT

W9802BY

Pique style of polo t-shirt that is sure to look great with any outfit.
The polo features a regular short sleeves and collar with a three button placket for a comfortable fit. The top is finished with split sides and an embroidered Singing Rock logo for an instantly recognisable branded look.

- polo shirt with short sleeves
- regular collar
- Singing Rock branding
- machine washable

Style: UNIsex
Size: S, M, L, XL
Material: 100 % pique cotton

ROCKLIFE T-SHIRT LONG SLEEVE

C1036VX – man
C1037AX – woman

Comfortable long-sleeved T-shirt for your climbing activities or everyday wear in a COMFORT FIT cut in a very pleasant meliert material.

- minimalist print and woven label on the sleeve
- women's model with a deeper V-neck
- printed size label
- made in the Czech Republic

Size: S – XL (men's), XS-XL (women's)
Material: 40 % cotton, 50 % polyester, 10 % elastan
Color: burgundy red (men's), blue (women's)

women size	chest width	waist width	bottom widht	front length	sleeve length	neck width
cm	A	B	C	D	E	F
XS	86/34	78/31	86/34	61,5/24	60/23.5	20/8
S	90/35.5	82/32	90/35.5	62,5/24.5	61/24	20,5/8
M	94/37	86/34	94/37	63/25	61,5/24	21/8.3
L	98/38.5	90/35.5	98/38.5	64,5/25.5	62,5/24.5	21/8.3
XL	102/40	94/37	102/40	66/66	63,5/25	21,5/8.5

men size	chest width	waist width	bottom widht	front length	sleeve length	neck width
cm	A	B	C	D	E	F
S	96	94	98	67	67	18
M	102	96	102	69	68	18,5
L	106	100	106	70	69	19
XL	112	106	112	72	70,5	19,5

Jizera Mountains, Czech Republic Photo: Jiří Bošek

T-SHIRT COOL

W9806BX

Men's functional T-shirt made of cool material for working at heights or sports activities even on the hottest summer days.

- NILIT® Breeze® ensures a cool feeling when worn, special nylon fibres ventilate perfectly and maintain an optimal temperature
- flat seams and compression fit guarantee comfort even under the most strenuous physical work
- CoolMax fresh FX prevents overheating thanks to the active thermoregulation of the material
- T-shirt has antimicrobial protection with silver ions to slow down the decomposition of bacteria during physical activities
- made in the Czech Republic

Size: S – XXL
Material: 100 % nylon (front NILIT ® Breeze®, back CoolMax fresh FX)
Color: black

T-SHIRT ACTIVE LONG SLEEVE

W9805BX

Comfortable functional long-sleeved T-shirt for cooler days when working at heights or sporting activities.

- specially developed quick-drying material and cut ensure thermal comfort during physical activities
- extended compression fit, prevents pilling during work or sports
- hybrid cut fits both men and women
- side panels ensure body temperature regulation during exercise
- flat seams guarantee wearing comfort
- T-shirt has antimicrobial protection with silver ions to slow down the decomposition of bacteria during physical activities
- made in the Czech Republic

Size: S – XXL
Material: 92 % PAD supplex, 8 % lycra (front and back),
92% PES, 2 % PAD, 6 % lycra (side panels)
Style: UNIsex
Color: black

HOODY

C1018BY

Warm, cozy and comfortable hoody with a kangaroo pocket and a big hood.

Style: UNIsex
Size: XS, S, M, L, XL
Material: 90 % cotton,
10 % soft polyester
Color: black and yellow

HOODY FULL ZIP

C1019BY – man
C1020BY – woman

Warm, cozy and comfortable hoody with two pockets, hood and full zipper

- longer sleeves and special cut for climbers gurantee maximal comfort when climbing or working at height

Style: Men, Women
Size: S, M, L, XL, XXL (XXL- man only)
Material: 90 % cotton, 10 % soft polyester
Color: black and yellow

T-SHIRT MONKEY

C1030Y

Fun, comfortable climbing t-shirts made from top quality cotton for your youngest climbing stars.

- Tagless size lable
- Relaxed fit
- made in the Czech Republic

Color: yellow
Size: 128 (7–8 yrs.) , 142 (9–10 yrs.)
Material: 100 % cotton, (170 g/m^2)

KIDS HOODY

C1031M

Warm, cozy and comfortable hoody for the youngest climbers.

- fits both boys and girls
- with a kangaroo pocket and a big hood

Color: blue
Size: 128 (7–8 yrs.) ,
142 (9–10 yrs.)
Material: 90 % cotton,
10 % polyester (300 g/m^2)

T- SHIRTS

		Code	Style	Size	Color	Material	Back length cm / in	Front length cm / in	Chest width cm / in	Waist width cm / in	Bottom width cm / in	Leeve circumference cm / in	Sleeve length cm / in	Neck width cm / in
BLUE MOUNTAIN		C1032MM02	men´s	XS	blue	96 % cotton, 4 % elastan (170 g/m²)	65|25,6	65|25,6	93|36,6	90|35,4	88|34,7	27|10,6	34|13,4	22|8,7
		C1032MM03		S			65|25,6	65|25,6	98|38,6	96|37,8	96|37,8	29|11,4	34|13,4	24|9,5
		C1032MM04		M			68|26,8	67|26,4	104|40,9	102|40,2	102|40,2	32|12,6	37|14,6	24|9,5
		C1032MM05		L			71|28	70|27,6	110|43,3	107|42,1	107|42,1	32|12,6	37|14,6	25|9,8
				XL			72|28,4	71|28	116|45,7	112|44,1	112|44,1	35|13,8	38|15	25|9,8
BLUE MOUNTAIN		C1033MM02	women´s	SX	blue	96 % cotton, 4 % elastan (170 g/m²)	58|22,8	58|22,8	73|28,7	67|26,4	80|31,5	29|11,4	18|7,1	22|8,7
		C1033MM03		S			59|23,2	59|23,2	77|30,3	69|27,2	87|34,3	30|11,8	20|7,9	24|9,5
		C1033MM04		M			61|24	61|24	83|32,7	77|30,3	92|36,2	30|11,8	20|7,9	26|10,2
		C1033MM05		L			62|24,4	62|24,4	92|36,2	84|33,1	101|39,8	32|12,6	23|9,1	26|10,2
				XL			64|25,2	64|25,2	96|37,8	88|34,7	106|41,7	33|13	24|9,5	28|11
ROCKET		C1028VX02	men´s	XS	purple	96 % cotton, 4 % elastan (170 g/m²)	66|26	66|26	93|36,6	89|35	89|35	35|13,8	28|11	22|8,7
		C1028VX03		S			66|26	66|26	95|37,4	93|36,6	93|36,6	35|13,8	28|11	24|9,5
		C1028VX04		M			68|26,8	68|26,8	103|40,6	100|39,4	100|39,4	35|13,8	31|12,2	24|9,5
		C1028VX05		L			70|27,6	70|27,6	108|42,5	105|41,3	106|41,7	35|13,8	32|12,6	26|10,2
				XL			74|29,1	74|29,1	113|44,5	110|43,3	110|43,3	37|14,6	34|13,4	26|10,2
ROCKET		C1029VX02	women´s	XS	purple	96 % cotton, 4 % elastan (170 g/m²)	60|23,6	60|23,6	74|29,1	69|27,2	82|32,3	29|11,4	18|7,1	22|8,7
		C1029VX03		S			60|23,6	60|23,6	78|30,7	73|28,7	88|34,7	30|11,8	19|7,5	26|10,2
		C1029VX04		M			62|24,4	62|24,4	85|33,5	77|30,3	93|36,6	30|11,8	19|7,5	26|10,2
		C1029VX05		L			64|25,2	64|25,2	90|35,4	82|32,3	100|39,4	32|12,6	21|8,3	28|11
				XL			68|26,8	68|26,8	94|37	85|33,5	105|41,3	32|12,6	24|9,5	28|11
BACKBONE		C1013BB01	men´s	XS	black	100 % cotton	67|26,4	66|26	89|35	91|35,8	94|37	30|11,8	30|11,8	23|9,1
		C1013BB02		S			69|27,2	68|26,8	100|39,4	101|39,8	103|40,6	32|12,6	35|13,8	25|9,8
		C1013BB03		M			71|28	70|27,6	107|42,1	107|42,1	110|43,3	34|13,4	35|13,8	25|9,8
		C1013BB04		L			72|28,4	71|28	115|45,3	115|45,3	120|47,2	38|15	38|15	26|10,2
		C1013BB05		XL			75|29,5	74|29,1	125|49,2	125|49,2	128|50,4	39|15,4	38|15	26|10,2
BACKBONE		C1014BB01	women´s	XS	black	100 % cotton	60|23,6	60|23,6	73|28,7	69|27,2	83|32,7	28|11	23|9,1	24|9,5
		C1014BB02		S			62|24,4	62|24,4	77|30,3	75|29,5	90|35,4	30|11,8	23|9,1	26|10,2
		C1014BB03		M			65|25,6	64|25,2	86|33,9	80|31,5	95|37,4	32|12,6	25|9,8	26|10,2
		C1014BB04		L			69|27,2	68|26,8	90|35,4	86|33,9	100|39,4	32|12,6	25|9,8	28|11
		C1014BB05		XL			69|27,2	68|26,8	96|37,8	91|35,8	105|41,3	33|13	27|10,6	29|11,4
MONKEY		C1030Y128	children´s	vel. 128	yellow	100 % cotton, (170 g/m²)	52|20,5	52|20,5	68|26,8	67|26,4	71|28	26|10,2	20|7,9	20|7,9
		C1030Y140		vel. 140			57|22,4	55|21,7	74|29,1	74|29,1	76|29,9	28|11	23|9,1	20|7,9
POLO T-SHIRT		W9802BY02	men´s	S	black	100 % cotton	72|28,4	71|28	100|39,4	97|38,2	99|39	31|12,2	30|11,8	21|8,3
		W9802BY03		M			72|28,4	71|28	106|41,7	100|39,4	104|40,9	31|12,2	32|12,6	23|9,1
		W9802BY04		L			74|29,1	73|28,7	114|44,9	108|42,5	114|44,9	33|13	35|13,8	26|10,2
		W9802BY05		XL			77|30,3	76|29,9	122|48	116|45,7	120|47,2	38|15	37|14,6	26|10,2
ROCKLIFE long sleeve		C1036VX02	men´s	S	burgundy red	40 % cotton, 50 % PES, 10 % elastan	68	67	96	94	98	25	67	18
		C1036VX03		M			69	69	102	96	102	25	68	18,5
		C1036VX04		L			70	70	106	100	106	25	69	19
		C1036VX05		XL			72	72	112	106	112	25	70	19,5

ROCKLIFE long sleeve

Code	Style	Size	Color	Material	Back length cm / in	Front length cm / in	Chest width cm / in	Waist width cm / in	Bottom width cm / in	Leeve circumference cm / in	Sleeve length cm / in	Neck width cm / in
C1037AX01	women´s	XS	blue	40 % cotton, 50 % PES, 10 % elastan	61|24	61|24	86|33,9	78|30,7	86|33,9	19|7,5	60|23,6	20|7,9
C1037AX02		S			62|24,4	62|24,4	90|35,4	82|32,3	90|35,4	19|7,5	61|24	20|7,9
C1037AX03		M			63|24,8	63|24,8	94|37	86|33,9	94|37	19|7,5	62|24,4	21|8,3
C1037AX04		L			64|25,2	64|25,2	98|38,6	90|35,4	98|38,6	20|7,9	63|24,8	21|8,3
C1037AX05		XL			65|25,6	65|25,6	102|40,2	94|37	102|40,2	20|7,9	63|24,8	21|8,3

ACTIVE long sleeve

Code	Style	Size	Color	Material	Back length cm / in	Front length cm / in	Chest width cm / in	Waist width cm / in	Bottom width cm / in	Leeve circumference cm / in	Sleeve length cm / in	Neck width cm / in
W9805BX02	UNI	S	black	front and back: 92 % PAD supplex, 8 % lycra side panels: 92% PES, 2 % PAD, 6 % lycra	68|26,8	66|26	94|37	74|29,1	86|33,9	19|7,5	70|27,6	20|7,9
W9805BX03		M			69|27,2	69|27,2	100|39,4	82|32,3	93|36,6	20|7,9	71|28	21|8,3
W9805BX04		L			69|27,2	69|27,2	111|43,7	90|35,4	100|39,4	22|8,7	73|28,7	22|8,7
W9805BX05		XL			72|28,4	72|28,4	114|44,9	93|36,6	104|40,9	22|8,7	74|29,1	23|9,1
W9805BX06		XXL			74|29,1	72|28,4	120|47,2	99|39	110|43,3	23|9,1	75|29,5	23|9,1

COOL

Code	Style	Size	Color	Material	Back length cm / in	Front length cm / in	Chest width cm / in	Waist width cm / in	Bottom width cm / in	Leeve circumference cm / in	Sleeve length cm / in	Neck width cm / in
W9806BX02	men´s	S	black	100 % nylon (front NILIT ® Breeze®, back CoolMax fresh FX)	76|29,9	76|29,9	101|39,8	96|37,8	98|38,6	35|13,8	37|14,6	24|9,5
W9806BX03		M			78|30,7	78|30,7	106|41,7	101|39,8	103|40,6	36|14,2	38|15	24|9,5
W9806BX04		L			80|31,5	80|31,5	111|43,7	106|41,7	108|42,5	37|14,6	39|15,4	26|10,2
W9806BX05		XL			83|32,7	83|32,7	116|45,7	110|43,3	113|44,5	38|15	40|15,8	26|10,2
W9806BX06		XXL			86|33,9	86|33,9	121|47,6	115|45,3	118|46,5	39|15,4	41|16,1	26|10,2

HOODIES

HOODY

Code	Style	Size	Color	Material	Back length cm / in	Front length cm / in	Chest width cm / in	Waist width cm / in	Bottom width cm / in	Leeve circumference cm / in	Sleeve length cm / in	Neck width cm / in
C1018BY01	UNI	XS	black/ yellow	90 % cotton, 10 % PES	67|26,4	65|25,6	92|36,2	92|36,2	88|34,7	17|6.69	68|26,8	28|11
C1018BY02		S			67|26,4	65|25,6	98|38,6	94|37	91|35,8	18|7,1	71|28	28|11
C1018BY03		M			69|27,2	68|26,8	105|41,3	100|39,4	96|37,8	20|7,9	75|29,5	30|11,8
C1018BY04		L			72|28,4	70|27,6	110|43,3	107|42,1	100|39,4	20|7,9	78|30,7	30|11,8
C1018BY05		XL			72|28,4	73|28,7	118|46,5	114|44,9	108|42,5	20|7,9	82|32,3	30|11,8

HOODY FULL ZIP

Code	Style	Size	Color	Material	Back length cm / in	Front length cm / in	Chest width cm / in	Waist width cm / in	Bottom width cm / in	Leeve circumference cm / in	Sleeve length cm / in	Neck width cm / in
C1019BY02	men´s	S	black- -yellow	90 % cotton, 10% PES	66|26	65|25,6	109|42,9	100|39,4	87|34,3	18|7,1	73|28,7	30|11,8
C1019BY03		M			70|27,6	69|27,2	117|46,1	107|42,1	95|37,4	18|7,1	76|29,9	30|11,8
C1019BY04		L			72|28,4	70|27,6	122|48	114|44,9	100|39,4	18|7,1	78|30,7	30|11,8
C1019BY05		XL			76|29,9	75|29,5	130|51,2	120|47,2	105|41,3	20|7,9	80|31,5	30|11,8
C1019BY06		XXL			79|31,1	77|30,3	135|53,2	125|49,2	115|45,3	20|7,9	82|32,3	30|11,8

HOODY FULL ZIP

Code	Style	Size	Color	Material	Back length cm / in	Front length cm / in	Chest width cm / in	Waist width cm / in	Bottom width cm / in	Leeve circumference cm / in	Sleeve length cm / in	Neck width cm / in
C1020BY02	women´s	S	black- -yellow	90 % cotton, 10% PES	66|26	66|26	98|38,6	83|32,7	86|33,9	18|7,1	74|29,1	24|9,5
C1020BY03		M			68|26,8	68|26,8	107|42,1	90|35,4	92|36,2	18|7,1	76|29,9	24|9,5
C1020BY04		L			70|27,6	70|27,6	114|44,9	95|37,4	100|39,4	20|7,9	80|31,5	24|9,5
C1020BY05		XL			72|28,4	72|28,4	120|47,2	105|41,3	108|42,5	22|8,7	84|33,1	24|9,5

KIDS HOODY

Code	Style	Size	Color	Material	Back length cm / in	Front length cm / in	Chest width cm / in	Waist width cm / in	Bottom width cm / in	Leeve circumference cm / in	Sleeve length cm / in	Neck width cm / in
C1031M128	children´s	vel. 128	blue/ yellow	90 % cotton, 10 % PES (300 g/m²)	54|21,3	53|20,9	70|27,6	68|26,8	65|25,6	18|7,1	53|20,9	23|9,1
C1031M140		vel. 140			58|22,8	56|22,1	77|30,3	74|29,1	70|27,6	18|7,1	57|22,4	24|9,5

PANTS / SHORTS

APOLLO PANTS

Code	Style	Size	Color	Material	Weight g|oz	Waist width cm / in	Hip width cm / in	Thigh width cm / in	Knee width cm / in	Step length cm / in	Total length from waist cm / in	Width of leg edge cm / in
C1034SS02	men´s	S	antracit	96 % cotton, 4 % spandex	420|14.82	86|33,9	101|39,8	50|19,7	45|17,7	82|32,3	105|41,3	37|14,6
C1034SS03		M			430|15.17	88|34,7	104|40,9	55|21,7	47|18,5	82|32,3	106|41,7	38|15
C1034SS04		L			440|15.52	89|35	107|42,1	58|22,8	47|18,5	82|32,3	106|41,7	39|15,4
C1034SS05		XL			455|16.05	95|37,4	112|44,1	60|23,6	47|18,5	82|32,3	107|24,1	40|15,8
C1034SS06		XXL			475|16.76	102|40,2	117|46,1	60|23,6	50|19,7	82|32,3	108|42,5	40|15,8

APOLLO SHORTS

Code	Style	Size	Color	Material	Weight g|oz	Waist width cm / in	Hip width cm / in	Thigh width cm / in	Knee width cm / in	Step length cm / in	Total length from waist cm / in	Width of leg edge cm / in
C1035SS02	men´s	S	antracit	96 % cotton, 4 % spandex	265|9.35	85|33,5	101|39,8	59|23,2		27|10,6	52|20,5	51|20,1
C1035SS03		M			275|9.70	89|35	101|39,8	62|24,4		27|10,6	53|20,9	51|20,1
C1035SS04		L			285|10.05	92|36,2	104|40,9	63|24,8		27|10,6	53|20,9	51|20,1
C1035SS05		XL			300|10.58	98|38,6	107|42,1	63|24,8		27|10,6	53|20,9	52|20,5
C1035SS06		XXL			320|11.29	100|39,4	112|44,1	65|25,6		27|10,6	53|20,9	52|20,5

SNAPBACK HAT

C0074BY00

Cool Singing Rock cap for your head.

- flat bill is a classic among snapback caps
- solid crown and front panels are reinforced in perfect shape
- mesh in the back perfectly ventilates even in warmer weather
- easy adjustment with a snap strap

Weight: 94 g
Material: 65% PES, 35 % cotton, flap 100 % cotton, net 100 % Nylon

TRUCKER HAT

C0089SX00

Trucker hat for casual wear, work or climbing trips.

- mid-crown trucker hat with a six-panel design
- Singing Rock original embroidery
- adjustable snap closure

Weight: 82 g
Color: grey
Material: flap 97 % cotton / 3 % elastan, front panel 100 % cotton, net 100 % PES

BASEBALL HAT

black – C0051BH
brown – C0051HH

Square-shaped visor. Logo on front.
Website singingrock.com on back.

BASEBALL HAT LIGHT

C0070SL00

Cool hat for hot sunny days to cool down your head.

SAFETY FIRST

BEANIE

- made from microfibre polyester fabric that keeps Its shape well, as well as being breathable, warm, soft and lightweight
- keep your had warm and dry during vertical activities
- fits very well under the helmet
- suitable also for running, skiing, biking and other outdoor activities

Size: S-M, L-XL
Material: 100 % Polyester

C0053RX
BEANIE REDHOT

C0053AX
BEANIE AZURE

C0053OX
BEANIE ORANGE

C0054BX
BEANIE LOGOS

C0055BX
BEANIE BLACK ARROW

BEANIE PRO

C0087SB

Protective beanie for cold and windy conditions.

- upper part made of breathable, warm, soft and lightweight micro fiber polyester fabric
- lower section is made of windproof micro fleece fabric to protect against wind in cold environments
- fits very well under a helmet
- lateral perforations in ear areas ensure hearing during work or other activity
- machine washable up to 30° C, not suitable for tumble dry
- available in two sizes

Weight: 21 g • 0.74 oz
Size: S–M (49–53 cm • 19–21 in),
L–XL (54–58 cm • 21–23 in)
Material: 100 % Polyester

BEANIE POLAR

C0090BB00

NEW

Warm Polartec® Power Stretch® beanie for sport and work activities.

- made of very warm stretch functional material that can wick away sweat and is more resistant to wind and abrasion compared to conventional materials
- fits well under the helmet for all vertical activities
- flat seams do not disturb when wearing the helmet
- suitable also for other outdoor activities – skiing, snowboarding, running, etc.
- machine washable up to 30 °C, not suitable for tumble dry
- available in one size, fits men & women

Size: UNI
Material: 100 % PES

BALACLAVA PRO

C0088SB

Balaclava for the ultimate protection of the head, face and neck at cold and extreme conditions.

- provides great comfort due to stretchy, breathable fabric protecting your face while wicking moisture away
- designed for wearing under a helmet during all vertical activities
- you can wear it as a balaclava, half ski mask or neck gaiter. Just don't wear it in an airport or bank!
- suitable also for skiing, snowboarding, mountainbiking
- machine washable up to 30 °C
- fits men & women, available in two sizes

Size: S–M (52–55 cm), L–XL (56–59 cm)
Material: 52 % polyamide,
42 % polypropylene, 6 % elastan

BEANIE HAT

C0067BS00
ARROW

C0069BG00
NANUK BLUE

C0069PB00
NANUK purple

A Wool/acrylic mix of beanies, featuring a double layered headband and embroidered design.

- fits well under the helmet
- fleece double layered headband for colder conditions

Size: UNI
Material: wool, acrylic

SCARF

BLACK ARROW – C0079BX00
LOGOS – C0080BX00
AZURE – C0081AX00
REDHOT – C0081RX00

Multifunctional scarf 8 in 1 with a wide variety of uses for your protection against wind and cold.

- can be used as a balaclava, cap, masc, scarf, beanie, shawl, ear warmer, etc.
- 5 different designs to fit all users' styles
- made from elastic high-tech 100% polyester microfibre fabric that keeps its shape well, as well as being breathable, warm, soft, lightweight, of a very high quality and antibacterial.
- machine washable at 30 °C, cannot be tumble dried, air dry very quickly

Size: UNI (approx. 25 cm wide x 46 cm long)
Weight: 35 g • 1.24 oz

PITCHER

0.5 l – P0010X050
0.3 l – P0010X030

Classical beer pitcher 0.5 l or 0.3 l
for all who likes climbing and all activities on our vertical playground.

BEER MAT

SQUARE – P0047XX01
CIRCULAR – P0047XX02

Wooden beer mats under your favorite glass of beer or cup of tea and coffee.

- perfect way to protect the surface of your table from the wet beer mugs or coffee cups
- made of very durable, high quality birch plywood coated with transparent varnish

Weight: 50 g • 1.76 oz
Material: plywood
Thickness: 8 mm
Dimensions: 9 x 9 cm • 3.5 x 3.5 in,
Ø 10,5 cm • 4.1 in

WHOLE BEAN COFFEE CAN

P0038W150

Whole bean coffee for outdoor enthusiasts and coffee lovers. Enjoy the coffee time before/after your climbing or working day.

- whole bean coffee in a practical can, thanks to which the coffee retains its freshness and aroma
- for finest taste, always use clean, filtered water

Weight: 150 g • 5.3 oz
Coffee: 100 % Arabica

TRAVEL MUG

P0048X400

Travel Mug for your favourite coffee, tea or cold drink when you are travelling, camping or working in the office.

- keeps your drink hot or cold exactly as you need it
- BPA free no-spill top features a handy hinged lid to securely close when it's not in use
- made from durable, high-grade stainless steel that preserves the flavour and freshness of your drink
- double vacuum-insulated wall keeps the drink hot / cold for long hours, making it ideal for travel by car or other means of transport
- exterior is made from a bamboo composite material which protect your hands from the heat
- non-slip bottom, suitable for all common drink holders in the cars

Weight: 170 g • 6 oz • Volume: 400 ml • 14 fl. oz
Height: 17 cm • 6.7 in
Material: stainless steel, bamboo, BPA free plastic

GROUND COFFEE OUTDOOR

P0038GB10

Coffee for outdoor enthusiasts and coffee lovers. Enjoy the coffee time before/after your climbing or working day.

- each bag includes tear open inner pack which can be placed on any cup
- for finest taste, always use clean, filtered water; pour 180-200 ml, leave for 5 minutes and enjoy your coffee
- bags contain A1 and Brazil ground coffee
- A1 (80 % Arabica / 20 % Robusta) with strong, full, medium bitter taste with a pleasant aftertaste, suitable for milk treatments
- 100 % Arabica Brazil Pergamino Sul de Minas has very well balanced delicate sweet taste with a slight acidity and a hint of chocolate and almonds
- packet includes 5 bags of A1 coffee blend and 5 bags of 100 % Arabica Brazil (marked with a stamp on the bag)

Weight: 10 g • 0.35 oz (bag)
Coffee: A1 (80 % Arabica / 20 % Robusta), Brazil (100 % Arabica)

BELT

C9091XX

for trousers with Rock&Lock smart buckle
Do not use for climbing or work at heights!

Size: M/L, XL
Width: 20 mm

SPEED BELT

black – C9092BX
various colors – C9092XX

Belt for trousers with Speed buckle for fast releasing.
Width: 44 mm
Size: M/L, XL
Color: mixed colors
Do not use for climbing or work at height!
Color: black, khaki, various colors

KEY HOLDER

P99100X

You will never lose your keys if you use Singing Rock key holders.

USB FLASH DRIVE

P0019XX00

Wooden flash drive to transport and store your personal files.

- small ring to connect it to your key holder or accessory cord.

Capacity: 8 GB
Material: Eco Friendly wood

Czech Police Special Forces training, Czech Republic Photo: Artsiom Hasiankou

WRISTBAND

P0024XX00

100% latex-free silicone wristband
with debossed Singing Rock. Made from premium high quality rubber.

TEXTILE BADGE

10x4 cm – P0031XX01
15x6 cm – P0031XX02

Singing Rock textile embroidered badge to be stitched to your clothing, backpack or bag.
Size: 10 x 4 cm, 15 x 6 cm

PAPER BAG

P0033XX00
small – P0033XX02

Eco-friendly paper bag
rounded paper handle
supports a respectful approach to the environment.
Dimensions: 35x44x18 cm24x33x12 cm

BANNER BAG

P0054XX00

NEW

There are many ways to save the environment. Like not leaving leftovers and not throwing away old stuff. That's the spirit behind this upcycle bag. It's made from old Singing Rock banners and has handles made from leftover ropes. When you get one, you give things that someone else would throw away a second life.

- bag made from old trade fair banners
- each piece is an original
- handles made from leftover ropes can be adjusted with any knot, factory made approx. 65 cm long
- hand wash the bag, rarely in the washing machine on gentle/sport programme (30 - 40°C), do not use fabric softener or dryer, the bag may not get a third chance
- made in the Czech Republic

Colour: various
Weight: 275 g
Materiál: used advertising banners, leftover ropes
Dimensions: 38 x 45 cm
Volume: approx. 3.5 l

NOTEPAD A5

P0030XX00

Manage your important tasks or jot down your to-do list with our Singing Rock notepads.

CONDOM

P0023XX00

Safety first
Your Personal Protective Equipment for your hardware.
Size: UNI
EN ISO 4074, CE 1023

SINGING ROCK PEN

P0022XX00

Ballpoint pen for everyday writing.

BANNERS

P0020

Singing Rock banners made from lightweight
PES with a holes to hang up.

Size:
P0020BB02
Small: 60 x 60 cm
P0020BB03
Medium: 30 x 150 cm
P0020BB04
Large: 200 x 100 cm
P0020BB05
XLarge: 150 x 150 cm

BEACH FLAG

P0021

Self standing event flag.
Made from elastic PES.
Comes with a footstand and carrier bag.

Size:
P0021BB00
Table: 29 x 60 cm
P0021BB03
Medium: 60 x 260 cm
P0021BB04
Large: 80 x 340 cm
P0021BB05
XLarge: 85 x 450 cm

SINGING ROCK STICKERS

P0025XX00

with back and front side adhesive.

TECH INFO EN

P0028WE00



690x990 mm

POSTERS

P0027WX00

1



2

3

4

5

Image posters with our gear in action.

1.	Silo	480x690 mm
2.	Helicopter Sweden	480x690 mm
3.	Tree Care	480x690 mm
4.	Tower Norway	690x480 mm
5.	Chairlift evacuation	690x480 mm

SERVICE & ACTIVITIES

POLYGON TRAINING CENTRES
SCAFFOLDS AND INDUSTRIAL HALLS
FRAMING AND ROOFING
FALL ARREST
ROPE ACCESS
LADDERS
TREE CARE
ROPE COURSES AND ADVENTURE PARKS
WIND TURBINES
CABLEWAY EVACUATION
MILITARY AND SPECIAL FORCES



POLYGON

POLYGON
singing rock

Over more than two decades on international markets, SINGING ROCK has become the world's leading manufacturer of Personal Protective Equipment (the "PPE"). In an effort to provide its customers with comprehensive services and solutions in the area of security of workers at height and above depth, SINGING ROCK was the first in the Czech Republic and former eastern Europe to build a completely unique multifunctional training center POLYGON.

POLYGON facilities create the ideal conditions for providing occupational health and safety (the "OHS") training for work at height and above depth, for testing PPE, for organizing industrial climbing contests and many other events associated with presentation and use of products and techniques related to this area. A number of specific simulations allow visitors to test safely proper techniques of safeguarding when working at height. All this under the direct supervision of experienced trainers while using complete equipment for these activities. With individual approach, high quality equipment and great emphasis on the practical part, our trainings in POLYGON became sought after among individuals and companies not only in the Czech Republic.

SINGING ROCK is certified as IRATA training company.

SINGING ROCK is the first and so far the only company in the Czech Republic to become a member of the globally recognized association IRATA.

IRATA – Industrial Rope Access Trade Association – was founded in the UK in order to ensure a safe working environment for workers at height. In a quarter of century of its existence, IRATA has become a leading expert in the field of security in work at height, and in this field it is the only global association with many member organizations around the world.

Our operated IRATA courses therefore provide, in conjunction with our certificated POLYGON training centers, a unique opportunity to obtain the best possible qualification for work at height and above depth. After successful completion of the training the participant receives an IRATA certificate, which is valid around the world and which is required by some foreign entities as the only possible prerequisite to carry out work at height.

irata International
Industrial Rope Access Trade Association
MEMBER
6017/T

POLYGON
singing rock



CZECH REPUBLIC
Polygon **Poniklá**
Polygon **Kladno**
Polygon Partner:
· **Brno**
· **Ostrava**
· **Karlovy Vary**

SLOVAKIA
Polygon Partner **Stúpava**

ROMANIA
Polygon Partner **Brasov**

BULGARIA
Polygon Partner **Sofie**

SPAIN
Polygon Partner **Navarra**

CHINA
Polygon Partner **Xi´an**

JORDAN
Polygon Partner **Amman**

COLOMBIA
Polygon Partner **Medellín**

Singing Rock Polygon training, IRATA Level 1, Kladno, Czech republic Photo: Ondřej Vitko

LIST OF SINGING ROCK POLYGON TRAINING CENTERS

POLYGON Poniklá Czech republic

Our first POLYGON is part of the SINGING ROCK headquarter and manufacturing factory in a picturesque valley of the Jizera river. It offers a number of model situations for work at height.
www.singingrock.com/polygon

POLYGON Kladno Czech republic

located in the former premises of Poldi Kladno – Konev. The former manufacturing building offers a real industrial environment to practice work situation when working at heights.
www.singingrock.com/polygon

Polygon Partner Brno Czech republic

Located in an industrial area in a former cement plant. Thanks to its height of more than 23m, it gives the opportunity to create a variety of model situations for work at height and rescue training.
www.klajda.cz/skoleni-prace-ve-vyskach-bozp

Polygon Partner Ostrava Czech Republic

Training centre situated in the unique historical industrial site where for more than 150 years thousands of miners used to mine a black coal.
www.polygonhlubina.cz

Polygon Partner Karlovy Vary Czech republic

Until recently, the Karlovy Vary region, situated in the west of the Czech Republic, didn´t have a proffesional training centre for work at height. It was changed in May 2019. Now, this new POLYGON parter offers high-quality services to all applicants from that part ouf our country.

Polygon Partner Stúpava Slovakia

The Slovak Polygon partner offers a very diverse range of health and safety training for work at heights. Especially for tree climbers, persons professionally qualified to perform periodic inspections for PPE and more.
www.polygony.sk

Polygon Partner Navarra, Spain

Total HSE training centre is equipped with structures that simulate wind turbines, in order to offer true-to-life experiences in their courses. Except basic range of general work at height trainings can also provide GWO and IRATA courses.
www.totalhse.com



Polygon Partner Amman, Jordan

Beit Jala Training Center is located in Amman, capital city of Jordan. Except basic range of general work at height trainings can also provide individual trainings in clients location.
www.beitjala.com.jo

Polygon Partner Medellín, Columbia

The first POLYGON partner in the American continent provides courses and training, which are specifically regulated for the entire Colombian territory and are part of the mandatory compliance with the Occupational Health and Safety Management System, as well as some at international level. Intervenes in the control and management of hazardous work activities.
www.deporteka.com.co

Polygon Partner Sofia Bulgaria

Training centre situated in Sofia is operated by PROFIXT Ltd, IRATA # 6026/T which has been providing work at heights trainings and IRATA trainings for over 10 years in Bulgaria and has certified more than 400 industrial rope access technicians by the standards of the international system of IRATA.
www.profixt.com

Polygon Partner Xi´an China

Training center is located in Xi´an, Shaanxi province capital city with long history. Provide trainings mainly for fire-fighters and rescuers.

Polygon Partner Brasov Romania

This training centre is the first provider of training courses in work-at-height in the south-east of Europe. The centre is evolved through the volume of it's services, the number of technicians and most importantly through it's techniques in providing rope access services.
www.e-solo.ro

BASIC SKILLS

Work at height

Workers at height are in permanent danger of falling from a height. That is why their safety should always come first. Worker's safety is achieved by using various methods for setting up a personal fall protection system. The structure of the fall protection system should always correspond with the type of activity considering high efficiency of work along with maximal possible safety.

FALL FACTOR



The impact force (IF) determines the maximum value of force generated during fall arrest of the object by the safety chain. The value of IP has a direct impact on the safety of worker at height. Ideally, we avoid IP if we reduce it to the lowest level possible (max 6kN)



When safeguarding an ascent using a fall arrest type „Y" it is necessary to move at the level FF1 and lower. It means that the connectors (EN362) connected to the fall absorber (EN355) during the ascent do not „fall" below the connection point of the harness (EN361) in which the absorber is connected to the harness.

ANCHORING





When anchoring from different point, it is necessary to take into account angle(s) of supporting elements.



Load of continuous anchoring point.
An example is creating a deviation using rope techniques.

KNOTS

Figure-Eight knot
Connection of two ropes using an eight knot
- Reduces the strength of rope in lab. conditions by approx. 46 %
- used to connect two roped of the same type and same diameter; connection of ends of a rope loop

Connection of ends of one rope loop

Connection of two ropes using an eight knot



Due to the character of this knot is necessary to leave at least 10 cm long tail of the rope or is essential to tie a backup knot, double fisherman´s knot

FRICTION KNOTS



Prusik knot
Simple and the easiest friction knot. It works in both directions. Normally made from accessory cords 5-6 mm diameter. It is possible to make it with one hand only. Note: the joining knot must be kept away from the rope to prevent slippage.



Klemheist (Machard) knot
Works very well, suitable also for flat slings, it´s possible to make it also from thicker diameter slings (up to 9mm).

ANCHORING KNOTS

Clove hitch
Reduces the strength of rope in lab conditions by approx. 12 %
Use: anchoring
It is possible to make it with one hand only, it is easy to untie after the loading

Double figure eight loop
(Bunny Ears)
Very useful for equalizing the load on two anchor points.





Lanyard with a whipped loop
Using lanyard with a loop is the best possible method of eliminating the possibility of erroneous tying of a knot during anchoring.



Due to the character of this knot is essential to tie a backup knot, double fisherman's knot.

CONNECTING KNOTS

Double fisherman knot
Connection of two ropes using a double fisherman knot
- Reduces the strength of rope in lab. conditions by approx. 32 %
- connection of two ropes (rope loops) of different type or diameter



Overhand follow through
Used to join two ropes or slings together. When loaded it is harder to untie it.



BELAY KNOT



Munter hitch
Knot used for belaying with HMS carabiner. There is no static friction on any part of the rope as it is a continuously moving knot. It is easy to tie even with one hand or with the gloves on the hands. The part of the rope going to belayer must not go through the gate of the carabiner.

Alpine butterfly
Reduces the strength of rope in lab. conditions by approx. 39 %
Use: anchoring; anchoring from separate points, inter-anchoring.



SCAFFOLDS AND INDUSTRIAL HALLS

Many people are injured each year when they fall from scaffolds. Scaffolds should be erected by trained and competent people. There are a number of organisations that provide training for the safe use of scaffolds. A scaffold is one way to prevent a fall when working at height. The type of scaffold selected must be suitable for the work and erected and dismantled by people who have been trained and are competent to do so. Those using tower scaffolds should also be trained in the potential dangers and precautions required during use. Tower scaffold provision and use must be properly managed and include rigorous scaffold inspection arrangements.

Delimitation of working area by restricting access to dangerous areas.







Use of mobile safety system (Fine line) to delimit safe working area







W0068BR
BODY II speed
fall arrest harness

RECOMMENDED GEAR

RK850X100
STEEL LANYARD „I"
130 cm

ADJUST
W1047Y100
adjustable lanyard

W4100Y120
JOULE 120
the fall absorber 120 cm

W2001
OPEN SLING
sewn sling, 120cm

W1011WB02
SITE
work positioning lanyard

A4000S
IKAR HWS
Retractable fall arrest system

X0075XX14
BANTAM BEAMER

W9601
FLASH INDUSTRY
working helmet

K4241Z005
OVAL STEEL CONNECTOR srew

K0122EE05
OXY screw
light alloy oval carabiner

K82310Z
MAILLON BOG D
steel maillon carabiner

W1010BB09
LOCKER
guided type fall arrester

L0041 – L0081
ACCESSORY CORD
6 mm, 20m

S9000BB50
GEAR BAG
waterproof bag

SCAFFOLDER SET

M0021XX
Scaffolder set is intended for those, who install scaffolds or work on tall structures and towers. It allows you to reach safely a place of work and position there for work.

ROOFING

When moving on the roofs, there is always the risk of fall through or slip followed by a fall. To eliminate this risk it is necessary to set up sufficiently strong anchor point and to use proper PPE. If there is no sufficiently strong anchor point, it is necessary to use more anchor points together. The anchorage must be placed above the worker to prevent him/her from a fall. If there is a risk of falling, it is necessary to incorporate a fall absorber into the safety chain. Pay attention to the horizontal distance from the vertical of the anchor point. The bigger it is the more dangerous possible fall will be.



Use of mobile safety system (fine line) to delimit safe working area.









W0091BY
ROOF MASTER
Lightweight and fully adjustable full body harness

RECOMMENDED GEAR

W9603RX
FLASH ACCESS
working helmet

K4241Z005
OVAL STEEL CONNECTOR
srew

K0122EE07
OXY triplelock
light alloy oval carabiner

K4241Z007
OVAL STEEL CONNECTOR
triplelock

W1010BB09
LOCKER
guided type fall arrester

C0012YB
FALCONER FULL

W2016*080
SLING LANYARD
sewn sling

W9004YX00
TOOLKIT
special carry bag

W1001WS10
FINE LINE BAG
mobile anchoring system bag

W1001WW10
FINE LINE
mobile anchoring system

L0250RR
Static 11.0
static rope

W8100B
ROPE PROTECTOR

ROOFER SET

M0020X1 – Roofer set 10 m,
M0020X2 – Roofer set 20 m
Roofer set 10 is ideal for those, who are fully devoted to roofing. It allows you to position yourself on a roof with up to 45° angle to prevent a possible fall due to slippage or breaking of a structure.

TOWERS AND RIGGING

- Working on tall structures may involve fall arrest, work positioning, rope access and possibly evacuation.
- If no stable safety system is present and the structure needs to be climbed repeatedly a flexible fall arrest line may be required
- For climbing on the frame construction of metal towers fall absorber may be essential.
- Construction demands a full range of fall protection solutions to meet the needs of a dynamic workplace. That's why workers turn to SINGING ROCK for expertise, superior quality products and continual systems innovation.

Some basic principles of using ropes and lanyards:

Keep your rope out of any sharp edges, rough surfaces and chemicals. Especially on slopes anticipate potential direction of fall and the strain of your rope. When working on constructions, pay attention to the direction of leading your rope and anticipate its possible strain. When using lanyards either to climb the construction or to positioning, take heed to reduce potential fall to minimum! Therefore always place the anchor point above the worker.



Ff = 0,5 Ff = 1 Ff = 1,5 Ff = 2 Ff > 2











Fall absorbers:
When using a fall absorber, the elongation of the fall absorber during breaking action shall be considered. As there are different types of fall absorbers on the market, safe use of this product requires careful reading and understanding of instructions for use, where the method of calculation maximal possible elongation of fall absorber is stated. For your safety we recommend to add another 0.5 m to the calculated distance.

Work positioning on a frame construction





W0081DR
PROFI WORKER 3D
standard
fully adjustable
fall arrest and
rope access harness

RECOMMENDED GEAR

W9603RX
FLASH ACCESS
working helmet

C006BH
GRIPPY
leather gloves

W1010BB09
LOCKER
guided type fall arrester

K0122EE07
OXY triplelock
light alloy oval carabiner

K4241Z005
OVAL STEEL CONNECTOR
triple lock

W0052B010
WORKING BAG
transport bag for working harness

W1012WB
SITE + K370
work positioning lanyard

W4400WW00
REACTOR 140
shock absorber

W2016080
SLING LANYARD
sewn sling

W2001
OPEN SLING
sewn sling

K9000BB03
PORTER
plastic holder

ROPE ACCESS

Rope access is called "royal discipline" in working at height activities. This working method is fast, effective, has little effect on the workplace and it is very quick to install and dismantle. It is used for a wide variety of work: cleaning, painting, inspection and other working situations.

Rope access or industrial climbing is a form of work, which applies practical ropework to allow workers to access difficult-to-reach locations without the use of scaffolding, cradles or an aerial work platform. Rope access technicians descend, ascend, and traverse ropes for access and work while suspended by their harness. Sometimes a work seat may be used. The support of the rope is intended to eliminate the likelihood of a fall altogether, but a back--up fall arrest system is used in case of the unlikely failure of the primary means of support. This redundancy system is usually achieved by using two ropes - a working line and a safety line.

rope ascend









rope descend



Working position with a descender.

Place hand and chest ascenders.

Position body into the descender and ascenders, re-place the fall arrester.

Take of the descender.

Place descender and take off a chest ascender.

Take off a hand ascender.



Short rope-to-rope transfer: off belay | descender (SIR) | hand ascender (LIFT) | chest ascender (CAM CLEAN) | positioning sling in a knot (COW'S TAIL) | fall arrester (LOCKER)



W0079DR
EXPERT 3D speed
fully adjustable rope access harness

RECOMMENDED GEAR

W9603RX
FLASH ACCESS
working helmet

RK804BX0R
LIFT
hand ascender

RK805BX00
CAM CLEAN
Chest ascender

W1010BB09
LOCKER
guided type fall arrester

K032SIR00
SIR
multipurpose device for rope acces

K0122EE07
OXY triplelock
light alloy oval carabiner

K4241Z005
OVAL STEEL CONNECTOR
triple lock

RK801EE00
PULLEY EXTRA
durable and lightweight pulley

W0010YB
FRANKLIN
work positioning seat

W1015B020
LOCKER SLING
certified sling for the Locker

W2001
OPEN SLING
sewn sling

L0450WG
STATIC R44 11.0
static rope

L0450RR
STATIC R44 11.0
static rope

W8100B
ROPE PROTECTOR

K00500S03
EDGE ROLLER
rope protector



PERMANENT LIFELINES

Permanent lifelines serve to secure workers in places where it is possible to set up fixed anchor point in the working place or near it. These are then interconnected by steel rope or a rail. For moving and securing, the worker uses connectors (EN 362) or special slider made for this purpose and supplied by the system manufacturer. The advantage of permanent lifelines is their long operating life and variability of use.

Fall arrest systems form an important element of the safety chain. When used correctly, they ensure sufficient absorption of fall energy, thus preventing the worker's body from being damaged. If the worker faints during or after fall, it is necessary to transport him to a safe place. The long hanging of unconscious body may have fatal consequences (trauma caused by hanging). Therefore keep in mind that fall arrest systems should be only used by trained workers. In case of need they should be able to aid each other at rescue and recovery action.



W0063BB
TECHNIC standard
fully adjustable
fall arrest
and positioning
harness

RECOMMENDED GEAR

W9600
FLASH INDUSTRY
working helmet

W0052B010
WORKING BAG
transport bag for
working harness

W1010BB09
LOCKER
guided type fall
arrester

K0122EE07
OXY triplelock
light alloy oval
carabiner

K4241Z005
OVAL STEEL CONNECTOR
triple lock

RK801EE00
PULLEY EXTRA
durable and
lightweight pulley

W1012WB
SITE + K370
work positioning
lanyard

W4462X085
REACTOR 140 ROPES „Y" 85 cm
shock absorber

X0075XX14
BANTAM BEAMER

W4100Y120
JOULE
energy
absorber

W2016080
SLING LANYARD
sewn sling

TREE CARE

An arborist is a professional in the practice of arboriculture, which is the cultivation, management, and study of individual trees, shrubs, vines, and other perennial woody plants in dendrology and horticulture. Arborists generally focus on the health and safety of individual plants and trees, rather than managing forests or harvesting wood.
Arborists who climb can use a variety of techniques to ascend into the tree. The least invasive, and most popular technique used is to ascend on rope.



There are two common methods of climbing:
Single Rope System (SRS) and Moving Rope System (MRS).



Prior to starting work, the arborist in the tree must always have two independent adjustable positioning devices.

One of the most effective options of getting into the tree is setting up ascent ropes from the ground. It is done by throwing a light bag carrying a thin rope over the required anchor point. The ascent system is then pulled by this light rope.





W0105BR
ARBO MASTER
tree care harness

RECOMMENDED GEAR

W9603RX
FLASH ACCESS
working helmet

RK804BX0R
LIFT
hand ascender

K0119EE00
BORA triplelock
light alloy HMS carabiner

K0122EE07
OXY triplelock
light alloy oval carabiner

L0460RV00
TILIA 11.5
static rope

K032SIR00
SIR
multipurpose device for rope acces

L9031YX10
THROW LINE
arboristic throwline

W1028BY00
TOOL HOLDER

W9500Y
TREEMOUSE
arboristic throwing bag

C0053RW
FIRS AID BAG
(without contents)

RK800EE00
PULLEY SMALL
durable and light weight pulley

C0001YY00
CARRY BAG
practical bag for a rope

W2608
TIMBER ACCESSORY CORD
with sewn eyes



W2001
OPEN SLING
sewn sling

W1024BX
FOOTER II
ascender webing

W2601R085
PRUSIK SLING
sewed accessory cord

W2603YB00
PULLEY SLING
prusik sling with a pulley

W2115
BARK PULLEY SAVER
cambium saver

W2117
ARBO SITE
work positioning

W2114
TREE ANCHOR
anchor device

W0108BR00
ARBO CHEST
padded chest harness

RK807BX0
FOOT LIFT
foot ascender



ROPES COURSES AND ADVENTURE PARKS

Rope parks are a combination of climbing and professional activities. It is a leisure-time activity mainly carried out by people who are gaining the experience with climbing. This activity combines working as well as sport equipment. The person (client) is ideally dressed in a full body harness, connected to the steel rope with two connectors and these are connected to the harness by a textile sling or lanyard. In addition, the client is equipped with a tandem pulley, which is connected to the harness by a sling or lanyard.



Zip Line At zip line the client first attaches a tandem pulley to the steel rope, behind the pulley, client attaches the first and second back up sling with the connector. The whole weight of a client is in the pulley. Back up slings move freely behind the pulley.



All the equipment used in the rope park must be checked every 12 months even if it is sports equipment.

Rope course elements are always divided by a platform, where client changes the connectors from a steel security rope to another one. The client always has to lock one security loop and the other security loop. It must never happen that both connectors are disconnected from the security steel rope at the same time. It is the same system as securing on via ferrata.



W0050
TARZAN
full body harness

RECOMMENDED GEAR

C0900
HEX
climbing helmet

K82008Z
SMALL CONNECTOR
with automatic locking

K82008Z
MAILLON SMALL OVAL
steel maillon carabiner



K0122EE07
OXY triplelock
light alloy oval carabiner

K4241Z005
OVAL STEEL CONNECTOR
triple lock

RK803BB00
TANDEM PULLEY

K9000BB03
PORTER
plastic holder

C0053RW
FIRS AID BAG
(without contents)

C0012YB
FALCONER FULL

W2200W100
LANYARD „I"

S9000YY35
GEAR BAG
waterproof bag

EVACUATION SET

K032SIR00
SIR
multipurpose device

RK713BB00
RIGGING PLATE 1/3
anchoring device

K4241Z005
OVAL STEEL CONNECTOR
srew

K0122EE07
OXY triplelock
light alloy oval carabiner

RK800EE00
PULLEY SMALL
durable and light weight pulley

RK801EE00
PULLEY EXTRA
durable and lightweight pulley

W1052XX00
RESCUE RATCHET

WIND TURBINES

Work at height for wind turbine operators includes the elements of a safe system of work, equipment selection and inspection, use of tools, risk assessment, method statements and emergency procedures. Evacuation and rescue using industry standard equipment are practiced at height.



rope descend





BASIC PULLEY SYSTEMS



W0079DR
EXPERT 3D speed
fully adjustable rope access harness

RECOMMENDED GEAR

W9603QX
FLASH ACCESS
working helmet

RK804BX0R
LIFT
hand ascender

W1010BB09
LOCKER
guided type fall arrester

RK805BX00
CAM CLEAN
Chest ascender

K0119EE00
BORA triplelock
light alloy HMS carabiner

K4080ZO
D STEEL CONNECTOR
srew

K032SIR00
SIR
multipurpose device for rope acces

RK801EE00
PULLEY EXTRA
durable and lightweight pulley

RK808OS00
EXTRA PLUS
large pulley

L0450RR
STATIC R44 11.0
150 m static rope

L045000
STATIC R44 11.0
150 m static rope

W8100B
ROPE PROTECTOR

W004*120
EYE SLING
sewn sling

W1024BX
FOOTER II
ascender webing

W2300W150
LANYARD „I"

W4462X085
REACTOR 140 ROPES „Y" 85 cm
shock absorber

ACCESSORIES

K9000BB03
PORTER
plastic holder

W0010YB
FRANKLIN

W0052B010
WORKING BAG

C0046BB
TARP DUFFLE

MILITARY AND SPECIAL FORCES

Complete range of black textile and metal (matt) products, including ropes and lanyards. Special ropes with unique features. Easy use of equipment in the cruelest conditions you can image. Handling in gloves, manipulation in a dark and quick releasing are obvious.





W0096BB
TACTIC MASTER

RECOMMENDED GEAR

X0033
FLASH INDUSTRY
work helmet

K0122BB06
OXY twist lock
light alloy
carabiner

RK804BX0R
LIFT
hand
ascender

K6180BB
RESCUE FIGURE EIGHT
special figure eight
for rescue

K6132BB
BUDDY
belay tube

W1010BB09
LOCKER
guided type fall
arrester

K032SIR00
SIR
multipurpose
device for rope
acces

L0230BB
STATIC 10,5
static rope

W004*120
EYE SLING
sewn sling

W8100B
ROPE
PROTECTOR

W0005BB09
LAIKA
dog harness

W1015B020
LOCKER SLING
certified sling
for the Locker

ACCESSORIES

K9000BB03
PORTER
plastic holder

S9000BB35
GEAR BAG
35 l

W1026BB
URNA
leg rope bag

C0088SB
BALACLAVA
PRO

CABLEWAY EVACUATION

Ski lift or gondola evacuations utilize specialized rescue techniques and gear that must perform regardless of weather conditions.
The success of evacuation operations begins with having the proper ski lift or gondola evacuation gear and proper training and practice of the operating personnel.
If the chair lift or gondola fails, the person in charge must evacuate passengers according to the evacuation plan. Evacuation of a ski lift requires pecific techniques for movement along a cable. For maximum efficiency, these operations are led simultaneously by several independent teams.
Evacuation is a team effort and requires perfect coordination by everyone involved. SINGING ROCK team cooperates with ski resorts all over Czech Republic to improve rescue methods and develop a new gear.





W0079DR
EXPERT 3D speed
fully adjustable rope access harness

RECOMMENDED GEAR

W9603QX
FLASH ACCESS
working helmet

K355OPP
CONNECTOR GIGA

K6180ZO
RESCUE FIGURE EIGHT
special figure eight for rescue

K0119EE00
BORA triplelock
light alloy HMS carabiner

K4241Z005
OVAL STEEL CONNECTOR
triple lock

K82310Z
MAILLON BIG D
steel maillon carabiner

K82008Z
MAILLON SMALL OVAL
steel maillon carabiner

L0250RR
Static 11.0
static rope

W4400WW00
REACTOR 140
shock absorber

W0003BY09
AXILLAR
rescue sling

W2001*060
OPEN SLING
sewn sling, 60 cm

RK809SO00
EASY LIFT
rescue pulley

W8201BY00
EVACUATION TRIANGLE SIT II

S9000YY35
GEAR BAG
waterproof bag

BELAYER

INDEX

PRODUCT NAME	PAGE
ACCESSORIES	187
ACCESSORIES	189
ACCESSORY CORD	50
ACCESSORY CORDS	53
ACCORD 8.3	47
ACCORD DRY 8.3	47
ADJUST	114
ALADIN	29
ANCHORING	170
ANTISHOCK I	17
APOLLO PANTS	143
APOLLO SHORTS	143
ARBO CHEST	29
ARBO MASTER	30
ARBO SITE	113
ATIKA ROPE PROTECTOR	50
AXILLAR	115
BABY RESCUE BAG	33
BACK-UP	89
BALACLAVA PRO	154
BANNER BAG	160
BANNERS	162
BARK PULLEY SAVER	112
BARK RING SAVER	113
BASEBALL HAT	152
BASEBALL HAT LIGHT	152
BASIC	21
BASIC LIGHT	21
BASIC PULLEY SYSTEMS	186
BEACH FLAG	162
BEANIE	153
BEANIE HAT	155
BEANIE POLAR	154
BEANIE PRO	153
BEER MAT	156
BELAYER	191
BELT	158
BIG CONNECTOR	63
BIG SQUARE	62
BIG TWIST	62
BODY II ENERGY SPEED	20
BODY II SPEED	19
BODY II STANDARD	19
BORA / SCREW, BORA / TWL	
BORA / TRIPLE LOCK	57
BORA GP / SCREW	57
BUDDY	86
CABLEWAY EVACUATION SYSTEM	126
CAM CLEAN	88
CANTILEVER ARM CONSOLE	104
CARRY BAG	131
CLASSIC ADAPTOR (PAIR)	78
COLT / SCREW	58
COLT SCREW 3PACK	58
CONDOM	161
CONNECTION STRAP	23
CONNECTOR GIGA	63
CONTRA 10.5	43
COVER	79
COW´S TAIL	49
CULTER	140
D – MOBILE	96
D STEEL / SCREW	63
D STEEL / TRIPLE LOCK	63
DEFENDER	51
DNA DRY 8.9	44
DOUBLE STOP PLUS	84
DRY BAG	131
DRY DUFFLE	131
DURAN 10.4	47
DYNAMIC ROPES	52
EASY LIFT	92
EDGE ROLLER	51
EDGE ROLLER – PART	51
ELECTRIC ARC VISOR	78
EVACUATION SET	185
EVACUATION TRIANGLE COMBI II	32
EVACUATION TRIANGLE SIT II	32
EXPERT 3D / SPEED	8
EXPERT 3D / SPEED STEEL	9
EXPERT 3D / STANDARD	9
EYE SLING	108
FALCONER 3/4	138
FALCONER FULL	138
FALCONER TACTICAL	138
FALL ARRESTER SET	124
FALL FACTOR	170
FAVORABLE COMBINATIONS	22
FIGURE 8 L	87
FIGURE 8 M	87
FINE LINE	115
FIRST AID BAG	136
FIRST AID BAG – LARGE	136
FIXING MATERIAL FOR GROUND AND WALL SLEEVE	103
FLASH	70
FLASH ACCESS	71
FLASH AERO	71
FLASH INDUSTRY	71
FLASH PADDING	81
FLAT WEBBING	114
FOOT LIFT	88
FOOTER II	118
FOOTER XP	119
FORGING	65
FRANKLIN	28
GEAR BAG	130
GEMINI DRY 7.9	48
GLUE IN ANCHOR	96
GRIPPY	139
GRIPPY 3/4	139
GROUND COFFEE OUTDOOR	157
GYM 10.1	46
HAMMER CORD	50
HARNESS PADDING	23
HECTOR / SCREW	56
HECTOR / TRIPLE LOCK	56
HECTOR BC / SCREW	
HECTOR BC / TRIPLE LOCK	56
HELMETS	77
HERO 9.6	45
HERO DRY 9.6	44
HEX	74
HEX PADDING	81
HOODY	148
HOODY FULL ZIP	148
HOOK PARKING LOOP	24
HOT	65
ICON 9.3	44
ICON DRY 9.3	44
IKAR AAS-1 CANTILEVER ARM	102
IKAR DB-A3 TRIPOD	105
IKAR GROUND SLEEVE	102
IKAR H	100
IKAR HRA	100
IKAR HRA TRIPOD CONSOLE	105
IKAR HWB	99
IKAR HWS	99
IKAR LOWER GROUND SLEEVE	103
IKAR LOWER GROUND SLEEVE CORE HOLE	103
IKAR MOBILE ATTICS BASE	104
IKAR MOBILE GROUND BASE	103
IKAR PLW WINCH	105
IKAR WALL SLEEVE	102
IKAR WINCH CANTILEVER ARM CONSOLE	104
IKAR WINCH TRIPOD CONSOLE	105
INDY EVO PLUS	85
JACOB	118
JACOB DYNEEMA	118
JINGLE II	111

JOULE 123
KATA 9.7 45
KATA DRY 9.7 45
KEY HOLDER 158
KEYLOCK 65
KIDS HOODY 149
KNOTS 171
LAIKA 32
LAMPFIX 80
LANYARD "I" 109
LANYARD "V" 109
LIFT 88
LOCKER 89
LOCKER SLING 89
MAILLON BIG D 62
MAILLON BIG DELTA 62
MAILLON MINI OVAL 62
MAILLON SMALL DELTA 62
MAILLON SMALL OVAL 62
MINI D 64
MINI D SCREW 64
MINI PEAR 64
MONTY BAG 132
MOVEMENT BAG 130
NOTEPAD A5 161
NUMBER 65
OPEN SLING 108
OPEN SLING 14 MM 108
OVAL STEEL / SCREW 63
OVAL STEEL / TRIPLE LOCK 63
OVERALL 141
OXY / SCREW, OXY / TWL, 59
OXY / TRIPLE LOCK 59
OXY BC / SCREW, OXY BC / TWL 59
OXY BC / TRIPLE LOCK 59
OZONE / SCREW, OZONE / 61
PALM CONNECTOR 63
PAPER BAG 160
PATRON 11.0 47
PATRON LANYARD 112
PENTA 72
PENTA 76
PENTA JUNIOR 73
PENTA PADDING 81
PILOT 93
PITCHER 156
POLE II 22
POLO T-SHIRT 145
POLYGON 166
PORTER 64
POSTERS 163
PPE INSPECTION SET 125
PRODUCTION
PROFI WORKER 3D / SPEED 11
PROFI WORKER 3D / STANDARD 12
PROTECTIVE CASE 132
PROTECTIVE SLEEVE FOR SRL 100
PRUSIK SLING 110
PULLER 89
PULLEY EXTRA 90
PULLEY EXTRA PLUS 90
PULLEY MIKY 91
PULLEY SLING 110
PULLEY SMALL 91
PULLEY TWIN 90
RAMA 85
RAMA SET 85
REACTOR 140 120
REDBLOCK 94
REFLECT VEST 24
RESCUE BAG 132
RESCUE FIGURE EIGHT 87
RESCUE KNIFE 140
RESCUE POLE 137
RESCUE RATCHET 115
RESCUE SET 127
RETRACTABLE TYPE FALL ARRESTERS: 99
RIGGING PLATE 1/3 92
RIGGING PLATE 3/5 92
RING 93
RING SLING 111
RINGO 93
RL CHEST 29
ROCK &LOCK 6
ROCKLIFE T-SHIRT LONG SLEEVE 146
ROOF MASTER 14
ROOFER SET 124
ROOFER SET 175
ROPE BAG 133
ROPE PROTECTOR 51
ROPEDANCER II 18
ROPEMARKER 49
ROUTE 44 40
SAFE 2 FLEX CARRIER 78
SAFE NYLON MESH VISOR 78
SAFE PC
SAFE STEEL MESH VISOR 78
SCAFFOLDER SET 125
SCAFFOLDER SET 173
SCARF 155
SCORE 10.1 46
SCORE DRY 10.1 46
SEAMASTER 3D STAINLESS STEEL 16
SECURE EARMUFFS 79
SHUTTLE 86
SINGING ROCK PEN 161
SINGING ROCK STICKERS 162
SIR 84
SIT WORKER 3D / SPEED 26
SIT WORKER 3D / SPEED STEEL 27
SIT WORKER 3D / STANDARD 26
SITE 94
SITE LANYARD 95
SLING LANYARD 109
SMALL CONNECTOR 62
SNAKE BRACE 97
SNAPBACK HAT 152
SPEED BELT 158
SPELEO 43
SPELEO R44 10.5 43
SPELEO ROPES 53
STAINLESS HANGER PLATE / WITH BOLT 96
STATIC 10.5 41
STATIC 11.0 41
STATIC 9.0 42
STATIC R44 10.5 40
STATIC R44 11.0 40
STATIC R44 NFPA 10.5 42
STATIC R44 NFPA 11.0 (7/16") 42
STATIC R44 NFPA 13.0 (1/2") 42
STATIC ROPES 52
STEEL ANCHOR 117
STEEL LANYARD "I" 117
STITCHED EYE 40
STORM 9.8 46
STORM DRY 9.8 45
STRAP FOR CAM CLEAN 88
SUSPENSION TRAUMA SAFETY STRAP 24
TACTIC MASTER 15
TANDEM PULLEY 91
TARP DUFFLE 130
TARZAN 17
TARZAN ECONOMIC 18
TECH INFO EN 163
TECHNIC 13
TECHNIC ANSI 13
TECHNIC PADDING 23
TECHNOLOGY 65
TEXTILE BADGE 160
THERMOCUTTER 49
THROW LINE 50
TILIA 11.5 43
TIMBER ACCESSORY CORD 110
TOOL BAG 134
TOOL HOLDER 119
TOOL HOLDER MAX 119
TOOLKIT 134
TRACK PLUS 114
TRAVEL MUG 157
TREE ANCHOR 113
TREEMOUSE 137
TRIPOD BAG 133

TRUCKER HAT	152
T-SHIRT ACTIVE LONG SLEEVE	147
T-SHIRT BACKBONE	144
T-SHIRT COOL	147
T-SHIRT MONKEY	149
T-SHIRT ROCKET	144
T-SHIRTS BLUE MOUNTAIN	145
TUBULAR WEBBING	114
TWISTER	94
TWL, OZONE / TRIPLE LOCK	61
ULTRASONIC	40
UNIQUE	
URBAN II	27
URNA	133
USB FLASH DRIVE	159
VERTICAL FIXED BEAM CLAMP	97
WHOLE BEAN COFFEE CAN	156
WORK KNIFE	140
WORKING BAG	134
WORKING PANTS	141
WRISTBAND	160
XSTREAM LD	80
ZINC PLATED HANGER PLATE / WITH BOLT	96

Descending on a wheel chair from Žižkov tower, Prague Photo: Artsiom Hasiankou

Descending on a wheel chair from Žižkov tower, Prague Photo: Artsiom Hasiankou

INDEX

PRODUCT NUMBER	PAGE
A4072YX03	100
A4072YX04	100
RK801BB00	90
A0002SS01	96
A0031BS	140
A003OY	140
A0050HH00	140
A4000S060	99
A4000S090	99
A4000S120	99
A4000S240	99
A4000W018	99
A4000W028	99
A4000W035	99
A4002BS33	100
A4002BS42	100
A4004BS12	100
A4004BS18	100
A4004BS33	100
A4064XX30	105
A4070XX00	133
A4072YX	100
A4072YX02	100
C0001BB	133
C0001YY00	131
C0006BH	139
C0006HH	139
C0012YB	138
C0013YB	138
C0014YB	138
C0035AO12	114
C0037BB12	114
C0037RR12	114
C0046B120	130
C0046BB70	130
C0046BB90	130
C0051BH	152
C0051HH	152
C0053AX	153
C0053OX	153
C0053RW	136
C0053RX	153
C0054BX	153
C0055BX	153
C0058RR00	136
C0067BS00	155
C0069BG00	155
C0069PB00	155
C0070SL00	152
C0071AA00	76
C0071RR00	76
C0071SS00	76
C0071WW00	76
C0073BY00	130
C0074BY00	152
C0079BX00	155
C0080BX00	155
C0081AX00	155
C0081RX00	155
C0087SB	153
C0088SB	154
C0089SX00	152
C0090BB00	154
C0091	72
C0091FX02	72
C0091FX03	72
C0091FX05	72
C0091GX02	72
C0091GX03	72
C0091GX05	72
C0091JY02	73
C0091SX02	72
C0091SX03	72
C0091SX05	72
C0091YX02	72
C0091YX03	72
C0091YX05	72
C0092XX	81
C0900AX03	74
C0900AX04	74
C0900MX03	74
C0900MX04	74
C0900RX03	74
C0900RX04	74
C0900WX03	74
C0900WX04	74
C0900YX03	74
C0900YX04	74
C0901SB	81
C1013BB	144
C1014BB	144
C1018BY	148
C1019BY	148
C1020BY	148
C1028VX	144
C1029VX	144
C1030Y	149
C1031M	149
C1032MM	145
C1033MM	145
C1034SS0	143
C1035SS0	143
C1036VX	146
C1037AX	146
C2150BY	118
C2151BY00	118
C5056	29
C9091XX	158
C9092BX	158
C9092XX	158
E0015XX	49
K0006RP00	94
K0016AA00	61
K0016BB00	61
K0017AA00	61
K0017BB00	61
K0018AA00	61
K0018BB00	61
K0027BY00	64
K0030OG00	94
K0043OX00	85
K0043SX00	85
K0050OS01	51
K0050OS03	51
K0101BX00	85
K0107BB00	57
K0107BP00	57
K0107EE00	57
K0107EP00	57
K0108BB00	57
K0108EE00	57
K0112BB00	58
K0112EE00	58
K0112XX30	58
K0114BB00	56
K0114BC00	56
K0114EC00	56
K0114EE00	56
K0119BB00	57
K0119EE00	57
K0121BB00	56
K0121BC00	56
K0121EC00	56
K0121EE00	56
K0122BB05	59
K0122BB06	59
K0122BB07	59
K0122EE05	59
K0122EE06	59
K0122EE07	59
K0123BC05	59
K0123BC06	59
K0123BC07	59
K0123EC05	59
K0123EC06	59
K0123EC07	59
K0124ST09	63
K0124SY09	63
K031DSD00	84
K032SIR00	84
K04000BB	89
K3536PP00	63
K3550PP00	63
K3690ZO	62
K3702PP	62
K4080ZO	63
K4081ZO	63
K4241ZO05	63
K4241ZO07	63
K5052EE00	64
K5182EE00	64

K6021BB	87
K6021EE	87
K6031BB	87
K6031EE	87
K6132BB	86
K6132EE	86
K6140BB00	86
K6140EE00	86
K6180BB	87
K7002BX46	93
K82006Z	62
K82008Z	62
K82207Z	62
K82210Z	62
K82310Z	62
K82410Z	62
K82508Z	62
K9000BB03	64
L0002	50
L0003	50
L0041 – L0081	50
L0220BB	42
L0220WR	42
L0230BB	41
L0230KK	41
L0230RR	41
L0230WR	41
L0240WR	43
L0250BB	41
L0250RR	41
L0250WR	41
L026	43
L0340AX	47
L0360GG	46
L0364LA00	46
L0380YX	44
L0384RX	44
L0430BB	40
L0430KK	40
L0430RR	40
L0430WR	40
L0440WR	43
L0450BB	40
L0450OO	40
L0450RR	40
L0450WG	40
L0460OV00	43
L0468O	43
L0510	47
L0514	47
L0520GW	45
L0524GW	44
L0540B450	49
L0540BB00	47
L0540C450	49
L0540YX	47
L057AA	45
L0580AA	45
L3020	48
L3040GA00	46
L3044AG00	45
L3050RY00	46
L3060CX	44
L9031YX10	50
L9991WB	125
M0000XSET	125
M0020X1	124
M0020X2	124
M0021XX	125
M0022XX	124
M0030X030	127
M0030X050	127
M0030X100	127
M0201XX00	85
MK006	126
P0010X030	156
P0010X050	156
P0019XX00	159
P0020	162
P0020BB02	162
P0020BB03	162
P0020BB04	162
P0020BB05	162
P0021	162
P0021BB00	162
P0021BB03	162
P0021BB04	162
P0021BB05	162
P0022XX00	161
P0023XX00	161
P0024XX00	160
P0025XX00	162
P0027WX00	163
P0027WX00	163
P0028WE00	163
P0030XX00	161
P0031XX01	160
P0031XX02	160
P0033XX00	160
P0033XX02	160
P0038GB10	157
P0038W150	156
P0047XX01	156
P0047XX02	156
P0048X400	157
P0054XX00	160
P99100X	158
R0430BB	42
R0430KK	42
R0430RR	42
R0430WR	42
R0450BB	42
R0450OO	42
R0450RR	42
R0450WG	42
R0460WB	42
RK400BB	93
RK702XX10	96
RK702XX12	96
RK703XX10	96
RK704XX10	96
RK704XX12	96
RK713BB00	92
RK714BB00	92
RK715XX10	96
RK715XX12	96
RK716XX10	96
RK716XX12	96
RK800BB00	91
RK800EE00	91
RK801EE00	90
RK802BB00	90
RK802EE00	90
RK803BB00	91
RK804BX0L	88
RK804BX0R	88
RK805BX00	88
RK806BB00	91
RK807BX0L	88
RK807BX0P	88
RK808BB00	90
RK808OS00	90
RK809SO00	92
RK850X100	117
RK850X130	117
RK850X180	117
RK851XX03	117
RK851XX05	117
RK900PP00	50
S1100BY	89
S9000BB35	130
S9000BB50	130
S9000RR35	130
S9000RR50	130
S9000YY35	130
S9000YY50	130
S9001BX60	131
S9001YX40	131
S9003YB60	131
S9003YY40	131
W0003BY09	115
W0005BB09	32
W0005YBO9	32
W0008BS	134
W0010BB	28
W0010YB	28
W0022BB	27
W0050	17
W0052B010	134
W0052B012	134
W0059BR	18
W0063BB	13
W0064BB	13
W0068BB	19
W0068BR	19
W0071BB	19
W0071BY	19
W0073	22
W0074DR	16
W0075DB	26
W0075DR	26
W0076DB	26
W0076DR	26

W0077DR 27
W0078DB 9
W0078DR 9
W0079DB 8
W0079DR 8
W0080DR 9
W0081DB 12
W0081DR 12
W0082DB 11
W0082DR 11
W0085BB00 88
W0086B0 17
W0087BY 18
W0089SY 21
W0090SY 21
W0091BY 14
W0092BB 23
W0093SY 20
W0096BB 15
W0097BB00 23
W0102YB00 24
W0103BB 13
W0104BB 13
W0105BR 30
W0108BR00 29
W0109RX00 30
W0110RX00 30
W0200BB 29
W1001WW10 115
W1001WW15 115
W1001WW20 115
W1002WO20 115
W1002WS10 115
W1002WY15 115
W1010BB09 89
W1011WB02 94
W1011WB04 94
W1012WB02 94
W1012WB04 94
W1015B020 89
W1023 125
W1023 132
W1024BX 118
W1025BX 118
W1026BB 133
W1027B 51
W1028BY00 119
W1029BX00 24
W1036W130 114
W1040R 111
W1041R 111
W1042R 111
W1047Y100 114
W1051BX 119
W1052XX00 115
W1054BR00 119
W2001*060 108
W2001*080 108
W2001*120 108
W2001*150 108
W2004*060 108
W2004*080 108
W2004*120 108
W2004*150 108
W2005 108
W2005A080 108
W2005B060 108
W2005B080 108
W2005B120 108
W2005B150 108
W2005R120 108
W2005W150 108
W2005Y060 108
W2016*060 109
W2016*080 109
W2016*120 109
W2016*150 109
W2018A060 97
W2018Y030 97
W2020X080 23
W2111Y 112
W2112Y 112
W2113Y 112
W2114 113
W2115 112
W2116 113
W2117 113
W2200*001 109
W2200*002 109
W2200*100 109
W2300*060 109
W2300*080 109
W2300*120 109
W2300*150 109
W2301*060 109
W2301*080 109
W2301*120 109
W2301*150 109
W2303*060 109
W2303*080 109
W2303*120 109
W2303*150 109
W2601R085 110
W2602Y085 110
W2603YB00 110
W2604RR00 111
W2608 110
W2610 110
W4100Y070 123
W4100Y120 123
W4100Y160 123
W4400WW00 120
W4410W085 121
W4410W155 121
W4411W085 121
W4411W155 121
W4412W085 121
W4412W155 121
W4413W085 121
W4413W155 121
W4420W085 121
W4420W155 121
W4421W085 121
W4421W155 121
W4422W085 121
W4422W155 121
W4423W085 121
W4423W155 121
W4430W155 121
W4433W155 121
W4440W155 121
W4441W155 121
W4442W155 121
W4450X085 121
W4450X155 121
W4452X085 121
W4452X155 121
W4453X085 121
W4453X155 121
W4460X085 121
W4460X155 121
W4462X085 121
W4462X155 121
W4463X085 121
W4463X155 121
W4470Y100 121
W4471Y100 121
W4472Y100 121
W4474Y100 121
W4480X085 121
W4480X155 121
W4482X085 121
W4482X155 121
W4483X085 121
W4483X155 121
W4484X085 121
W4484X155 121
W4490W155 121
W4492W155 121
W4493W155 121
W4494W155 121
W8000BX00 137
W8100B 51
W8201BY00 32
W8211BY00 32
W8220 33
W9002XX17 132
W9002XX46 132
W9003RX45 132
W9004YX00 134
W9500Y 137
W9601BB00 71
W9601QX00 71
W9601RX00 71
W9601WX00 71
W9601YX00 71
W9602QX00 71
W9602RX00 71
W9603QX00 71
W9603RX00 71
W9604BX00 81
W9605XX00 79
W9606SX00 80

W9801BY	141
W9802BY	145
W9803BY	141
W9804YX	24
W9805BX	147
W9806BX	147
X0004GB	49
X0004GB00	125
X0013XX02	125
X0014XX00	125
X0015XX00	125
X0016XX00	125
X0017XX00	125
X0018XX00	125
X0020XX00	125
X0021XX11	125
X0022XX11	125
X0023X200	125
X0048XX25	79
X0048XX29	79
X0048XX31	79
X0049XX00	78
X0050XX00	78
X0051XX00	78
X0052XX00	78
X0053XX00	78
X0062XX00	80
X0070XX34	93
X0077XX00	97
X4002XX00	105
X4003XX00	105
X4005XX00	102
X4006XX00	102
X4007XX00	102
X4008XX00	103
X4009XX00	103
X4010XX00	103
X4011XX00	103
X4012XX00	104
X4013XX00	104
X4014XX00	104
X4015XX00	104

Tree climbing, Česky nad Jizerou, Czech Republic. Photo: Ondřej Vilko

Rock&Lock

Patented smart buckle used on SINGING ROCK harnesses and other products enables to lock and open very quickly.

Lady fit

Specially designed products for women.

Route 44

SINGING ROCK patented technology for rope production. A rope is produced on 44 carrier machine which provides great handling, low weight and durability.

Inter Core

The unique patented technology providing maximum safety even in case of a damaged sheath. The rope is made from 4 layers of parallel core filaments, braided core, braided intermediate sheath made from staple fibres and single tech sheath.

Single Tech

With the Single Tech system each strand is braided into the sheath separately. Single Tech sheath construction increases the rope's wear resistance and improves the rope's mechanical properties, such as flexibility.

Single rope

Marking of single dynamic rope for climbing and mountaineering used in single strand.

Half rope

Marking of half rope for mountaineering, multipitch and ice climbing. Individual strands of rope are used in alternation in the protection system. This system reduces the risk of rope breakage caused by falling stones, and provides maximum safety in alpine conditions and for difficult climbs.

Twin rope

Marking of twin ropes for mountaineering, multipitch and ice climbing. Pairs of the same type of rope are always used, sharing the same protection points. Twin ropes guarantee a high level of safety, especially for multipitch climbing in alpine conditions.

Stitched eye

sewn loop at the end of kernmentle low stretch rope used as a subsitute of a knot. Used mainly to attach ropes to anchor or attachment points.

UIAA

Products marked with this symbol meet strict UIAA safety requirements. The UIAA is the International Mountaineering and Climbing Federation. In most cases, UIAA requirements are sometimes stricter than EN standards.

UIAA Water repelent

A standard for water repellent ropes approved by the UIAA Safety Commission. To pass the test at a certified laboratory, the amount of absorbed water must not be greater than 5% of the rope's weight. For comparison, a non-treated rope absorbs around 50% of water in this test, and ropes labelled as „dry" but lacking adequate treatments can absorb between 20% and 40% of water.

Symbol of compliance

The CE symbol declares that the product is in compliance with the safety requirements of the applicable European standard. The number after the symbol CE (e.g. CE 1019) identifies the relevant accredited testing lab.

ANSI

American National Standards Institute – is a private non-profit organization that oversees the development of voluntary consensus standards for products, services, processes, systems, and personnel in the United States.[3] The organization also coordinates U. S. standards with international standards so that American products can be used worldwide.

NFPA

The National Fire Protection Association is a US nonprofit organization devoted to eliminating death, injury, property and economic loss due to fire, electrical and related hazards. It is widely known as an organization that creates and maintains standards and codes for usage and adoption by local governments.

ABS	Acrylonitrile butadiene styrene is a common thermoplastic polymer. The most important mechanical properties of ABS are impact resistance and toughness. ABS is stronger than pure polystyrene.
Acryl	Lightweight, soft, and warm, with a wool-like feel fabrics or yarn. Strong and warm, acrylic fiber is often used for sweaters and tracksuits and as linings for boots and gloves, as well as in furnishing fabrics and carpets. It is manufactured as a filament, then cut into short staple lengths similar to wool hairs, and spun into yarn.
Anodizing	Electrolytic passivation process used to increase the thickness of the natural oxide layer on the surface of metal parts. Anodizing increases resistance to corrosion and wear, and provides better adhesion for paint primers and glues than bare metal does.
Bamboo	Cloth, yarn, and clothing made out of bamboo fibres. Bamboo fabric is exceptionally soft and light. It is also incredibly hydrophilic, absorbing more water than other conventional fibres such as cotton and polyester.
Cold forging	Deformation of metal while it is below its recrystallization point. This process is usually less expensive than hot forging and the end product requires little, if any, finishing work. Residual stress of material may occur as it handles high stress and high die loads
Cordura	Brand name for a collection of fabrics used in a wide array of products including luggage, backpacks, trousers, military wear and performance apparel. Cordura fabrics are known for their durability and resistance to abrasions, tears and scuffs. Cordura fabrics are usually made of nylon.
Cortex	Polyamide ealstic woven fabrics. Cortex fabrics are designed to ensure the maximum ergonomy and comfort.
Dyneema	Registered trademark for a synthetic fabric that is stronger than Kevlar®. Dyneema® is composed of ultra high molecular weight polyethylene. It is resistant to water, most chemicals, UV radiation and bacterial.
ED coating	Electrophoretic deposition coating. A characteristic feature of this process is that colloidal particles suspended in a liquid medium migrate under the influence of an electric field (electrophoresis) and are deposited onto an electrode.
Elastane (Spandex)	Synthetic polyether-polyurea copolymer known for its exceptional elasticity. It is stronger and more durable than natural rubber.
EPS	Expanded polystyrene is a rigid and tough, closed-cell foam. It is made of pre-expanded polystyrene beads. Due to its technical properties such as low weight, rigidity, and formability, EPS can be used in a wide range of different applications.
Fiber glass	Type of fiber-reinforced plastic where the reinforcement fiber is specifically glass fiber. The glass fiber may be randomly arranged, flattened into a sheet (called a chopped strand mat), or woven into a fabric. Fiberglass is unique in its strength and yet it is lightweight. Although it is not as strong and stiff as composites based on carbon fiber, it is less brittle, and its raw materials are much cheaper.
Fleece	Soft napped insulating fabric made from a type of polyester called polyethylene terephthalate (PET) or other synthetic fibers. A lightweight, warm, soft and hydrofobic fabric. Regular polar fleece is not wind-proof and does not absorb moisture. It is readily generates static electricity.
G10 fiber	High-pressure fiberglass laminate, a kind of composite material. It is created by stacking multiple layers of glass cloth, soaking in epoxy resin, and compressing the resulting material under heat until the epoxy cures. G10 is favoured for its high strength, low moisture absorption, excellent electrical insulating properties and chemical resistance.
HF welding	Joining of materials by supplying High Frequency energy in the form of an electromagnetic field (27.12 MHz) and pressure to the material surfaces to be joined.
Hot forging	Deformation of metal while it is above the recrystallization point. Hot forging is recommended for the deformation of metal that features a high formability ratio. Hot forging provides a homorgenized grain structure
Injection	Manufacturing process for producing parts by injecting material into a mould. Material for the part is fed into a heated barrel, mixed, and forced into a mould cavity, where it cools and hardens to the configuration of the cavity.
Kernmantle rope	Rope constructed with its interior core protected by a woven exterior sheath designed to optimize strength, durability, and flexibility. The core fibers provide the tensile strength of the rope, while the sheath protects the core from abrasion during use.
Kevlar	Kevlar is the registered trademark for a para-aramid synthetic fiber. Kevlar has many applications, ranging from bicycle tires and racing sails to body armor, because of its high tensile strength-to-weight ratio; by this measure it is 5 times stronger than steel. It is designed to protect users from cuts, abrasions and heat. Kevlar-based protective gear is often considerably lighter and thinner than equivalent gear made of more traditional materials.
Nylon	Generic designation for a family of synthetic polymers, based on aliphatic or semi-aromatic polyamides. Nylon is a thermoplastic silky material that can be melt-processed into fibers, films or shapes. Nylon is very much suitable for hosiery and the knitted fabrics because of its smoothness, light weight and high strength.
Polyamide (PA, PAD)	Macromolecule with repeating units linked by amide bonds. Synthetic polyamides are commonly used in textiles, automotive applications, carpets and sportswear due to their high durability and strength. Fibres are very tear-proof and abrasion-resistant and absorb little moisture (thus good transport of moisture away from the body) and are stretchy, crease-free, but also prone to pilling. Polyamide has the highest resistance of all textile raw materials (also when wet) and is very stretchy.
Polycarbonate	Group of thermoplastic polymers containing carbonate groups in their chemical structures. Polycarbonates used in engineering are strong, tough materials, and some grades are optically transparent.
Polyester (PES)	Category of polymers that contain the ester functional group in their main chain. Fabrics woven or knitted from polyester thread or yarn are used extensively in apparel and home furnishings. Industrial polyester fibers, yarns and ropes are used in car tire reinforcements, fabrics for conveyor belts, safety belts, coated fabrics and plastic reinforcements with high-energy absorption. Polyester has excellent return conduct thanks to the rippling property and is very light. Polyester also retains its shape and is colourfast, as well as resistant to sweat and UV-rays (lightfast). Polyester has a high melting point and transfers can therefore be printed on this material)
Polyethylene (PE)	Most common plastic, which is usually a mixture of similar polymers of ethylene. Polyethylene is of low strength, hardness and rigidity, but has a high ductility and impact strength as well as low friction. It shows strong creep under persistent force, which can be reduced by addition of short fibers. Its primary use is in packaging (plastic bags, plastic films, geomembranes, containers including bottles, etc.)
POLYMAR	Registered trademark for a polyester coated with polyurethane tarpaulin fabric. It is UV and weatherproof resistant.
Polypropylene (PP)	Thermoplastic polymer used in a wide variety of applications including packaging and labeling, textiles (e.g., ropes, thermal underwear and carpets), stationery, plastic parts and reusable containers of various types, laboratory equipment, loudspeakers, automotive components and polymer banknotes. An addition polymer made from the monomer propylene, it is rugged and unusually resistant to many chemical solvents, bases and acids. Polypropylene is the world's second-most widely produced synthetic plastic, after polyethylene.
Polystyrene	Synthetic aromatic polymer made from the monomer styrene. Polystyrene can be solid or foamed. General-purpose polystyrene is clear, hard, and rather brittle. Polystyrene is one of the most widely used plastics. Uses include protective packaging (such as packing peanuts and CD and DVD cases), containers (such as "clamshells"), lids, bottles, trays, tumblers, and disposable cutlery.
Polyvinyl chloride (PVC)	World's third-most widely produced synthetic plastic polymer, after polyethylene and polypropylene. PVC comes in two basic forms: rigid and flexible. The rigid form of PVC is used in construction for pipe and in profile applications such as doors and windows. It is also used for bottles, other non-food packaging, and cards (such as bank or membership cards). In flexible form, it is used in plumbing, electrical cable insulation, imitation leather, signage, phonograph records, inflatable products, and many applications where it replaces rubber.
Polyurethane (PU)	Polymer composed of organic units joined by carbamate (urethane) links. While most polyurethanes are thermosetting polymers that do not melt when heated, thermoplastic polyurethanes are also available.
Ripstop	Woven fabrics, using a special reinforcing technique that makes them resistant to tearing and ripping. During weaving, (thick) reinforcement threads are interwoven at regular intervals in a crosshatch pattern. Advantages of ripstop are the favourable strength-to-weight ratio and that small tears can not easily spread.
Stainless Steel	Steel alloy with a minimum of 10.5% chromium content by mass. Stainless steel is notable for its corrosion resistance. Stainless steel does not readily corrode, rust or stain with water as ordinary steel does. However, it is not fully stain-proof in low-oxygen, high-salinity, or poor air-circulation environments.
Teflon	Registered trademark for a synthetic fluoropolymer of tetrafluoroethylene. It is famous for its hydrophobic and abrasive protection properties.
Technora	Registered trademark for an aramid that is useful for a variety of applications that require high strength or chemical resistance. It is closely related to Kevlar (see Kevlar).
Thermolite	Synthetic material made by Invista and used as an insulator. The performance fibers are engineered with a differentiated fiber shape, able to produce battings with sought-after lightweight warmth.
Thermotransfer	Digital printing process in which material is applied to paper (or some other material) by melting a coating of ribbon so that it stays glued to the material on which the print is applied.
Ultrasonic finishing	Sound waves with frequencies higher than the upper audible limit of human hearing is joining the load-bearing core and the protective sheath into a compact unit. It is used to finish kernmantle ropes ends.
Velcro	Registered trademark for a hook-and-loop fastener, which consists of two components: typically, two lineal fabric strips (or, alternatively, round "dots" or squares) which are attached (sewn or otherwise adhered) to the opposing surfaces to be fastened.
Zinc plating	Prevents oxidation of the protected metal by forming a barrier and by acting as a sacrificial anode if this barrier is damaged.

STANDARDS The list of EN and US standards for persona protective equipment (PPE) against falls from a height

EN 341
PPE against falls from height. Descender devices for rescue.

EN 353–1, 2
PPE against falls from a height. Guided type fall arresters.

EN 354
PPE against falls from a height. Connecting equipment max. length 2 m (incl. connectors).

EN 355
PPE against falls from a height. Energy absorbers.

EN 358
PPE for work positoning and prevention of falls from a height. Work positioning systems.

EN 360
PPE against falls from a height. Retractable type fall arresters.

EN 361
PPE against falls from a height. Full body harnesses.

EN 362
PPE against falls from a height. Connectors.

EN 388
Protection gloves against mechanical risks

EN 397
PPE against falls from a height. Industrial safety helmets.

EN 564
Mountaineering equipment – Accessory cords

EN 566
Mountaineering equipment – Slings

EN 567
Mountaineering equipment. Rope clamps.

EN 795, EN 795/A1
PPE against falls from a height. Anchor devices.

EN 813
PPE against falls from a height. Sit harnesses.

EN 892
Mountaineering equipment. Dynamic (strech) ropes.

EN 959
Mountaineering equipment – Rock anchors

EN 1496
Rescue equipment. Rescue lifting devices.

EN 1497
Rescue equipment. Rescue harnesses.

EN 1498
Personal fall protection equipment – Rescue loops

EN 1808
Safety requirements for suspended access equipment

EN 1891
PPE against falls from a height. Low stretch kernmantel ropes.

EN 12275
Mountaineering equipment – Connectors

EN 12277
Mountaineering equipment – Harnesses

EN 12278
Mountaineering equipment. Pulleys.

EN 12492
Mountaineering equipment – Helmets for mountaineers

EN 12841
PPE against falls from a height. Descender device for rope access system and rope adjustment devices.

EN 15151
Mountaineering equipment – Braking devices

ANSI Z359.1
Safety Requirements for Personal Fall Arrest Systems, Subsystems and Components

CEN/TS 16415
Recommendations for anchor devices for use by more than one person simultaneously

NFPA Class II
defined by NFPA 1983 as being designed to fit around the waist and thighs or under the buttocks and may be utilized for a maximum of a two–person load

NFPA Class III
defined by NFPA 1983 as being designed to fit around the waist and thighs or under the buttocks and over both shoulders, rated for as maximum of a two–person load and is designed to prevent inverting



SINGING ROCK was founded in 1992. During its existence, Singing Rock has established itself as a pro-fessional and innovative producer and supplier of personal fall protective equipment. Nowadays SINGING ROCK is one of the world leaders on the market of professional protective equipment for work at height, military and rescue. The range of equipment available includes harnesses, ropes, hardware, rappeling devices, safety equipment for heights, anchor points, life lines and sets for typical work situations. All of the high-performance and innovative products are developed and produced in Czech Republic, Europe. The products are certifi ed and fully comply with the international industrial safety standards. Our products are innovative, modern and easy to use, with great strength and with maximum comfort... SINGING ROCK specializes in its production on: • Development and production of climbing and mountaineering equipment (harnesses, mountaineering ropes, belay and rappel devices carabiners, helmepts, ice axes, crampons etc.) • Development and production of professional equipment for working in height (harnesses, ropes, connectors, anchor devices, helmets, lanyards and fall absorbers) • Methodology and preparation of rope access and secure anchor systems • Supply or development of suitable safety equipment • Training services • Follow-up service – regular product inspection All activities at Singing Rock run under QMS certifi cation according to ISO 9001 standards with special attention to development, production and sales of Personal Fall Protective Equipment. (Article 11B of Council Directive 89/686/EEC). SINGING ROCK products fulfi l appropriate EU directives and standards and requirements of US market (CE, NFPA and ANSI). Singing Rock actively participates in preparation of these standards and directives by its work in the UIAA Safety Commission and CEN working group. SINGING ROCK also cooperates with Czech Standard Organization as an expert in the fi eld of standards for personal protective equipment. SINGING ROCK simply has everything what you need for your Personal Protective Equipment to prevent falling (PPE) and for permanent fall protection.

www.singingrock.com

Warning:

Activities at height such as climbing, via ferrata, caving, rappelling, ski-touring, rescue, work at height and exploration are dangerous activities, which may lead to severe injury or even death. Thus the following is essential before use: careful reading and understanding of the instructions for use acquaintance with the possibilities and limitations of the product adequate apprenticeship in appropriate techniques and methods of use understanding and acceptance of the risk involved. In case of doubt or problem of understanding, contact SINGING ROCK.

Address:

Singing Rock
Poniklá 317
512 42 Poniklá
Czech Republic

Contact:

tel.: +420 481 585 007
e-mail: info@singingrock.com
www.singingrock.com

Social:

singingrock.page
singingrock_official
user/sigrvideo

Catalogue PROFESSIONAL SINGING ROCK 2023/24 – PPE equipment
Published by: SINGING ROCK s.r.o. • Copyright © SINGING ROCK s.r.o.

All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of the publisher, except in the case of brief quotations embodied in critical reviews and certain other noncommercial uses permitted by copyright law. Technical specifications may change without notice.

safety FIRST