





CLIMBING

CATALOGUE 2021 |  EN

SINGING ROCK was founded in 1992. During 29 years of its existence, Singing Rock has established itself as a professional and innovative producer and supplier of climbing equipment. Nowadays SINGING ROCK is one of the world leaders on the market of climbing equipment for all activities in a vertical world. Most of the high-performance and innovative products are developed and produced in Czech Republic, Europe. All products are certified and fully comply with the international industrial safety standards. Our products are innovative, modern and easy to use, with great strength and with maximum comfort.



- Parallel core
- Braided core
- Braided intermediate sheath made from staple fibres
- Single tech sheath



INNOVATION

It is not necessary to talk too much about the innovation as it is inherently present in all our products.

TESTING

Meeting minimum requirements is obvious – but we go further by performing tests to simulate all kind of usage as the basis for further development.

TECHNOLOGY

Appropriate technology and tools are essential to produce first-class products.



KNOWLEDGE & EXPERIENCE

Our products and techniques are thoroughly validated not only in our testing centers. But also by our supported athletes and UIAGM mountain guides.

INVOLVEMENT

We are climbers and we love climbing. Enthusiasm drives our innovations and improvements.

PERFORMANCE

Do your climbing efficiently, safely and comfortably – we are here to give you the tools to do this. Enjoy your climb!



TRADITION & STABILITY

We draw on 28 years of our own experience and we are proudly inspired by vast knowledge and experience of climbers from our region.

EFFICIENCY

We run lean management system with horizontal organization structure. Thanks to this we are able to react immediately and customize our products and services for your specific needs.

ENVIRONMENT

We bear the responsibility to keep our planet green and to preserve its riches for our kids. SINGING ROCK is member of the European Outdoor Conservation Association.

SINGING ROCK CLIMBING TEAM 2020

Despite the fact that a year 2020 was unusual and really specific, our athletes did some nice projects and achievements. It is important to mention that they always followed the rules and regulations of the pandemic situation in their country and did what they love the most – to climb as they used to be before the pandemic. Here are some of our athletes and their best climbs during 2020. Also other our athletes as Koen Baekelandt, Daria Brylova, Adam Karpierz, Lucie Hrozová and others climbed as much as they could and climbed nice routes.

FELIPE CAMAGRO

First ascents in Brazil, Logan 9a (14d) and Aquaman 8c+ (14c)

After staying isolated in his apartment in São Paulo for 43 days, Felipe rented at airbnb in a farm down south in Brasil close to a great sector with a few projects! He took the necessary precautions for the drive and stayed isolated in the farm and only started climbing after a few days without showing any symptoms. Climbing, surfing and other outdoor sports were allowed in this state down south!

After couple of days he was able to do the first ascent of "Logan" and "Aquaman". Logan is a super powerful route that starts with a v11 boulder right off the ground, followed by a long v10 and then the crux a super reachy v11 (may be easier for taller people)! "Its always hard to grade a first ascent but I think it is either real hard 8c+ or 9a!" Later Felipe graded this route 9a (14d) as a first Brazilian 9a.

"Aquaman" is the route with basically two v11s with no rest. One is a beautiful compression style boulder in a really steep prow and the second one is just really powerful on two finger pockets. "This one really reminded me of Frankenjura!! Grade should be either really hard 8c or 8c+!"

Check the video from those 2 first ascents:



CARLOS "CITRO" LOGROÑO

8c + at age of 50: "I am the Benjamin Button of climbing"

'Citro' returns to his maximum grade by repeating the route 'Hulk total extension' in the cave of Ali Babá. Carlos Logroño 'Citro' is one of the most charismatic characters in sport climbing in Spain. As he likes to say, "I did my first 8c in the last century." By age, it would have corresponded to him to send the 8c + before this millennium, with Patxi Arocena, Carles Brascó or Alex Huber. Some would say that he missed that opportunity. He, on the other hand, continued doing what he liked the most with the passion of always and the results have been coming.

Read more details and the secret of his longevity in this Desnivel interview:





MARTIN STRÁŇÍK

Two 8C and 9a for boulder specialist Martin Stráňík

The boulder specialist who was #11 in the Lead WC in 2019, #2 in the World Championship in 2007 did during last year two 8C, FA of Iceberg in Moravský kras, Czechia and Primitivo 8C in Valle Bavona, Switzerland.

Although Martin is a boulder specialist, at the beginning of October 2020 Martin Stráňík repeated a 9a route by Adam Ondra, Senzace at the Krkavka climbing area, Czechia. For Martin it was his first 9a in his climbing career.

In total, the 30-year-old Czech has now done 65 boulders 8B+ and 8C. In the 8a annual ranking game, he is #4 including having done 17 FAs 8B and harder. Last year he also did his first 8c+ and 9a, so one might wonder how he could be so productive recently.

"Just keep my training and motivation and maybe I am a bit more relaxed with my climbing goals because of little twins, they are the most important now."



Check more about Martin:

KLEMEN BEČAN

New member of SINGING ROCK CLIMBING TEAM

Klemen Bečan, climbing coach and professional climber, has become a new member of our international climbing team. Klemen is from Slovenia, has started to climb in 1989 and climbing is his main goal and passion. We've asked Klemen couple of questions:

What do you enjoy about climbing?

Everything. I like traveling to remote places, searching for rocks, getting lost and finding myself again. I like company of other climbers, but most of all I like to climb. While moving up I like to disconnect from the real world and just enjoy the movement. I really like getting pumped and fight until I can't hold anymore and then take a big flight as a reward. I was never obsessed too much with finishing the routes. Actually a big fight means a lot more to me than those 2 seconds of happiness while clipping the top. Still, sometimes is good to send something.)

Plans for the future?

Since I remember I wanted to onsight 9a. Hope one day I will see that day and if not I will be just enjoying while trying. I would also like to do some 9b since I got close already with few of them but had to stop trying for some stupid reasons. I would like help others to achieve their climbing goals. That is why I started with coaching so I can transfer all my precious knowledge to others who would like to become better climbers.

Welcome on board and let's hope, that this year you will onsight your first 9a.



Check more about Klemen:

6
harnesses



32
ropes



50
carabiners
quickdraws



70
helmets



76
ice line



88
hardware
ascenders belay
devices



102
slings
via ferrata sets



110
accessories
bouldering
promotional





HARNESSES

ROPES

CARABINERS

HELMETS

ICE LINE

HARDWARE

SLINGS

ACCESSORIES



HARNESSES



CLIMBERS FOR CLIMBERS

Ergonomic braided gear loops

Belay loop with a strength 15 kN made from 12 mm wide webbing.

Patented 16 mm wide stainless steel Rock & Lock buckles on the leg loops enable fast adjustment.



Rear haul loop at all models with a load capacity 30 kg

Abrasion resistance fabric at tie-in points for longer lifetime of the harness.

Variable width webbing used at leg loops and waist belt for higher comfort and lower weight.




ROCK&LOCK

patented smart buckle system

Easy to lock and open: Only small effort of your fingers is needed to lock and open.

- Fast lace-through: Make the loop, put it through the buckle frame, hook the loop on cross bar and tighten. It is easy as that.
- Smart function: Rock&Lock allows you to put on your harness very quickly
- Double safety: Webbing cannot slip through Rock&Lock due to safety loop at the end. Spontaneous opening of Rock&Lock is virtually impossible.
- Lightweight and extra strong.
- Excellent function in all-season conditions: Function guaranteed even when webbing is wet or frozen.



BMI

Revolutionary size adjusting system by SINGING ROCK.

You can easily adjust free end of your waist belt padding and fix it in the right position and minimize so called "sticking out" of padding including the first gear loop in the line. Suitable for situation as losing or putting on your weight, putting more clothes or changing of your climbing seasons. The best position is when the buckle is on the padding and BMI system doesn't allow the gear loops to get out of the right position.




PADDING

Padded waist belt and leg loops

- breathable PES fabric with high abrasion resistance
- EVA foam
- soft 3D fabric



Load distribution at the waist:



SINGING ROCK harnesses are so comfortable and soft that you may forget you wear some.

Make sure to take it off when you finish climbing.

- For both leg loops and waist belt the variable width webbing is used.
- This ergonomic construction combines maximum comfort and low weight.
- Flat profile of harness also guarantees unlimited movement.
- Unique, patented Rock&Lock buckles are made of stainless steel to increase corrosion resistance.
- New webbing is more durable and works better in our R&L buckle, making the tightening smoother.
- The ergonomic braided gear loops are shaped to facilitate handling and to provide enough space for your climbing gear.
- Fixed bridge between the leg loops provides a greater safety in case of incorrect tie-in.
- More durable reinforced tie-in points for longer lifetime of the harness
- Belay loop 12 mm wide with strength 15 kN



ROCKET



C5076



High-end ultralight sport climbing harness for your best climbing achievements. Provides low weight and maximum comfort. Designed for sport climbing or wherever you want to climb light.

- laminated thin and light construction still provide great comfort and maximalized freedom and focus for your climbing.
- unique, patented Rock&Lock 16 mm buckle is made of stainless steel to increase corrosion resistance
- leg loops construction, made by ultrathin and ultralight HMPE (high-modulus polyethylene) webbings, still provide optimal load distribution and comfort
- elasticized fixed leg loops fit perfectly and provide freedom of movement
- abrasion resistance fabric at tie-in points for longer lifetime of the harness
- belay loop 12 mm wide with strength 15 kN.
- 2 front rigid and 2 rear light gear loops for enough equipment

Size: XS, S, M, L, XL
 Weight: 250 g • 8.8 oz [size M]
 CE1019 • EN 12277 •

ONYX



C5071YX



One buckle climbing harness providing maximum comfort, low weight and freedom of movement. Designed for sport or gym climbing.

- flexible leg loops with elastic straps adapt to the user's legs
- one Rock&Lock buckle on the waist belt
- 4 gear loops
- rear haul loop with a load capacity 30 kg
- fresh and simple design

Size: XS, S, M, L, XL
 Weight: 335 g • 11.8 oz [size M]

CE 1019 • EN 12277 •

PEARL



C5072SC



All-round harness specially designed to fit female body.

- specially shaped waist belt and longer belay loop to fit women's physique
- patented 16 mm wide Rock&Lock buckles on leg loops enable to put the harness on without having to take your skis or crampons off
- 3 Rock&Lock buckles
- 4 gear loops
- rear haul loop with a load capacity 30 kg
- graceful design for women's climbing

Size: XS, S, M, L, XL
Weight: 376 g • 13.3 [size M]

CE 1019 • EN 12277 •



GARNET



RED C5073RT
GREY C5073ST



All-round harness with adjustable leg loops. A perfect choice for climbers who want one harness for all rock and mountain activities.

- 3 Rock&Lock buckles
- patented 16 mm wide Rock&Lock buckles on leg loops enable to put the harness on without having to take your skis or crampons off
- 4 gear loops
- 2 slots for additional carabiner PORTER
- rear haul loop with a load capacity 30 kg
- fresh, attractive design
- available in 2 color versions

Size: XS, S, M, L, XL, XXL
Weight: 380 g • 13.4 oz [size M]

CE 1019 • EN 12277 •



SPINEL



C5074TS



Fully adjustable four buckles sit harness ideal for mountaineering and winter climbing.

- 4 Rock&Lock buckles
- patented 16 mm wide Rock&Lock buckles on leg loops enable to put the harness on without having to take your skis or crampons off
- 2 buckles in a waist belt enable to center the harness, keeping the gear loops in an optimal position
- 4 gear loops
- rear haul loop with a load capacity 30 kg
- 2 slots for additional carabiner PORTER

Size: S, M/L, XL

Weight: 430 g • 13.3 oz [size M/L]

€1019 • EN 12277 •



ROB



C5075OX



All-round 1-buckle harness. Suitable mainly for beginners for gym and outdoor climbing due to comfortable construction and low weight.

- patented Rock&Lock buckle for fast and safe adjustment
- flexible leg loops with elastic straps adapt to the user's legs
- very smooth tightening due to soft and durable webbing
- inside mesh wicks moisture away and dries quickly in wet conditions
- reinforced tie-in points for longer lifetime of the harness
- 4 gear loops in two sizes with a bearing capacity 5 kg
- removable and adjustable rear stretch straps

Size: XS, S, M, L, XL, XXL

Weight: 325 g • 11.5 oz [size M]

€1019 • EN 12277 •



RAY



C5038



All-round 3-buckles harness suitable mainly for beginners, climbing gyms and outdoor centers due to comfortable construction, low weight and affordable price.

- 3 patented Rock&Lock buckles for fast and safe adjustment
- very smooth tightening due to soft and durable webbing
- inside mesh wicks moisture away and dries quickly in wet conditions
- reinforced tie-in points for longer lifetime of the harness
- two sizes of gear loops with a bearing capacity 5 kg
- removable and adjustable rear stretch straps

Size: XS, S, M, L, XL, XXL
Weight: 390 g • 13.76 oz [size M]

CE 1019 • EN 12277 •



VERSA II



C5067



The second generation of the universal harness for all kinds of climbing activities suitable mainly for beginners, climbing courses and gyms.

- comes in two sizes which adapt to all users
- 3 patented Rock&Lock buckles enable fast and safe adjustment
- BMI adjusting system on the waist belt (consists of two loops on one side and two velcro straps on the other one) keeps the waist belt webbing with the belay loop in a proper position in various sizes
- rear size label makes size adjusting very easy
- construction of the waist belt and leg loops provides maximum support and comfort when hanging in the harness
- reinforced tie-in points for longer lifetime of the harness
- red color belay loop for proper tie-in/ attachment point, strength 15 kN
- inside mesh wicks moisture away and dries quickly in wet conditions
- laced technical textile increases the waist belt rigidity and abrasion resistance
- 4 braided gear loops in two sizes with a load capacity of 5 kg
- fixed bridge between the leg loops provides a higher safety in case of wrong tie-in
- removable and adjustable rear stretch straps

Weight: 410 g • 14.5 oz [size XS-M]
Size: XS-M, L-XXL

CE 1019 • EN 12277 •



DOME



C5017



The ultimate big wall harness designed with essential aid climbing features. Built for the maximum comfort and durability.

- even being the most robust harness in our line, it is still very lightweight
- waist belt with more coverage than most harnesses and rugged exterior fabrics designed to withstand serious abrasion
- ergonomically shaped padding provides maximum support and comfort for long days on the wall
- two buckles on the waist belt: Rock&Lock buckle provides fast and smooth adjustment while the threading buckle allows the harness to be perfectly centered
- adjustable leg loops with Rock&Lock buckle enable to put on the harness when wearing skis or crampons
- tie-in points which have the most abrasive wear are reinforced by PAD webbing
- 7 braided gear loops with a load capacity 5 kg
- rear haul loop with a load capacity 50 kg
- 2 color distinctive belay loops for proper tie-in/attachment point, strength 15 kN
- 2 slots for additional carabiner PORTER
- fixed bridge between the leg loops provides a higher safety in case of wrong tie-in
- easily detachable rear elastic straps
- suitable in combination with the chest harnesses ALADIN and ALADIN PLUS

Size: S/M/L and XL
Weight: 560 g • 19.75 oz [size S/M/L]

€€ 1019 • EN 12277 •

KID'S

ARA



C5070RY



Sit harness with adjustable leg loops for your small rock stars.

- designed for children which have well defined hips for a waistbelt to hold
- for both leg loops and the waist belt the variable width webbing is used
- wider construction of the waist belt provides maximum support and comfort when hanging in the harness
- adjustable leg loops with 16 mm wide patented Rock & Lock buckles
- 3 patented stainless steel Rock&Lock buckles for fast and safe adjustment
- tie-in points which have the most abrasive wear are reinforced by PAD webbing
- inside mesh dissipate moisture and dries quickly in wet conditions
- 2 ergonomic gear loops with a load capacity 5 kg are shaped to facilitate handling and to provide enough space for the gear.
- color belay loop for proper tie-in/ attachment point, strength 15 kN
- fixed bridge between the leg loops provides a higher safety in case of wrong tie-in
- plastic buckle and sleeve for quick removing and adjustment of the rear elastic straps
- rear haul loop with a load capacity of 30 kg

Size:
K1: waist: 55 - 65 cm (19.5 - 23.5 in) K2: waist: 60 - 70 cm (21.5 - 25.5 in)
leg loop: 35 - 40 cm (14 - 16 in) leg loop: 40 - 45 cm (16 - 17.5 in)
Weight: 305 g • 10.8 oz (size K2)

€€ 1019 • EN 12277

ZAZA

C50690A



Lightweight full body adjustable harness for kids without well-defined hips necessary for a standard waist belt harness.

- one size fits all children with a height of 95–130 cm and a maximum weight of 40 kg (37–51 in / 88 lb)
- red color textile loops for correct attachment to the harness
- three fast buckles enable very quick and easy size adjustment
- elastic straps with a plastic buckle keep harness on the body when kids are playing on the ground
- rear padding of the harness keeps shoulder straps apart and makes dressing easier
- 40 mm wide webbing for leg loops to provide comfort when climbing

Weight: 338 g • 11.9 oz. Size: UNI

CE 1019 • EN 12277 type B • 



COMPLETE



C0710

**Full body harness suitable for via ferrata and/or for climbing beginners.**

- stabilizes the body in an upright position
- prevents flipping upside down
- adjustable shoulder straps and leg loops
- reinforced tie-in points
- two gear loops with a load capacity 5 kg
- rock&Lock buckle system on the leg loops

Size: UNI
Weight: 550 g • 19.4 oz

€€ 1019 • EN 12277

ROPEDANCER II



W0087

**Fully adjustable full body harness with various attachment points intended for rope courses and adventure parks.**

- easy to put on and off, easy to adjust, thanks to 5 double buckles and 1 SPEED buckle
- color front lower attachment point for rappelling and belaying
- waist belt in different (black) color for better orientation when putting on the harness
- front and rear attachment points according to EN 361 for fall-arrest
- 2 gear loops with a bearing capacity of 5 kg
- max. rated load of the harness 150 kg
- different color of the rear triangle for each size

Weight: 1170 g [S/M/L] • 41.3 oz
Size: XS, S/M/L, XL/XXL

€€ 1019 • EN 12277

TARZAN



W0050BR



Fully adjustable full body harness intended for rope courses and adventure parks

- front attachment point according to EN 813 for hanging position, rappelling and other vertical activities
- padded waist belt and leg loops provide maximum comfort
- SPEED buckle connecting shoulder straps with waist belt increases comfort when putting the harness on
- shoulder webbing and left leg loop have different colour for easy manipulation
- different colour of rear plate for each size.
- dorsal steel D-ring with a bearing capacity of 15 kN according EN 361.

Size: XS-S, M-XL

Weight: 1530 g • 53.97 oz [M – XL]

CE 1019 • EN 813 • EN 361

TARZAN ECONOMIC



W0059BR



Fully adjustable full body harness intended for rope courses and adventure parks.

- front attachment point for belaying and rappelling according to EN 12277 type C
- waist belt and leg loops without the padding enables to put a harness to every person
- rear steel D-ring with a bearing capacity of 15 kN according EN 361
- shoulder straps, waist belt and leg loops are easily adjustable with Easy Lock buckles
- all steel components are finished with E coating technology for higher corrosion resistance
- left leg loop with red colour helps to put the harness on
- webbing strap stitched in the buckle simplify handling with a buckle
- dorsal plastic plate with different color according the size of the harness (S – yellow, UNI – red)

Size: S (110 – 150 cm), UNI (150 – 200 cm)

Weight: 1050 g • 34 oz (UNI)

CE 1019 • EN 12277 • EN 361



TOP



C5031BS00
black - C5031BB00



Universal harness with simple design for all activities especially suitable for climbing schools, gyms, via ferrata or glacier tours.

- one size fits all (from children to adults)
- adjustable leg loops with Rock&Lock buckles allow the harness to be put on even with skis or crampons
- lightweight construction
- 3 Rock&Lock smart buckles for easy and fast adjustment
- reinforced tie-in point /belay loop for increased durability
- tie-in point placed above the center of gravity prevents the body rotation on case of fall
- colour belay loop for proper tie-in/ attachment point, strength 15 kN
- 1 gear loop with a load capacity 10 kg

Size: UNI
Weight: 366 g • 12.91 oz

CE 1019 • EN 12277 •

TOP PADDED



C5032BS00



Harness with simple design and padded leg loops mainly for climbing schools, gyms, via ferrata or glacier tours.

- lightweight harness with padded leg loops for higher comfort
- one size fits all (from children to adults)
- adjustable leg loops with Rock&Lock buckles allow the harness to be put on even with skis or crampons
- 3 Rock&Lock smart buckles for easy and fast adjustment
- reinforced tie-in point /belay loop for increased durability
- tie-in point placed above the center of gravity prevents the body rotation on case of fall
- colour belay loop for proper tie-in/ attachment point, strength 15 kN
- sewed gear loop with a load capacity 10 kN

Size: UNI
Weight: 402 g • 14.18 oz

CE 1019 • EN 12277 •



TOP RENTAL



C5078RB

NEW



Padded sit harness with three buckles suitable mainly for beginners, rentals in climbing gyms or rope courses.

- non-openable buckles for easier dressing the harness
- removable and adjustable rear stretch straps
- one gear loop with a load capacity 10 kN (1 tone) increases safety in case of incorrect tying in
- marking label below the gear loop allows any marking on the harness
- comes in two sizes (XS-M; L-XXL) which adapt to all users
- inside mesh wicks moisture away and dries quickly in wet conditions
- reinforced tie-in loop for longer lifetime of the harness
- color distinguished tie-in loop
(white = size XS-M, red = size L-XXL)
for quick orientation when choosing a size

Size: XS-M; L-XXL
Weight: 395 g • 13.93 oz [XS-M] CE 1019 • EN 12277 • UIAA

SERAC



C5079WB

NEW


Extremely lightweight harness for skitouring, mountaineering and glacier tours.

- can be put on/off safely and quickly with skis/crampons on, with feet on the ground
- construction made of HMPE (high-modulus polyethylene) lace webbing which is super lightweight and strong
- fine nylon fabric inside the harness doesn't absorb water and it is very breathable
- tying in two color distinguished tying loops with a strength of 15 kN
- opening and adjusting the leg loops with the patented 12 mm wide Rock&Lock aluminium buckle, easy and fast manipulation even with the gloves on
- two gear loops with a load capacity of 5 kg, each gear loop is divided into 3 sections which allow easier gear management
- gear loop is made of thin webbing and long enough that doesn't restrain when wearing a backpack
- two slots for the additional plastic carabiner Porter to carry ice screws or other gear
- rear haul loop with a load capacity of 5 kg
- two elastic loops on each leg loop for comfortable carrying an ice screw
- transport bag included
- this harness is designed for demanding mountaineering and skitouring with minimal weight under 100 grams and super packable size

Size: S, M, L, XL

Weight: 96 g (M) • 3.39 oz (1019) • EN 12277 • UIAA



CANYON XP



C5030BS



Canyoning harness with padded waistbelt and protective seat for advanced users.

- ergonomic design and padded waistbelt for higher comfort
- reinforced tie-in point/belay loop for increased durability
- colour belay loop for proper tie-in/ attachment point, strength 15 kN
- padded leg loops with 3 rock&lock smart buckles for easy and fast adjustment
- removable and replaceable sit protector protects the wet suit from abrasion
- 2 reinforced gear loops with a load capacity 10 kg

Size: S, M/L, XL

Weight: 614 g • 21.66 oz [M/L]

CE 1019 • EN 12277 •

TOP CANYON



C5029BS



Canyoning harness for canyoning schools and centers.

- one size fits all (from children to adults)
- 3 smart buckles Rock&Lock for easy and fast adjustment
- lightweight construction
- reinforced tie-in point/belay loop for increased durability
- colour belay loop for proper tie-in/ attachment point, strength 15 kN
- removable and replaceable sit protector protects the wet suit from abrasion
- 1 reinforced gear loop with a load capacity 10 kg

Size: UNI

Weight: 502 g • 17.71 oz

CE 1019 • EN 12277 •

CANYON SIT PROTECTION

C9630BB00



This rear protection sheet extends lifetime of your neoprene suit.

- replacement of sit reinforcement for canyoning harnesses
- welded abrasion resistant fabric on the basis of Plastex.

Color: black

Weight: 135 g • 4.8 oz

Size: UNI

DIGGER LIGHT

S0101YB00

**Speleo harness**

- ergonomic design
- fully adjustable waistbelt and leg loops
- abrasion resistant cover on exposed parts
- two special textile loops for light battery placing
- attachment point for jumar tightening strap
- specially designed steel triangles for maillon placing

Size: UNI

Weight: 520 g • 18.34 oz

€ 1019 • EN 12277

CHEST

ALADIN



C5056

**Chest harness**

- designed to be used together with a sit harness
 - optimising body position while hanging or falling
 - made from lightweight wide nylon webbing
 - very durable and affordable to all climbers
 - two gear loops with a load capacity of 5 kg
- Must be worn with sit harness.
Do not use chest harness alone!

Size: UNI

Weight: 240 g • 8.5 oz

€ 1019 • EN 12277 • 

Do not use chest harness alone!





ALADIN PLUS



C5057

**Padded chest harness for your vertical adventures.**

- provides more comfort when climbing long multi-pitch routes
- optimizing body position while hanging or falling
- reduces the pressure on the upper body when having a large quantity of climbing material
- two large climbing gear loops with a load capacity of 15 kg with a possibility of adjusting the length of the loops
- two gear loops and one small gear loop with a load capacity of 5 kg
- easy to dress
- made of lightweight breathable padded material

Size: UNI

Weight: 435 g • 15.34 oz

CE 1019 • EN 12277 •

Do not use a chest harness alone!
Must be worn with a sit harness!



ALADIN PADDING

C5058

**Padding for the chest harness Aladin.**

- the padding is designed for use only in combination with the chest harness Aladin
- provides more comfort when climbing long multi-pitch routes
- reduces the pressure on the upper body when having a large quantity of climbing material
- two large climbing gear loops with a load capacity of 15 kg with a possibility of adjusting the length of the loops
- one small gear loop with a load capacity of 5 kg
- easy to put on
- made of lightweight breathable padded material

Size: UNI

Weight: 195 g • 6.88 oz

Do not use a chest padding alone!
Padding can be used only with a chest harness Aladin.



RAY PACKET

M0029



Ray

Oxy screw

Rama

Ideal set for all who want to start with climbing. Perfect choice for beginners who prefer single pitch climbing.

This set at a reduced price includes:

- padded all-round RAY harness with adjustable leg loops
- light alloy oval carabiner OXY screw with easy locking system
- RAMA single rope belay device with enhanced braking feature for 8.7 – 11 mm single ropes

LADY PACKET



M0014



Pearl

Bora GP

Buddy

Chalk bag Mountains

Chalk bag belt

Unique set for all women who want to start with climbing in the gym or out at the crags

- woman's climbing and mountaineering harness PEARL with adjustable leg loops (size: XS, S, M, L, XL)
- HMS carabiner BORA GP designed specifically to eliminate the dangers of cross loading.
- light and compact belay tube BUDDY designed for twin, half and single ropes of the diameter 7.8 – 10.5 mm
- Chalk bag Mountains with prompt closing system and braced welt for easy handling
- adjustable BELT for chalk bag with a quick release plastic buckle

GYM PACKET

M0027



Versa II

Oxy screw

Rama

Chalk bag Large

Chalk bag belt

Magnum ball

Perfect choice for all who climb indoor or prefer single pitch climbing.

- all-round harness VERSA II with adjustable leg loops (size: XS/M, L/XXL)
- light alloy oval carabiner OXY screw with easy locking system
- RAMA single rope belay device with enhanced braking feature for the ropes 8.7 – 11 mm diameter
- chalk bag LARGE with prompt closing system and braced welt for easy handling
- adjustable BELT for chalk bag with a quick release plastic buckle
- MAGNUM ball with perfect grade natural chalk for maximum sweat absorption and friction

FERRATA PACKET RAY

M0028



Ray

Phario palm

Starter kit for those who want to save some money and get comfortable via ferrata equipment.

This set at a reduced price includes:

- all-round 3-buckles RAY sit harness
 - PHARIO PALM energy absorber with palm Keylock carabiners, elastic lanyards and a fall indicator
- this basic equipment should be completed with your climbing helmet and ideally with a chest harness as well*

FERRATA PACKET II

M0017



Top

Phario palm

Penta

Perfect package containing the basic equipment for via ferratas

This set at reduced price includes:

- lightweight TOP harness with 3 rock&lock smart buckles (UNI size)
- energy absorber Phario palm with the palm key lock carabiner
- fully adjustable and well ventilated climbing and mountaineering helmet PENTA
- chest harness not included but highly recommended

FERRATA PACKET EXP

M0018



Phario palm

Spinel

Aladin














Penta

Advanced package at via ferratas containing the equipment for multiple use.


This set at reduced price includes:

- energy absorber Phario palm with the palm Keylock carabiner
- fully adjustable four buckles sit harness SPINEL for all climbing activities (size: S, M/L, XL)
- chest harness ALADIN made from lightweight wide nylon webbing (UNI size)
- extremely lightweight, super-comfortable and fully ventilated helmet PENTA in grey color

HARNESSES

		weight			UNI	K1	K2	XS
ROCKET C5076		(M) 250 g	A B	cm in cm in				65-75 25,5-29,5 49 19
ONYX C5071		(M) 335 g	A B	cm in cm in				65-75 25,5-29,5 49 19
PEARL C5072		(M) 376 g	A B	cm in cm in				60-70 23,5-27,5 50-55 19,5-21,5
GARNET C5073RT C5073ST		(M) 380 g	A B	cm in cm in				65-75 25,5-29,5 50-55 19,5-21,5
SPINEL C5074		(M) 430 g	A B	cm in cm in				
VERSA II C5067		(XS-M) 410 g	A B	cm in cm in				63-90 25-35,5 45-58 18-23
ROB C5075OX		(M) 325 g	A B	cm in cm in				65-75 25,5-29,5 49 19
RAY C5038		(M) 390 g	A B	cm in cm in				65-75 25,5-29,5 45-50 17,5-19,5
DOME C5017		(S/M/L) 560 g	A B	cm in cm in				
ARA C5070		(K2) 305 g	A B	cm in cm in		55-65 21,5-25,5 35-40 14-16	60-70 23,5-27,5 40-45 16-17,5	
ZAZA C5069OA		(UNI) 338 g	C	cm in	95-130 37-49			
TARZAN W0050BR		(M-XL) 1530 g	A B C	cm in cm in cm in				50-80 20 - 31 45-60 18-24 145-165 57-65
TARZAN ECONOMIC W0059BR		(UNI) 1050 g	C	cm in	150 -200 59-78			

TECHNICAL DATA



S	M	L	XL	XXL	EN stand.	CE	UIAA
70-80 27,5-31,5 52 20	75-85 29,5-33,5 55 21	80-90 31,5-35,5 58 22	85-95 33,5-37,5 60 23		EN 12277	CE 1019	
70-80 27,5-31,5 52 20	75-85 29,5-33,5 55 21	80-90 31,5-35,5 58 22	85-95 33,5-37,5 60 23		EN 12277	CE 1019	
65-75 25,5-29,5 50-55 19,5-21,5	70-80 27,5-31,5 55-60 21,5-23,5	75-85 29,5-33,5 60-65 23,5-25,5	80-90 31,5-35,5 65-70 25,5-27,5		EN 12277	CE 1019	
70-80 27,5-31,5 50-55 19,5-21,5	75-85 29,5-33,5 55-60 21,5-23,5	80-90 31,5-35,5 60-65 23,5-25,5	85-95 33,5-37,5 65-70 25,5-27,5	90-100 35,5-39,5 65-70 25,5-27,5	EN 12277	CE 1019	
65-80 25,5-31,5 50-55 19,5-21,5	75-90 29,5-35,5 60-65 23,5-25,5	75-90 29,5-35,5 60-65 23,5-25,5	85-100 33,5-39,5 65-70 25,5-27,5		EN 12277	CE 1019	
63-90 25-35,5 45-58 18-23	63-90 5-35,5 45-58 18-23	75-100 29,5-39,5 55-68 21,5-26,5	75-100 29,5-39,5 55-68 21,5-26,5	75-100 29,5-39,5 55-68 21,5-26,5	EN 12277	CE 1019	
70-80 27,5-31,5 52 20	75-85 29,5-33,5 55 21	80-90 31,5-35,5 58 22	85-95 33,5-37,5 60 23	90-100 35,5-39,5 65-70 25,5-27,5	EN 12277	CE 1019	
70-80 27,5-31,5 50-55 19,5-21,5	75-85 29,5-33,5 55-60 21,5-23,5	80-90 31,5-35,5 60-65 23,5-25,5	85-95 33,5-37,5 65-70 25,5-27,5	90-100 35,5-39,5 65-70 25,5-27,5	EN 12277	CE 1019	
67-95 26-37 48-66 19-26	67-95 26-37 48-66 19-26	67-95 26-37 48-66 19-26	90-120 35-47 56-72 21-28	90-120 35-47 56-72 21-28	EN 12277	CE 1019	
					EN 12277	CE 1019	
					EN 12277	CE 1019	
50-80 20-31 45-60 18-24 145-165 57-65	70-130 27-51 50-75 20-29 160-205 63-80	70-130 27-51 50-75 20-29 160-205 63-80	70-130 27-51 50-75 20-29 160-205 63-80		EN 358, EN 813, EN 361	CE 1019	
110-150 43-59					EN 12277, EN 361	CE 1019	

HARNESSES

ROPES

CARABINERS

HELMETS













ICE LINE

HARDWARE


SLINGS

ACCESSORIES

HARNESSES

		weight			UNI	K1	K2	XS
COMPLETE C0710		(UNI) 550 g	C	cm in	140-200 55-78			
ROPEDANCER II W0087		(S/M/L)C 1170 g		cm in				
BRIO II C5066BY00		UNI 480 g	A B	cm in cm in	60-116 24-46 42-72 17-29			
TOP C5031BS		UNI 366 g	A B	cm in cm in	60-120 24-47 42-66 17-27			
TOP PADDED C5032BS		UNI 402 g	A B	cm in cm in	60-120 24-47 42-66 17-27			
TOP RENTAL C5078RB		(XS-M) 395 g	A B	cm in cm in				55 - 90 22 - 35 35 - 65 14 - 25
SERAC C5079WB		(M) 96 g	A B	cm in cm in				
CANYON XP C5030BS		(M/L) 614 g	A B	cm in cm in				
TOP CANYON C5029BS		UNI 502 g	A B	cm in cm in	60-120 24-47 42-66 17-27			
DIGGER LIGHT S0101YB00		UNI 520 g	A B	cm in cm in	max. 110 max. 43 50-80 20-31			
ALADIN C5056		UNI 240 g	D	cm in	75-110 30-43			
ALADIN PLUS C5057		(UNI) 435 g	D D	cm in	75-110 30-43			

TECHNICAL DATA



S	M	L	XL	XXL	EN stand.	CE	UIAA
					EN 12277	CE 1019	
130-155 51-61	150-185 59-73	150-185 59-73	180-210 71-83	180-210 71-83	EN 12277	CE 1019	
					EN 12277	CE 1019	USA
					EN 12277	CE 1019	USA
					EN 12277	CE 1019	USA
55 - 90 22 - 35 35 - 65 14 - 25	55 - 90 22 - 35 35 - 65 14 - 25	75 - 125 29 - 49 40 - 75 16 - 29	75 - 125 29 - 49 40 - 75 16 - 29	75 - 125 29 - 49 40 - 75 16 - 29	EN 12277	CE 1019	USA
71-83 28-32.6 48-55 19-21.6	78-90 30.7-35.4 53-60 20.8-23.6	85-97 33.4-38.2 58-65 22.8-25.6	92-104 36.2-40.9 63-70 24.8-27.5		EN 12277	CE 1019	USA
70-100 28-40 42-66 17-27	80-110 32-43 42-66 17-27	80-110 32-43 42-66 17-27	90-120 36-48 42-66 17-27		EN 12277	CE 1019	USA
					EN 12277	CE 1019	USA
					EN 12277	CE 1019	
					EN 12277	CE 1019	USA
					EN 12277	CE 1019	USA

HARNESSES

ROPES

CARABINERS

HELMETS

ICE LINE

HARDWARE

SLINGS

ACCESSORIES





HARNESSES

ROPES

CARABINERS

HELMETS

ICE LINE

HARDWARE

SLINGS

ACCESSORIES



ROPES



CLIMBERS FOR CLIMBERS



THERMO-TRANSFER

Thermotransfer end marking of Singing Rock ropes.
Special etiquette applied to the rope sheath by the heat and pressure. This marking ID is durable and does not create any broad forms on the ends of the ropes which can stuck e.g. when pulling down the rope from rappel station..


ULTRASONIC

an excellent way of rope ending
Our own special technology has been used for the ends of the rope.
All SINGING ROCK ropes are ended by a unique technology ULTRASONIC. It means that the load-bearing core and the protective sheath are joined into a compact unit in the last 15 mm of the rope.



UIAA WATER REPELENT

A standard for water repellent ropes approved by the UIAA Safety Commission. To pass the test at a certified laboratory, the amount of absorbed water must not be greater than 5% of the rope's weight. For comparison, a non-treated rope absorbs around 50% of water in this test, and ropes labelled as "dry" but lacking adequate treatments can absorb between 20% and 40% of water.



STITCHED EYE

an excellent way of rope ending
Selected SINGING ROCK static ropes which are marked with Stitched eye icon are possible to produce with one or two stitched eyes at the end of the rope.



INTERCORE

The unique patented technology providing maximum safety even in case of a damaged sheath. The rope is made from 4 layers of parallel core filaments, braided core, braided intermediate sheath made from staple fibres and single tech sheath.



MIDDLE MARKING

At half of the length, the rope is visibly marked by colour, which does not affect the core structure and its mechanical properties.



ROUTE 44

experience the touch of the future
Route 44 is unique technology invented and patented by Singing Rock. It opens new horizons for braiding of climbing and static ropes. Route 44 technology allows blending of properties that were considered impossible before. Rope braided by using Route 44 technology is more compact, softer and above all it is more durable than conventional rope.
All that is achieved by making no compromises in using correct sheath thickness, which is round-braided by 44 carriers. These features combine to give you better rope.



TEFLON®

permanent dry
Selected SINGING ROPES are produced with a DuPont™ Teflon® fabric protector license. Ropes protected by a Teflon® layer have extra-ordinary water and abrasion resist- ance.
The Teflon® layer also effectively prevents the intrusion of dust particles into the rope structure and thus increases its lifespan.



SINGLE TECH

With the single tech system each strand is braided into the sheath separately. Single tech sheath construction increases the rope's wear resistance and improves the rope's mechanical properties, such as flexibility.

ICON DRY 9.3 ①   

L0384RX




Excellent single rope for high-level climbers or glacier/mountain usage thanks to its lightness and water resistant.

- extremely lightweight and robust; it is ideal for hard routes onsight, flash or redpointing where every gram counts.
- produced on 44-carrier machine, Route 44, Singing Rock's patented technology.
- with our special Teflon® treatment Icon 9.3 Dry is ideal for rock climbing, pumpy routes or extreme ascents in the mountains.
- Teflon® is applied on the ropes by revolutionary nanotechnology.
- the sheath is more resistant against breakage, but on the other hand it is smoother.
- Teflon® Treatment
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

ICON 9.3 ① 

CE 1019 • EN 892 • 

L0380YX




Excellent single rope for high-level climbers.

- extremely lightweight and robust; it is ideal for hard routes onsight, flash or redpointing where every gram counts.
- produced on 44-carrier machine, Route 44, Singing Rock's patented technology.
- this unique technology gives to the rope great handling, low-weight and high durability.
- the sheath is more resistant against breakage, but on the other hand it is smoother.
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • 

HERO DRY 9.6 ①   

L0524GW



A top-class single rope with low weight and great handling qualities for high-level climbers.


- Single Tech construction provides increased resistance to abrasion and great handling qualities
- rope is soft and easy to manipulate in the belay devices
- although having a small diameter, this rope provides long lifespan
- special Teflon® treatment provides longer lifetime during the usage.
- Teflon® is applied on the ropes by revolutionary nanotechnology.
- ideal for sport climbing and single pitch ice climbing
- Teflon® Treatment
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • 

HERO 9.6 ①



L0520GW



Excellent single rope for sport climbers.

- Single Tech construction provides increased resistance to abrasion, low weight and great handling qualities
- rope is soft and easy to manipulate in the belay devices
- even with a small diameter, this rope provides long lifespan
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • 

KATA DRY 9.7 ①



L0580AA



High-end climbing single rope with high safety factors and extremely high durability. Suitable for both experienced climbers and beginners.


- the unique patented InterCore technology provides maximum safety even in case of a damaged sheath
- narrow diameter and great handling provide easy manipulation in all belay devices
- thanks to the sandwich-type construction of braided layers and the use of specially developed staple fibres the rope has super high resistance to abrasion.
- special Teflon treatment provides longer lifetime during the usage. Teflon treatment is applied on the core and sheath by revolutionary nanotechnology.
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending
- Teflon® Treatment

CE 1019 • EN 892 • 

KATA 9.7 ①



L0570AA



High-end climbing single rope with high safety factors and extremely high durability. Suitable for both experienced climbers and beginners.

- narrow diameter and great handling provide easy manipulation in all belay devices
- the unique patented InterCore technology provides maximum safety even in case of a damaged sheath
- thanks to the sandwich-type construction of braided layers and the use of specially developed staple fibres the rope has super high resistance to abrasion
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • 

STORM DRY 9.8 ①



L3044AG00




Single rope with great balance in weight, durability and use. Perfect choice for all-round climbing.

- this rope provides great handling, low-weight and high durability
- special Teflon® Eco treatment provides longer life-time during the usage
- Teflon® is applied on the ropes by revolutionary nanotechnology which makes the top of the line impregnated ropes
- narrow diameter and higher UIAA fall rating (UIAA falls 9) help you to improve your climbing achievements
- ideal for all-round climbing, training hard routes and RP ascents.
- Teflon® Treatment
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 •

STORM 9.8 ①

L3040GA00



Single rope with great balance in weight, durability and use. Perfect choice for all-round climbing.

- narrow diameter and higher UIAA fall rating (UIAA falls 9) help you to improve your climbing achievements
- this rope provides great handling, low-weight and high durability
- the rope is very compact, durable and pleasant to use
- ideal for all-round climbing, training hard routes and RP ascents.
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 •

GYM 10.1 ①

L3050RY00



Single rope specially invented for the climbing gyms, adventure parks or rope courses.

- this rope is designed for heavy usage with high safety factors and extremely high durability
- special technology of braided core gives the rope great resistance parameters
- braided core and compact sheat minimize the inter-fiber friction which gives the result of the increased resistance to abrasion mainly when top-roping
- narrow diameter and great handling provide easy manipulation in all belay devices
- ideal for climbing schools, gyms, adventure parks and rope courses.
- thermotransfer end marking
- Middle marking
- ultrasonic ending

CE 1019 • EN 892 •




Carlos „Citro“ Logroño, Desarrollo insostenible 8c+, Alquezar, Spain • Photo: Javi Pec

MYSTIC 10.1 DRY ①



L0534AG



Great water resistant single rope with an unusual design.


- Single Tech construction provides high resistance to abrasion, great handling qualities and low weight
- runs smoothly in all devices on the market
- special Teflon® treatment provides longer lifetime during the usage.
- Teflon® is applied on the ropes by revolutionary nano-technology.
- Perfect choice for all-round climbers
- Teflon® Treatment
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • USA

MYSTIC 10.1 ①



L0530RA



Great single rope with an unusual design.

- Single Tech construction provides low weight, high resistance to abrasion and great handling qualities
- extraordinary durability and great technical performance
- perfect choice for all-round climbers
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • USA

SCORE 10.1 ①



L0360GG



Great rope for sport climbing with excellent visibility.

- made by Singing Rock patented technology R44, which gives to the rope well – balanced rate of weight and diameter.
- this unique technology gives to the rope great handling, low-weight and high durability
- rope is very compact, durable and pleasant to use.
- suitable for all belay devices on the market
- Thermotransfer end marking
- Middle marking
- Ultrasonic ending


CE 1019 • EN 892 • USA

DURAN 10.4

①

ROPE
44

L0340AX

**Ideal rope for indoor climbing and crags with rough rocks.**


- made by Singing Rock patented technology R44, which gives to the rope well – balanced rate of weight and diameter.
- rope is very compact, durable and pleasant to use.
- rope has thicker sheath with perfect abrasion resistance still keeping good handling characteristics.
- suitable for the most types of belay devices on the market
- Thermo-transfer end marking
- Middle marking
- Ultrasonic ending

CE 1019 • EN 892 • 

PATRON 11.0

①

L0540YX

**Dynamic single rope with high safety factor and great durability.**

- designed for heavy usage in rope training centres, climbing schools and rescue situations
- rope has thicker sheath with perfect abrasion resistance
- suitable for the most types of the belay devices on the market
- Thermo-transfer end marking
- Middle marking
- Ultrasonic ending



CE 1019 • EN 892 • 



ACCORD DRY 8.3



L0514

**Half and twin rope with excellent durability and special Teflon® treatment.**


- tested and certified according to the EN 892 standard requirements for half ropes and twin ropes
- with our special Teflon® treatment is ideal for ice climbing or wet conditions in the mountains
- Teflon® is applied on ropes by revolutionary nanotechnology
- weight, diameter and number of falls are balanced in such a way that can be used as a half and twin rope
- used in pairs, the climber can choose between the twin rope technique or half rope technique. Whatever technique is required at the time
- Thermotransfer end marking
- Ultrasonic ending

CE 1019 • EN 892 •

ACCORD 8.3



L0510

**Half and twin rope with excellent durability and lightness.**

- compact rope which has minimal interfiber friction, thereby increasing durability
- tested and certified according to the EN 892 standard requirements for half ropes and twin ropes
- weight, diameter and number of falls are balanced in such a way that can be used as a half and twin rope
- used in pairs, the climber can choose between the twin rope technique or half rope technique. Whatever technique is required at the time
- Thermotransfer end marking
- Ultrasonic ending

CE 1019 • EN 892 •

GEMINI 7.9



L3020

**Half and twin rope for those who count every gram.**

- lightweight rope with top parameters allows wide use: ice climbing, mix routes, glacier tours or mountaineering
- tested and certified according to EN 892 standard requirements as half rope and twin rope
- with our special Teflon® treatment Gemini 7.9 is ideal for ice climbing or extreme ascents in the mountains.
- Teflon® is applied on ropes by revolutionary nanotechnology
- used in pairs, the climber can choose between the twin rope technique or half rope technique. Whatever technique is required at the time
- Teflon® Treatment
- Thermotransfer end marking
- Ultrasonic ending

CE 1019 • EN 892 •

STATIC ROPES


Excellent static ropes of different diameters are intended for rescuing the injured, manipulation with objects and rope access methods for work at a height. They meet the most exacting requirements, especially the best quality, that the rescuers, firemen, specialists in working at a height and other professionals require when working every day.

STATIC R44 11.0



L0450WG white
L0450RR red
L0450BB black
L0450OO orange

CE 1019 • EN 1891 • NFPA • 




STATIC R44 10.5



L0430WR white
L0430RR red
L0430BB black
L0430KK khaki

CE 1019 • EN 1891 • NFPA • 



STATIC 11.0



L0250WR white
L0250RR red
L0250BB black

CE 1019 • EN 1891 • NFPA • 



STATIC 10.5



L0230WR white
L0230RR red
L0230BB black
L0230KK khaki

CE 1019 • EN 1891 • 



STATIC 9.0



L0220WR white
L0220BB black

CE 1019 • EN 1891 • 




CONTRA 10.5



L026
Static rope for various
purposes.

CE 1019 • EN 1891 • 



SPELEO R44 10.5 L0440WR



The cave explorers lay stress on the maximum abrasion resistance and on the high rope lifetime. The speleo ropes SINGING ROCK keep their great qualities even after the usage in the extreme condition.

The working and speleo ropes meet the EN 1891 regulations - Semi static ropes with core sheathing.

CE 1019 • EN 1891 • 

SPELEO 10.5 L0240WR



CE 1019 • EN 1891 • 

STATIC R44 NFPA 10.5



R0430BB black R0430KK khaki
R0430RR red R0430WR white



Excellent static rope designed for technical use for rope access, rescue and for manipulation with the objects. Meet NFPA 1983 Technical Use requirements that the rescuers, firemen, specialists working at height and other professionals require when working every day.

Weight: 72 g/m
Strength: 32 kN
Length: pack: 150, 200, 300 ft / 46, 61, 92 m
coil: 330, 600, 660 ft / 100, 183, 200 m
Diameter: 10.5 mm
Static elongation:
3.5% (at 3.5 kN, 300 lbs)
7.2% (at 2.7 kN, 600 lbs)
9.9% (at 4.4 kN, 1000 lbs)
NFPA 1983 Technical Use
EN 1891 • CE 1019 • EN 1891 •

STATIC R44 NFPA 11.0 / 7/16"



R0450BB black R0450OO orange
R0450RR red R0450WG white




Excellent static rope, meet NFPA 1983 Technical Use requirements that the rescuers, firemen, specialists working at height and other professionals require when working every day. Manufactured by patented rope-braiding technology ROUTE 44 with ultrasonic ending.

Weight: 77 g/m
Strength: 33.5 kN
Length: pack: 150, 200, 300 ft / 46, 61, 92 m
coil: 330, 600, 660 ft / 100, 183, 200 m
Diameter: 11.0 mm • 7/16 in
Static elongation:
3.0% (at 1.35 kN, 300 lbs)
6.8% (at 2.7 kN, 600 lbs)
10.8% (at 4.4 kN, 1000 lbs)
NFPA 1983 Technical Use

STATIC R44 NFPA 13.0



R0460WB



Excellent static rope for everyday work at height designed for general use for rope access, rescue and for manipulation with the objects. Meet NFPA 1983 General Use requirements.

Weight: 109.6 g/m
Strength: 48.2 kN
Length: pack: 150, 200, 300 ft / 46, 61, 92 m
• coil: 330, 600, 660 ft / 100, 183, 200 m
Diameter: 13.0 mm • 1/2 in
Static elongation:
3.4% (at 3.5 kN, 300 lbs)
5.4% (at 2.7 kN, 600 lbs)
7.6% (at 4.4 kN, 1000 lbs)
NFPA 1983 General Use



HARNESSES

ROPES

CARABINERS

HELMETS

ICE LINE


HARDWARE

SLINGS

ACCESSORIES

ACCESSORY CORD


L0041 - L0081



Suitable for a multitude of uses, SINGING ROCK accessory cords are strong and supple.

- easy handling
 - strong
 - multitude of uses
- Diameters: 4, 5, 6, 7 and 8 mm

CE 1019 • EN564 • 



HAMMER CORD

2 mm L0021

3 mm L0031



Durable, strong, easy to tie, for example for securing climbing equipment, backpack, tools or laces. Suitable for climbing purposes, guiding or work at height.
Strength: 1.2 / 1.9 kN

ROPE PROTECTOR

W8100B



Protects rope sheath against abrasion on rough surfaces.

50/70/100/120 cm • 20/28/40/48 in
Material: PVC
Colour: mix colours

DEFENDER

W1027B



Protects rope sheath against abrasion on rough surfaces.

Allows to put 2 ropes in.
80/120 cm • 32/48 in
Material: Cortex

EDGE ROLLER

K0050OS03 - set

**Compact light edge roller for rope protection made from aluminium alloy.**

- suitable for working on the sharp edges
- perfectly copy the terrain
- protects a moving rope against the abrasion.
- fully adjustable to any work situation
- intended for safe work at height or heavy weights hauling.
- parts are connected by maillons. Number of parts can be added as needed.

Weight: 777 g • 27.41 oz

EDGE ROLLER – PART

K0050OS01



- it is possible to extend the size of Edge Roller set by adding the separate modul

Weight: 232g • 8.18 oz

THERMOCUTTER

X0004GB



Ideal machine for cutting the ropes and accessory cords. Compact hand-held. The blade heats quickly. For save and fast cutting the ropes.

ROPE MARKER

X0015XX

**When you need to mark your rope, use SINGING ROCK Rope Marker**

- with dark ink and easy-to-use design, you'll never be left wondering in those unsure situations
- when the middle marking fades you can mark it again with this specially formulated rope marker
- you can mark the centre of ropes or any other part of the harness or sling.


For use with: PA, PP, PES, PE.

DYNAMIC ROPES

CE • EN 892 • *pack – 30, 40, 50, 60, 70, 80, 100 m • spool – 200 m







	name / code	colour	length*	diamet. m	weight mm	static elong. g/m	dynamic elong. %	falls %	impact force	type kN
	ICON DRY L0384RX	red	30 – 200	9.3	56	7.5	34	5	8.6	single
	ICON L0380YX	yellow	30 – 200	9.3	56	7.5	34	5	8.6	single
	HERO DRY L0524GW	blue	30 – 200	9.6	50	5.1	35	8	7.9	single
	HERO L0520GW	white	30 – 200	9.6	50	5.1	35	8	7.9	single
	KATA DRY L0580AA	blue	30 – 200	9.7	61	9.0	30	5	7.7	single
	KATA L0570AA	blue	30 – 200	9.7	61	9.0	30	5	7.7	single
	STORM DRY L3044AG	blue	30 – 200	9.8	65	7.9	35	9	9.1	single
	STORM L3040GA	green	30 – 200	9.8	65	7.9	35	9	9.1	single
	GYM L3050RY	red	30 – 200	10.1	68	7.4	37	6	7.9	single
	MYSTIC DRY L0534AG	rainbow	30 – 200	10.1	68	5.7	32	9	7.9	single
	MYSTIC L0530RA	rainbow	30 – 200	10.1	68	5.7	32	9	7.9	single
	SCORE L0360GG	green	30 – 200	10.1	66	7	32	8	9.1	single
	DURAN L0340AX	blue	30 – 200	10.4	70	7.1	31	9	9.1	single
	PATRON L0540YX	yellow	30 – 200	11.0	79	5.3	31	16	9.1	single
	ACCORD L0510AG	blue	30 – 200	8.3	43	9 / 6.4	32 / 34	5 / 15	5.9 / 9.7	half / twin
	ACCORD L0510GA	green	30 – 200	8.3	43	9 / 6.4	32 / 34	5 / 15	5.9 / 9.7	half / twin
	ACCORD DRY L0514OG	orange	30 – 200	8.3	43	9 / 6.4	32 / 34	5 / 15	5.9 / 9.7	half / twin
	ACCORD DRY L0514GO	green	30 – 200	8.3	43	9 / 6.4	32 / 34	5 / 15	5.9 / 9.7	half / twin
	GEMINI L3020RX	red	30 – 200	7.9	39	10.5 / 8	38 / 33	5 / 16	5.1 / 7.9	half / twin
	GEMINI L3020YX	yellow	30 – 200	7.9	39	10.5 / 8	38 / 33	5 / 16	5.1 / 7.9	half / twin

ROPE TERMINOLOGY:



STATIC ROPES

CE • EN 1891 •  pack – 30, 40, 50, 60, 70, 80, 100 m • spool – 100, 200 m

	name / code	strength kN	knot breaking force kN	stitched eye strength kN	static elongation %	number of falls	weight g/m	type
	STATIC R44 10,5 L0430	31.5	19.8	27.7	3.4	>15	72	A
	STATIC R44 11 L0450	34.9	22.3	28.5	3.2	>20	77	A
	STATIC 9 L0220	24.4	13.6	–	3.3	>15	54	B
	STATIC 10,5 L0230	30.4	18.6	24.3	3.3	>10	69	A
	STATIC 11 L0250	34.5	22.0	28.1	3.3	>20	80	A
	CONTRA 10.5 L026	30	18	–	2	>20	69	A

Some notes:

Type A rope – low stretch kernmantel rope designed for general use by persons in rope access including all kinds of work positioning and restraint; in rescue and in caving

Type B rope – low stretch kernmantel rope of a lower performance than type A ropes, requiring greater care in use (standard does not content other specification)

Static strength defined in the standard:

22 kN for the ropes of type A
18 kN for the ropes of type B
Another standard requirement says, the material used for rope production shall have the melting point higher than 195°C, so polyethylene or polypropylene are not suitable for the production of the ropes.

Rope elongation

The rope elongation shall not be higher than 5%, tested by loading the rope for 3 min with 150kg load (pretension 50 kg)








Dynamic performance

Fall test with two meters long rope terminated with figure-eight knots; fall factor 1.

The testing mass 100 kg for type A ropes, 80 kg for type B ropes.



ACCESSORY CORDS

CE • EN 1019 • EN 564 •  note: Hammer Cords L0002, L0003 do not fulfill EN standards and CE


	coil	diameter mm	weight g/m	strength kN	length m	ft
	L0021	2	2.8	1.2	100	328
	L0031	3	6.5	1.9	100	328
	L0041	4	12.6	3.2	100	328
	L0051	5	18.7	5	100	328
	L0061	6	23.2	9	100	328
	L0071	7	35.1	11.5	100	328
	L0081	8	39.8	16	100	328

SPELEO ROPES

CE • EN 1891 •  pack – 30, 40, 50, 60, 70, 80, 100 m • spool – 100, 200 m

		strength kN	knot breaking force kN	static elongation %	number of falls	weight g/m
	SPELEO R44 10.5	33.4	20	3.3	>15	72
	SPELEO 10.5	29.4	17.2	4.5	>10	71








CARABINERS



CLIMBERS FOR CLIMBERS



KEYLOCK

for easy manipulation

Keylock is an extremely simple and ingenious locking system that solves the problems associated with the traditional design of carabiners.

It eliminates any risk of ropes or slings becoming entangled in the gate or in the carabiner nose when it is being connected or released.

Neither the gate, which is completely cylindrical, nor the nose has any sharp edges. Ropes and slings do not, therefore, come into the contact with any cutting edges.



HOT FORGING

The latest technology in manufacturing carabiners, where the aluminum alloy is heated to reach very plastic state when being forged, in other words when it takes the final shape. This allows the metal to be formed more easily and to be moved to the areas where it is needed and removed from the areas where it is not necessary. Compared to the cold forged carabiners, hot forged can provide better strength/weight ratio and resistance.



SERIAL UNIQUE NUMBER

identification of metal parts

For better traceability and inspection recording the Singing Rock metal parts are marked with the serial unique number.



SCREW LOCK



TWL-TWIST LOCK



TRIPLE LOCK



BORA CARABINERS

Versatile pear-shaped HMS carabiners designed for multiple uses related to belaying or anchoring when climbing or working at heights. Manufactured with the latest features (Keylock, Hot forging, I-beam construction) to ensure long-lasting quality and maximum strength.

BORA GP / SCREW

K0107EP00
black K0107BP00




HMS carabiner designed specifically to eliminate the dangers of cross loading.

- safety wire gate keeps the carabiner in its proper orientation
- hot-forged I-beam construction offers an improved strength/weight ratio
- large rope bearing area for better rope glide and reduced wear on the carabiner
- screw locking sleeve for great handling and effective locking
- very popular for climbing gyms and ropes centres
- each carabiner is individually tested for the strength 10 kN
- serial unique number for better traceability and inspection

Strength: \blacktriangleleft 23 \blacktriangleright 8 \square 8 kN

Gate opening (d): 22 mm

Weight: 64 g • 2.26 oz

CE 1019 • EN 12275 • EN 362 • 

BORA / SCREW BORA / TWL BORA / TRIPLE LOCK

screw K0107EE00
screw black K0107BB00
TWL K0108EE00
TWL black K0108BB00
triple lock K0119EE00
triple lock black K0119BB00



BORA SCREW



BORA TWL



BORA TRIPLE LOCK

Versatile pear-shaped HMS locking biner designed for belaying, rappelling and anchor building.

- hot-forged I-beam construction makes the carabiner extremely strong, stiff and light
- large rope bearing area for better rope glide and reduced wear on the carabiner
- pear-shaped basket facilitates belaying with the MÜNTER hitch or other belay devices
- angled snag free Keylock nose for smooth clipping and unclipping maneuvers
- opening and basket area are large enough to easily accommodate the clove hitch
- available with screw, twist and triple lock gate, all of them easy to handle
- for better gear management the screw gates are in different colors
- each carabiner is individually tested for the strength 10 kN
- serial unique number for better traceability and inspection

Strength: \blacktriangleleft 23 \blacktriangleright 8 \square 8 kN

Gate opening (d): 22 mm

Weight:

Screw: 63 g • 2.22 oz

TWL/Triple lock: 68 g • 2.4 oz

CE 1019 • EN 12275 • EN 362 • 

COLT / SCREW

K0112EE00
black K0112BB00



Our smallest, super light locking carabiner. Ideal for belaying and anchor building on trad and alpine climbs.

- hot-forged I-beam construction makes the biner very light and still extremely strong with 11 kN gate open rating
- angled snag free Keylock nose for smooth clipping and unclipping maneuvers
- ergonomic shape and gate position designed to provide large opening and large basket area
- screw locking sleeve for great handling and effective locking
- for better gear management the screw gates are in different colors
- each carabiner is individually tested for the strength 10 kN
- serial unique number for better traceability and inspection

Strength: ◀ 26 ▶ 8 ◻ 11 kN
Gate opening (d): 18 mm
Weight: 48 g • 1.69 oz
€€ 1019 • EN 12275 • EN 362 •

COLT / STRAIGHT COLT / BENT

straight K0111EE00
straight black K0111BB00
bent K0110EE00
bent black K0110BB00



Full size size hot forged quickdraw carabiner with solid gate. This real all-round biner is engineered to be equally used for both sport and trad climbing.

- hot-forged I-beam construction makes the biner very light and still extremely strong with 11 kN gate open rating
- the overall shape and gate position designed to provide large opening and large basket area
- angled snag free Keylock nose for smooth clipping and cleaning the bolts
- shaped grooves on the straight gate facilitate clipping and unclipping
- large rope bearing radius reduces the wear of rope
- available with straight and bent gate
- each carabiner is individually tested for the strength 10 kN

Strength: ◀ 26 ▶ 8 ◻ 11 kN
Gate opening (d): 21 mm
Weight: 42 g • 1.48 oz
€€ 1019 • EN 12275 •

COLT WIRE / STRAIGHT COLT WIRE / BENT

straight K0113EE00
bent K0120EE00



Full size hot forged carabiner with a wire gate. This real all-round biner is engineered to be equally used for sport, trad and ice climbing.

- hot-forged I-beam construction makes the biner very light and still extremely strong with 11 kN gate open rating
- hooded nose for smooth clipping and unclipping
- the overall shape and gate position designed to provide large opening and large basket area
- large rope bearing radius reduces the wear of rope
- available with straight and bent wire gate
- each carabiner is individually tested for the strength 10 kN

Strength: ◀ 26 ▶ 8 ◻ 11 kN
Gate opening (d): 22 mm
Weight: 36 g • 1.27 oz
€€ 1019 • EN 12275 •

VISION

straight K0009EE00
bent K0025EE00



Our lightest carabiner for your most difficult ascents.

with wire gate, anodized

↔ 25 kN ↕ 7 kN ↔ 8 kN

Gate opening: (d) 19 mm

Weight: 33 g • 1.16 oz

CE 1019 • EN 12275 •

VISION STRAIGHT 6PACK

K0009EE60



The ultra-lightweight and user-friendly VISION 6PACK comes in six different colors, coordinating with different sizes of mobile belay devices, such as nuts and friends.

- very lightweight hot-forged construction
- large rope-bearing surface
- lightweight and versatile standard size for all-around use
- does not freeze up in alpine and winter conditions
- compact shape and minimal pack size
- wire gates reduce whip-lash effect on the gate in a fall
- the color scheme fits the established camming devices
- each carabiner is individually tested for the strength 10 kN

Strength: ↔ 25 kN ↕ 7 kN ↔ 8 kN

Gate opening (d): 19 mm

Weight: 33 g • 1.16 oz

CE 1019 • EN 12275 •

MIRAGE STRAIGHT 6PACK

RK001EE63

NEW



Light alloy wire gate carabiners for all-around use. Designed with focus on light weight and excellent handling.

- very lightweight hot-forged construction with wire gate
- wire gates do not freeze up in alpine and winter conditions
- wire gates reduce whip-lash effect on the gate in a fall
- large rope-bearing surface
- compact shape and minimal pack size
- anodized finishing increases corrosion resistance
- 3 black and 3 silver carabiners in the pack
- manufactured in the Czech Republic
- unique serial number

Weight: 31 g • 1 oz

Material: aluminum alloy, stainless steel

Strength major axis: 25 kN

Strength minor axis: 8 kN

Strength open gate: 8 kN

Gate opening (d): 20 mm

CE 1019 • EN 12275 •

HECTOR / SCREW HECTOR / TRIPLE LOCK

screw K0114EE00
screw black K0114BB00
triple lock K0121EE00
triple lock black K0121BB00



Large versatile pear-shaped HMS carabiner with screw/triple lock gate designed for multiple uses mainly for belaying or anchoring belaying or anchoring. Due to high strength and large gate opening it is mainly used as a central carabiner when anchoring.

- angled snag free Keylock nose for smooth clipping and unclipping maneuvers
- rough notches on the screw / triple locking sleeve for easy manipulation even with gloves
- each carabiner is individually tested for a strength of 10 kN
- large rope bearing area for better rope glide and reduced wear on the carabiner
- gate opening and basket area are large enough to easily accommodate a big anchor point or more slings
- hot-forged I-beam construction makes the carabiner extremely strong, stiff and light
- serial unique number for better traceability and inspection

Strength: \blacktriangleleft 30 \blacklozenge 9 \blacktriangleright 8 kN
Gate opening (d): 26 mm
Weight: screw – 83 g / 2.9 oz
Triple – 89 g / 3.1 oz
CE 1019 • EN 12275 • EN 362

HECTOR BC / SCREW HECTOR BC / TRIPLE LOCK

screw BC K0114EC00
screw BC black K0114BC00
triple BC K0121EC00
triple BC black K0121BC00



Large versatile pear-shaped HMS carabiner with screw/triple lock gate and removable captive bar designed especially as a fixed connector in anchor systems or lanyards.

- captive bar keeps the carabiner in its proper orientation
- bar is easily removable with an Allen key no. 3
- this carabiner keeps your gear well-arranged and minimizes the chance of cross loading
- serial unique number for better traceability and inspection

Strength: \blacktriangleleft 30 \blacklozenge 9 \blacktriangleright 8 kN
Gate opening (d): 26 mm
Weight: screw – 85 g / 3 oz
Triple – 91 g / 3.2 oz
CE 1019 • EN 12275 • EN 362

OXY / SCREW
OXY / TWL
OXY / TRIPLE LOCK

Screw K0122EE05
Screw black K0122BB05
TWL K0122EE06
TWL black K0122BB06
Triple lock K0122EE07
Triple lock black K0122BB07



Hot-forged light alloy oval carabiners designed to be used especially with pulleys, ascenders and descenders.

- hot-forged I-beam construction makes the carabiner extremely strong, stiff and light
- rough notches on the locking sleeve for easy manipulation
- angled snag free Keylock nose for smooth clipping and unclipping
- almost oval shape makes the carabiner easy to turn around in device's attachment points, anchors or slings
- thanks to the oval shape, pulleys attached are loaded symmetrically
- large rope bearing area for better rope glide and reduced wear of the carabiner
- each carabiner is individually tested for a strength of 10 kN
- anodized finishing increases the corrosion resistance
- serial unique number for better traceability and inspection

Strength: ◀ 26 ⚡ 8 ▶ 7 kN
Gate opening (d): 21 mm
Weight:
Screw: 74 g • 2.61 oz
TWL/Triple lock: 81 g • 2.86 oz

CE 1019 • EN 12275 • EN 362

OXY BC / SCREW
OXY BC / TWL
OXY BC / TRIPLE LOCK

Screw K0123EC05
Screw black K0123BC05
TWL K0123EC06
TWL black K0123BC06
Triple lock K0123EC07
Triple lock black K0123BC07



Hot-forged light alloy oval carabiner with a removable captive bar.

- captive bar keeps the carabiner in its proper orientation
- the bar is easily removable with an Allen key no. 2
- this carabiner keeps your equipment well-arranged and minimizes the chance of cross loading
- missing captive bar does not affect the strength of the carabiner and it is allowed to use the carabiner without a bar
- serial unique number for better traceability and inspection

Strength: ◀ 26 ⚡ 8 ▶ 7 kN
Gate opening (d): 21 mm
Weight:
Screw: 76 g • 2.68 oz
TWL/Triple lock: 83 g • 2.93 oz

CE 1019 • EN 12275 • EN 362

OZONE / SCREW

K0016AA00
black matt K0016BB00



Oval carabiner,
key lock, screw gate
◆ 26 kN ◆ 10 kN ◻ 7 kN
Gate opening (d): 21 mm
Weight: 80 g • 2.82 oz
serial unique number
€€ 1019 • EN 362 • EN 12275

OZONE / TRIPLE LOCK

K0018AA00
black matt K0018BB00



Oval carabiner,
key lock, triple lock
◆ 26 kN ◆ 9 kN ◻ 7 kN
Gate opening (d): 21 mm
Weight: 85 g • 3 oz
serial unique number
€€ 1019 • EN 362 • EN 12275

OZONE / TWL

K0017AA00
black matt K0017BB00



Oval carabiner,
key lock, twist lock
◆ 26 kN ◆ 9 kN ◻ 7 kN
Gate opening (d): 21 mm
Weight: 85 g • 3 oz
serial unique number
€€ 1019 • EN 362 • EN 12275

ARTWALL

K4310PP00



Steel carabiner specially designed for long-term placement in climbing gyms

- center bar can be easily removed by alan key
- captive bar prevents the twisting of carabiner
- wire gate minimizes accidental opening of the gate
- zinc-coated steel provides longer lifetime than light alloy carabiners

◆ 30 kN ◆ 10 kN ◻ 10 kN
Gate opening (d): 25 mm
Weight: 130 g • 4.59 oz
€€ 1019 • EN 12275

VIA FERRATA / LOCK

K5330PE



Light alloy carabiner specially designed for via ferrata, rope parks and adventure centers

- quick and easy automatic spring locking
- big gate opening for clipping on big diameter wires
- key lock to avoid snagging when clipping and unclipping

◆ 30 kN ◆ 8 kN ◻ 9 kN
Gate opening (d): 21 mm
Weight: 90 g • 3.2 oz
€€ 0333 • EN 12275



COLT

K6715E011



Full size hot forged durable quickdraw with solid gates intended for sport climbing.

- top straight carabiner equipped with the Keylock system and a special shaped grooves which facilitates clipping and cleaning the bolts
- bottom bent carabiner with the Keylock system for smooth clipping and unclipping the rope
- bottom bent carabiner equipped with a rubber O-ring to hold the carabiner in the correct position and to facilitate clipping the rope
- durable and easy-to-grab vari-width 16/25 mm polyamide webbing
- each carabiner is individually tested for the strength 10 kN
- COLT quickdraw is reliable and durable solution for crag climbing and when working on routes

Strength:

Quickdraw sling: 22 kN

Carabiners: ⚡ 26 ⚡ 8 ⚡ 11 kN

Gate opening (d): 21 mm

Length of sling: 12 cm • 4.3 in

Weight: 99 g • 3.49 oz

CE 1019 • EN 566 • EN 12275 •

COLT MIX

K6716E011



Super versatile quickdraw with a snag-free Keylock carabiner on the top and a smooth-clipping wire biner on the bottom.

- COLT MIX combines smooth clippability and wiregate functionality
- wire gate eliminates gate flutter and freezing up in winter conditions
- hot-forged I-beam construction makes the biners very light and still extremely strong with 11 kN gate open rating
- durable and easy-to-grab vari-width 16/25 mm polyamide webbing
- top straight carabiner equipped with the Keylock system and a special shaped grooves which facilitates clipping and cleaning the bolts
- bottom wire carabiner equipped with a rubber O-ring to hold the carabiner in the correct position and to facilitate clipping the rope
- each carabiner is individually tested for the strength 10 kN

Strength:

Quickdraw sling: 22 kN

Carabiners: ⚡ 26 ⚡ 8 ⚡ 11 kN

Gate opening (d): 21 / 22 mm

Length of sling: 12 cm • 4.3 in

Weight: 93 g • 3.28 oz

CE 1019 • EN 566 • EN 12275 •

COLT WIRE

K6613E011



The lightest full size quickdraw engineered to be equally used for trad, alpine and ice climbing.

- full sized hot forged top and bottom carabiners with wire gates
- wire gates eliminate gate flutter and freezing up in winter conditions
- hooded nose for smooth clipping and unclipping
- bottom carabiner equipped with a rubber O-ring to hold the carabiner in the correct position and to facilitate clipping the rope
- 11 mm wide Dyneema® sling offers an excellent weight to strength ratio
- each carabiner is individually tested for the strength 10 kN

Strength:

Quickdraw sling: 22 kN

Carabiners: ⚡ 26 ⚡ 8 ⚡ 11 kN

Gate opening (d): 22 mm

Length of sling: 11 cm • 4.3 in

Weight: 83 g • 2.93 oz

CE 1019 • EN 566 • EN 12275 •

COLT 16

K6719E016



Full size hot forged durable quickdraw with solid gates intended for sport climbing.

- top straight carabiner equipped with the Keylock system and a special shaped grooves which facilitates clipping and cleaning the bolts
- durable 16 mm polyamide webbing
- each carabiner is individually tested for the strength 10 kN

Strength:

Quickdraw sling: 22 kN

Carabiners: \blacklozenge 26 \blacklozenge 8 \square 11 kN

Gate opening: (d): 21 mm

Length of sling: 11 cm • 4.3 in

Weight: 95 g • 3.35 oz

CE 1019 • EN 566 • EN 12275 •

COLT 16 MIX

K6720E016



Super versatile quickdraw with a snagfree Keylock carabiner on the top and a smooth-clipping wire biner on the bottom.

- COLT 16 MIX combines smooth clippability and wiregate functionality
- wire gate eliminates gate flutter and freezing up in alpine conditions
- durable 16 mm polyamide webbing
- each carabiner is individually tested for the strength 10 kN

Strength:

Quickdraw sling: 22 kN

Carabiners: \blacklozenge 26 \blacklozenge 8 \square 11 kN

Gate opening: (d): 21 / 22 mm

Length of sling: 11 cm • 4.3 in

Weight: 89 g • 3.14 oz

CE 1019 • EN 566 • EN 12275 •

COLT 16 WIRE

K6721E016



Full size quickdraw engineered to be equally used for trad, alpine and ice climbing.

- full sized hot forged top and bottom carabiners with wire gates
- wire gates eliminate gate flutter and freezing up in winter conditions
- durable 16 mm polyamide webbing
- each carabiner is individually tested for the strength 10 kN

Strength:

Quickdraw sling: 22 kN

Carabiners: \blacklozenge 26 \blacklozenge 8 \square 11 kN

Gate opening (d): 22 mm

Length of sling: 11 cm • 4.3 in

Weight: 83 g • 2.9 oz

CE 1019 • EN 566 • EN 12275 •

COLT 17 CM

K6715E017



Full size hot forged durable quickdraw with solid gates intended for sport climbing overhanging routes.

- hot-forged I-beam construction makes the biners very light and still extremely strong with 11 kN open gate rating
- top straight carabiner equipped with the Keylock system and a special shaped grooves which facilitates clipping and cleaning the bolts
- durable easy-to-grab vari-width 16/25 mm polyamide webbing
- 17 cm length of the webbing reduces the rope friction in the carabiners when climbing overhanging routes
- bottom bent carabiner with the Keylock system for smooth clipping and unclipping the rope
- bottom bent carabiner equipped with a rubber fix to hold the carabiner in the correct position and to facilitate clipping the rope
- each carabiner is individually tested for the strength 10 kN

Strength:

Quickdraw sling: 22 kN

Carabiners: ◀ 26 ⚡ 8 ◻ 11 kN

Gate opening (d): 21 mm

Weight: 105 g • 3.7 oz

CE 1019 • EN 566 • EN 12275 • 

VISION

K6604E011



Ultra light set with a straight and bent wire gate carabiners. Ideal partner for lightweight style.

Dyneema® webbing 11 mm

Strength:

Quickdraw sling: 22 kN

Carabiners: ◀ 25 kN ⚡ 7 kN ◻ 8 kN

Gate opening (d): 19 mm

Length of sling: 11 cm • 4.3 in

Weight: only 75 g • 2.64 oz

CE 1019 • EN 566 • EN 12275

ARTWALL SET

K6950



Steel quickdraw mainly made for long-term placement in the climbing gyms.

- captive bar can be easily removed by alan key
- captive bar prevents the twisting of carabiner
- wire gate minimizes accidental opening of the gate
- zinc-coated steel provides longer lifetime than light alloy carabiners
- both connectors eliminate a theft

Strength:

Polyamide webbing 20 mm: 22 kN

Carabiners: ◀ 30 kN ⚡ 10 kN ◻ 10 kN

Gate opening (d) 25 mm

Length: 13, 16, 20, 30 and 60 cm • 4, 6, 8, 12 and 24 in

Weight: 230 g [13cm] • 8.11 oz [4 in]

CE 1019 • EN 566 • EN 12275

MIRAGE 6PACK

K6722E611

NEW



Wire-gate quickdraws for all-around use. Designed with focus on light weight and excellent handling.

- ideal partner for lightweight style and winter ascents
- ergonomic design
- two hot forged wire gate carabiners MIRAGE
- wire gates do not freeze up in alpine and winter conditions and reduce a whip-lash effect on the gate in case of fall
- large rope-bearing surface
- compact shape and minimal pack size
- anodized finishing increases corrosion resistance
- PAD sling 16 mm wide and 11 cm long
- lower carabiner fixed in the right position by a rubber fix
- produced in the Czech Republic

Weight: 74 g (2.65 oz)


Material: light alloy, polyamide

Strength: sling: 22 kN, carabiners: ◀ 25 ▶ 8 ◻ 8 kN

Width: sling: 16 mm

Length: sling: 11 cm (4.3 in)

Gate opening (d): 20 mm

CE 1019 • EN 566 • EN 12275 • 



MIRAGE LONG

K6723E030 – 30 cm
K6723E050 – 50 cm

NEW



Wire-gate quickdraw for overhanging routes, multi-pitch sport and trad climbing. Designed with focus on light weight and excellent handling.

- ideal partner for lightweight style, overhanging sport routes, winter ascents, trad or multi-pitch sport climbing
- longer quickdraw sling reduces the rope friction in the carabiners
- two hot forged wire gate carabiners MIRAGE
- wire gates do not freeze up in alpine and winter conditions and reduce a whip-lash effect on the gate in case of fall
- large rope-bearing surface reduces the wear of rope
- compact shape and minimal pack size
- anodized finishing increases the corrosion resistance
- Dyneema® webbing 11 mm wide and 30 or 50 cm long
- lower carabiner fixed in the right position by a rubber fix
- produced in the Czech Republic

Weight: 79; 86 g • 2.79; 3.03 oz

Material: light alloy, Dyneema®
Strength: sling: 22 kN, carabiners: ⬠ 25 ⬡ 8 ⬢ 8 kN
Width: sling: 11 mm
Length: sling: 30, 50 cm • 11.8; 19.7 in
Gate opening (d): 20 mm

CE 1019 • EN 566 • EN 12275 • UIAA

MIRAGE ALPINE

K6724E016

NEW



Wire-gate quickdraw with 60 cm Dyneema® sling for trad climbing. Designed with focus on light weight and excellent handling.

- ideal partner for lightweight style, trad climbing and winter ascents
- 8 mm wide and 60 cm long Dyneema® sling is thin, strong, light which perfectly fits into wet conditions at alpine terrain
- longer sling reduces the rope friction in the carabiners
- sling allows to use the quickdraw at two lengths depending on the style of the route
- two hot forged wire gate carabiners MIRAGE perfectly fits into pitons, bolt hangers, or cam slings
- wire gates do not freeze up in alpine and winter conditions and reduce a whip-lash effect on the gate in case of fall
- large rope-bearing surface reduces the wear of rope
- compact shape and minimal pack size
- anodized finishing increases the corrosion resistance
- produced in the Czech Republic

Weight: 82 g • 2.9 oz
Material: light alloy, Dyneema®
Strength: sling: 22 kN, carabiners: ⬠ 25 ⬡ 8 ⬢ 8 kN
Width: sling: 8 mm
Length: sling: 60 cm • 23.6 in

Gate opening (d): 20 mm
CE 1019 • EN 566 • EN 12275 • UIAA

COLT 6PACK

K6715E611



Six full size hot forged durable quickdraws COLT with solid gates intended for sport climbing at reduced price

COLT 17 CM 6PACK

K6715E617



Ideal set for hard core sport climbers working on overhanging routes. Six full size hot forged durable Colt 17 cm quickdraws at reduced price.

COLT 16 6PACK

K6719E616



Full size hot forged durable quickdraws with a snagfree Keylock carabiners in the affordable set of 6 quickdraws.

COLT 16 MIX 6PACK

K6720E616



Super versatile quickdraws for all-round climbing in the favorable set of 6 quickdraws.

COLT 16 WIRE 6PACK

K6721E616



Great set of 6 full sized hot forged quickdraws for trad, alpine and ice climbing.

VISION 6PACK

K6604E611



Ultra light set with six VISION quickdraws for lightweight style at reduced price.

D STEEL /
SCREW

K4080ZO



with screw gate, key lock,
zinc plated
 ◆ 50 kN ◆ 13 kN □ 20 kN
 Gate opening (d): 25 mm
 Weight: 255 g • 9 oz
 serial unique number
 C€ 1019 • EN 362

D STEEL /
TRIPLELOCK

K4081ZO



with triple lock gate, key lock,
zinc plated
 ◆ 50 kN ◆ 13 kN □ 20 kN
 Gate opening (d): 25 mm
 Weight: 267 g • 9.42 oz
 serial unique number
 C€ 1019 • EN 362

OVAL STEEL /
SCREW

K4241ZO05



with screw gate, key lock,
zinc plated
 ◆ 30 kN ◆ 9 kN □ 8 kN
 Gate opening (d): 18 mm
 176 g • 6.21 oz
 serial unique number
 C€ 1019 • EN 362

OVAL STEEL /
TRIPLELOCK

K4241ZO07



triple lock gate, key lock,
zinc plated
 Gate opening (d): 18 mm
 Weight: 176 g • 6.21 oz
 ◆ 30 kN ◆ 9 kN □ 8 kN
 serial unique number
 C€ 1019 • EN 362



MINI OVAL

K82006Z



Ø 6 mm • 4 kN
Gate open. (d) 7.5 mm
zinc-plated
Weight: 33 g • 1.16 oz

SMALL OVAL

K82008Z



Ø 8 mm • 35 kN
Gate open. (d) 11 mm
zinc-plated
Weight: 77 g • 2.72 oz
CE 0082 • EN 362
EN 12275 •

SMALL DELTA

K82207Z



Ø 7 mm • 4 kN
Gate open. (d) 8.5 mm
zinc-plated
Weight: 58 g • 2.1 oz

BIG DELTA

K82210Z



Ø 10 mm • 45 kN
Gate open. (d) 12 mm
zinc-plated
Weight: 153 g • 5.4 oz
CE 0082 • EN 362
EN 12275 •

BIG D

K82310Z



Ø 10 mm • 45 kN
Gate open. (d) 10 mm
zinc-plated
Weight: 153 g • 5.4 oz
CE 0082 • EN 362
EN 12275 •

BIG SQUARE

K82410Z



Ø 10 mm • 45 kN
gate opening 12 mm
zinc-plated
166 g • 5.86 oz
CE 0082 • EN 12275
• EN 362 •

BIG TWIST

K82508Z



Ø 8 mm • 32 kN
gate opening 17,5 mm
zinc-plated
• 106 g • 3.74 oz
CE 0082 • EN 12275
• EN 362 •

PORTER

K9000BB03



Plastic holder for racking ice screws, pitons and industrial tools.

- for racking ice screws, pitons and industrial tools on the harness
- easy clipping and un-clipping
- the nose on the upper part allows to set away some staff in order to access staff on the bottom.
- rubber part fixes the Porter on place and prevent it from rotation

Max. load: 5 kg
 Weight: 32 g • 1.13 oz
 Color: black
 Material: plastic

MINI PEAR

K5052EE00



mix colour
 16 g • 0.56 oz
 gate opening (d) 11 mm
 not for climbing

MINI D

K5182EE00



mix colour
 25 g • 0.88 oz
 gate opening (d) 14 mm
 6 kN
 not for climbing

MINI D SCREW

K0027BY00



black colour
 28 g • 0.99 oz
 gate opening (d) 12 mm
 3 kN
 not for climbing

QUICKDRAW RUBBER FIX

11 mm C0084XX11
 16 mm C0084XX16



Ideal for fixing the carabiner to the quickdraw sling.

- holds the carabiner in the correct position and avoids the unwanted twisting
- facilitates rope clipping
- pack of 10 pieces

















Color: black
 Width: 11 mm, 16 mm










WARNING:

ALL ACCESSORY CARABINERS ARE NOT FOR CLIMBING!


Accessory carabiners are not load-bearing! They are not designed to hold human's weight. Do not use them for protection or belaying!

CARABINERS

	code	colour / surface	material	EN12275		EN362		↕	⊖	gate open. mm	weight	
				sport	work	kN	kN				g	oz
	BORA SCREW K0107EE00 K0107BB00	orange black	AL alloy	✓	✓	23	8	8	22	63	2,2	
	BORA TWL K0108EE00 K0108BB00	grey black	AL alloy	✓	✓	23	8	8	22	68	2,4	
	BORA TRIPLE LOCK K0119EE00 K0119BB00	orange	AL alloy	✓	✓	23	8	8	22	68	2,4	
	BORA GP SCREW K0107EP00 K0107BP00	grey	AL alloy	✓	✓	23	8	8	22	64	2,3	
	COLT SCREW K0112EE00 K0112BB00	silver black	AL alloy	✓	✓	26	8	11	18	48	1,7	
	COLT STRAIGHT K0111EE00 K0111BB00	grey black	AL alloy	✓	✓	26	8	11	21	42	1,5	
	COLT BENT K0110EE00 K0110BB00	yellow black	AL alloy	✓	x	26	8	11	21	42	1,5	
	COLT WIRE STRAIGHT K0113EE00	silver	AL alloy	✓	x	26	8	11	22	36	1,3	
	COLT WIRE BENT K0120EE00	blue	AL alloy	✓	x	26	8	11	22	36	1,3	
	VISION STRAIGHT K0009EE00	brown	AL alloy	✓	x	25	7	8	19	33	1.16	
	VISION BENT K0025EE00	red	AL alloy	✓	x	25	7	8	19	33	1.16	
	MIRAGE RK001EE63	black silver	AL alloy	✓	x	25	8	8	20	3	1.0	
	HECTOR SCREW K0114EE00 K0114BB00	blue black	AL alloy	✓	✓	30	9	8	26	83	2.9	
	HECTOR TRIPLE LOCK K0121EE00 K0121BB00	blue black	AL alloy	✓	✓	30	9	8	26	89	3.1	
	HECTOR BC SCREW K0114EC00 K0114BC00	blue black	AL alloy	✓	✓	30	9	8	26	85	3	
	HECTOR BC TRIPLE K0121EC00 K0121BC00	blue black	AL alloy	✓	✓	30	9	8	26	91	3.2	

	code	colour / surface	material	EN12275	EN362	↔	↕	⊙	gate open. mm	weight g	weight oz
				sport	work	kN	kN	kN			
	OXY SCREW K0122EE05 K0122BB05	yellow black	Al alloy	✓	✓	26	8	7	21	81	2.86
	OXY TWL K0122EE06 K0122BB06	yellow black	Al alloy	✓	✓	26	8	7	21	81	2.86
	OXY TRIPLE LOCK K0122EE07 K0122BB07	yellow black	Al alloy	✓	✓	26	8	7	21	81	2.86
	OXY BC SCREW K0123EC05 K0123BC05	yellow black	Al alloy	✓	✓	26	8	7	21	76	2.93
	OXY BC TWL K0123EC06 K0123BC06	yellow black	Al alloy	✓	✓	26	8	7	21	76	2.93
	OXY BC TRIPLE LOCK K0123EC07 K0123BC07	yellow black	Al alloy	✓	✓	26	8	7	21	76	2.93
	OZONE SCREW K0016AA00 K0016BB00	blue black	Al alloy	✓	✓	26	10	7	21	80	2.8
	OZONE TWL K0017AA00 K0017BB00	blue black	Al alloy	✓	✓	26	9	7	21	85	3
	OZONE TRIPLE LOCK K0018AA00 K0018BB00	blue black	Al alloy	✓	✓	26	9	7	21	85	3
	ARTWALL K4310PP	silver	steel	✓	x	30	10	10	25	125	4.4
	VIA FERRATA K5330PE	silver	Al alloy	✓	x	30	8	9	26	87	3.1
	D STEEL SCREW K4080ZO	zinc-plated	steel	x	✓	50	13	20	25	255	9
	D STEEL TRIPLE LOCK K4081ZO	zinc-plated	steel	x	✓	50	13	20	25	267	9.4
	OVAL STEEL SCREW K4241ZO05	zinc-plated	steel	x	✓	30	9	8	18	176	6.2
	OVAL STEEL TRIPLE LOCK K4241ZO07	zinc-plated	steel	x	✓	30	9	8	18	195	6.8





Jan "Tráva" Trávníček, Ama Dablam 6812 m • Photo: Petr Jan Juračka



HELMETS



CLIMBERS FOR
CLIMBERS

PENTA


blue C0071AA00
 red C0071RR00
 grey C0071SS00
 white C0071WW00



Extremely lightweight, super-comfortable and fully ventilated climbing helmet.

All this combined with a maximum head protection. For its comfort and lightweight design is ideal for sport climbing, mountaineering, trad climbing or via ferrata.

- Co-molded expanded polystyrene foam and hard polycarbonate shell engineered to ensure maximal head protection and still keep lightweight and low profile
- Narrow straps of retention system are very soft and light and do not press as standard hard-plastic headbands
- Soft (webbing made) rear adjustment system (headband) conforms better to the head and provides compact storage in the backpack
- Extended chin strap length allows to wear a hat under the helmet
- 4 headlamp clips are imbedded to avoid snagging, robust for easy handling and secure attachment of any headlamp on the market
- 11 vents and air channels built in the foam facilitate excellent ventilation
- Inside padding is fully removable and washable
- Available in 4 color versions

Weight: 205 g • 7.23 oz
 Color: blue, grey, red, white
 Size: UNI (51-60 cm)
 CE • EN 12492 • 



HEX

C0900

NEW



Durable, fully ventilated helmet for climbing, mountaineering and other rope activities. Due to its durability, ventilation and versatility, it is suitable for both sport and trad climbing, via ferrata or rope parks.

- durable EPP + ABS shell protects against falling objects and guarantees a high degree of protection against impact force, including repeated impact force
- the "OPEN CELL" construction with 35 ventilation holes with a total area of 108 cm² guarantees maximum ventilation
- easy and quick size adjustment mechanism in the back of the helmet
- chin strap made of a soft and wide webbing provides maximum comfort
- inner padding is made as one piece, which prevents the loss of smaller parts and holds better
- inner padding is removable and washable
- integrated "EASY CLIP" front clips for reliable attachment of a headlamp, their shape prevents jamming of a hood / slings
- the "UNI FIX" elastic system on the backside simply attaches any headlamp or ski goggles
- available in two sizes (M 52/58cm a L 55/61cm)
- modern design and 5 colors

Size M (52-58 cm):

- ice white C0900WX03
- arnica yellow C0900YX03
- garish blue C0900MX03
- mountain lake azure C0900AX03
- fox red C0900RX03

Size L (55-61 cm):

- ice white C0900WX04
- arnica yellow C0900YX04
- garish blue C0900MX04
- mountain lake azure C0900AX04
- fox red C0900RX04

Weight: M 300 g • 10.6 oz, L 330 g • 11.6 oz (± 5%)
CE • EN 12492





HARNESSES

ROPES

CARABINERS

HELMETS

ICE LINE


HARDWARE

SLINGS

ACCESSORIES



ICELINE



CLIMBERS FOR CLIMBERS

BANDIT

with hammer RK003YX00H
with adze RK004YX00A

NEW



BANDIT VERSATILE ICE AXE FOR TECHNICAL MOUNTAINEERING AND ICE CLIMBING

ERGONOMIC HEAD WITH OPTIMALLY BALANCED WEIGHT FOR A PERFECT SWING AND PLACEMENT

HARDENED STEEL REPLACEABLE ICE OR DRY PICK

REMOVABLE EXTRA PICK WEIGHT FOR STRONGER SWING

REMOVABLE HOOK RHINO FOR HIGHER GRIP

HARDENED STEEL HAMMER EASILY REMOVABLE OR REPLACEABLE WITH ADZE

HEAD CARABINER HOLE IS BIG ENOUGH TO PLACE ANY CARABINER ON THE MARKET

CURVED SHAPE ENABLES COMFORTABLE CLIMBING IN A STEEP TERRAIN

ERGONOMIC AND ANTI-SLIP HANDLE FROM DUAL-DENSITY PLASTIC FOR THE PERFECT GRIP

HOLE FOR CARABINER OR BUNGEE TETHER

REMOVABLE BOXER FINGER PROTECTOR FOR COMFORTABLE LEASHLESS CLIMBING

Versatile ice axe for a wide range of use. Given its modular design, the ice axe can be adapted to a particular ascent. Especially suitable for demanding technical mountaineering and ice climbing.

- Bent shaft makes hooking in steep ice or rock easy while creating an optimum grip angle.
- Hot forged head allows use of adze/hammer and choice of ice/dry pick. For demanding mixed climbing, the ice axe can be used without adze/hammer.
- Head shape is designed so that it can be jammed into the cracks and to provide support for climbing in soft snow. The weight of the head is concentrated in the trajectory of the swing making penetration into hard ice as easy as possible. Possible to connect a carabiner to the head.
- Ergonomically shaped handle is made of dual-density plastic for thermal insulation and safe grip. A carabiner or "Bungee" tether may be attached to the spike.
- "Boxer" protects fingers against injury and getting drenched and enables leashless climbing. "Rhino" hook is designed for higher grip in demanding ice/mixed climbing or, in contrast, in climbing snow slopes. You may remove both accessories and get a light ice axe for classic technical mountaineering.
- Removable extra pick weights MASS for stronger swing improve pick penetration into the hardest ice.
- Included with ICE pick

Weight of fully mounted ice axe (ice pick, Mass, hammer/adze, Boxer, Rhino)
660 g • 23.28 oz
Length: 50 cm (20 in)

Material:

Pick – chromoly steel
Head, spike, shaft – aluminium alloy
Grip – dual-density plastic
Mass – stainless steel

CE 1019 • EN 13089
Ice/dry pick type 2 (T)
Shaft type 2 (T)

EDGE

adze RK009AX00A
hammer RK008AX00H

NEW



Material:
spike, pick – chromolly steel
head, shaft – aluminium alloy

Weight of fully mounted ice axe
(EDGE pick, hammer/adze)
without the leash: 555 g • 19.56 oz
Length: 54 cm (21 in)

The performance of this tool is situated between classical ice axe and modern technical tool. It combines the advantages of both: curved shaft for large clearance useful in technical terrain and traditional spike that penetrates the snow easily when climbing snow slopes. It is the best choice for steep couloirs and classical alpine terrain.

- Bent shaft makes hooking on ice bulges or rock easy while creating an optimum grip angle.
- Hot forged head allows use of adze/hammer and pick replacement. If focused on the lowest weight, the ice axe can be used also without adze/hammer.
- The EDGE pick is aggressive enough for hard ice and moderate mixed climbing and also has a smooth grip zone which protects your gloves when holding the head.
- Head shape is designed so that it can be jammed into the cracks and to provide support for climbing in soft snow. Hole in the head is big enough to fit any carabiner.
- The spike is narrow and penetrates the snow easily. A carabiner or “Bungee” tether may be attached to its eye.
- The leash FIX PLUS included

CE 1019 • EN 13089
EDGE pick type 2 (T)
Shaft type 2 (T)

WIZARD

RK005TX0

NEW



Light ice axe designed for traditional alpine mountaineering.

- Curved shaft under the head makes climbing in icy or mixed terrain easier while the bottom straight part easily penetrates snow. The shaft is made of high-quality 7075-class aluminium alloy. The bottom part includes an anti-slip grip.
- Pick is made of durable chromolly steel and it easily penetrates even hard snow or alpine ice.
- Adze is designed for easy cutting of steps or snow platforms.
- The ice axe head is ergonomically shaped and makes self-arrest maneuver easier.
- Holes in the head as well as in the spike are big enough for attaching a carabiner.
- Leash “Fix” included.

Weight: 445 – 495 g • 15.7 – 17.46 oz
Length: 55, 62, 69 cm • 22, 24, 27 in
CE 1019 • EN 13089
Shaft type 1 (B)

WIZARD LIGHT

RK006WX0

NEW



Our lightest ice axe designed especially for ski touring, altitude climbing and all adventures where every gram counts.

- curved shaft under the head makes climbing in icy or mixed terrain easier while the bottom straight part easily penetrates snow
- pick is made of durable chromoly steel and it easily penetrates even hard snow or alpine ice
- adze is designed for easy cutting of steps or snow platforms
- ice axe head is ergonomically shaped and makes self-arrest manoeuvre easier
- holes in the head is big enough for attaching a carabiner
- without steel spike
- bottom part of the shaft is sealed against snow and equipped with a hole for attaching a carabiner
- FIX AND BUNGEE SINGLE leashes compatible

Weight: 390, 415 g • 13.76 – 14.64 oz
Length: 52, 59 cm (20, 23 in)

€ 1019 • EN 13089
Shaft type 1 (B)

MERLIN

RK007BX0

NEW



Light ice axe designed for glacier tours and easy snow ascents in the mountains.

- Classic straight shaft is made of high-quality 7075-class aluminium alloy.
- Pick is made of durable chromoly steel and it easily penetrates even hard snow or alpine ice.
- Adze is designed for easy cutting of steps or snow platforms.
- Ice axe head ergonomically shaped especially for holding when walking.
- Holes in the head as well as in the spike are big enough for attaching a carabiner.
- Leash "Fix" included.

Weight: 455 – 505 g • 16.05 – 17.81 oz
Length: 58, 65, 72 cm (23, 26, 28 in)

€ 1019 • EN 13089
Shaft type 1 (B)

LUCIFER III TECH



RK207AX00T

NEW



Extra lightweight and versatile chromoly crampons with replaceable front points. Designed for climbing steep icefalls, difficult mixed routes and mountaineering.

- extra lightweight design alongside with durable chromoly construction
- modular construction for both mono and dual front points
- adjustable length of front points
- aggressive front teeth provide additional support and extra balance
- back facing teeth for balance on free standing pillars and columns
- down facing teeth for stability on ice bulges
- patented stainless steel Rock&Lock buckle enables fast and easy fastening and releasing the webbing
- tool-free length adjustment
- front points and frame are made of durable hardened chromoly steel
- BOUNCER anti-snow plates included
- budget-wise spare parts
- available with fastening system for rigid mountaineering boots with a rim
- front toe bail is possible to change for toe bail Semi-Classic for the boots with the rim on the heel only and toe bail SKI for touring ski boots

Weight: 960 g (33,9 oz) / with monopoint 910 g (32,1 oz)
Size: 37 - 47 EU

FAKIR III CLASSIC

RK206AX00C

NEW



All-round lightweight twelve-point crampons for classic mountaineering. Designed specially for glacier tours and steep snow slopes.

- asymmetrical shape of crampons ideally adapts to the boot and the front points thus providing maximum efficiency in a steep terrain
- lowered teeth profile provides better stability while keeps traction
- toolfree size adjustment
- frame is made of hardened chromoly steel
- center bar made of flexible stainless steel for better walking comfort
- BOUNCER anti-snow plates included
- fastening system suitable for softer trekking boots without the rim

Weight: 810 g (28.6 oz)
Size: 37 - 47 EU

FAKIR III SEMI-CLASSIC



RK206AX00S

NEW



All-round lightweight twelve-point crampons for classic mountaineering. Designed for all terrain from glacier tours to steep snow slopes or classic ice couloirs.

- asymmetrical shape of crampons ideally adapts to the boot and the front points thus providing maximum efficiency in a steep terrain
- lowered teeth profile provides better stability while keeps traction
- toolfree size adjustment
- frame is made of hardened chromoly steel
- patented stainless steel Rock&Lock buckle enables fast and easy fastening and releasing the webbing
- BOUNCER anti-snow plates included
- fastening system suitable for rigid mountaineering boots with the rim on the heel

Weight: 900 g (31.7 oz)

Size: 37 – 47 EU

CE • EN 893

FAKIR III TECH



RK206AX00T

NEW



All-round lightweight twelve-point crampons for classic mountaineering. Designed for all terrain from glacier tours to steep snow slopes or classic ice couloirs.

- asymmetrical shape of crampons ideally adapts to the boot and the front points thus providing maximum efficiency in a steep terrain
- lowered teeth profile provides better stability while keeps traction
- toolfree size adjustment
- frame is made of hardened chromoly steel
- patented stainless steel Rock&Lock buckle enables fast and easy fastening and releasing the webbing
- BOUNCER anti-snow plates included
- fastening system suitable for rigid mountaineering boots with the rim
- front toe bail is possible to change for toe bail Semi-Classic for the boots with the rim on the heel only and toe bail SKI for touring ski boots

Weight: 880 g (31 oz)

Size: 37 – 47 EU

CE • EN 893

ICE AXES SPARE PARTS

		colour	weight	parts	description
	HAMMER RK105BB000	black	44 g 1.55 oz	1	hammer for Bandit and Edge ice axe
	ADZE RK106BB000	black	49 g 1.73 oz	1	adze for Bandit and Edge ice axe
	PICK SPACER RK113BB000	black	12 g 0.42 oz	1	pick spacer for Bandit and Edge ice axe
	ICE PICK RK107BB000	black	133 g 4.69 oz	1	pick for Bandit ice axe for ice climbing
	DRY PICK RK108BB000	black	139 g 4.90 oz	1	pick for Bandit ice axe for drytooling
	EDGE PICK RK116XX000	black	116 g 4.09 oz	1	pick for EDGE ice axe
	MASS RK115XX000	stainless steel	50 g 1.76 oz	pair	stainless steel extra weight for ICE PICK
	GRIP STICKER RK114BB000	black	2 g 0.07 oz	1	anti-slip sticker for all kind of ice axes
	BOXER RK109BB000	black	10 g 0.35 oz	1	finger protector for Bandit ice axe
	RHINO RK110BB000	black	7 g 0.25 oz	1	finger rest for Bandit ice axe

CRAMPONS SPARE PARTS

		colour	weight	parts	description
	BOUNCER FAKIR III RK607AX000	blue	70 g 2.5 oz	pair	anti snow plates for Fakir III crampons
	BOUNCER LUCIFER III RK608AX000	blue	74 g 2.61 oz	pair	anti snow plates for Lucifer III crampons
	FRONTPOINT LUCIFER III RK609YY000	black	23 g 0.8 oz	4 pcs.	set of replaceable front points for Lucifer III crampons
	CENTER BAR III M/L RK610XX03 XL RK610XX05	black	100 g 3.5 oz	pair	CrMo center bar compatible with crampons FAKIR III and LUCIFER III. Size: M/L (EU 37-47), XL (EU 43-53)
	CENTER BAR III FLEX M/L RK611XX03 XL RK611XX05	silver	80 g 2.8 oz	pair	Flexible stainless spring steel center bar improves walking comfort and increases a lifetime of the crampons used with flexible boots. Compatible with the crampons FAKIR III and LUCIFER III M/L (EU 37-47), XL (EU 43-53)
	TOE BAIL SEMI-CLASSIC RK612XX000		66 g 2.3 oz	pair	Front bail semi-classic for crampons FAKIR II TECH, FAKIR III TECH, LUCIFER II TECH, LUCIFER III TECH
	TOE BAIL SKI RK613XX000		40 g 1.4 oz	pair	Front bail tech for touring ski boots. Compatible with crampons FAKIR II TECH, FAKIR III TECH, LUCIFER II TECH, LUCIFER III TECH



QUICK SPIN

112 cm RK303SX012
 17 cm RK303SX017
 22 cm RK303SX022

**Hardened steel ice screw with a light alloy hanger and a folding crank intended for ice climbing.**

- integrated folding crank makes it easier and faster to screw in during more advanced climbing
- crank is equipped with a fluted handle for a more secure grip with gloves on
- shaft is made of hardened CrMo steel for higher strength and durability
- anti-corrosion coating of the shaft ensures high resistance against rust
- four high-quality sharp teeth make gear placement easier
- thin profile of the shaft allows easy screwing even in over frozen ice (below -10°C)
- light alloy hanger is designed to provide good ergonomics while screwing, to ensure easy stacking on a holder and to allow clipping of two carabiners
- screw is available in three different lengths (variants are color-coded - blue, yellow, grey)

Length: 12, 17, 22 cm • 4.7, 6.7, 8.7 in
 Strength: \downarrow 8 kN (L12), \downarrow 10 kN (L17, L22), \rightarrow 5 kN (L12, 17, 22)
 Weight: 135 g • 4.4 oz (L17)
 Material: hardened steel, light alloy

CE1019 • EN 568 (L17 and L22 only)

SPIN

12 cm RK302SX012
 17 cm RK302SX017
 22 cm RK302SX022

**Hardened steel ice screw with light alloy hanger. The screw is best suited to be used for glacier tours and classic alpine climbs.**

- Shaft made of hardened steel for higher strength and durability
- Thin profile of the shaft allows easy screwing even in over-frozen ice (under -10°C)
- Anti-corrosion coating of the shaft ensures high resistance against the rust
- 4 millimeters thick anodized light alloy hanger ensures better grip while screwing
- Hanger is designed to provide easy stacking on the holder and to allow clipping of two carabiners
- Four high-quality sharp teeth make gear placement easier

Length: 12, 17, 22 cm • 4.7, 6.7, 8.7 in
 Strength: \downarrow 8 kN (L12), \downarrow 10 kN (L17, L22), \rightarrow 5 kN (L12, 17, 22)
 Weight: 125 g • 4.4 oz
 Material: hardened steel, light alloy
 CE1019 • EN 568 (L17 and L22 only)

BUNGEE

RK112WX000

NEW



A lightweight tether for leashless climbing. Bungee attaches ice tools to the harness which makes the loss of the tool impossible.

- two mini screw lock carabiners can be attached to the tool's spike or head
- V-shaped elastic webbing is short enough for tangle-free handling and may be stretched for maximum reach
- length of the lanyards can be extended from 80 up to 135 cm (incl. carabiners) and so allows free movements
- suitable for ice climbing, mix climbing and steep couloirs

**WARNING! Do not use as a fall absorber!
Do not use as a belay stance lanyard!**

Strength: 300 kg
Gate opening (d): 12 mm
Weight: 94 g • 3.32 oz
Length: 80 – 135 cm incl. carabiners
Material: 85% PAD, 0,5% PES, 14.5% elastic fibre
carabiner – aluminium alloy

BUNGEE SINGLE

RK117WX000

NEW



Lightweight tether for attaching the ice tools to the harness

- prevents lost or fall of the ice axes
- mini screw lock carabiner can be attached to the tool's spike or head
- elastic webbing is short enough for tangle-free handling and may be stretched for maximum reach
- length of the lanyard can be extended from 80 up to 120 cm (incl. carabiner) and so allows free movements
- suitable for glacier walking and mountaineering

**WARNING! Do not use as a fall absorber!
Do not use as a belay stance lanyard!**

Color white/yellow
Weight 47 g • 1.66 oz
Material 85% PAD, 0.5% PES, 14.5% elastic fibre; light alloy
Strength 300 kg
Length 80 - 120 cm (incl. carabiner)
Gate opening (d) 12 mm

FIX

RK111BY000



Simple leash with minimal weight for MERLIN and WIZARD ice axes.

Strength: 200 kg (2 kN)

Weight: 24 g • 0.85 oz

Material: Polyamide

FIX PLUS

RK111BY001



Advanced leash with padding and easy releasing/tightening system.

- padding provides better comfort in a wrist area

- The leash can be operated by one hand only: hook and pull the loop with hammer/adze to release from wrist and simply load for tightening.

Max. load: 100 kg

Weight: 40 g • 1.4 oz

Material: Polyamide



CRAMPON BAG

RK251XX000



Protective and storage bag for your crampons.

- designed to hold the crampons, also suitable to storage your ice screws or picks.
- protects your rope, jacket and backpack when transporting the crampons
- reinforced, durable bottom protects your pack from sharp objects.
- zippered mesh top panel allows water to escape and your equipment to dry
- an internal velcro strap keeps the crampons in place.

Color: black
Weight: 188 g
Dimension: 30 x 12 x 10 cm

ICE SCREWS BAG

RK351XX000



To protect and organize your ice screws.

- lightweight and convenient roll-up bag protects the threads and teeth of your ice screws
- saves the space when they are stored in your backpack.
- snag-free slots for 8 ice screws of the length 12 – 22 cm
- made from durable material
- zippered mesh pocket for small items

Color: black
Weight: 150 g (± 15g)
Material: PVC



ICE SCREW COVER

RK352XX000

NEW



Soft plastic slip-on cap to protect sharp teeth of ice screws.

- protects your clothing and other gear when ice screws are in your backpack without a protective bag
- also fits most other ice screws on the market
- sold in a package of 5 pcs.

Dimensions: 30 mm length, 20 mm diameter
Weight: 4 g • 0.14 oz
Material: plastic





HARNESSES

ROPES

CARABINERS

HELMETS



ICE LINE

HARDWARE

SLINGS

ACCESSORIES



HARDWARE



CLIMBERS FOR CLIMBERS

RAMA

grey K0043SX00
orange K0043OX00



Intuitive single rope belay device with enhanced braking feature. Designed for gym or single pitch sport climbing.

- reliable locking geometry provides added level of safety to your belay
- operating is very simple, as it works without any moving parts or lever
- large clipping area for most common carabiner shapes, works best with BORA or OXY carabiner
- durable stainless steel braking surface provides longer lifetime and the smooth and secure control for gradual lowering
- functionality is according to the tube principle and is therefore suitable for lead and top-rope climbing
- compact geometry makes paying out rope even faster and easier, while the handle has a comfortable and firm grip.

Weight: 84 g • 3 oz
Rope diameter: 8.7 – 11 mm
Material: light alloy, steel, plastic
EN 15151-2

RAMA SET

M0201XX00



Single rope belay device with enhanced braking feature and hot-forged light alloy oval carabiner OXY TWL create a perfect set for lead or top-rope climbing.

Weight: 165 g • 5.82 oz
Rope diameter: 8.7 – 11 mm
Material: light alloy, steel, plastic

SHUTTLE

K6140EE00
black matt K6140BB00



One device to do it all, the Shuttle offers maximum versatility. It has a groove, designed and shaped to provide equal friction for both thin and thick ropes. When you're belaying from above, the "guide mode" lets you bring up one or two seconding climbers under control. For lowering, it has a small secondary hole that you can clinch carabiner for or sling more leverage to release the device.

- designed for twin, half and single ropes
- lightweight and compact, only 65 g
- V-grooves for high friction when belaying the leader or rappelling
- self locking function when belaying the second
- eye for releasing the weight
- possibility of simultaneous belaying two climbers

Weight: 65 g • 2.29 oz

Rope diameter:

Ⓜ 7.8 – 10.5 mm

① 9 – 10.5 mm

Material: Light alloy

EN 15151-2

BUDDY

K6132EE
black matt K6132BB



Buddy is light and compact belay tube.

For all round climbers.

Designed for ropes 7.8 – 11 mm

mix color

Weight: 54 g • 1.91 oz

EN 15151-2

BUDDY SET

M0200XX00



Buddy is light and compact tube and with BORA GP key lock carabiner creates superb unit for belaying in the gyms or at the crags, suitable also for rappelling.

Designed for ropes 7.8 – 11 mm

Weight: 119 g • 4.2 oz

FIGURE 8 L

K6031EE
black matt K6031BB



Simple rappeling device designed for the ropes of bigger diameters.

30 kN • color mix
Weight: 125 g • 4.41 oz
Rope diameter: 8.5 – 13 mm
EN 15151-2

- for ropes of various diameters
- many color variants
- easy rappelling
- effective heat distribution

FIGURE 8 M

K6021EE
black matt K6021BB



Simple rappeling device designed for the ropes of smaller diameters.

25 kN • color mix
Weight: 104 g • 3.67 oz.
Rope diameter: 7.5 – 11 mm
EN 15151-2

ASCENDERS

CAM CLEAN



RK805BX00



Compact and lightweight chest ascender for safe and smooth rope ascent, rescue and special rope techniques.

- simple and quick manipulation
- lower hole angled to keep flat position on the harness
- stainless steel toothed cam for higher corrosion resistance and for any conditions (frozen or dirty ropes)
- Upper hole for attaching a PULLER shoulder strap to keep the rope clamp in a correct position

Weight: 125 g • 4.4 oz
Material:
body – light alloy
cam – stainless steel
trigger – plastic
EN 12841 Static rope \varnothing 10–13 mm
EN 567 Rope \varnothing 8–13 mm
CE 1019 • EN 567 • EN12841 type B

LIFT



LEFT RK804BX0L
RIGHT RK804BX0R



Hand ascender for safe and smooth ascent.

Extra wide handle and attachment point for two carabiners will fit everyone from bigwall climbers to workers at height or special forces.

- available in two variants – for left and right hand
- stainless steel toothed cam for higher corrosion resistance and for any conditions (frozen or dirty ropes)
- overmolded grip and ergonomic upper part for a comfortable and powerful grip
- wide lower hole allows to connect two standard carabiners
- upper hole for clipping a carabiner around the rope

Weight: 190 g • 6.7 oz

Material:

body – light alloy

cam – stainless steel

trigger – plastic

EN 12841 Static rope \varnothing 10–13 mm

EN 567 Rope \varnothing 8–13 mm

CE 1019 • EN 567 • EN 12841 type B

DESCENDERS

DOUBLE STOP PLUS

K031DSD00



Descender with double locking and self-braking anti-panic system in case of accidental loss of descent control.

- the descender doesn't have movable flanges. This makes it a robust and mistake-resilient device (quick insertion and release, no need to unclip it for rope insertion)
- new cam tested for higher loads – enhanced braking in both stop positions.
- unique way of rope insertion. Diminished possibility of incorrect insertion of the rope. Even incorrect insertions will not result in a fall as the rope is blocked.
- sensitive and longer handle enables smooth descent without harmful rope twisting, gentle and progressive braking (enhanced press stop braking mode).
- rubberized handle provides pleasant feeling, non slip and thermal insulation.
- ergonomically improved curved edges and longer flanges provide the user with a comfortable grip with the handle.
- integrated wear indicator
- high strength plain bearing added to the pivoting cam.
- all parts in contact with the rope are made of stainless steel – minimum possible wear.

Breaking loads in excess of 22 kN.

Increased maximum rated load to 200 kg.

Reduced slippage of the rope to 600 daN.

Reduced force required on the handle.

Rope \varnothing : 9 – 12 mm

\varnothing 9 mm – max. working load 130 kg

\varnothing 10 – 12 mm – max. working load 200 kg

Weight: 421 g • 14.85 oz

CE 0123 • EN 12841 type C

PULLEY SMALL



RK800EE00
black version RK800BB00



Small pulley for textile ropes for those who occasionally need to build simple hauling systems or manipulate with the objects.

- lightweight single pulley for hauling and rescue
- brass self lubricating bearing ensures reliable efficiency up to 81 %
- suitable for use with a Prusik friction knot

strength: 22 kN
max. Ø rope: 13 mm
static and dynamic ropes
sheave: aluminium alloy
side plates: aluminium alloy

axle: stainless steel
friction bearing: brass
weight: 92 g • 3.3 oz
serial unique number
CE 1019 • EN 12278

PULLEY EXTRA



RK801EE00
black version RK801BB00



Large single pulley for textile ropes for those who need great hauling efficiency, durability and lightweight pulley.

- durable and lightweight high-efficiency single pulley for industrial use and hauling systems
- sealed ball bearing and large diameter of the sheave provides great efficiency 94%
- designed and optimized for use with a Prusik friction knot or any clamps
- top attachment point accepts up to three carabineers
- formed side plates provides protection of rope against contact with a surrounding
- fixed-by-forging sheave and anti dust cover of ball bearing provides great lifespan
- side plate holes enable cleaning of the ball-bearing surrounding

strength: 32 kN
working load: 2x3 kN
max. Ø rope: 13 mm
static and dynamic ropes
sheave: aluminium alloy
side plates: aluminium alloy

sealed ball bearing: steel
axle: stainless steel
weight: 257 g • 9.1 oz
serial unique number
CE 1019 • EN 12278

PULLEY TWIN



RK802EE00
black version RK802BB00



Large double pulley for textile ropes for those who need great hauling efficiency, durability and still lightweight pulley.

- designed and optimized for use with a Prusik friction knot or any clamps
- sealed ball bearing and large diameter of the sheave provides great efficiency 94%
- top attachment point accepts up to three carabineers
- durable and lightweight high-efficiency single pulley for industrial use and hauling systems
- formed side plates provides protection of rope against contact with a surrounding
- fixed-by-forging sheave and anti dust cover of ball bearing provides great lifespan
- side plate holes enable cleaning of the ball-bearing surrounding

strength: 36 kN
working load: 4x3 kN
max. Ø rope: 13 mm
static and dynamic ropes
sheave: aluminium alloy
side plates: aluminium alloy

sealed ball bearing: steel
axle: stainless steel
weight: 421 g • 14.9 oz
serial unique number
CE 1019 • EN 12278

PULLEY MIKY



RK806BB00



Lightweight pulley with two attachment holes Designed for tree climbing application. Suitable for use with Prusik friction knot.

- two attachment holes with strength 28 kN
- anodized aluminum alloy side plates
- aluminum alloy sheave for textile ropes and auxiliary cords up to 13 mm in diameter
- bronze self lubricating bearing ensures reliable efficiency up to 81%

strength: 28 kN
max. \varnothing rope: 13 mm
sheave and side plates:
aluminium alloy
bearing: bronze

axle: stainless steel
bearing: friction
weight: 105 g • 3.7 oz
serial unique number
CE 1019 • EN 12278

TANDEM PULLEY



RK803BB00



Double pulley for Tyrolean traverses and zip-lines with two stainless steel sheaves.

- each sheave is equipped with a pair of sealed ball bearings for great durability
- hard aluminium alloy body is black anodized and protects the sheaves from damage
- large attachment point can accommodate up to three carabiners
- second attachment point for back-up carabiner or tackle systems building

strength: 25 kN
max. \varnothing rope: 13 mm
static and dynamic ropes
12 mm steel cable
sheave: stainless steel
side plates: aluminium alloy

sealed ball bearing: steel
axle: stainless steel
weight: 290 g • 10.2 oz
serial unique number
CE 1019 • EN 12278

PITONS

PITON V



RK710XX08 – L8
RK710XX10 – L10
RK710XX12 – L12

V pitons fit to larger cracks and pockets.

- easy clip-in point
- Material:
Cr-Mo hardened steel
Thickness: 8-13 mm
Length: 8, 10, 12 cm • 3, 4, 4.7 in
Weight: 84 g (L8) • 3 oz (L8)
CE 1019 • EN 569

PITON A5



RK709XX05 – L5
RK709XX07 – L7
RK709XX09 – L9

Hardened steel piton for classical cracks intended for mountaineering or aid climbing.

- Material:
Cr-Mo hardened steel
Thickness: 5 mm
Length: 5, 7, 9 cm • 2, 2.8, 3.5 in
Weight: 103 g (L7) • 3.6 oz (L7)
CE 1019 • EN 569

PITON A3



RK708XX03 – L3
RK708XX05 – L5
RK708XX07 – L7

Hardened steel piton for thinner cracks.

- Material:
Cr-Mo hardened steel
Thickness: 3 mm
Length: 3, 5, 7 cm • 1.2, 2, 2.8 in
Weight: 54 g (L5) • 1.9 oz (L5)
CE 1019 • EN 569

ROCK HAMMER

RK750XX00

**Classic rock hammer for big wall climbing, first ascents or work at height.**

- clip-in point in a head enables to remove the pitons from the cracks
- narrowed head for easier nut and copperhead placement
- anti-vibration rubber handle
- attachment point in the handle for the accessory cord
- clip-in point in the head for easier handling

Length: 30 cm • 11.8 in
Weight: 590 g • 20.8 oz

ULTIMA

RK706XX00

**A special piton which makes the unclimbable passages possible to climb.**

- for thin cracks up to 2,5 mm wide
- possible to use in vertical or horizontal cracks
- rust resistant steel wire
- great tool for aid climbing or first ascents

Strength: 5 kN
Material: Cr-Mo hardened steel blade, steel wire
Weight: 21 g • 0.7 oz

SENTINEL

RK711XX00

**Hook for fragile edges and drilled holes.**

- important tool for aid climbing or first ascents
 - 10 cm polyamide webbing included
- Material: Cr-Mo steel, PAD webbing
Length: 13 cm
Weight: 43 g • 1.5 oz

CAPTAIN

RK705XX00

**Hook for small to medium flakes, edges and rugosities.**

- important tool for aid climbing or first ascents
- 10 cm polyamide webbing included

Material: Cr-Mo steel, PAD webbing
Length: 13 cm
Weight: 46 g • 1.63 oz

ZINC PLATED HANGER PLATE / WITH BOLT

10 mm RK704XX10
12 mm RK704XX12
10 mm w/bolt RK716XX10
12 mm w/bolt RK716XX12



Zinc plated steel hanger plates and bolts for permanent anchor points. Available in two different bolt sizes.

- recommended for indoor, dry environment

Plate thickness: 4 mm
Bolt length: 84 mm
Length of the hole: 75 mm
Strength: 25 kN
Weight:
Hanger plate 62 g • 2.19 oz
10 mm w/bolt 100 g • 3.53 oz
12 mm w/bolt 125 g • 4.41 oz

EN 795 • EN 959

STAINLESS HANGER PLATE / WITH BOLT

10 mm RK702XX10
12 mm RK702XX12
10 mm w/bolt RK715XX10
12 mm w/bolt RK715XX12



Stainless steel hanger plates and bolts for permanent anchor points. Available in two different bolt sizes.

- recommended for outdoor, wet environment. Not recommended for aggressive environment (e.g. sea water, chlorinated pool water, chemically polluted environment, etc.)

Plate thickness: 3 mm
Bolt length: 84 mm
Length of the hole: 75 mm
Strength: 25 kN
Weight:
Hanger plate 42 g • 1.48 oz
10 mm w/bolt 112 g • 3.95 oz
12 mm w/bolt 140 g • 4.94 oz

EN 795 • EN 959

GLUE IN ANCHOR

RK703XX10



Stainless steel durable permanent anchor point.

- works also in soft or pocketed stone
- smooth eye allows safe rope threading for retreat
- made of welded, grade AISI 316 stainless steel
- for drilled hole with diameter 12 mm
- recommended glue: UPM 44 or FIS 360V, resin capsule RM10

Diameter: 10 mm
Length of shaft: 80 mm
Weight: 120 g • 3.18 oz
Strength: ↗ 30 kN ↘ 25 kN
EN 959 • EN 795 Type A

RAPPELLING STATION 12 MM

RK500XX00

**Rappelling station for the climbing gyms or crags.**

Includes: 2 hanger plates 12 mm,
2 chains and 1 ring
Strength: 25 kN
Length of the chain: 17,5 cm
Inside diameter of the ring: 5 cm
Material: zinc-coated steel
Weight: 580 g • 20.46 oz
Strength: 25 kN
Length of the chain: 17,5 cm
EN 959 • EN 795 Type B

RIGGING PLATE 1/3



RK713BB00

**Aluminium alloy device for multi-point anchoring.**

- helps to organize carabiners at the anchor point
- provides efficient force distribution at different load directions
- rounded holes allow direct attachment of ropes and slings to the rigging plate
- central attachment point can accommodate up to three carabiners
- all attachment points are big enough to allow locking sleeves of most carabiners passing through

Weight: 65 g • 2.3 oz
Material: light alloy
Strength: 36 kN
Thickness: 6 mm
CE 1019

RIGGING PLATE 3/5



RK6371BB

**Aluminium alloy device for multi-point anchoring.**

- provides efficient force distribution at different load directions
- low profile of the plate makes the connection as short as possible
- provides plenty of attachment holes
- rounded holes allow direct attachment of the ropes and slings to the rigging plate
- all attachment points are big enough to allow locking sleeves of most carabiners passing through

Weight: 145 g • 5.1 oz
Material: light alloy
Strength: 50 kN
Thickness: 8 mm
CE 1019



REDBLOCK

K0006RP00



Anchor device, that extends lifetime of the rope when toppling.

- ideal partner for adventure parks, rope courses and climbing gyms
- allows to be installed in two axes

Max. diameter of rope: 12 mm

Color: red

Weight: 375 g • 13.23 oz

Material:

side plate: light alloy

sheave: stainless steel

Strength: 26 kN

serial unique number

CE 1019

TWISTER

K00300G00



Rotating hanger

Placed between a load and either rope or cable, the twister avoids severe rope twisting while the load turns.

Working load: 4 kN

Strength: 22 kN

Weight: 91 g • 3,25 oz.)


Color: anthracite / yellow

serial unique number

CE 0321 • EN 354







HARNESSES

ROPES

CARABINERS

HELMETS

ICE LINE

HARDWARE

SLINGS

ACCESSORIES




SLINGS AND LANYARDS



CLIMBERS FOR
CLIMBERS

SLINGS 16 MM

C2075

**Light and strong nylon slings for multiple use at traditional protection.**

- versatile, strong and extremely durable
- for better gear management available in different colors in the lengths from 60 to 150 cm.

Width: 16 mm
 Material: polyamide
 Strength: 22 kN
 Length: 60, 80, 120, 150 cm / 24, 32, 48, 60 in
 Length deviation: 60, 80 cm +/- 2 cm
 120, 150 cm -2/+4 cm
 Weight: 48 g (60 cm) / 1.7 oz (24 in)
 120, 150 cm -2/+4 cm
 CE 1019 • EN 566 •

DYNEEMA® SLINGS 11 MM

C2001

**Light, thin and still very strong slings for the trad climbing.**

- ideal for all applications where the weight and strength come first
- for better gear management available in different colors in the lengths from 30 to 150 cm.

Width: 11 mm
 Material: dyneema
 Strength: 22 kN
 Length: 30, 60, 80, 120, 150 cm / 12, 24, 32, 48, 60 in
 Weight: 27 g (60 cm) • 0.95 oz (24 in)
 CE 1019 • EN 566 •

DYNEEMA® SLINGS 8 MM

C2004



22 kN

Light, thin and still very strong.

Perfect for threads. This 8 mm sling is ideal for all applications where weight and strength come first.

Lengths: 60 and 120 cm / 24 and 48 in
 Length deviation: 60 cm +/- 2 cm
 120 cm -2/+4 cm
 Weight: 21 g [60 cm] • 0.74 oz [24 in]
 Color: yellow (60 cm), red (120 cm)
 CE 1019 • EN 566 •

QUICKDRAW SLINGS 16/25 MM

12 cm C2087X012
17 cm C2087X017



Vari-width quickdraw sling for your own quickdraw customization.

- easy to grab and it is ideal for building custom sport climbing quickdraws

Width: 16/25 mm
Material: polyamide
Strength: 22 kN
Length: 12, 17 cm • 4.7, 6.7 in
Weight: 12, 18 g • 0.42, 0.64 oz
Color: blue / yellow
CE 1019 • EN 566 •

QUICKDRAW SLINGS 16 MM

C2085



Designed for your own easy quickdraw customization.

- light, durable and easy to grab
- available in different lengths to create your quickdraws

Width: 16 mm
Material: polyamide
Strength: 22 kN
Length: 11, 13, 16, 20 and 30 cm / 4.4, 5.2, 6.4, 8 and 12 in
Weight: 12 g (11 cm) • 0.42 oz (4,4 in)
CE 1019 • EN 566 •

QUICKDRAW SLING DYNEEMA® 11

C2000



Ideal for your own easy quickdraw customization or the replacement of the worn sling.

- 11 mm wide dyneema sling offers an excellent weight to strength ratio

Width: 11 mm
Material: Dyneema®
Strength: 22 kN
11, 13, 16, 20 and 30 cm / 4.4, 5.2, 6.4, 8 and 12 in
Weight: 8 g (11 cm) • 0.28 oz (4,4 in)
CE 1019 • EN 566 •

JACOB DYNEEMA

C2151BY00



Versatile and ultra light ladder.

- used for technical climbing and working at heights
 - any cell may be loaded in any directions, which can become useful in emergency situations
 - strength of each loop – 22 kN
 - may be also used as an open sling for the anchoring
- Material: Dyneema®
Length: 140 cm
Weight: 140 g • 4.94 oz
CE 1019 • EN 566 • EN 354

FOOTER II


W1024BX
complete W1025BX**Ascender webbing for aid climbing and rope access.**

- big loop for easy releasing the webbing
- small loop for the attachment to the carabiner
- reinforced step loop
- FOOTER II COMPLETE includes Mini D screw connector

Min. length: 40 cm • 16 in
 Max. length: 140 cm • 55 in
 Weight: 90 g • 3.2 oz /
 125 g • 4.4 oz (complete)
 Max. load: 150 kg

FOOTER XP

W1025BX

**Lightweight adjustable ascender loop made from 6 mm accessory cord.**

- light-alloy XP buckle allows to adjust the length even when loaded
- webbing in the buckle simplifies length adjustment
- big hole in the buckle enables to attach any type of carabiner
- reinforced step loop is equipped with an elastic strap
- which keeps the proper position of the foot

Weight 105 g • 3.7 oz
 Material PAD, light alloy
 Length 30-170 cm • 12-67 in
 Max. load 180 kg • 390 lb

REGULATOR

W1051BX

**Adjustable tether for aid climbing and first ascents.**

- adjustment of the length is fast and repeatable
 - easily releasable buckle
 - this product IS NOT belaying stance lanyard
- DO NOT USE FOR BELAYING!
 DO NOT USE AS AN ATTACHMENT POINT!**


Color: anthracite / red
 Weight: 90 g • 3.17 oz
 Material:
 webbing PAD, buckle steel
 Strength: 1.5 kN (150 kg ≈ 330 lb)
 Width: 20 mm • 0.8 in
 Length: 18 - 136 cm • 7 - 53.5 in

SAFETY CHAIN

C2419X
black C2419B**The safest classical daisy chain for aid climbing on the market.**

- innovated daisy chain with patented double loop at the end provides safe and adjustable attachment for the climber to the anchor point
- avoids dangerous use of the traditional daisy chain
- can be shortened to any loop safely without using more than one carabiner or unclip the first loop
- 16 mm polyamide webbing provides longer life-time

Length: 120 cm • 48 in
 140 cm • 56 in

Strength:
 22 kN / 3,5 kN individual loop
 Weight: 102 g • 3.6 oz
 CE 1019 • EN 566 • 

JACOB

C2150BY

**Ultra light six staves aider**

Staves reinforced with plastic keep
 its shape even when loaded.
 Strength 500 kg.
 Strength of grab loop 100 kg.
 Weight: 210 g • 7.40 oz

TUBULAR WEBBING

black C0037BB12
red C0037RR12



- width of webbing 20 mm (0.79 in)
- made of low stretch PAD
- max. length 120 m (393 ft)
- weight: 39.4 g/m • 1.39 oz/m
- strength: 17 kN
- EN 565

FLAT WEBBING

C0035A012




- width of webbing 16 mm (0.63 in)
- made of low stretch PAD
- max. length 120 m (393 ft)
- weight: 37.7 g/m • 1.33 oz/m
- strength: 15 kN
- EN 565

PHARIO

New generation of energy absorbers for via ferrata routes, ropes courses and adventure parks in accordance with a new standard EN 958:2017

- for all users, from the kids to the adults weighting 40 – 120 kg (88 – 265 lb)
- new fall indicator label enables fast inspection of tear webbing energy absorber
- tear webbing energy absorber stored in more resistant cover
- twisted loop for an easy attachment to the harness
- maximal length of the activated fall absorber 190 cm (Phario 360° max. 215 cm)
- rounded shape for easy handling
- central eye with the strength 12 kN for resting and belaying
- unique production number



PHARIO 360°



C2316XX00

**New energy absorber with elastic arms and stainless steel swivel.**

- stainless steel swivel minimizes twisting the elastic arms
- the user has maximal useable area of 360°
- elastic arms with a length 50 cm and maximum elongation 85 cm
- resistance of the arms is tested on a cyclic machine.

Cyclic process is done by minimally 50 000 cycles

Weight: 595 g • 21 oz

(incl. carabiners and swivel)

CE 1019 • EN 958 • EN 12275 type „K“ •

PHARIO PALM



C2315XX00

**Energy absorber for via ferrata routes with palm Keylock carabiners.**

- keylock carabiners, type „K“ according EN 12275
- color distinction between the lanyards for easy manipulation and avoiding the twisting
- elastic lanyards length: 50 cm, extended length: 90cm

Weight: 540 g • 19 oz

(incl. carabiners)

CE 1019 • EN 958 • EN 12275 type „K“ •

PHARIO SLIDE



C2314XX00

**Energy absorber for via ferrata routes with sliding carabiners type „K“ according EN 12275.**

- color distinction between the lanyards for easy manipulation and avoiding the twisting

Weight: 470 g • 16.6 oz

CE 1019 • EN 958 • EN 12275 type „K“ •

PHARIO



C2313XX00

**Shock absorber for via ferrata routes, ropes courses and adventure parks. (without the carabiners)**

- ideal for all of those who wish to choose their own carabiners
- recommended carabiners type „K“ EN 12275

Weight: 290 g • 10.2 oz

CE 1019 • EN 958 •





HARNESSES

ROPES

CARABINERS

HELMETS

ICE LINE

HARDWARE

SLINGS

ACCESSORIES



ACCESSORIES



CLIMBERS FOR CLIMBERS

SLACKLINE 15 M

C0064BY15



Slackline set 15 m is ideal for the beginners and allrounders. Also suitable for the schools, climbing gyms or special training purposes.

- superlight 2 colours webbing with the strength 3 tones and width 25 mm has excellent qualities
- fast assembly with the ratchet
- anchoring around the solid anchor with the slings and smart Rock&Lock buckles
- slackline set is made as simple as possible that even a beginner can assemble it easily

Width of webbing: 25 mm • 0,98 in
Material: low stretch PES

Strength: 3t

Slackline Set 15 m includes:

- 2 anchoring slings with Rock&Lock buckles and sewed eyes
- 15 m slackline webbing with sewed eye.
- 1 ratchet
- Transport bag

SLACKLINE 25 M

C0064BY25



Slackline set 25 m is ideal for the advanced slackliners.

- superlight 2 colours webbing with the strength 3 tones and width 25 mm has excellent qualities
 - tension made by multi-pull system
- Width of webbing: 25 mm • 0,98 in
Material: low stretch PES

Strength: 3t

Slackline Set 25 m includes:

- 25 m slackline webbing with sewed eye.
- 2 anchor slings
- 1 accessory sling for multi-pull system
- 1 sheckle
- 1 Oval Steel connector / screw
- 1 lock pin
- 2 o-rings
- Transport bag

SLACKLINE WEBBING

C0065BY15



Ideal webbing for all kind of slackline

– longline, highline, waterline...

Width of webbing: 25 mm • 0,98 in

Material: low stretch PES

Strength: 3t

Weight: 59 g/m

Elongation: 8%

Max. length 150 m

FONT

C0075BX00



Lightweight one-part sit start pad

- suitable for outdoor bouldering as well as for indoor walls and gyms
- abrasion and water-resistant fabric with high-quality printing
- thin layer of anti-slip rubber on the bottom (the pad does not slip on the grass, on a slope...)
- inner construction consisting of two layers of high quality foam (the upper foam is with closed cells and the bottom with open cells)
- great in a combination with the MAGIC two-part crash pad and the HUECO three-part crash pad

Weight: 1.2 kg (2.65 lb)

Size: 90 x 50 x 5 cm (35.4 x 19.7 x 2 in)

Material: 25% polyethylene foam, 75% polyurethane foam, nylon + antislip finishing

MAGIC

C0076BX00



Two-part crash pad with two-layer shock absorbing construction.

- suitable for outdoor bouldering as well as for indoor walls and gyms
- velcro stripes hold the parts of the pad tightly together when unfolded
- easy transportation thanks to comfortable shoulder straps which can be easily adjusted using unbreakable light-alloy buckles
- fast closing and opening are ensured by light-alloy buckles as well
- abrasion and water-resistant fabric
- thin layer of anti-slip rubber on the bottom (the pad does not slip on the grass, on a slope...)
- inner construction consisting of two layers of high quality foam (the upper foam is with closed cells and the bottom with open cells)
- great in a combination with the FONT sit start pad and the HUECO three-part crash pad

Weight: 5.1 kg (11.3 lb)

Size: 116 x 95 x 10 cm (3.8 x 3.1 x 0.3 ft)

Material: 25% polyethylene foam, 75% polyurethane foam, nylon + antislip finishing

HUECO

C0077BX00



Three-part crash pad with two-layer shock absorbing construction.

- suitable for outdoor bouldering as well as for indoor walls and gyms
- abrasion and water-resistant fabric with high quality printing
- thin layer of anti-slip rubber on the bottom (the pad does not slip on the grass, on a slope...)
- inner construction consisting of two layers of high quality foam (the upper foam is with closed cells and the bottom with open cells)
- velcro stripes hold the parts of the pad tightly together when unfolded
- easy transportation thanks to comfortable shoulder straps which can be easily adjusted using unbreakable light-alloy buckles
- fast closing and opening are ensured by light-alloy buckles as well
- great in a combination with the MAGIC three-part crash pad

Weight: 6.7 kg (14.77 lb)

Size: 150 x 100 x 10 cm (4.9 x 3.3 x 0.3 ft)

Material: 25% polyethylene foam, 75% polyurethane foam, nylon + antislip finishing

BOULDER BAG

C3066BY00



- the biggest chalk bag in our production
- great for the gyms where sits on the floor
- adjustable belt
- 2 brush holders and 1 pocket
- weight: 205 g • 7,23 oz.

SUPER TAPE

C0034W125 – white 12,5 mm
C0034Y380 – yellow 38 mm



- very strong
 - super adhesive
 - non-allergic (clinically tested)
 - no glue marks on your skin
 - convenient for long-term usage
- Size: 12,5 mm x 10 m (2 pcs. in a package), 38 mm x 10 m

CHALK BAGS

CHALK BAG MOUNTAINS



C3004CC00 - coral
C3004AA00 - blue
C3004YY00 - yellow
C3004RR00 - red
C3004TT00 - grey

- soft and pleasant to touch outer fabric. Fleece lining inside.
- dustproof closing system
- brush holder loop and double loops for the belt or accessory cord attachment

Colors:
coral, blue, yellow, red, grey

CHALK BAG LARGE



C3003RR04 - coral
 C3003YY04 - yellow
 C3003SS04 - grey
 C3003TT04 - dark grey
 C0002BBX4 - black

- made from polyester and polyamide material.
- inside fleece material provides continuous circulation of magnesium and so its high usage
- prompt closing system and braced welt provide an easy handling of the chalk bag

Colors: coral, yellow, grey, dark grey, black

CHALK BAG COMIC



C3002XX00 - yellow
 C3002SS00 - grey

A large chalk bag with ergonomic shape and unique printing design.

- ergonomic shape and enough volume for chalking of the whole hand.
- soft and pleasant to touch corduroy outer fabric. Fleece lining inside.
- dustproof closing system.
- wide elastic brush holder for more comfort when cleaning holds.
- double loops for stable attachment to the waist belt.

CHALK BAG ROCKET

NEW



A large chalk bag with ergonomic shape and enough volume for chalking of the whole hand.

- soft and pleasant fleece lining inside
- dust proof closing system
- wide elastic brush holder for easy brush placement
- double loops for stable attachment to the waist belt

BELT FOR CHALK BAG C309



Adjustable belt with a quick release buckle

Magnum is perfect grade natural chalk specifically designed for climbing and all rock activities. Great for absorbing moisture and creating friction between fingers & palms and stone.

MAGNUM BALL M3001WO35



35 g • 1.24 oz
Creates less dust,
less sweat and better grip.

MAGNUM BALL TWINS M3001XO70T



2 × 35 g • 2 × 1.24 oz
Creates less dust,
less sweat
and better grip.

MAGNUM BALL REFILL M3001WO35R



refill
35 g • 1.24 oz
Creates less dust, less
sweat and better grip.
This ball allows refilling.

MAGNUM CUBE M3001X056



56 g • 1.98 oz

MAGNUM CRUNCH BAG M3001X30P



300 g • 10.58 oz
For maximum sweat
absorption and friction.

MAGNUM CRUNCH DOSE M3001W10C



100 g • 3.53 oz
For maximum sweat
absorption and friction.
This box allows refilling.

MAGNUM LIQUID CHALK, TUBE M3002W150



150 ml
Quick-drying chalk for
maximum sweat absorp-
tion and friction. Creates
less dust, less sweat
and better grip.

MAGNUM LIQUID CHALK, BAG M3002W010



10 ml
Quick-drying chalk for
maximum sweat absorp-
tion and friction.
Creates less dust, less
sweat and better grip.

ROCKING 40

C0086BX40



Crag climbing backpack with top and back panel easy access to the main compartment and lots of cool features.

- large top and back panel easy access to the main compartment equipped with YKK zippers
- ergonomic and comfortable shoulder straps and back panel
- adjustable sternum strap
- simple hip belt is possible to hide inside the side pockets
- spacious zippered top pocket for your essentials
- zippered inside pocket with the key clip secures your keys, wallet and other small items
- two internal gear loops and internal pocket for the rope tarp, climbing shoes or other equipment
- 120 x 140 cm rope tarp with the Partner Check info graphic and different color of the loops for easy rope ends identification
- zippered side pocket for quick access to a guide book, water bottle or other essentials
- helmet attachment on the lid or on the front part using the flexible net
- rope attachment on the lid using the rope fixing straps (the straps can be easily hidden inside the lid)
- "daisy chain" loops to secure gear outside the backpack
- with the loops and a bungee cord you can attach additional gear like a sleeping mat and the like (a bungee cord is not included)
- reinforced carrying handles on the top part enable easy manipulation with the backpack
- super durable nylon fabric with foam padding on the bottom and front panel ensures a long lifetime and protects your gear

Weight: 1190 g • 42 oz
Material: PES, PAD, plastics
Volume: 40 litres

ROCKSTAR 28

C0085BX28



Urban style shoulder bag with a removable rope tarp for gym climbing or bouldering.

- main compartment suitable for a 70m rope and other climbing gear
- easy adjustment by a closure system with light alloy buckles
- fully adjustable shoulder strap with comfortable padding
- durable handle for easy carrying in hand
- two side pockets for small items (one with a Velcro, the other one open)
- slots for a toothbrush and other equipment
- zippered pocket with a key clip for your essentials
- removable rope tarp with dimensions 135 x 150 cm
- two handles in the corners of the tarp for fast storage of a rope into the bag, different color of the loops for easy rope ends identification
- two internal handles for easy carrying of the opened bag
- reinforced bottom, sides and back part for longer lifetime and comfortable wearing of the bag

Weight: 845 g • 29.8 oz
Material: PES, PAD, light alloy
Volume: 28 litres

GEAR BAG



Transport bag for your gear

- waterproof, durable and washable
- very convenient to carry your gear
- takes up little space and stays dry
- transparent pocket (A4) on the top flap for your documents
- intended for speleology and working at heights
- minimum amount of seams
- main seams feature HF welding

Colors: yellow, red and black

Capacity: 35 and 50 litres

Material: PVC

Weight: 700 g • 24.7 oz – 35 l version

S9000YY35 35 l yellow

S9000RR35 35 l red

S9000BB35 35 l black

S9000YY50 50 l yellow

S9000RR50 50 l red

S9000BB50 50 l black

CANYON BAG

S9002YX30



Durable backpack intended mainly for aquatic caves and canyoning. It provides great carrying comfort and water drainage.

- fast opening/closing with a durable toggle
- padded shoulder straps and an adjustable sternum strap
- emergency buckles on the shoulder straps for quick unfastening
- 2 side moulded handles and 1 handle on the back
- inside mesh pocket
- two metal D-rings inside to fasten rope ends
- inside pocket with a back plastic reinforcement which can be used as emergency fracture fixation
- reflective stripes for increased visibility
- excellent water drainage through drain holes in the bottom and sides
- bottom reinforcement for additional durability

Weight: 1345 g • 47.5 oz

Material: PVC, PES

Volume: 30 litres

DRY BAG

40 l - S9001YX40

60 l - S9001BX60



Dry bag with detachable shoulder straps intended for complete waterproof protection of your gear.

- classic rolling system with an additional guide bar
- retaining rings against unwanted opening of the closure buckle
- washable extra-durable PLASTEL® fabric, UV and waterproof resistant
- metal D-ring for safety attachment
- easily detachable foam padded shoulder straps
- color differentiation of the bag volume

Color: yellow [40 l], black [60 l]

Weight: 750 g g • 26.5 oz [40 l]

Material: PVC, PE

Volume: 40 or 60 litres

EXPEDITION BAG TARP DUFFLE



70 l, 90 l



120 l

Made from a durable laminate material, the TARP DUFFLE is almost indestructible bag. Resilient enough to be roughed up in-flight or to be transported up a mountain via a yak or off-road, this is one burly duffel bag. For trips lasting longer, grab the 120 liters size to have enough room for your climbing gear.

- alpine-cut shoulder straps
- dual daisy chains to attach your gear
- Twin haul handles at the ends
- rugged construction with extra bartacks and double stitching
- four compression straps
- internal mesh pockets and pocket on top for your small items
- 120 l version with side opening

Weight:

1820 g • 4 lb (70 l)

2270 g • 5 lb (90 l)

2720 g • 6 lb (120 l)

Dimension:

59 x 35 x 34 cm (70 l)

69 x 40 x 33 cm (90 l)

85 x 42 x 38 cm (120 l)

C0046BB70 70 litres

C0046BB90 90 litres

C0046B120 120 litres

MOVEMENT BAG

C0073BY00



Resistant traveling bag with wheels for your climbing adventures, business trips or work at height missions

- large u-shaped opening with heavy duty double zippers provides easy access to contents; zippers can be easily locked with a padlock
- convenient side pocket allows you to keep e.g. footwear separate from clothing
- durable webbing straps and grab handle with reinforced stitching
- smooth rolling with all-terrain wheels for effortless mobility
- durable internally constructed push button locking handle adjusts to multiple heights for comfort whether gliding or pulling the bag
- side organization pocket for all of your travel needs
- heavy-duty PVC fabric backing
- rubberized, textured corner protectors guard against wear and tear at critical contact points
- plastic piping reinforce high friction zones
- one internal accessory pocket provide easy packing organization

Color: black

Weight: 4600 g • 10.1 lb

Dimension: 77 x 39 x 38 cm •

30.3 x 15.4 x 15.0 in

Material: PVC

Capacity: 110 litres

Max. load: 23 kg

DRY DUFFLE

40 l – S9003YY40
60 l – S9003YB60



Water resistant dry duffle that opens fully across its length so you can get to your compartment without having to unload half your stuff.

- Classic rolling system with additional guide bar
- L large top access to the compartment
- Quality fasteners to fix the closure and adjust the volume
- Daisy chain for fixing and attaching further gear
- Closure buckles on both sides to prevent unwanted opening
- Additional handle for short distance transfers
- Removable foam padded shoulder strap
- Colour differentiation of the bag volume

Color yellow [40 L], black/yellow [60 L]
Weight 780 g • 27.5 oz [40 L] 1040 g • 36.7 oz [60 L]
Size side Ø 27 cm, length 55 cm [40 L] side Ø 30 cm, length 70 cm [60 L]
Material PVC, PE

CARRY BAG

C0001YY00



Practical bag intended for storage and transport of ropes as well as other gear.

- made from durable and washable material
- plastic reinforcements keep the bag self-standing
- due to its shape it is easy to store the rope and rigging tools properly
- very convenient to carry your gear
- reinforced ergonomic plastic handle to haul the bag
- loop on the bottom to shake out the gear and dirt
- water resistant
- side pocket for the accessories
- 2 steel rings for shoulder strap to carry the bag easily
- fast closing system

Color: yellow / black
Dimension: 30x40(58) cm
Max. load: 28 kg
Capacity: 28 + 10 l
Material: PVC
Weight: 940 g • 33.16 oz

ROPE BAG

C0001BB



- With removable sheet
 - Dimension of sheet is 137 x 137 cm
 - Hidden pocket for keys and money
 - Shoulder straps are well padded
 - Abrasion resistant material
 - Keeps your rope and gear clean
 - Extends a lifetime of your rack and rope
 - Brightly color loops to keep your rope untangled
- Weight: 620 g (±15 g) • 21.87 oz
Color: black

MONTY BAG

W1023



**Bag for your gear and documents
adjustable shoulder strap**

- made of high resistant and durable fabric POLYMAR
- washable
- durable material
- colors: grey, yellow, red

FIRST AID BAG

C0053RW



(without the content)

Compact and light first aid bag for mini-malists.

- ideal for all of those who wish to choose their own contents.
 - all-round zip fastener with reflective component guarantees a good overview and easy access.
 - two attachment loops;
 - insert compartment in different sizes; zipped mesh pocket
 - velcro attachment loop on the harness or a hip strap of backpack
 - easily removable from the harness by one hand
 - emergency whistle included
- dimension: 13 x 10 x 5 cm
material: polyamid, polyester

FIRST AID BAG

C0053RW



(without the content)

- ideal for all of those who wish to choose their own content
 - bright colour increases the visibility in a bad weather or inside the backpack
 - big attachment loop
 - insert compartments in different sizes
 - zipped big mesh pocket
 - inside buckle with the emergency whistle
 - high-durable material for the use in demanding conditions
- dimension: 22 x 18 x 5 cm
material: polyamid, polyester
weight: 189 g • 6.67 oz

FALCONER FULL

C0012YB



Lightweight gloves featuring great grip, dexterity and disability.

- durable double layer of artificial and split cow grade A leather on the palm
 - additional reinforcement of the high-wear area between forefinger and thumb
 - breathable abrasion resistant nylon on the back
 - neoprene cuff with a reinforced attachment hole
- Size: 8, 9, 10, 11
EN 388

FALCONER 3/4

C0014YB



Lightweight gloves with removed tops of fingers removed making manipulation of metalwork simpler.

- durable double layer of artificial and split cow grade A leather on the palm
 - additional reinforcement of the high-wear area between thumb and index finger
 - breathable abrasion resistant nylon on the back
 - neoprene cuff with a reinforced attachment hole
 - two special pull-off half-loops on top of middle and ring fingers to secure an easy put off.
- Size: 8, 9, 10, 11
EN 388

FALCONER TACTICAL

C0013YB



Lightweight gloves with top of forefinger, thumb and middle finger removed making manipulation of metalwork simpler.

- durable double layer of artificial and split cow grade A leather on the palm
 - additional reinforcement of the high-wear area between forefinger and thumb
 - breathable abrasion resistant nylon on the back
 - neoprene cuff with a reinforced attachment hole.
- Size: 8, 9, 10, 11
EN 388

GRIPPY

C0006BH



Made out of quality leather. Reinforced palm area. Closed fingers. Abrasion resistant. Easy to put on thanks to special loop.

Size: 8, 9, 10, 11
EN 388, EN 420

GRIPPY 3/4

C0006HH



Made out of quality leather. Reinforced palm area and lower part of finger area. Intended for via ferrata and big wall climbing. Tested in Yosemite! Free ends of your fingers does not affect your sensibility and fine manipulation with your gear. Easy to put on thanks to special loop.

Size: 8, 9, 10, 11
EN 388, EN 420

CRAGGY

C0082YB



Gloves providing hand protection against the scratching during crack climbing.

- gloves don't restrain the wrist movement and don't crush the arteries on the wrist
- elastic rubber bands do not cut between the fingers.
- double elastic band for a little finger for greater durability
- thumb hole in the leather provides greater comfort and grip when climbing
- high quality rubber on upper part provides increased friction during use
- comfortable artificial stretch leather allows maximum sensitivity during climbing
- rubber pocket for velcro closure protects against the scratching and breaking
- very effective hand protection for demanding climbing

Weight: 52 g (size M) • 1.83 oz.

Size: S, M, L, XL

Material: artificial leather, rubber, PES, PVC

ANKLE PROTECTOR

C0083YB



Light ankle protector against scratching the ankle while climbing in low climbing shoes.

- comfortable and simple dressing with velcro closure
- rear elastic rubber band does not cut on the tendons when moving
- comfortable artificial stretch leather providing light protection against scratching the ankle
- the rubber band for fixation on the leg allows the freedom of movement when climbing
- lace webbing for greater durability

Weight: 38 g • 1.34 oz.

Size: UNI

Material: artificial leather, PES, PVC



T-SHIRTS BACKBONE

man C1013BB
woman C1014BB



T-shirts made of 100 % cotton with short sleeves and classic round collar.

- very comfortable to wear for daily use
- made in the Czech republic
- tag less label

Style: men/ women

Size: XS – XL

Weight: 170 g/m²

T-SHIRT ROCKET

men C1028VX
women C1029VX



Comfortable t-shirt made of top quality cotton with elastan, ensures the freedom of movement when climbing or wearing it everyday.

- tag less label
- relaxed fit
- made in the Czech Republic

Color: purple

Size: S, M, L, XL

Material: 96 % cotton,
4 % elastan, 170 g/m²

T-SHIRTS BLUE MOUNTAIN

man C1013BB
woman C1014BB

NEW

**Comfortable t-shirt designed by climbers for climbers.**

Made of top quality cotton with elastan, keeps you moving freely at the crag or at the mountains.

- tag less label
- relaxed regular fit
- classic round collar
- made in the Czech Republic

Color: blue
Size: S, M, L, XL
Material: 96 % cotton,
4 % elastan (170 g/m²)

POLO T-SHIRT

W9802BY

**Pique style of polo t-shirt that is sure to look great with any outfit.**

The polo features a regular collar and short sleeves with a three button placket for a comfortable fit. The top is finished with split sides and an embroidered Singing Rock logo for an instantly recognisable branded look.

- mens polo shirt with short sleeves
- regular collar
- Singing Rock branding
- machine washable

Style: UNlsex
Size: S, M, L, XL
Material: 100 % pique cotton

T-SHIRT MONKEY

C1030Y

NEW

**Fun, comfortable climbing t-shirts made from top quality cotton for your youngest climbing stars.**

- Tagless size lable
- Relaxed fit
- made in the Czech Republic

Color: yellow
Size: 128 (7-8 yrs.), 142 (9-10 yrs.)
Material: 100 % cotton, (170 g/m²)

HOODY

C1018BY



Warm, cozy and comfortable hoodie with a kangaroo pocket and a big hood.

Style: UNisex

Size: XS - XL

Material: 90 % cotton,
10 % soft polyester

Color: black and yellow

HOODY FULL ZIP

man C1019BY
woman C1020BY



Warm, cozy and comfortable hoodie with two pockets, hood and full zipper

- longer sleeves and special cut for climbers guarantee maximal comfort when climbing or working at height

Style: Men, Women

Size: S, M, L, XL, XXL
(XXL- man only)

Material: 90 % cotton,
10 % soft polyester

Color: black and yellow



KIDS HOODY

CI031M

NEW

Warm, cozy and comfortable hoody for the youngest climbers.

- fits both boys and girls
- with a kangaroo pocket and a big hood

Color: blue

Size: 128 (7-8 yrs.),
142 (9-10 yrs.)

Material: 90 % cotton,
10 % polyester (300 g/m²)

SCARF



Multifunctional scarf 8 in 1 with a wide variety of uses for your protection against wind and cold.

- can be used as a balaclava, cap, masc, scarf, beanie, shawl, ear warmer, etc.
- 5 different designs to fit all users' styles
- made from elastic high-tech 100% polyester microfibre fabric that keeps its shape well, as well as being breathable, warm, soft, lightweight, of a very high quality and antibacterial
- machine washable at 30 °C, cannot be tumble dried, air dry very quickly

Size: UNI

(approx. 25 cm wide x 46 cm long)

Weight: 35 g • 1.24 oz

C0079BX00 – BLACK ARROW

C0080BX00 – LOGOS

C0081AX00 – AZURE

C0081RX00 – REDHOT

SNAP BACK HAT

C0074BY00



Cool Singing Rock cap for your head.

- flat bill
- "singing rock" and the embroidered SR arrow on the front
- "climbers for climbers" on the back
- mesh in the back
- adjustable snap strap

TRUCKER HAT

C0089SX00



Trucker hat for casual wear, work or climbing trips.

- mid-crown trucker hat with a six-panel design
- Singing Rock original embroidery
- adjustable snap closure

Weight: 82 g

Color: grey

Material: flap 97 % cotton / 3 % elasthan,
front panel 100 % cotton, net 100 % PES

BASEBALL HAT

black C0051BH
brown C0051HH



Square-shaped visor. Logo on front.
Website singingrock.com on back.

BASEBALL HAT LIGHT

C0070SL00



Cool hat for hot sunny days to cool down your head.

BEANIE PRO



Protective beanie for cold and windy conditions.

- upper part made of breathable, warm, soft and lightweight microfiber polyester fabric
 - lower section is made of windproof microfleece fabric to protect against wind in cold environments
 - fits very well under a helmet
 - lateral perforations in ear areas ensure hearing during work or other activity
 - machine washable up to 30° C
 - available in two sizes
- Size: S-M (49-53 cm • 19-21 in),
L-XL (54-58 cm • 21-23 in)
Color: black
Weight: 21 g • 0.74 oz
Material: 100 % Polyester

C0087SB02 S-M
C0087SB04 L-XL

BEANIE



- made from breathable, warm, soft and lightweight microfibre polyester fabric
 - keeps your head warm and dry during vertical activities
 - fits very well under the helmet
 - suitable also for running, skiing, biking and other outdoor activities
- Size: S-M (49-53 cm)
L-XL (54-58 cm)
Material: 100 % Polyester

C0053RX BEANIE REDHOT
C0053AX BEANIE AZURE
C0053OX BEANIE ORANGE
C0054BX BEANIE LOGOS
C0055BX BEANIE BLACK ARROW

BEANIE HAT



A Wool/acrylic mix of beanies, featuring a double layered headband and embroidered design.

- fleece double layered headband for colder conditions
- Size: UNI
Material: wool, acrylic

C0069BG00 NANUK BLUE
C0069PB00 NANUK PURPLE
C0067BS00 ARROW

WORK KNIFE

A0031BS



Pocket knife with first class stainless steel blade.

- blade length 80 mm
- one hand operation and safety lock of opened knife
- stainless steel flexible clip for belt fixation
- hole for the accessory cord fixation

Material: blade and clip – stainless steel, plastic handle

Weight: 83 g • 2.9 oz

CULTER

A0050HH00



Reliable knife for daily work or emergency situations including belt cutter and window breaker.

- half-serrated 80 mm blade made of 420B stainless steel
- handle made of stainless steel and red G10 fiber
- one hand opening and closing, safety lock
- G10 line of fiber materials is not electrically conductive
- G10 fiber exhibits superior mechanical and dimensional stability and doesn't shrink, it can also resist high temperature (up to 180 °C)

Color: red

Weight: 208 g • 7.34 oz

Material: stainless steel, G10 material

RESCUE KNIFE

A0030Y



Special rescue knife with first class stainless steel ejection blade.

- blade length 80 mm and safety lock of opened knife
- special shape of the blade with the hook at the end for cutting of ropes or webbing
- other features: glass cutter, hammer for glass window breaking, opener of electrical cases – wrench
- stainless steel flexible clip for belt fixation

Material: Blade and clip – stainless steel, plastic handle

Weight: 196 g • 6.9 oz

BELT FOR TROUSERS

C9091XX



With Rock&Lock smart buckle.
This buckle is used on almost every harness from SINGING ROCK production.
Size: M/L, XL
Width: 20 mm
Color: various colors
Do not use for climbing or work at heights!

SPEED BELT

black C9092BX
various colors C9092XX



Belt for trousers with Speed buckle for fast releasing.
Size: M/L, XL
Width: 44 mm
Color: black, various colors
Do not use for climbing or work at heights!

ARROW

ARROW MUSCLE P0017YY





Climbing holds for your climbing and bouldering gyms. Perfect for creating medium to difficult routes.
Size: S, M, L
Material: PES

POSTERS

P0027CX00



- 1 Motive:
- 1) FELIPE CAMARGO
FORTALEZA V15
 - 2) ICE CLIMBING ICELAND
 - 3) ICE CLIMBING ALASKA
 - 4) LUCIE HROZOVA ALASKA
 - 5) MARTIN STRANIK
 - 6) STEPAN STRANIK
 - 7) MARTIN STRANIK TICINO
 - 8) STEPAN STRANIK TICINO
 - 9) SANDSTONE
 - 10) FELIPE CAMARGO
EL BON COMBAT
 - 11) AMA DABLAM



Climbing and bouldering posters with our sponsored athletes. Size 690 x 480 mm



SINGING ROCK STICKERS

P0025XX00



Various stickers with Singing Rock logo with back side adhesive.

AUTHORIZED DEALER STICKER

P0025XX02



Authorized dealer sticker with front and back side adhesive to be put on the door or window in the store.

Size: 14,5 cm

BEACH FLAG

P0021



Self standing event flag.
Made from elastic PES.
Comes with a footstand
and carrier bag.

Size:

- P0021BB00 Table: 29 x 60 cm
- P0021BB03 Medium: 60 x 260 cm
- P0021BB04 Large: 80 x 340 cm
- P0021BB05 XLarge: 85 x 450 cm

ATTENTION:

Price and minimum quantity of all promotional products are on request.

BANNERS

P0020



Singing Rock banners made from lightweight PES with a holes to hang up.

Size:

P0020BB02 Small: 60 x 60 cm

P0020BB03 Medium: 30 x 150 cm

P0020BB04 Large: 200 x 100 cm

P0020BB05 XLarge: 150 x 150 cm



MUG

P0012BB00



Thermo cup with sturdy handle keeps your coffee or tea hot.

Capacity: 400 ml • 14.8 fl oz

Weight: 250 g • 8,8 oz

PITCHER

0.5 l P0010X050

0.3 l P0010X030



Classic beer pitcher 0.5 l or 0.3 l for all who likes climbing and all activities on our vertical playground.

GROUND COFFEE OUTDOOR

P0038GU01
packet P0038GB10



Coffee for outdoor enthusiasts and coffee lovers. Enjoy the coffee time before/after your climbing or working day.

- each bag includes tear open inner pack which can be placed on any cup
- for finest taste, always use clean, filtered water; pour 180-200 ml, leave for 5 minutes and enjoy your coffee
- bags contain A1 and Brazil ground coffee
- A1 (80 % Arabica / 20 % Robusta) with strong, full, medium bitter taste with a pleasant aftertaste, suitable for milk treatments
- 100 % Arabica Brazil Pergamino Sul de Minas has very well balanced delicate sweet taste with a slight acidity and a hint of chocolate and almonds
- packet includes 5 bags of A1 coffee blend and 5 bags of 100 % Arabica Brazil (marked with a stamp on the bag)

Weight: 10 g • 0.35 oz (bag)
Coffee: A1 (80 % Arabica / 20 % Robusta),
Brazil (100 % Arabica)

WRISTBAND

P0024XX00



100% latex-free silicone wristband with debossed Singing Rock. Made from premium high quality rubber.

KEY HOLDER

P99100X



You will never lose your keys if you use Singing Rock key holders.

QUICKDRAW COVER

P0016BB00



Antislippery cover to increase the logo visibility. Great for all photographers. Fits for the quickdraw with the width of the sling 16 – 20 mm

TEXTILE BADGE

10x4 cm P0031XX01
15x6 cm P0031XX02



Singing Rock textile embroidered badge to be stitched to your clothing, backpack or bag. Size: 10 x 4 cm, 15 x 6 cm

PAPER BAG


P0033XX00



Eco-friendly paper bag with rounded paper handle.
Size: 35 x 44 x 18 cm

NOTEPAD A5

P0030XX00



Manage your important tasks or jot down your to-do list with our Singing Rock notepads.

SINGING ROCK PEN

P0022XX00



Ballpoint pen for everyday writing.

USB FLASH DRIVE

P0019XX00



Wooden flash drive to transport and store your personal files.

- small ring to connect it to your key holder or accessory cord.

Capacity: 8 GB

Material: Eco Friendly wood

CONDOM SAFETY FIRST

P0023XX00



Comes in handy for your rest days.

Size: UNI
CE 1023

ATTENTION:

Price and minimum quantity of all promotional products are on request.



PICTOGRAMS



BMI – the adjusting system

Revolutionary size adjusting system by SINGING ROCK. You can easily adjust free end of your waistbelt padding and fix it in the right position and minimize so called "sticking out" of padding incl. the first gear loop in the line. Suitable for situation as losing or putting on your weight, putting more clothers or changing of your climbing seasons. The best position is when the buckle is on the padding and BMI system doesn't allow the gear loops to get out of the right position.



CE – symbol of compliance

The CE symbol declares that the product is in compliance with the safety requirements of the applicable European standard. The number after the symbol CE (e.g. CE 1019) identifies the relevant accredited testing lab.



InterCore

The unique patented technology providing maximum safety even in case of a damaged sheath. The rope is made from 4 layers of parallel core filaments, braided core, braided intermediate sheath made from staple fibres and single tech sheath.



Lady fit

Specially designed products for women.



Paper Trail

Symbol means, that the products are supplemented with a scannable Data Matrix code and all information like serial number, production date, photo, description, instructions etc. are uploaded to a cloud based PaperTrail, an all-in-one system for equipment management and maintenance records.

For more information visit - www.singingrock.com/papertrail



Rock & Lock

Patented smart buckle used on SINGING ROCK harnesses and other products enables to lock and open very quickly.



Route 44

SINGING ROCK patented technology for rope production. A rope is produced on 44 carrier machine which provides great handling, low weight and durability.



Single Tech

With the Single Tech system each strand is braided into the sheath separately. Single Tech sheath construction increases the rope's wear resistance and improves the rope's mechanical properties, such as flexibility.



Stitched eye

Selected SINGING ROCK static ropes which are marked with Stitched eye icon are possible to produce with one or two stitched eyes at the end of the rope.



Single rope

Marking of single dynamic rope for climbing and mountaineering used in single strand.



Half rope

Marking of half rope for mountaineering, multipitch and ice climbing. Individual strands of rope are used in alternation in the protection system. This system reduces the risk of rope breakage caused by falling stones, and provides maximum safety in alpine conditions and for difficult climbs



Twin rope

Marking of twin ropes for mountaineering, multipitch and ice climbing. Pairs of the same type of rope are always used, sharing the same protection points. Twin ropes guarantee a high level of safety, especially for multipitch climbing in alpine conditions.



Teflon®

Ropes protected with a DuPont™ Teflon® fabric protector have extraordinary water and abrasion resistance.



UIAA

Products marked with this symbol meet strict UIAA safety requirements. The UIAA is the International Mountaineering and Climbing Federation. In most cases, UIAA requirements are sometimes stricter than EN standards.



UIAA WATER REPELENT

A standard for water repellent ropes approved by the UIAA Safety Commission. To pass the test at a certified laboratory, the amount of absorbed water must not be greater than 5% of the rope's weight. For comparison, a non-treated rope absorbs around 50% of water in this test, and ropes labelled as "dry" but lacking adequate treatments can absorb between 20% and 40% of water.

MATERIALS & TECHNOLOGIES

ABS	Acrylonitrile butadiene styrene is a common thermoplastic polymer. The most important mechanical properties of ABS are impact resistance and toughness. ABS is stronger than pure polystyrene.
Acryl	Lightweight, soft, and warm, with a wool-like feel fabrics or yarn. Strong and warm, acrylic fiber is often used for sweaters and tracksuits and as linings for boots and gloves, as well as in furnishing fabrics and carpets. It is manufactured as a filament, then cut into short staple lengths similar to wool hairs, and spun into yarn.
Anodizing	Electrolytic passivation process used to increase the thickness of the natural oxide layer on the surface of metal parts. Anodizing increases resistance to corrosion and wear, and provides better adhesion for paint primers and glues than bare metal does.
Bamboo	Cloth, yarn, and clothing made out of bamboo fibres. Bamboo fabric is exceptionally soft and light. It is also incredibly hydrophilic, absorbing more water than other conventional fibres such as cotton and polyester.
Cold forging	Deformation of metal while it is below its recrystallization point. This process is usually less expensive than hot forging and the end product requires little, if any, finishing work. Residual stress of material may occur as it handles high stress and high die loads
Cordura	Brand name for a collection of fabrics used in a wide array of products including luggage, backpacks, trousers, military wear and performance apparel. Cordura fabrics are known for their durability and resistance to abrasions, tears and scuffs. Cordura fabrics are usually made of nylon.
Cortex	Polyamide elastic woven fabrics. Cortex fabrics are designed to ensure the maximum ergonomoy and comfort.
Chromoly steel	Low alloy steel that gets its name from a combination of the words "chromium" and "molybdenum". Chromoly steel is often used when more strength is required than that of mild carbon steel, though it often comes at an increase in cost.
Dyneema	Registered trademark for a synthetic fabric that is stronger than Kevlar®. Dyneema® is composed of ultra high molecular weight polyethylene. It is resistant to water, most chemicals, UV radiation and bacterial.
ED coating	Electrophoretic deposition coating. A characteristic feature of this process is that colloidal particles suspended in a liquid medium migrate under the influence of an electric field (electrophoresis) and are deposited onto an electrode.
Elastane (Spandex)	Synthetic polyether-polyurea copolymer known for its exceptional elasticity. It is stronger and more durable than natural rubber.
EPS	Expanded polystyrene is a rigid and tough, closed-cell foam. It is made of pre-expanded polystyrene beads. Due to its technical properties such as low weight, rigidity, and formability, EPS can be used in a wide range of different applications.
Ethylene-vinyl	Copolymer of ethylene and vinyl acetate. The material has good clarity and gloss, low-temperature toughness, stress-crack resistance, hot-melt adhesive waterproof properties, and resistance to UV radiation.
Fiber glass	Type of fiber-reinforced plastic where the reinforcement fiber is specifically glass fiber. The glass fiber may be randomly arranged, flattened into a sheet (called a chopped strand mat), or woven into a fabric. Fiberglass is unique in its strength and yet it is lightweight. Although it is not as strong and stiff as composites based on carbon fiber, it is less brittle, and its raw materials are much cheaper.
Fleece	Soft napped insulating fabric made from a type of polyester called polyethylene terephthalate (PET) or other synthetic fibers. A lightweight, warm, soft and hydrofobic fabric. Regular polar fleece is not windproof and does not absorb moisture. It is readily generates static electricity.
G10 fiber	High-pressure fiberglass laminate, a kind of composite material. It is created by stacking multiple layers of glass cloth, soaking in epoxy resin, and compressing the resulting material under heat until the epoxy cures. G10 is favoured for its high strength, low moisture absorption, excellent electrical insulating properties and chemical resistance.
Hardened steel	Medium or high carbon steel that has been given heat treatment and then quenching followed by tempering.
HF welding	Joining of materials by supplying High Frequency energy in the form of an electromagnetic field (27.12 MHz) and pressure to the material surfaces to be joined.
Hot forging	Deformation of metal while it is above the recrystallization point. Hot forging is recommended for the deformation of metal that features a high formability ratio. Hot forging provides a homogenized grain structure
Injection	Manufacturing process for producing parts by injecting material into a mould. Material for the part is fed into a heated barrel, mixed, and forced into a mould cavity, where it cools and hardens to the configuration of the cavity.
Kernmantle rope	Rope constructed with its interior core protected by a woven exterior sheath designed to optimize strength, durability, and flexibility. The core fibers provide the tensile strength of the rope, while the sheath protects the core from abrasion during use.
Kevlar	Kevlar is the registered trademark for a para-aramid synthetic fiber. Kevlar has many applications, ranging from bicycle tires and racing sails to body armor, because of its high tensile strength-to-weight ratio; by this measure it is 5 times stronger than steel. It is designed to protect users from cuts, abrasions and heat. Kevlar-based protective gear is often considerably lighter and thinner than equivalent gear made of more traditional materials.
Nylon	Generic designation for a family of synthetic polymers, based on aliphatic or semi-aromatic polyamides. Nylon is a thermoplastic silky material that can be melt-processed into fibers, films or shapes. Nylon is very much suitable for hosiery and the knitted fabrics because of its smoothness, light weight and high strength.

MATERIALS & TECHNOLOGIES

Plastex	Material made of polyester with PVC cover
Polyamide (PA, PAD)	Macromolecule with repeating units linked by amide bonds. Synthetic polyamides are commonly used in textiles, automotive applications, carpets and sportswear due to their high durability and strength. Fibres are very tear-proof and abrasion-resistant and absorb little moisture (thus good transport of moisture away from the body) and are stretchy, crease-free, but also prone to pilling. Polyamide has the highest resistance of all textile raw materials (also when wet) and is very stretchy.
Polycarbonate	Group of thermoplastic polymers containing carbonate groups in their chemical structures. Polycarbonates used in engineering are strong, tough materials, and some grades are optically transparent.
Polyester (PES)	Category of polymers that contain the ester functional group in their main chain. Fabrics woven or knitted from polyester thread or yarn are used extensively in apparel and home furnishings. Industrial polyester fibers, yarns and ropes are used in car tire reinforcements, fabrics for conveyor belts, safety belts, coated fabrics and plastic reinforcements with high-energy absorption. Polyester has excellent return conduct thanks to the rippling property and is very light. Polyester also retains its shape and is colourfast, as well as resistant to sweat and UV-rays (lightfast). Polyester has a high melting point and transfers can therefore be printed on this material)
Polyethylene (PE)	Most common plastic, which is usually a mixture of similar polymers of ethylene. Polyethylene is of low strength, hardness and rigidity, but has a high ductility and impact strength as well as low friction. It shows strong creep under persistent force, which can be reduced by addition of short fibers. Its primary use is in packaging (plastic bags, plastic films, geomembranes, containers including bottles, etc.)
POLYMAR	Registered trademark for a polyester coated with polyurethane tarpaulin fabric. It is UV and weatherproof resistant.
Polypropylene (PP)	Thermoplastic polymer used in a wide variety of applications including packaging and labeling, textiles (e.g., ropes, thermal underwear and carpets), stationery, plastic parts and reusable containers of various types, laboratory equipment, loudspeakers, automotive components, transvaginal mesh and polymer banknotes. An addition polymer made from the monomer propylene, it is rugged and unusually resistant to many chemical solvents, bases and acids. Polypropylene is the world's second-most widely produced synthetic plastic, after polyethylene.
Polystyrene	Synthetic aromatic polymer made from the monomer styrene. Polystyrene can be solid or foamed. General-purpose polystyrene is clear, hard, and rather brittle. Polystyrene is one of the most widely used plastics. Uses include protective packaging (such as packing peanuts and CD and DVD cases), containers (such as "clamshells"), lids, bottles, trays, tumblers, and disposable cutlery.
Polyvinyl chloride (PVC)	World's third-most widely produced synthetic plastic polymer, after polyethylene and polypropylene. PVC comes in two basic forms: rigid and flexible. The rigid form of PVC is used in construction for pipe and in profile applications such as doors and windows. It is also used for bottles, other non-food packaging, and cards (such as bank or membership cards). In flexible form, it is used in plumbing, electrical cable insulation, imitation leather, signage, phonograph records, inflatable products, and many applications where it replaces rubber.
Polyurethane (PU)	Polymer composed of organic units joined by carbamate (urethane) links. While most polyurethanes are thermosetting polymers that do not melt when heated, thermoplastic polyurethanes are also available.
Ripstop	Woven fabrics, using a special reinforcing technique that makes them resistant to tearing and ripping. During weaving, (thick) reinforcement threads are interwoven at regular intervals in a crosshatch pattern. Advantages of ripstop are the favourable strength-to-weight ratio and that small tears can not easily spread.
Spandex	see Elastane
Stainless Steel	Steel alloy with a minimum of 10.5% chromium content by mass. Stainless steel is notable for its corrosion resistance. Stainless steel does not readily corrode, rust or stain with water as ordinary steel does. However, it is not fully stain-proof in low-oxygen, high-salinity, or poor air-circulation environments.
Teflon	Registered trademark for a synthetic fluoropolymer of tetrafluoroethylene. It is famous for its hydrophobic and abrasive protection properties.
Technora	Registered trademark for an aramid that is useful for a variety of applications that require high strength or chemical resistance. It is closely related to Kevlar (see Kevlar).
Thermolite	Synthetic material made by Invista and used as an insulator. The performance fibers are engineered with a differentiated fiber shape, able to produce battings with sought-after lightweight warmth.
Thermotransfer	Digital printing process in which material is applied to paper (or some other material) by melting a coating of ribbon so that it stays glued to the material on which the print is applied.
Ultrasonic finishing	Sound waves with frequencies higher than the upper audible limit of human hearing is joining the load-bearing core and the protective sheath into a compact unit. It is used to finish kernmantle ropes ends.
Velcro	Registered trademark for a hook-and-loop fastener, which consists of two components: typically, two lineal fabric strips (or, alternatively, round "dots" or squares) which are attached (sewn or otherwise adhered) to the opposing surfaces to be fastened.
Zinc plating	Prevents oxidation of the protected metal by forming a barrier and by acting as a sacrificial anode if this barrier is damaged.

STANDARDS

The list of selected EN standards for mountaineering equipment and personal protective equipment (PPE) against falls from a height which our products fulfill.



EN 354
PPE against falls from a height.
Connecting equipment max. length 2 m
(incl. connectors).



EN 958
Mountaineering equipment Energy
absorbing systems for use in via ferrata
(klettersteig) climbing



EN 361
PPE against falls from a height.
Full body harnesses.



EN 959
Mountaineering equipment
– Rock anchors



EN 362
PPE against falls from a height.
Connectors.



EN 1891
PPE against falls from a height.
Low stretch kernmantel ropes.



EN 388
Protection gloves against mechanical
risks



EN 12275
Mountaineering equipment
– Connectors



EN 564
Mountaineering equipment
– Accessory cords



EN 12277
Mountaineering equipment
– Harnesses



EN 566
Mountaineering equipment
– Slings



EN 12278
Mountaineering equipment.
Pulleys.



EN 567
Mountaineering equipment.
Rope clamps.



EN 12492
Mountaineering equipment
– Helmets for mountaineers



EN 569
Mountaineering equipment - Pitons



EN 12841
PPE against falls from a height.
Descender device for rope access
system and rope adjustment devices.



EN 813
PPE against falls from a height.
Sit harnesses.



EN 13089
Mountaineering equipment - Ice tools



EN 892
Mountaineering equipment.
Dynamic (streck) ropes.



EN 15151
Mountaineering equipment
– Braking devices



EN 893
Mountaineering equipment - Crampons

PRODUCT NAMES

NAME	PAGE	NAME	PAGE	NAME	PAGE
ACCORD 8.3	43	COLT 6PACK	68	GRIPPY	129
ACCORD DRY 8.3	43	COLT MIX	63	GRIPPY 3/4	129
ALADIN	23	COLT WIRE	63	GROUND COFFEE OUTDOOR	143
ALADIN PADDING	25	COLT WIRE / BENT	57	GYM 10.1	38
ALADIN PLUS	25	COLT WIRE / STRAIGHT	57	GYM PACKET	26
ANKLE PROTECTOR	130	COMPLETE	17	HAMMER CORD	48
ARA	15	CONDOM	144	HECTOR / SCREW	59
ARROW	139	CONTRA 10.5	45	HECTOR / TRIPLE LOCK	59
ARTWALL	61	COVER	143	HECTOR BC / SCREW	59
ARTWALL SET	65	CRAGGY	130	HECTOR BC / TRIPLE LOCK	59
AUTHORIZED DEALER STICKER	141	CRAMPON BAG	94	HERO 9.6	37
BANDIT	83	CRAMPONS SPARE PARTS	89	HERO DRY 9.6	36
BANNERS	142	CRUNCH BAG	123	HEX	79
BASEBALL HAT	136	CRUNCH DOSE	123	HOODY	134
BASEBALL HAT LIGHT	136	CULTER	138	HOODY FULL ZIP	134
BEACH FLAG	141	D STEEL / SCREW	69	HOT FORGING	55
BEANIE	137	D STEEL / TRIPLELOCK	69	HUECO	120
BEANIE HAT	137	DEFENDER	48	CHALK BAG COMIC	122
BEANIE PRO	137	DIGGER LIGHT	23	CHALK BAG LARGE	122
BELT FOR CHALK BAG	122	DOME	15	CHALK BAG MOUNTAINS	121
BELT FOR TROUSERS	139	DOUBLE STOP PLUS	100	CHALK BAG ROCKET	122
BIG D	70	DRY BAG	125	ICE AXES SPARE PARTS	88
BIG DELTA	70	DRY DUFFLE	127	ICE SCREW COVER	94
BIG SQUARE	70	DURAN 10.4	41	ICE SCREWS BAG	94
BIG TWIST	70	DYNEEMA® SLINGS 11 MM	111	ICON 9.3	36
BORA / SCREW	56	DYNEEMA® SLINGS 8 MM	111	ICON DRY 9.3	36
BORA / TRIPLE LOCK	56	EDGE	84	JACOB	113
BORA / TWL	56	EDGE ROLLER	49	JACOB DYNEEMA	112
BORA GP / SCREW	56	EDGE ROLLER - PART	49	KATA 9.7	37
BOULDER BAG	121	EXPEDITION BAG TARP DUFFLE	126	KATA DRY 9.7	37
BUDDY	98	FAKIR III CLASSIC	86	KEY HOLDER	143
BUDDY SET	98	FAKIR III SEMI-CLASSIC	87	KEYLOCK	55
BUNGEE	92	FAKIR III TECH	87	KIDS HOODY	135
BUNGEE SINGLE	92	FALCONER	129	LADY PACKET	26
CAM CLEAN	99	FALCONER 3/4	129	LIFT	100
CANYON BAG	125	FALCONER FULL	129	LUCIFER III TECH	86
CANYON SIT PROTECTION	22	FERRATA PACKET EXP	27	MAGIC	120
CANYON XP	22	FERRATA PACKET II	27	MAGNUM	123
CAPTAIN	103	FERRATA PACKET RAY	27	MAGNUM	123
CARRY BAG	127	FIGURE 8 L	99	MAGNUM BALL	123
COLT	63	FIGURE 8 M	99	MAGNUM BALL	123
COLT / BENT	57	FIRST AID BAG	128	MAGNUM BALL TWINS	123
COLT / SCREW	57	FIRST AID BAG	128	MAGNUM CUBE	123
COLT / STRAIGHT	57	FIX	93	MAGNUM LIQUID CHALK, BAG	123
COLT 16	64	FIX PLUS	93	MAGNUM LIQUID CHALK, TUBE	123
COLT 16 6PACK	68	FLAT WEBBING	114	MERLIN	85
COLT 16 MIX	64	FONT	120	MINI D	71
COLT 16 MIX 6PACK	68	FOOTER II	113	MINI D SCREW	71
COLT 16 WIRE	64	FOOTER XP	113	MINI OVAL	70
COLT 16 WIRE 6PACK	68	GEAR BAG	125	MINI PEAR	71
COLT 17 CM	65	GEMINI 7.9	43	MIRAGE 6PACK	66
COLT 17 CM 6PACK	68	GLUE IN ANCHOR	104	MIRAGE ALPINE	67

PRODUCT NAMES

NAME	PAGE	NAME	PAGE	NAME	PAGE
MIRAGE LONG	67	REFILL	123	T-SHIRT MONKEY	133
MIRAGE STRAIGHT 6PACK	58	REGULATOR	113	T-SHIRT ROCKET	132
MONTY BAG	128	RESCUE KNIFE	138	T-SHIRTS BACKBONE	132
MOVEMENT BAG	126	RIGGING PLATE 1/3	105	T-SHIRTS BLUE MOUNTAIN	133
MUG	142	RIGGING PLATE 3/5	105	TACTICAL	129
MYSTIC 10.1	40	ROB	13	TANDEM PULLEY	102
MYSTIC 10.1 DRY	40	ROCK HAMMER	103	TARZAN	18
NOTEPAD A5	144	ROCKET	11	TARZAN ECONOMIC	18
NUMBER	55	ROCKING 40	124	TEXTILE BADGE	143
ONYX	11	ROCKSTAR 28	124	THERMOCUTTER	49
OVAL STEEL /	69	ROPE BAG	127	TOP	20
OVAL STEEL / SCREW	69	ROPE MARKER	49	TOP CANYON	22
OXY / SCREW	60	ROPE PROTECTOR	48	TOP PADDED	20
OXY / TRIPLE LOCK	60	ROPEDANCER II	17	TOP RENTAL	20
OXY / TWL	60	RUBBER FIX	71	TRIPLE LOCK	61
OXY BC / SCREW	60	SAFETY FIRST	144	TRIPLELOCK	69
OXY BC / TRIPLE LOCK	60	SAFETY CHAIN	113	TRIPLELOCK	69
OXY BC / TWL	60	SCARF	135	TRUCKER HAT	136
OZONE / SCREW	61	SCORE 10.1	40	TUBULAR WEBBING	114
OZONE / TRIPLE LOCK	61	SCREW	69	TWISTER	107
OZONE / TWL	61	SCREW	61	TWL	61
PAPER BAG	144	SENTINEL	103	ULTIMA	103
PATRON 11.0	41	SERAC	21	UNIQUE	55
PEARL	12	SERIAL	55	USB FLASH DRIVE	144
PENTA	77	SHUTTLE	98	VERSA II	14
PHARIO	115	SINGING ROCK PEN	144	VIA FERRATA / LOCK	61
PHARIO 360°	115	SINGING ROCK STICKERS	141	VISION	65
PHARIO PALM	115	SLACKLINE 15 M	119	VISION	58
PHARIO SLIDE	115	SLACKLINE 25 M	119	VISION 6PACK	68
PITCHER	142	SLACKLINE WEBBING	119	VISION STRAIGHT 6PACK	58
PITON A3	102	SLINGS 16 MM	111	WIZARD	84
PITON A5	102	SMALL DELTA	70	WIZARD LIGHT	85
PITON V	102	SMALL OVAL	70	WORK KNIFE	138
POLO T-SHIRT	133	SNAP BACK HAT	136	WRISTBAND	143
PORTER	71	SPEED BELT	139	ZAZA	16
POSTERS	140	SPELEO 10.5	45	ZINC PLATED HANGER PLATE	104
PULLEY EXTRA	101	SPELEO R44 10.5	45		
PULLEY MIKY	102	SPIN	91		
PULLEY SMALL	101	SPINEL	13		
PULLEY TWIN	101	STAINLESS HANGER PLATE	104		
QUICK SPIN	91	STATIC 10.5	44		
QUICKDRAW	143	STATIC 11.0	44		
QUICKDRAW	71	STATIC 9.0	45		
QUICKDRAW SL. DYNEEMA® 11 MM	112	STATIC R44 10.5	44		
QUICKDRAW SLINGS 16 MM	112	STATIC R44 11.0	44		
QUICKDRAW SLINGS 16/25 MM	112	STATIC R44 NFPA 10.5	46		
RAMA	97	STATIC R44 NFPA 11.0 / 7/16"	46		
RAMA SET	97	STATIC R44 NFPA 13.0	46		
RAPPELLING STATION 12 MM	105	STATIC ROPES	44		
RAY	14	STORM 9.8	38		
RAY PACKET	26	STORM DRY 9.8	38		
REDBLOCK	107	SUPER TAPE	121		

PRODUCT CODES

CODE	PAGE	CODE	PAGE	CODE	PAGE	CODE	PAGE
A003IBS	138	C0710	17	C5058	25	K0121BB00	59
A003OY	138	C0900	79	C5067	14	K0121BC00	59
A0050HH00	138	C1013BB	132	C5069OA	16	K0121EC00	59
C0001BB	127	C1013BB	133	C5070RY	15	K0121EE00	59
C0001YY00	127	C1014BB	132	C5071YX	11	K0122BB05	60
C0002BBX4	122	C1014BB	133	C5072SC	12	K0122BB06	60
C0006BH	129	C1018BY	134	C5074TS	13	K0122BB07	60
C0006HH	129	C1019BY	134	C5075OX	13	K0122EE05	60
C0012YB	129	C1020BY	134	C5076	11	K0122EE06	60
C0013YB	129	C1026AX	132	C5078RB	20	K0122EE07	60
C0014YB	129	C1027AX	132	C5079WB	21	K0123BC05	60
C0034W125	121	C1028VX	132	C9091XX	139	K0123BC06	60
C0034Y380	121	C1029VX	132	C9092BX	139	K0123BC07	60
C0035AO12	114	C1030Y	133	C9092XX	139	K0123EC05	60
C0037BB12	114	C1031M	135	C9630BB00	22	K0123EC06	60
C0037RR12	114	C2000	112	GREY C5073ST	12	K0123EC07	60
C0051BH	136	C2001	111	K0006RP00	107	K031DSD00	100
C0051HH	136	C2004	111	K0009EE00	58	K4080ZO	69
C0053AX	137	C2075	111	K0009EE60	58	K4081ZO	69
C0053OX	137	C2085	112	K0016AA00	61	K4241ZO05	69
C0053RW	128	C2087X012	112	K0016BB00	61	K4241ZO07	69
C0053RW	128	C2087X017	112	K0017AA00	61	K4310PP00	61
C0053RX	137	C2150BY	113	K0017BB00	61	K5052EE00	71
C0054BX	137	C2151BY00	112	K0018AA00	61	K5182EE00	71
C0055BX	137	C2313XX00	115	K0018BB00	61	K5330PE	61
C0064BY15	119	C2314XX00	115	K0025EE00	58	K6021BB	99
C0064BY25	119	C2315XX00	115	K0027BY00	71	K6021EE	99
C0065BY15	119	C2316XX00	115	K00300G00	107	K6031BB	99
C0067BS00	137	C2419B	113	K0043OX00	97	K6031EE	99
C0069BG00	137	C2419X	113	K0043SX00	97	K6132BB	98
C0069PB00	137	C3002SS00	122	K0050OS01	49	K6132EE	98
C0070SL00	136	C3002XX00	122	K0050OS03	49	K6140BB00	98
C0071AA00	77	C3003RR04	122	K0107BB00	56	K6140EE00	98
C0071RR00	77	C3003SS04	122	K0107BP00	56	K6604E011	65
C0071SS00	77	C3003TT04	122	K0107EE00	56	K6604E611	68
C0071WW00	77	C3003YY04	122	K0107EP00	56	K6613E011	63
C0073BY00	126	C3004AA00	121	K0108BB00	56	K6715E011	63
C0074BY00	136	C3004CC00	121	K0108EE00	56	K6715E017	65
C0075BX00	120	C3004RR00	121	K0110BB00	57	K6715E611	68
C0076BX00	120	C3004TT00	121	K0110EE00	57	K6715E617	68
C0077BX00	120	C3004YY00	121	K0111BB00	57	K6716E011	63
C0079BX00	135	C3066BY00	121	K0111EE00	57	K6719E016	64
C0080BX00	135	C309	122	K0112BB00	57	K6719E616	68
C0081AX00	135	C5017	15	K0112EE00	57	K6720E016	64
C0081RX00	135	C5029BS	22	K0113EE00	57	K6720E616	68
C0082YB	130	C5030BS	22	K0114BB00	59	K6721E016	64
C0083YB	130	C5031BB00	20	K0114BC00	59	K6721E616	68
C0084XX11	71	C5031BS00	20	K0114EC00	59	K6722E611	66
C0084XX16	71	C5032BS00	20	K0114EE00	59	K6723E030	67
C0085BX28	124	C5038	14	K0119BB00	56	K6723E050	67
C0086BX40	124	C5056	23	K0119EE00	56	K6724E016	67
C0089SX00	136	C5057	25	K0120EE00	57	K6950	65

PRODUCT CODES

CODE	PAGE	CODE	PAGE	CODE	PAGE	CODE	PAGE
K82006Z	70	M0028	27	RK106BB000	88	RK710XX12	102
K82008Z	70	M0029	26	RK107BB000	88	RK711XX00	103
K82207Z	70	M0200XX00	98	RK108BB000	88	RK713BB00	105
K82210Z	70	M0201XX00	97	RK109BB000	88	RK715XX10	104
K82310Z	70	M3001W10C	123	RK110BB000	88	RK715XX12	104
K82410Z	70	M3001WO35	123	RK111BY000	93	RK716XX10	104
K82508Z	70	M3001WO35R	123	RK111BY001	93	RK716XX12	104
K9000BB03	71	M3001X056	123	RK112WX000	92	RK750XX00	103
L0021	48	M3001X30P	123	RK113BB000	88	RK800BB00	101
L0031	48	M3001XO70T	123	RK114BB000	88	RK800EE00	101
L0041 - L0081	48	M3002W010	123	RK115XX000	88	RK801BB00	101
L0220BB	45	M3002W150	123	RK116XX000	88	RK801EE00	101
L0220WR	45	P0010X030	142	RK117WX000	92	RK802BB00	101
L0230BB	44	P0010X050	142	RK206AX00C	86	RK802EE00	101
L0230KK	44	P0012BB00	142	RK206AX00S	87	RK803BB00	102
L0230RR	44	P0016BB00	143	RK206AX00T	87	RK804BX0L	100
L0230WR	44	P0017YY	139	RK207AX00T	86	RK804BX0R	100
L0240WR	45	P0019XX00	144	RK251XX000	94	RK805BX00	99
L0250BB	44	P0020	142	RK302SX012	91	RK806BB00	102
L0250RR	44	P0021	141	RK302SX017	91	S0101YB00	23
L0250WR	44	P0022XX00	144	RK302SX022	91	S9000BB35	125
L026	45	P0023XX00	144	RK303SX012	91	S9000BB50	125
L0340AX	41	P0024XX00	143	RK303SX017	91	S9000RR35	125
L0360GG	40	P0025XX00	141	RK303SX022	91	S9000RR50	125
L0380YX	36	P0025XX02	141	RK351XX000	94	S9000YY35	125
L0384RX	36	P0027CX00	140	RK352XX000	94	S9000YY50	125
L0430BB	44	P0030XX00	144	RK500XX00	105	S9001BX60	125
L0430KK	44	P0031XX01	143	RK607AX000	89	S9001YX40	125
L0430RR	44	P0031XX02	143	RK608AX000	89	S9002YX30	125
L0430WR	44	P0033XX00	144	RK609Y000	89	S9003YB60	127
L0440WR	45	P0038GB10	143	RK610XX03	89	S9003YY40	127
L0450BB	44	P0038GU01	143	RK610XX05	89	W0050BR	18
L0450OO	44	P99100X	143	RK611XX03	89	W0059BR	18
L0450RR	44	R0430BB	46	RK611XX05	89	W0087	17
L0450WG	44	R0430KK	46	RK612XX000	89	WI023	128
L0510	43	R0430RR	46	RK613XX000	89	WI024BX	113
L0514	43	R0430WR	46	RK6371BB	105	WI025BX	113
L0520GW	37	R0450BB	46	RK702XX10	104	WI025BX	113
L0524GW	36	R0450OO	46	RK702XX12	104	WI027B	48
L0530RA	40	R0450RR	46	RK703XX10	104	WI051BX	113
L0534AG	40	R0450WG	46	RK704XX10	104	W8100B	48
L0540YX	41	R0460WB	46	RK704XX12	104	W9802BY	133
L0570AA	37	RED C5073RT	12	RK705XX00	103	X0004GB	49
L0580AA	37	RK001EE63	58	RK706XX00	103	X0015XX	49
L3020	43	RK003YX00H	83	RK708XX03	102		
L3040GA00	38	RK004YX00A	83	RK708XX05	102		
L3044AG00	38	RK005TX0	84	RK708XX07	102		
L3050RY00	38	RK006WX0	85	RK709XX05	102		
M0014	26	RK007BX0	85	RK709XX07	102		
M0017	27	RK008AX00H	84	RK709XX09	102		
M0018	27	RK009AX00A	84	RK710XX08	102		
M0027	26	RK105BB000	88	RK710XX10	102		



SINGING ROCK IS CLIMBING

has its spirit as a company where climbing equipment is produced by Climbers for Climbers. Our company is located in Czech Republic near Krkonoše National Park and Bohemian Paradise where are situated the amazing and unique sand stone rock climbing areas.

Most of our staff are climbers, alpinists or backcountry skiers. "Crazy cools" with ice axes, haul bags, skis and crampons. Most of us took our first steps within the sand stone labyrinths of Bohemian Paradise or hard granite of the Ji-zera Mountains. Some of us later on continued to the higher mountains or have specialized on sport climbing or bouldering.

The Singing Rock Climbing Team with our world class athletes help us to test, improve and develop new functional as well as a high quality climbing equipment. Felipe Camargo, Carlos Logroño, Martin Stranik Lucie Hrozová, Czech UIAGM Mountain guides and others help us to test and improve every product which is coming out of our factory.

SINGING ROCK is climbing and we are committed to bring you high quality and highly-functional equipment with minimal impact on the environment.

SINGING ROCK TEAM

Warning:

Activities at height such as climbing, via ferrata, caving, rappelling, ski-touring, rescue, work at height and exploration are dangerous activities, which may lead to severe injury or even death. Thus the following is essential before use: careful reading and understanding of the instructions for use acquaintance with the possibilities and limitations of the product adequate apprenticeship in appropriate techniques and methods of use understanding and acceptance of the risk involved. In case of doubt or problem of understanding, contact SINGING ROCK.




Address:

Singing Rock
Poniklá 317
512 42 Poniklá
Czech Republic

Contact:

tel.: +420 481 585 007
e-mail: info@singingrock.com
www.singingrock.com

Social:

 [singingrock.page](https://www.facebook.com/singingrock.page)
 [singingrock_official](https://www.instagram.com/singingrock_official)
 [user/sigrvideo](https://www.youtube.com/user/sigrvideo)



Carlos „Citro“ Logroño. El templo de Escalé 8c+, Aiguaz de Sornin, Pinaro, Jany, Bec

CLIMBERS FOR
CLIMBERS